



FCC RF Test Report

APPLICANT : Quetel Wireless Solutions Co., Ltd.
EQUIPMENT : Wi-Fi & Bluetooth Module
BRAND NAME : Quetel
MODEL NAME : FCE860L
FCC ID : XMR2023FCE860L
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : Oct. 19, 2023 ~ Dec. 21, 2023

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant 5

 1.2 Manufacturer 5

 1.3 Product Feature of Equipment Under Test..... 5

 1.4 Product Specification of Equipment Under Test..... 6

 1.5 Modification of EUT 6

 1.6 Testing Location 7

 1.7 Test Software..... 7

 1.8 Applicable Standards..... 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1 Carrier Frequency and Channel 8

 2.2 Test Mode..... 9

 2.3 Connection Diagram of Test System 10

 2.4 Support Unit used in test configuration and system 11

 2.5 EUT Operation Test Setup 11

 2.6 Measurement Results Explanation Example..... 11

3 TEST RESULT 12

 3.1 6dB and 99% Bandwidth Measurement 12

 3.2 Output Power Measurement..... 13

 3.3 Power Spectral Density Measurement 16

 3.4 Conducted Band Edges and Spurious Emission Measurement 18

 3.5 Radiated Band Edges and Spurious Emission Measurement 19

 3.6 AC Conducted Emission Measurement..... 23

 3.7 Antenna Requirements 25

4 LIST OF MEASURING EQUIPMENT 26

5 MEASUREMENT UNCERTAINTY 27

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. AC CONDUCTED EMISSION TEST RESULT

APPENDIX C. RADIATED SPURIOUS EMISSION

APPENDIX D. DUTY CYCLE PLOTS

APPENDIX E. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	99% Bandwidth	-	Report Only	-
3.2	15.247(b)	Power Output Measurement	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges	≤ 20dBc	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.04 dB at 7386.00 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 10.20 dB at 0.435 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Quectel Wireless Solutions Co., Ltd.

Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai 200233, China

1.2 Manufacturer

Quectel Wireless Solutions Co., Ltd.

Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai 200233, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Wi-Fi & Bluetooth Module
Brand Name	Quectel
Model Name	FCE860L
FCC ID	XMR2023FCE860L
SN Code	Conducted: E1N23CH0F000074 Conduction: D1823HKCC000062 Radiation: E1N23CH0F000074
HW Version	R1.0
SW Version	NA
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	<SISO Ant 0/1 > 802.11b : 26.06 dBm (0.4036 W) 802.11g : 27.67 dBm (0.5848 W) <MIMO Ant 0+1> 802.11n HT20 : 26.35 dBm (0.4315 W) 802.11n HT40 : 27.52 dBm (0.5649 W) 802.11ax HE20 : 26.49 dBm (0.4457 W) 802.11ax HE40 : 27.67 dBm (0.5848 W)
99% Occupied Bandwidth	802.11b : 11.908 MHz 802.11g : 17.463 MHz 802.11n HT20 : 18.182 MHz 802.11n HT40 : 36.763 MHz 802.11ax HE20 : 19.061 MHz 802.11ax HE40 : 37.962 MHz
Antenna Type / Gain	Ant 0: Dipole Antenna with gain 0.73 dBi Ant 1: Dipole Antenna with gain 0.73 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ax : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM)

Note:

1. The device only supports 802.11b/g SISO mode, 802.11n/11ax support SISO & MIMO mode.
2. For WLAN 802.11n/11ax SISO & MIMO mode, the whole testing has assessed only MIMO mode by referring to the higher normal output power.
3. 802.11ax support OFDMA full RU tone and partial RU tone, both full RU and partial RU-left (for low CH) and partial RU-right (for high CH) test output power, the full RU power/PSD > partial RU, therefore the full RU perform full, and partial RU verify bandedge/spurious.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People’s Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH05-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH05-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-



2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

SISO Antenna

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps

MIMO Antenna


Modulation	Data Rate
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ax HE20	MCS0
802.11ax HE40	MCS0

Test Cases	
AC Conducted Emission	Mode 1 :Bluetooth Link + WLAN Link (2.4G) + Test Jig
Remark: For Radiated Test Cases, The tests were performance with Notebook	


RSE Co-location
Bluetooth LE(2 Mbps) CH39_TX (ANT.1) + 802.11b_CH11_2462MHz (ANT.0)

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:





2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Notebook	Lenovo	V130-15IKB005	N/A	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
2.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded, 1.8m
3.	Adapter	N/A	N/A	N/A	N/A	N/A
4.	Antenna	N/A	N/A	N/A	N/A	N/A
5.	Test Jig	N/A	N/A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

$$\text{Offset} = \text{RF cable loss} + \text{attenuator factor}.$$

Following shows an offset computation example with cable loss 1.91 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 1.91 + 10 = 11.91 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1%~5% of OBW and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

3.2.4 Test Setup





3.2.5 Test Result of Peak Output Power

2.4GHz Band Single Antenna																	
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail	
					Ant0	Ant1	SUM	Ant0	Ant1	Ant0	Ant1	Ant0	Ant1	Ant0	Ant1		
11b	1Mbps	1	1	2412	26.06	22.91		30.00	30.00	0.73	0.73	26.79	23.64	36.00	36.00	Pass	
11b	1Mbps	1	6	2437	25.64	20.92		30.00	30.00	0.73	0.73	26.37	21.65	36.00	36.00	Pass	
11b	1Mbps	1	11	2462	25.42	20.44		30.00	30.00	0.73	0.73	26.15	21.17	36.00	36.00	Pass	
11g	6Mbps	1	1	2412	24.06	26.26		30.00	30.00	0.73	0.73	24.79	26.99	36.00	36.00	Pass	
11g	6Mbps	1	6	2437	24.97	27.67		30.00	30.00	0.73	0.73	25.70	28.40	36.00	36.00	Pass	
11g	6Mbps	1	11	2462	24.08	26.73		30.00	30.00	0.73	0.73	24.81	27.46	36.00	36.00	Pass	
2.4GHz Band MIMO																	
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail	
					Ant0	Ant1	SUM	Ant0	Ant1	Ant0	Ant1	Ant0	Ant1	Ant0	Ant1		
HT20	MCS0	2	1	2412	19.46	19.17	22.33	30.00		0.73		23.06		36.00		Pass	
HT20	MCS0	2	6	2437	21.47	21.21	24.35	30.00		0.73		25.08		36.00		Pass	
HT20	MCS0	2	11	2462	23.48	23.19	26.35	30.00		0.73		27.08		36.00		Pass	
HT40	MCS0	2	3	2422	24.06	24.92	27.52	30.00		0.73		28.25		36.00		Pass	
HT40	MCS0	2	6	2437	24.47	24.48	27.49	30.00		0.73		28.22		36.00		Pass	
HT40	MCS0	2	9	2452	22.45	21.86	25.18	30.00		0.73		25.91		36.00		Pass	
2.4GHz Band MIMO																	
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
						Ant0	Ant1	SUM	Ant0	Ant1	Ant0	Ant1	Ant0	Ant1	Ant0	Ant1	
HE20	MCS0	2	1	2412	Full	20.28	19.57	22.95	30.00		0.73		23.68		36.00		Pass
HE20	MCS0	2	1	2412	26/0	17.41	15.05	19.40	30.00		0.73		20.13		36.00		Pass
HE20	MCS0	2	1	2412	52/37	19.24	17.46	21.45	30.00		0.73		22.18		36.00		Pass
HE20	MCS0	2	1	2412	106/53	20.28	19.57	22.95	30.00		0.73		23.68		36.00		Pass
HE20	MCS0	2	6	2437	Full	21.55	21.29	24.43	30.00		0.73		25.16		36.00		Pass
HE20	MCS0	2	6	2437	26/0	18.77	17.67	21.27	30.00		0.73		22.00		36.00		Pass
HE20	MCS0	2	6	2437	52/37	21.06	20.32	23.72	30.00		0.73		24.45		36.00		Pass
HE20	MCS0	2	6	2437	106/53	21.51	20.62	24.10	30.00		0.73		24.83		36.00		Pass
HE20	MCS0	2	11	2462	Full	23.62	23.33	26.49	30.00		0.73		27.22		36.00		Pass
HE20	MCS0	2	11	2462	26/8	20.98	20.44	23.73	30.00		0.73		24.46		36.00		Pass
HE20	MCS0	2	11	2462	52/40	22.56	22.20	25.39	30.00		0.73		26.12		36.00		Pass
HE20	MCS0	2	11	2462	106/54	23.54	23.13	26.35	30.00		0.73		27.08		36.00		Pass
HE40	MCS0	2	3	2422	Full	24.21	25.06	27.67	30.00		0.73		28.40		36.00		Pass
HE40	MCS0	2	6	2437	Full	24.62	24.58	27.61	30.00		0.73		28.34		36.00		Pass
HE40	MCS0	2	9	2452	Full	22.56	21.99	25.29	30.00		0.73		26.02		36.00		Pass



3.2.6 Test Result of Average Output Power (Reporting Only)

Table with 20 columns: Mod., Data Rate, NTX, CH., Freq. (MHz), Duty Factor (dB), Average Conducted Power with duty factor (dBm), Conducted Power Limit (dBm), DG (dBi), EIRP Power (dBm), EIRP Power Limit (dBm), Pass/Fail, Setting. Subtitle: 2.4GHz Band Single Antenna.

Table with 20 columns: Mod., Data Rate, NTX, CH., Freq. (MHz), Duty Factor (dB), Average Conducted Power with duty factor (dBm), Conducted Power Limit (dBm), DG (dBi), EIRP Power (dBm), EIRP Power Limit (dBm), Pass/Fail, Setting. Subtitle: 2.4GHz Band MIMO.

Table with 20 columns: Mod., Data Rate, NTX, CH., Freq. (MHz), RU Config., Duty Factor (dB), Average Conducted Power with duty factor (dBm), Conducted Power Limit (dBm), DG (dBi), EIRP Power (dBm), EIRP Power Limit (dBm), Pass/Fail, Setting. Subtitle: 2.4GHz Band MIMO.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01:

Method (b): Measure and sum spectral maxima across the outputs.

The measurement on each individual output were performed with the same span and number on each individual output. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.11
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Please refer to Appendix A.



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

<CDD Modes >

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(N_{ANT}/N_{SS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with G_{ANT} set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain G_{ANT} is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

<CDD Modes>						
	Ant. 0 (dBi)	Ant. 1 (dBi)	DG for Power (dBi)	DG for PSD (dBi)	Power Limit Reduction (dB)	PSD Limit Reduction (dB)
2.4 GHz	0.73	0.73	0.73	3.74	0.00	0.00

Note: 802.11b/g does not support MIMO mode, the DG gain is from the maximum of Ant.0 / Ant.1.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz;Max 30dBm	Oct. 10, 2023	Dec. 18, 2023	Oct. 09, 2024	Radiation (03CH05-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44G,MAX 30dB	Mar. 24, 2023	Dec. 18, 2023	Mar. 23, 2024	Radiation (03CH05-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 10, 2023	Dec. 18, 2023	Oct. 09, 2024	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz~1GHz	Apr. 09, 2023	Dec. 18, 2023	Apr. 08, 2024	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218642	1GHz~18GHz	Apr. 06, 2023	Dec. 18, 2023	Apr. 05, 2024	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101093	18GHz~40GHz	Jan. 08, 2023	Dec. 18, 2023	Jan. 07, 2024	Radiation (03CH05-KS)
Amplifier	SONOMA	310N	380826	9KHz~1GHz	Jul. 06, 2023	Dec. 18, 2023	Jul. 05, 2024	Radiation (03CH05-KS)
Amplifier	EM	EM18G40GA	060852	18~40GHz	Jan. 05, 2023	Dec. 18, 2023	Jan. 04, 2024	Radiation (03CH05-KS)
high gain Amplifier	EM	EM01G18GA	060839	1Ghz~18Ghz	Oct. 10, 2023	Dec. 18, 2023	Oct. 09, 2024	Radiation (03CH05-KS)
Amplifier	EM	EM01G18GA	060833	1Ghz~18Ghz	Jan. 05, 2023	Dec. 18, 2023	Jan. 04, 2024	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Dec. 18, 2023	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Dec. 18, 2023	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Dec. 18, 2023	NCR	Radiation (03CH05-KS)
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	May 16, 2023	Oct. 19, 2023	May 15, 2024	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 11, 2023	Oct. 19, 2023	Oct. 10, 2024	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	May 16, 2023	Oct. 19, 2023	May 15, 2024	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000811	AC 0V~300V, 45Hz~1000Hz	Oct. 11, 2023	Oct. 19, 2023	Oct. 10, 2024	Conduction (CO01-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	May 16, 2023	Dec. 16, 2023~Dec. 21, 2023	May 15, 2024	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 05, 2023	Dec. 16, 2023~Dec. 21, 2023	Jan. 04, 2024	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 05, 2023	Dec. 16, 2023~Dec. 21, 2023	Jan. 04, 2024	Conducted (TH01-KS)

NCR: No Calibration Required



5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	±2.26 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.46 dB
Conducted Power Spectral Density	±0.88 dB
Frequency	±0.4 Hz

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.94 dB
---	---------

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.30 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.28 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.88 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.26 dB
---	---------

----- THE END -----



Appendix A. Conducted Test Results



Ambient Condition: <u>25 °C, 45 %RH</u>
Test Date: <u>2023/12/16~2023/12/21</u> Test Engineer: <u>Rise Liu</u>


DTS Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	7.56	2408.00	2415.56	0.5	PASS
	Ant2	2412	7.52	2408.00	2415.52	0.5	PASS
	Ant1	2437	7.12	2433.44	2440.56	0.5	PASS
	Ant2	2437	7.56	2433.00	2440.56	0.5	PASS
	Ant1	2462	8.04	2458.00	2466.04	0.5	PASS
	Ant2	2462	7.56	2458.00	2465.56	0.5	PASS
11G	Ant1	2412	15.44	2404.12	2419.56	0.5	PASS
	Ant2	2412	15.32	2404.48	2419.80	0.5	PASS
	Ant1	2437	15.12	2429.44	2444.56	0.5	PASS
	Ant2	2437	15.12	2429.44	2444.56	0.5	PASS
	Ant1	2462	15.04	2454.48	2469.52	0.5	PASS
	Ant2	2462	15.32	2454.44	2469.76	0.5	PASS
11N20MIMO	Ant1	2412	15.20	2404.36	2419.56	0.5	PASS
	Ant2	2412	15.84	2403.80	2419.64	0.5	PASS
	Ant1	2437	15.60	2428.96	2444.56	0.5	PASS
	Ant2	2437	15.48	2429.08	2444.56	0.5	PASS
	Ant1	2462	15.12	2454.44	2469.56	0.5	PASS
	Ant2	2462	15.12	2454.44	2469.56	0.5	PASS
11N40MIMO	Ant1	2422	35.12	2404.48	2439.60	0.5	PASS
	Ant2	2422	35.12	2404.48	2439.60	0.5	PASS
	Ant1	2437	35.12	2419.48	2454.60	0.5	PASS
	Ant2	2437	35.12	2419.48	2454.60	0.5	PASS
	Ant1	2452	35.12	2434.48	2469.60	0.5	PASS
	Ant2	2452	35.12	2434.48	2469.60	0.5	PASS
11AX20MIMO	Ant1	2412	15.12	2404.44	2419.56	0.5	PASS
	Ant2	2412	17.36	2403.56	2420.92	0.5	PASS
	Ant1	2437	15.12	2429.48	2444.60	0.5	PASS
	Ant2	2437	16.52	2428.08	2444.60	0.5	PASS
	Ant1	2462	15.68	2453.92	2469.60	0.5	PASS
	Ant2	2462	16.04	2454.44	2470.48	0.5	PASS
11AX40MIMO	Ant1	2422	35.20	2404.40	2439.60	0.5	PASS
	Ant2	2422	35.12	2404.48	2439.60	0.5	PASS
	Ant1	2437	35.12	2419.48	2454.60	0.5	PASS
	Ant2	2437	35.12	2419.48	2454.60	0.5	PASS
	Ant1	2452	35.12	2434.48	2469.60	0.5	PASS
	Ant2	2452	35.12	2434.48	2469.60	0.5	PASS




Test Graphs






11B_Ant1_2437




11B_Ant2_2437






11B_Ant1_2462



Date: 16.DEC.2023 00:51:52


11B_Ant2_2462



Date: 16.DEC.2023 00:59:38




11G_Ant1_2412



Date: 16.DEC.2023 00:53:29


11G_Ant2_2412



Date: 16.DEC.2023 01:01:57




11G_Ant1_2437



Date: 16.DEC.2023 00:54:59


11G_Ant2_2437



Date: 16.DEC.2023 01:03:16




11G_Ant1_2462



Date: 16.DEC.2023 00:56:00


11G_Ant2_2462



Date: 16.DEC.2023 01:04:19




11N20MIMO_Ant1_2412



Date: 21 DEC.2023 09:37:00


11N20MIMO_Ant2_2412



Date: 21 DEC.2023 09:38:17




11N20MIMO_Ant1_2437



Date: 21 DEC.2023 09:40:00


11N20MIMO_Ant2_2437



Date: 21 DEC.2023 09:41:15




11N20MIMO_Ant1_2462



Date: 21 DEC.2023 09:42:49


11N20MIMO_Ant2_2462



Date: 21 DEC.2023 09:44:07




11N40MIMO_Ant1_2422



Date: 21 DEC.2023 09:47:53


11N40MIMO_Ant2_2422



Date: 21 DEC.2023 09:49:23




11N40MIMO_Ant1_2437



Date: 21 DEC.2023 09:52:52


11N40MIMO_Ant2_2437



Date: 21 DEC.2023 09:54:26




11N40MIMO_Ant1_2452



Date: 21 DEC.2023 09:55:57


11N40MIMO_Ant2_2452



Date: 21 DEC.2023 09:57:28




11AX20MIMO_Ant1_2412



Date: 16.DEC.2023 08:28:41


11AX20MIMO_Ant2_2412



Date: 16.DEC.2023 08:30:54




11AX20MIMO_Ant1_2437



Date: 16.DEC.2023 08:32:33


11AX20MIMO_Ant2_2437



Date: 16.DEC.2023 08:34:11




11AX20MIMO_Ant1_2462



Date: 16.DEC.2023 08:35:37


11AX20MIMO_Ant2_2462



Date: 16.DEC.2023 08:37:07




11AX40MIMO_Ant1_2422



Date: 16.DEC.2023 08:39:20


11AX40MIMO_Ant2_2422



Date: 16.DEC.2023 08:41:00




11AX40MIMO_Ant1_2437



Date: 16.DEC.2023 08:42:52


11AX40MIMO_Ant2_2437



Date: 16.DEC.2023 08:44:16




11AX40MIMO_Ant1_2452



Date: 16.DEC.2023 08:46:07

11AX40MIMO_Ant2_2452



Date: 16.DEC.2023 08:47:39




Occupied Channel Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]
11B	Ant1	2412	11.908	2406.0859	2417.9940
	Ant2	2412	11.149	2406.4056	2417.5544
	Ant1	2437	11.788	2431.1658	2442.9540
	Ant2	2437	11.149	2431.4456	2442.5944
	Ant1	2462	11.828	2456.1658	2467.9940
	Ant2	2462	11.189	2456.4056	2467.5944
11G	Ant1	2412	17.143	2403.3686	2420.5115
	Ant2	2412	17.103	2403.4086	2420.5115
	Ant1	2437	17.463	2428.2887	2445.7512
	Ant2	2437	17.103	2428.4486	2445.5514
	Ant1	2462	17.063	2453.4885	2470.5514
	Ant2	2462	17.143	2453.4086	2470.5514
11N20MIMO	Ant1	2412	18.022	2402.9690	2420.9910
	Ant2	2412	18.062	2402.9291	2420.9910
	Ant1	2437	18.182	2427.8492	2446.0310
	Ant2	2437	18.022	2427.9690	2445.9910
	Ant1	2462	17.942	2452.9291	2470.8711
	Ant2	2462	18.022	2453.0490	2471.0709
11N40MIMO	Ant1	2422	36.763	2403.6983	2440.4615
	Ant2	2422	36.284	2403.8581	2440.1419
	Ant1	2437	36.603	2418.6983	2455.3017
	Ant2	2437	36.364	2418.8581	2455.2218
	Ant1	2452	36.683	2433.6983	2470.3816
	Ant2	2452	36.284	2433.8581	2470.1419
11AX20MIMO	Ant1	2412	19.021	2402.4895	2421.5105
	Ant2	2412	19.021	2402.4895	2421.5105
	Ant1	2437	19.021	2427.4895	2446.5105
	Ant2	2437	19.021	2427.4895	2446.5105
	Ant1	2462	19.061	2452.4496	2471.5105
	Ant2	2462	19.061	2452.4895	2471.5504
11AX40MIMO	Ant1	2422	37.962	2402.9790	2440.9411
	Ant2	2422	37.802	2403.0589	2440.8611
	Ant1	2437	37.802	2418.1389	2455.9411
	Ant2	2437	37.722	2418.1389	2455.8611
	Ant1	2452	37.882	2433.0589	2470.9411
	Ant2	2452	37.802	2433.0589	2470.8611




Test Graphs






11B_Ant1_2437



Date: 16.DEC.2023 00:50:33


11B_Ant2_2437



Date: 16.DEC.2023 00:58:41




11B_Ant1_2462



Date: 16.DEC.2023 00:51:58


11B_Ant2_2462



Date: 16.DEC.2023 00:59:44




11G_Ant1_2412



Date: 16.DEC.2023 00:53:36


11G_Ant2_2412



Date: 16.DEC.2023 01:02:03




11G_Ant1_2437



Date: 16.DEC.2023 00:55:05


11G_Ant2_2437



Date: 16.DEC.2023 01:03:22




11G_Ant1_2462



Date: 16.DEC.2023 00:56:06


11G_Ant2_2462



Date: 16.DEC.2023 01:04:25




11N20MIMO_Ant1_2412



Date: 21 DEC.2023 09:37:05


11N20MIMO_Ant2_2412



Date: 21 DEC.2023 09:38:23




11N20MIMO_Ant1_2437



Date: 21 DEC.2023 09:40:05


11N20MIMO_Ant2_2437



Date: 21 DEC.2023 09:41:20




11N20MIMO_Ant1_2462



Date: 21 DEC.2023 09:42:54


11N20MIMO_Ant2_2462



Date: 21 DEC.2023 09:44:14




11N40MIMO_Ant1_2422



Date: 21 DEC. 2023 09:47:59


11N40MIMO_Ant2_2422



Date: 21 DEC. 2023 09:49:29




11N40MIMO_Ant1_2437



Date: 21 DEC. 2023 09:52:57


11N40MIMO_Ant2_2437



Date: 21 DEC. 2023 09:54:31




11N40MIMO_Ant1_2452



Date: 21 DEC.2023 09:56:03


11N40MIMO_Ant2_2452



Date: 21 DEC.2023 09:57:33




11AX20MIMO_Ant1_2412



Date: 16.DEC.2023 08:28:47


11AX20MIMO_Ant2_2412



Date: 16.DEC.2023 08:31:00




11AX20MIMO_Ant1_2437



Date: 16.DEC.2023 08:32:39


11AX20MIMO_Ant2_2437



Date: 16.DEC.2023 08:34:17




11AX20MIMO_Ant1_2462



Date: 16.DEC.2023 08:35:43


11AX20MIMO_Ant2_2462



Date: 16.DEC.2023 08:37:13




11AX40MIMO_Ant1_2422



Date: 16.DEC.2023 08:39:26


11AX40MIMO_Ant2_2422



Date: 16.DEC.2023 08:41:06




11AX40MIMO_Ant1_2437



Date: 16.DEC.2023 08:42:58


11AX40MIMO_Ant2_2437



Date: 16.DEC.2023 08:44:21




11AX40MIMO_Ant1_2452



Date: 16.DEC.2023 08:46:13

11AX40MIMO_Ant2_2452



Date: 16.DEC.2023 08:47:45




Maximum power spectral density

Test Result

TestMode	Antenna	Freq(MHz)	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
11B	Ant1	2412	0.65	≤8.00	PASS
	Ant2	2412	-2.02	≤8.00	PASS
	Ant1	2437	0.02	≤8.00	PASS
	Ant2	2437	-4.34	≤8.00	PASS
	Ant1	2462	0.23	≤8.00	PASS
	Ant2	2462	-4.7	≤8.00	PASS
11G	Ant1	2412	-8.57	≤8.00	PASS
	Ant2	2412	-7.22	≤8.00	PASS
	Ant1	2437	-7.55	≤8.00	PASS
	Ant2	2437	-4.35	≤8.00	PASS
	Ant1	2462	-11.07	≤8.00	PASS
	Ant2	2462	-8.03	≤8.00	PASS
11N20MIMO	Ant1	2412	-16.71	≤8.00	PASS
	Ant2	2412	-16.58	≤8.00	PASS
	total	2412	-13.63	≤8.00	PASS
	Ant1	2437	-17.12	≤8.00	PASS
	Ant2	2437	-15.23	≤8.00	PASS
	total	2437	-13.06	≤8.00	PASS
	Ant1	2462	-13.63	≤8.00	PASS
	Ant2	2462	-13.46	≤8.00	PASS
	total	2462	-10.53	≤8.00	PASS
11N40MIMO	Ant1	2422	-15.53	≤8.00	PASS
	Ant2	2422	-14.22	≤8.00	PASS
	total	2422	-11.82	≤8.00	PASS
	Ant1	2437	-15.59	≤8.00	PASS
	Ant2	2437	-12.74	≤8.00	PASS
	total	2437	-10.92	≤8.00	PASS
	Ant1	2452	-14.71	≤8.00	PASS
	Ant2	2452	-14.02	≤8.00	PASS
	total	2452	-11.34	≤8.00	PASS
11AX20MIMO	Ant1	2412	-17.91	≤8.00	PASS
	Ant2	2412	-16.83	≤8.00	PASS
	total	2412	-14.33	≤8.00	PASS
	Ant1	2437	-15.49	≤8.00	PASS
	Ant2	2437	-13.8	≤8.00	PASS
	total	2437	-11.55	≤8.00	PASS
	Ant1	2462	-12.88	≤8.00	PASS
	Ant2	2462	-14.03	≤8.00	PASS
	total	2462	-10.41	≤8.00	PASS
11AX40MIMO	Ant1	2422	-14.46	≤8.00	PASS
	Ant2	2422	-13.91	≤8.00	PASS
	total	2422	-11.17	≤8.00	PASS
	Ant1	2437	-14.05	≤8.00	PASS
	Ant2	2437	-12.72	≤8.00	PASS
	total	2437	-10.32	≤8.00	PASS
	Ant1	2452	-17.14	≤8.00	PASS
	Ant2	2452	-17.57	≤8.00	PASS
	total	2452	-14.34	≤8.00	PASS




Test Graphs






11B_Ant1_2437



Date: 16.DEC.2023 00:51:38


11B_Ant2_2437




Date: 16.DEC.2023 00:58:52



11B_Ant1_2462




11B_Ant2_2462






11G_Ant1_2412



Date: 16.DEC.2023 00:53:47

11G_Ant2_2412



Date: 16.DEC.2023 01:02:14