

# **RF Test Report**

**Applicant:** Quectel Wireless Solutions Co., Ltd.

Address:

Building 5, Shanghai Business Park Phase III (Area B), No.1016

Tianlin Road, Minhang District, Shanghai, 200233, China

**Product:** Wi-Fi & Bluetooth Module

Model No.: FCS852R

**Brand Name:** QUECTEL

FCC ID: XMR2023FCS852R

Standards: FCC CFR47 Part 2.1091

**Report No.:** PD20230218RF13

**Issue Date:** 2024/03/01

Test Result: PASS \*

\* The above equipment has been tested and compliance with the requirement of the relative standards by Hefei Panwin Technology Co., Ltd.

Stee Jung

Reviewed By: Charlie Wang Approved By: Alec Yang

Charlie. Wang

## Hefei Panwin Technology Co., Ltd.

Floor 1, Zone E, Plant 2#, Mingzhu Industrial Park, No.106 Chuangxin Avenue, High-tech Zone, Hefei City, Anhui Province, China

TEL: +86-0551-63811775

## **Test Report**

Report No.: PD20230218RF13

Report Version: 01

#### **Revision History**

Report No.	Version	Description	Issue Date	Note	
PD20230218RF13 01		Initial Report	2024/03/01	Valid	

#### Remark:

We, Hefei Panwin Technology Co., Ltd., would like to declare that the tested sample has been evaluated in accordance with the procedures given in FCC CFR47 Part 2.1091 and shown compliance with the applicable technical standards. The evaluation related to FCC CFR47 Part 2 is not within the scope of A2LA accreditation.

# **Test Report**

Report No.: PD20230218RF13

Report Version: 01

#### **CONTENTS**

l Test Laboratory	
1.1 Notes of the Test Report	4
2 General Description of Equipment under Test	
2.1 Details of Application	
2.2 Details of EUT	5
3 Test Condition	6
3.1 Laboratory Environment	ε
Maximum Permissible Exposure (EMF)	7
Appendix A – Test Results	8
Appendix B – The EUT Appearance	9

Report Version: 01

#### 1 Test Laboratory

#### 1.1 Notes of the Test Report

This report is invalid without signature of auditor and approver or with any alterations. The report shall not be partially reproduced without written approval of the testing company. Entrusted test results are only responsible for incoming samples. If there is any objection to the testing report, it shall be raised to the testing company within 15 days from the date of receiving the report. In the test results, "NA" means "not applicable", and the test items marked with " $\Delta$ " are subcontracted projects.

#### 1.2 Testing Laboratory

Company Name	Hefei Panwin Technology Co., Ltd.		
Address Floor 1, Zone E, Plant 2#, Mingzhu Industrial Park, No.106 ( Avenue, High-tech Zone, Hefei City, Anhui Province, China			
Telephone	+86-0551-63811775		
Post Code	230031		

## 2 General Description of Equipment under Test

#### 2.1 Details of Application

Applicant	Quectel Wireless Solutions Co., Ltd.		
Applicant Address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin		
Applicant Address	Road, Minhang District, Shanghai, 200233, China		
Manufacturer	Quectel Wireless Solutions Co., Ltd.		
Manufactura Addus a	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin		
Manufacturer Address	Road, Minhang District, Shanghai, 200233, China		

Report Version: 01

#### 2.2 Details of EUT

Product	Wi-Fi & Bluetooth Module		
Model	FCS852R		
HW Version	R1.0		
SW Version	NA		
Antenna Type	External Antenna		
	Bluetooth		
	Bluetooth LE		
Mode of Operation	Wi-Fi 2.4G		
	Wi-Fi 5G		
	Bluetooth: 8.82dBm		
	Bluetooth LE: 8.10dBm		
Max. Conducted Power	Wi-Fi 2.4G: 18.85dBm		
	Wi-Fi 5G: 19.28dBm		
	Bluetooth & Bluetooth LE & Wi-Fi 2.4G: -0.10dBi		
	Wi-Fi 5G: 5150MHz to 5250MHz: -0.90dBi		
Max Gain	Wi-Fi 5G: 5250MHz to 5350MHz: -1.40dB		
	Wi-Fi 5G: 5470MHz to 5725MHz: -0.30dBi		
	Wi-Fi 5G: 5725MHz to 5850MHz: 0.40dBi		
Beamforming Gain	NA		
Rated Power Supply Voltage Typical 3.3V			

**Note:** The declared of product specification for EUT and/or Antenna presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Report Version: 01

#### **3 Test Condition**

#### 3.1 Laboratory Environment

Temperature	Min.= 18℃, Max.=25℃		
Relative Humidity	Min.= 30%, Max.=70%		
Ground System Resistance	< 1 Ω		

- Ambient noise is checked and found very low and in compliance with requirement of standards.
- Reflection of surrounding objects is minimized and in compliance with requirement of standards.

Report Version: 01

### 4 Maximum Permissible Exposure (EMF)

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
	(A) Limits for Oc	ccupational/Controlled Expos	sures	
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/	4.89/	f *(900/f2)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
	(B) Limits for Gene	ral Population/Uncontrolled I	Exposure	
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/	2.19/1	f *(180/f2)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

 $S = PG/4\Pi R^2$ 

Where:

**S** = Power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

**P** = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = The numeric gain of the antenna

**R** = Distance to the center of radiation of the antenna (20 cm = limit for MPE)

Report Version: 01

## Appendix A - Test Results

#### A.1 Maximum Measured Conducted Output Power and Antenna Gain

Band	TX Freq. (MHz)	Max. Conducted Power (dBm)	Antenna Gain (dBi)	
Bluetooth	2402 to 2480	8.82	-0.10	
Bluetooth LE	2402 to 2480	8.10	-0.10	
Wi-Fi 2.4G	2412 to 2462	18.85	-0.10	
Wi-Fi 5G	5150 to 5850	19.28	0.40	

#### A.2 Test Results of Maximum Permissible Exposure

Band	Max. Co Power		Antenna Gain	Maximum EIRP(dBm)			Test Result	Limit Value
	(dBm)	(mW)	(dBi)		(mW)	(mW/cm <sup>2</sup> )	(mW/cm²)	
Bluetooth	8.82	7.62	-0.10	8.72	7.45	0.001	1.000	
Bluetooth LE	8.10	6.46	-0.10	8.00	6.31	0.001	1.000	
Wi-Fi 2.4G	18.85	76.74	-0.10	18.75	74.99	0.015	1.000	
Wi-Fi 5G	19.28	84.72	0.40	19.68	92.90	0.018	1.000	

**Note**: For mobile or fixed location transmitters, minimum separation distance is 20cm, even if calculations indicate EMF distance is less. The EUT does not support simultaneous operation of BT, Wi-Fi 2.4G, and Wi-Fi 5G.

#### **Conclusion:**

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

## **Test Report**

Report No.: PD20230218RF13

Report Version: 01

## Appendix B – The EUT Appearance

Refer to "Attachment 1: External Photograph" and "Attachment 2: Internal Photograph" file.

\*\*\*\*\* End of the Report \*\*\*\*\*