



FCC RF Test Report

APPLICANT : Quetel Wireless Solutions Co., Ltd.
EQUIPMENT : Wi-Fi & Bluetooth Module
BRAND NAME : QUECTEL
MODEL NAME : FCU760K
FCC ID : XMR2023FCU760K
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure
TEST DATE(S) : Jul. 14, 2023 ~ Aug. 23, 2023

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant 5

 1.2 Manufacturer..... 5

 1.3 Product Feature of Equipment Under Test..... 5

 1.4 Product Specification of Equipment Under Test..... 6

 1.5 Modification of EUT 7

 1.6 Testing Location 8

 1.7 Test Software..... 8

 1.8 Applicable Standards..... 8

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 9

 2.1 Carrier Frequency and Channel 9

 2.2 Test Mode..... 10

 2.3 Connection Diagram of Test System..... 12

 2.4 Support Unit used in test configuration and system 13

 2.5 EUT Operation Test Setup 13

 2.6 Measurement Results Explanation Example..... 13

3 TEST RESULT 14

 3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement 14

 3.2 Maximum Conducted Output Power Measurement 16

 3.3 Power Spectral Density Measurement 18

 3.4 Unwanted Emissions Measurement 21

 3.5 AC Conducted Emission Measurement..... 26

 3.6 Antenna Requirements 28

4 LIST OF MEASURING EQUIPMENT 29

5 MEASUREMENT UNCERTAINTY 30

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. AC CONDUCTED EMISSION TEST RESULT

APPENDIX C. RADIATED SPURIOUS EMISSION

APPENDIX D. DUTY CYCLE PLOTS

APPENDIX E. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit for U-NII-1/2A/2C	Limit for U-NII-3	Result	Remark
3.1	2.1049 & 15.403(i)	6dB, 26dB & 99% Bandwidth	-	6dB Bandwidth > 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 24 dBm	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 11 dBm/MHz	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b) & 15.209(a)	15.407(b)(4)(i) & 15.209(a)	Pass	Under limit 3.15 dB at 5149.87 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	15.207(a)	Pass	Under limit 11.29 dB at 0.151 MHz
3.6	15.203 & 15.407(a)	Antenna Requirement	N/A	N/A	Pass	-

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Quectel Wireless Solutions Co., Ltd.

Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai 200233, China

1.2 Manufacturer

Quectel Wireless Solutions Co., Ltd.

Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai 200233, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Wi-Fi & Bluetooth Module
Brand Name	QUECTEL
Model Name	FCU760K
FCC ID	XMR2023FCU760K
SN Code	Conducted: E1M23EA09000084 Conduction: E1M23EA09000096 Radiation: E1M23EA09000091
HW Version	R1.0
SW Version	NA
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	5180 MHz ~ 5240 MHz 5260 MHz ~ 5320 MHz 5500 MHz ~ 5700 MHz 5745 MHz ~ 5825 MHz
Maximum Output Power to Antenna	<p><5180 MHz ~ 5240 MHz> 802.11a : 16.79 dBm / 0.0478 W 802.11n HT20 : 16.19 dBm / 0.0416 W 802.11n HT40 : 15.77 dBm / 0.0378 W 802.11ac VHT20: 16.02 dBm / 0.0400 W 802.11ac VHT40: 15.74 dBm / 0.0375 W 802.11ac VHT80: 9.97 dBm / 0.0099 W 802.11ax HE20: 16.20 dBm / 0.0417 W 802.11ax HE40: 15.80 dBm / 0.0380 W 802.11ax HE80: 10.05 dBm / 0.0101 W</p> <p><5260 MHz ~ 5320 MHz> 802.11a : 17.14 dBm / 0.0518 W 802.11n HT20 : 16.00 dBm / 0.0398 W 802.11n HT40 : 15.48 dBm / 0.0353 W 802.11ac VHT20: 15.78 dBm / 0.0378 W 802.11ac VHT40: 15.43 dBm / 0.0349 W 802.11ac VHT80: 10.29 dBm / 0.0107 W 802.11ax HE20: 16.12 dBm / 0.0409 W 802.11ax HE40: 15.49 dBm / 0.0354 W 802.11ax HE80: 10.38 dBm / 0.0109 W</p> <p><5500 MHz ~ 5700 MHz > 802.11a : 16.10 dBm / 0.0407 W 802.11n HT20 : 15.67 dBm / 0.0369 W 802.11n HT40 : 15.96 dBm / 0.0394 W 802.11ac VHT20: 15.61 dBm / 0.0364 W 802.11ac VHT40: 16.05 dBm / 0.0403 W 802.11ac VHT80: 13.01 dBm / 0.0200 W 802.11ax HE20: 15.77 dBm / 0.0378 W 802.11ax HE40: 16.11 dBm / 0.0408 W 802.11ax HE80: 13.23 dBm / 0.0210 W</p> <p><5745 MHz ~ 5825 MHz> 802.11a : 15.47 dBm / 0.0352 W 802.11n HT20 : 15.02 dBm / 0.0318 W 802.11n HT40 : 14.75 dBm / 0.0299 W 802.11ac VHT20: 15.17 dBm / 0.0329 W 802.11ac VHT40: 15.17 dBm / 0.0329 W 802.11ac VHT80: 15.03 dBm / 0.0318 W 802.11ax HE20: 15.25 dBm / 0.0335 W 802.11ax HE40: 15.25 dBm / 0.0335 W 802.11ax HE80: 15.25 dBm / 0.0335 W</p>



<p>99% Occupied Bandwidth</p>	<p><5180 MHz ~ 5240 MHz> 802.11a : 18.382 MHz 802.11ax HE20: 19.620 MHz 802.11ax HE40: 38.601 MHz 802.11ax HE80: 77.842 MHz <5260 MHz ~ 5320 MHz> 802.11a : 19.141 MHz 802.11ax HE20: 19.780 MHz 802.11ax HE40: 38.761 MHz 802.11ax HE80: 78.322 MHz <5500 MHz ~ 5700 MHz> 802.11a : 18.701 MHz 802.11ax HE20: 19.940 MHz 802.11ax HE40: 38.761 MHz 802.11ax HE80: 78.641 MHz <5745 MHz ~ 5825 MHz> 802.11a : 18.462 MHz 802.11ax HE20: 19.900 MHz 802.11ax HE40: 38.761 MHz 802.11ax HE80: 78.482 MHz</p>
<p>Antenna Type / Gain</p>	<p><5180 MHz ~ 5240 MHz> Dipole Antenna with gain 1.14 dBi <5260 MHz ~ 5320 MHz> Dipole Antenna with gain 1.00 dBi <5500 MHz ~ 5700 MHz> Dipole Antenna with gain 0.60 dBi <5745 MHz ~ 5825 MHz> Dipole Antenna with gain 0.95 dBi</p>
<p>Type of Modulation</p>	<p>802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac/ax : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM)</p>

Note:

1. WLAN operation in 5600 MHz ~ 5650 MHz is notched.
2. For 802.11n/ac & 802.11ax mode, the whole testing have assessed only 802.11ax HE20/40/80 by referring to the higher output power.
3. 802.11ax support full RU tone and partial RU tone, both full RU and partial RU-left (for low CH) and partial RU-right (for high CH) are tested for conducted power/PSD/RSE, the full RU power > partial RU, therefore the full RU perform full test and Partial RU verified power/PSD/RSE

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

<FCC>-KS

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH08-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH08-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5180-5240 MHz U-NII-1	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	42 [#]	5210		

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5260-5320 MHz U-NII-2A	52	5260	60	5300
	54*	5270	62*	5310
	56	5280	64	5320
	58 [#]	5290		

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5500-5700MHz U-NII-2C	100	5500	112	5560
	102*	5510	116	5580
	104	5520	132	5660
	106 [#]	5530	134*	5670
	108	5540	136	5680
	110*	5550	140	5700

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5745-5825 MHz U-NII-3	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825



Note:

1. The above Frequency and Channel in "" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "" were 802.11ac VHT80.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11ax HE80	MCS0

AC Conducted Emission	Mode 1 : WLAN Link(5G)+ USB Cable(Charging From Notebook)
Remark: For Radiated Test Cases, the tests were performance with Adapter	

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		802.11a	802.11a	802.11a	802.11a
L	Low	36	52	100	149
M	Middle	44	60	116	157
H	High	48	64	140	165

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		802.11n HT20	802.11n HT20	802.11n HT20	802.11n HT20
L	Low	36	52	100	149
M	Middle	44	60	116	157
H	High	48	64	140	165



Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		802.11n HT40	802.11n HT40	802.11n HT40	802.11n HT40
L	Low	38	54	102	151
M	Middle	-	-	110	-
H	High	46	62	134	159

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		802.11ac VHT80	802.11ac VHT80	802.11ac VHT80	802.11ac VHT80
L	Low	-	-	106	-
M	Middle	42	58	-	155
H	High	-	-	-	-


Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		802.11ax HE20	802.11ax HE20	802.11ax HE20	802.11ax HE20
L	Low	36	52	100	149
M	Middle	44	60	116	157
H	High	48	64	140	165

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		802.11ax HE40	802.11ax HE40	802.11ax HE40	802.11ax HE40
L	Low	38	54	102	151
M	Middle	-	-	110	-
H	High	46	62	134	159


Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		802.11ax HE80	802.11ax HE80	802.11ax HE80	802.11ax HE80
L	Low	-	-	106	-
M	Middle	42	58	-	155
H	High	-	-	-	-

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:





2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
2.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
3.	Hard Disk	Lenovo	F310	DoC	Shielded, 1.2m	N/A
4.	Test Jig	N/A	N/A	N/A	N/A	N/A
5.	Adapter	N/A	N/A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 3.88 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 3.88 + 10 = 13.88 \text{ (dB)}
 \end{aligned}$$



3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

3.1.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

- The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

<input checked="" type="checkbox"/>	Section C) Bandwidth Measurement 1. Emission Bandwidth (EBW) and 99% OBW
	<ol style="list-style-type: none"> Set RBW = approximately 1% of the emission bandwidth. Set the VBW > RBW. Detector = Peak. Trace mode = max hold Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set to 1%~5% of the OBW and set the Video bandwidth (VBW) ≥ 3 * RBW. Measure and record the results in the test report.
<input checked="" type="checkbox"/>	Section C) Bandwidth Measurement 2. Minimum Emission Bandwidth for the band 5.725 - 5.85 GHz
	<ol style="list-style-type: none"> Set RBW = 100kHz. Set the VBW ≥ 3 x RBW. Detector = Peak. Trace mode = max hold Measure the maximum width of the emission that is 6 dB down from the peak of the emission. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.



3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW.

For the 5.25–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note that U-NII-2 band, devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

For the 5.25–5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.



3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04. Section F) Maximum power spectral density.

For devices operating in the bands 5.15 - 5.25 GHz, 5.25 - 5.35 GHz, and 5.47 - 5.725 GHz

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz.
- Set VBW \geq 3 MHz.
- Number of points in sweep \geq 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

For devices operating in the band 5.725 - 5.85 GHz

Method SA-2


(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 500KHz (or 300 kHz if the SA can't set RBW=500KHz).
- Set VBW \geq 1 MHz.
- Number of points in sweep \geq 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- If the SA can't set RBW=500KHz, then add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the

average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part 15.205.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27dBm/MHz .

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz . Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.

For transmitters operating in the 5470-5600 MHz and 5650-5725MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725MHz band shall not exceed an EIRP of -27 dBm/MHz .

- (2) For transmitters operating in the 5.725-5.85 GHz band:
15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.



(3) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

(4) EIRP (dBm)	Field Strength at 3m (dBµV/m)
- 27	68.2

Note: The following formula is used to convert the EIRP to field strength.

$$EIRP = E_{Meas} + 20\log (d_{Meas}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBµV/m

d_{Meas} is the measurement distance, in m

(4) ANSI C63.10-2013 clause 12.7.3 note 97

As specified by regulatory requirements, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit. However, an out-of-band emission that complies with both the average and peak general regulatory limits is not required to satisfy the peak emission limit.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.



3.4.3 Test Procedures


1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04. Section G) Unwanted emissions measurement.
 - (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
 - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW \geq 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
 - (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW \geq 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
 - (4) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 3 MHz
 - Detector = power averaging (rms), set span/(# of points in sweep) \geq RBW/2.
 - Averaging type = power averaging(RMS)
 - The correction factor shall be offset is 10 log (1/x), where x is the duty cycle.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal

polarization and vertical polarization of the antenna.


5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix C.



3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Antenna Requirements

3.6.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2), if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 12, 2022	Jul. 14, 2023~ Aug. 08, 2023	Oct. 11, 2023	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 05, 2023	Jul. 14, 2023~ Aug. 08, 2023	Jan. 04, 2024	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 05, 2023	Jul. 14, 2023~ Aug. 08, 2023	Jan. 04, 2024	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 06, 2023	Jul. 14, 2023~ Aug. 08, 2023	Jul. 05, 2024	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400023	3Hz~8.5GHz;Max 30dBm	Jan. 05, 2023	Aug. 23, 2023	Jan. 04, 2024	Radiation (03CH08-KS)
Spectrum Analyzer	R&S	FSV40	101932	10kHz~40GHz;Max 30dBm	Oct. 12, 2022	Aug. 23, 2023	Oct. 11, 2023	Radiation (03CH08-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 22, 2022	Aug. 23, 2023	Sep. 21, 2023	Radiation (03CH08-KS)
Bilog Antenna	TESEQ& VGT	CBL 61110	59915	30MHz~1GHz	Aug. 12, 2023	Aug. 23, 2023	Aug. 11, 2024	Radiation (03CH08-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Mar. 18, 2023	Aug. 23, 2023	Mar. 17, 2024	Radiation (03CH08-KS)
high gain Amplifier	EM	EM01G18GA	060845	1Ghz-18Ghz	Jan. 05, 2023	Aug. 23, 2023	Jan. 04, 2024	Radiation (03CH08-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 08, 2023	Aug. 23, 2023	Jan. 07, 2024	Radiation (03CH08-KS)
Amplifier	SONOMA	310N	413741	9KHz-1GHz	Jan. 05, 2023	Aug. 23, 2023	Jan. 04, 2024	Radiation (03CH08-KS)
Amplifier	EM	EM01G18GA	060834	1Ghz-18Ghz	Oct. 12, 2022	Aug. 23, 2023	Oct. 11, 2023	Radiation (03CH08-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 05, 2023	Aug. 23, 2023	Jan. 04, 2024	Radiation (03CH08-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Aug. 23, 2023	NCR	Radiation (03CH08-KS)
Turn Table	EM	EM 1000-T	N/A	0~360 degree	NCR	Aug. 23, 2023	NCR	Radiation (03CH08-KS)
Antenna Mast	EM	EM 1000-A	N/A	1 m~4 m	NCR	Aug. 23, 2023	NCR	Radiation (03CH08-KS)
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	May 16, 2023	Jul. 14, 2023	May 15, 2024	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2022	Jul. 14, 2023	Oct. 12, 2023	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	May 16, 2023	Jul. 14, 2023	May 15, 2024	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2022	Jul. 14, 2023	Oct. 11, 2023	Conduction (CO01-KS)

NCR: No Calibration Required



5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	±0.46 dB
Conducted Emissions	±2.26 dB
Occupied Channel Bandwidth	±0.1 %
Conducted Power Spectral Density	±0.88 dB

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.94 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.28 dB
---	---------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.90 dB
---	---------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.26 dB
---	---------



Appendix A. Conducted Test Results

Report Number : FR351906D

Test Engineer:	Long Wu	Temperature:	21~25	°C
Test Date:	2023.7.14~2023.8.8	Relative Humidity:	51~54	%

TEST RESULTS DATA
Average Power Table

FCC U-NII-1 single antenna											
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail	Power Setting
					Ant 1	Ant 1	Ant 1	Ant 1			
11a	6Mbps	1	36	5180	2.40	14.03	24.00	1.14		Pass	15.5
11a	6Mbps	1	44	5220	2.40	16.30	24.00	1.14		Pass	17
11a	6Mbps	1	48	5240	2.40	16.79	24.00	1.14		Pass	17
HT20	MCS0	1	36	5180	0.77	13.85	24.00	1.14		Pass	15.5
HT20	MCS0	1	44	5220	0.77	15.80	24.00	1.14		Pass	16
HT20	MCS0	1	48	5240	0.77	16.19	24.00	1.14		Pass	16
HT40	MCS0	1	38	5190	0.81	10.71	24.00	1.14		Pass	12
HT40	MCS0	1	46	5230	0.81	15.77	24.00	1.14		Pass	16
VHT20	MCS0	1	36	5180	0.77	13.88	24.00	1.14		Pass	15.5
VHT20	MCS0	1	44	5220	0.77	15.90	24.00	1.14		Pass	16
VHT20	MCS0	1	48	5240	0.77	16.02	24.00	1.14		Pass	16
VHT40	MCS0	1	38	5190	0.81	10.75	24.00	1.14		Pass	12
VHT40	MCS0	1	46	5230	0.81	15.74	24.00	1.14		Pass	16
VHT80	MCS0	1	42	5210	0.90	9.97	24.00	1.14		Pass	11.5

TEST RESULTS DATA
Average Power Table

FCC U-NII-2A single antenna											
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail	Power Setting
					Ant 1	Ant 1	Ant 1	Ant 1			
11a	6Mbps	1	52	5260	2.40	16.09	23.98	1.00	26.9897	Pass	17
11a	6Mbps	1	60	5300	2.40	17.14	23.98	1.00	26.9897	Pass	17
11a	6Mbps	1	64	5320	2.40	13.35	23.98	1.00	26.9897	Pass	13
HT20	MCS0	1	52	5260	0.77	15.46	23.98	1.00	26.9897	Pass	16
HT20	MCS0	1	60	5300	0.77	16.00	23.98	1.00	26.9897	Pass	16
HT20	MCS0	1	64	5320	0.77	13.24	23.98	1.00	26.9897	Pass	13.5
HT40	MCS0	1	54	5270	0.81	15.48	23.98	1.00	26.9897	Pass	16
HT40	MCS0	1	62	5310	0.81	11.88	23.98	1.00	26.9897	Pass	12.5
VHT20	MCS0	1	52	5260	0.77	15.49	23.98	1.00	26.9897	Pass	16
VHT20	MCS0	1	60	5300	0.77	15.78	23.98	1.00	26.9897	Pass	16
VHT20	MCS0	1	64	5320	0.77	13.26	23.98	1.00	26.9897	Pass	13.5
VHT40	MCS0	1	54	5270	0.81	15.43	23.98	1.00	26.9897	Pass	16
VHT40	MCS0	1	62	5310	0.81	11.93	23.98	1.00	26.9897	Pass	12.5
VHT80	MCS0	1	58	5290	0.90	10.29	23.98	1.00	26.9897	Pass	11.5

TEST RESULTS DATA
Average Power Table

FCC U-NII-2C single antenna											
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail	Power Setting
					Ant 1			Ant 1			
11a	6Mbps	1	100	5500	2.40	14.28	23.98	0.60	26.9897	Pass	15.5
11a	6Mbps	1	116	5580	2.40	16.10	23.98	0.60	26.9897	Pass	17
11a	6Mbps	1	140	5700	2.40	13.24	23.98	0.60	26.9897	Pass	13.5
HT20	MCS0	1	100	5500	0.77	13.48	23.98	0.60	26.9897	Pass	14
HT20	MCS0	1	116	5580	0.77	15.67	23.98	0.60	26.9897	Pass	16
HT20	MCS0	1	140	5700	0.77	13.02	23.98	0.60	26.9897	Pass	13.5
HT40	MCS0	1	102	5510	0.81	12.97	23.98	0.60	26.9897	Pass	13.5
HT40	MCS0	1	110	5550	0.81	15.96	23.98	0.60	26.9897	Pass	16
HT40	MCS0	1	134	5670	0.81	14.45	23.98	0.60	26.9897	Pass	15
VHT20	MCS0	1	100	5500	0.77	13.53	23.98	0.60	26.9897	Pass	14
VHT20	MCS0	1	116	5580	0.77	15.61	23.98	0.60	26.9897	Pass	16
VHT20	MCS0	1	140	5700	0.77	13.05	23.98	0.60	26.9897	Pass	13.5
VHT40	MCS0	1	102	5510	0.81	12.96	23.98	0.60	26.9897	Pass	13.5
VHT40	MCS0	1	110	5550	0.81	16.05	23.98	0.60	26.9897	Pass	16
VHT40	MCS0	1	134	5670	0.81	14.48	23.98	0.60	26.9897	Pass	15
VHT80	MCS0	1	106	5530	0.90	13.01	23.98	0.60	26.9897	Pass	13

TEST RESULTS DATA
Average Power Table

FCC U-NII-1 single antenna										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	Pass/Fail
						Ant 1	Ant 1	Ant 1	Ant 1	
HE20	MCS0	1	36	5180	Full	0.99	14.05	24.00	1.14	Pass
HE20	MCS0	1	36	5180	26/0	8.21	3.10	24.00	1.14	Pass
HE20	MCS0	1	36	5180	52/37	8.21	5.23	24.00	1.14	Pass
HE20	MCS0	1	36	5180	106/53	8.21	8.14	24.00	1.14	Pass
HE20	MCS0	1	44	5220	Full	0.99	16.02	24.00	1.14	Pass
HE20	MCS0	1	44	5220	26/0	8.21	5.19	24.00	1.14	Pass
HE20	MCS0	1	44	5220	52/37	8.21	8.07	24.00	1.14	Pass
HE20	MCS0	1	44	5220	106/53	8.21	10.53	24.00	1.14	Pass
HE20	MCS0	1	48	5240	Full	0.99	16.20	24.00	1.14	Pass
HE20	MCS0	1	48	5240	26/8	8.21	5.92	24.00	1.14	Pass
HE20	MCS0	1	48	5240	52/40	8.21	8.82	24.00	1.14	Pass
HE20	MCS0	1	48	5240	106/54	8.21	11.11	24.00	1.14	Pass
HE40	MCS0	1	38	5190	Full	1.04	10.89	24.00	1.14	Pass
HE40	MCS0	1	46	5230	Full	1.04	15.80	24.00	1.14	Pass
HE80	MCS0	1	42	5210	Full	1.04	10.05	24.00	1.14	Pass

Power Setting
Ant 1
15.5
-28
-23
-17
16
-25
-20
-15
16
-25
-20
-15
12
16
11.5

TEST RESULTS DATA
Average Power Table

FCC U-NII-2A single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail	Power Setting
						Ant 1	Ant 1	Ant 1	Ant 1			
HE20	MCS0	1	52	5260	Full	0.99	15.57	23.98	1.00	26.9897	Pass	Ant 1
HE20	MCS0	1	52	5260	26/0	8.21	5.17	23.98	1.00	26.9897	Pass	16
HE20	MCS0	1	52	5260	52/37	8.21	7.37	23.98	1.00	26.9897	Pass	-22
HE20	MCS0	1	52	5260	106/53	8.21	10.32	23.98	1.00	26.9897	Pass	-17
HE20	MCS0	1	60	5300	Full	0.99	16.12	23.98	1.00	26.9897	Pass	-12
HE20	MCS0	1	60	5300	26/0	8.21	6.22	23.98	1.00	26.9897	Pass	16
HE20	MCS0	1	60	5300	52/37	8.21	8.42	23.98	1.00	26.9897	Pass	-22
HE20	MCS0	1	60	5300	106/53	8.21	11.35	23.98	1.00	26.9897	Pass	-17
HE20	MCS0	1	64	5320	Full	0.99	13.41	23.98	1.00	26.9897	Pass	-12
HE20	MCS0	1	64	5320	26/8	8.21	2.12	23.98	1.00	26.9897	Pass	13.5
HE20	MCS0	1	64	5320	52/40	8.21	5.25	23.98	1.00	26.9897	Pass	-31
HE20	MCS0	1	64	5320	106/54	8.21	7.92	23.98	1.00	26.9897	Pass	-25
HE20	MCS0	1	64	5320	106/54	8.21	7.92	23.98	1.00	26.9897	Pass	-20
HE40	MCS0	1	54	5270	Full	1.04	15.49	23.98	1.00	26.9897	Pass	16
HE40	MCS0	1	62	5310	Full	1.04	12.07	23.98	1.00	26.9897	Pass	12.5
HE80	MCS0	1	58	5290	Full	1.04	10.38	23.98	1.00	26.9897	Pass	11.5

TEST RESULTS DATA
Average Power Table

FCC U-NII-2C single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail	Power Setting
						Ant 1	Ant 1	Ant 1	Ant 1			
HE20	MCS0	1	100	5500	Full	0.99	13.68	23.98	0.60	26.99	Pass	Ant 1
HE20	MCS0	1	100	5500	26/0	8.21	2.26	23.98	0.60	26.99	Pass	14
HE20	MCS0	1	100	5500	52/37	8.21	5.02	23.98	0.60	26.99	Pass	-29
HE20	MCS0	1	100	5500	106/53	8.21	8.47	23.98	0.60	26.99	Pass	-24
HE20	MCS0	1	116	5580	Full	0.99	15.77	23.98	0.60	26.99	Pass	-19
HE20	MCS0	1	116	5580	26/0	8.21	3.87	23.98	0.60	26.99	Pass	16
HE20	MCS0	1	116	5580	52/37	8.21	6.91	23.98	0.60	26.99	Pass	-27
HE20	MCS0	1	116	5580	106/53	8.21	10.57	23.98	0.60	26.99	Pass	-21
HE20	MCS0	1	140	5700	Full	0.99	13.17	23.98	0.60	26.99	Pass	-16
HE20	MCS0	1	140	5700	26/8	8.21	1.69	23.98	0.60	26.99	Pass	13.5
HE20	MCS0	1	140	5700	52/40	8.21	4.97	23.98	0.60	26.99	Pass	-28
HE20	MCS0	1	140	5700	106/54	8.21	7.51	23.98	0.60	26.99	Pass	-23
HE20	MCS0	1	140	5700	106/54	8.21	7.51	23.98	0.60	26.99	Pass	-18
HE40	MCS0	1	102	5510	Full	1.04	13.16	23.98	0.60	26.99	Pass	13.5
HE40	MCS0	1	110	5550	Full	1.04	16.11	23.98	0.60	26.99	Pass	16
HE40	MCS0	1	134	5670	Full	1.04	14.62	23.98	0.60	26.99	Pass	15
HE80	MCS0	1	106	5530	Full	1.04	13.23	23.98	0.60	26.99	Pass	13

TEST RESULTS DATA
Average Power Table

U-NII-3 single antenna										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	Pass/Fail	Power Setting
					Ant 1	Ant 1	Ant 1	Ant 1		
11a	6Mbps	1	149	5745	2.40	15.45	30.00	0.95	Pass	17
11a	6Mbps	1	157	5785	2.40	15.42	30.00	0.95	Pass	17
11a	6Mbps	1	165	5825	2.40	15.47	30.00	0.95	Pass	17
HT20	MCS0	1	149	5745	0.77	14.89	30.00	0.95	Pass	16
HT20	MCS0	1	157	5785	0.77	14.82	30.00	0.95	Pass	16
HT20	MCS0	1	165	5825	0.77	15.02	30.00	0.95	Pass	16
HT40	MCS0	1	151	5755	0.81	14.75	30.00	0.95	Pass	16
HT40	MCS0	1	159	5795	0.81	14.72	30.00	0.95	Pass	16
VHT20	MCS0	1	149	5745	0.77	14.77	30.00	0.95	Pass	16
VHT20	MCS0	1	157	5785	0.77	15.01	30.00	0.95	Pass	16
VHT20	MCS0	1	165	5825	0.77	15.17	30.00	0.95	Pass	16
VHT40	MCS0	1	151	5755	0.81	15.17	30.00	0.95	Pass	16
VHT40	MCS0	1	159	5795	0.81	15.13	30.00	0.95	Pass	16
VHT80	MCS0	1	155	5775	0.90	15.03	30.00	0.95	Pass	16

TEST RESULTS DATA
Average Power Table

U-NII-3 single antenna											
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	Pass/Fail	Power Setting
						Ant 1	Ant 1	Ant 1	Ant 1		
HE20	MCS0	1	149	5745	Full	0.99	15.02	30.00	0.95	Pass	16
HE20	MCS0	1	149	5745	26/0	8.21	2.87	30.00	0.95	Pass	-26
HE20	MCS0	1	149	5745	52/37	8.21	5.66	30.00	0.95	Pass	-21
HE20	MCS0	1	149	5745	106/53	8.21	8.48	30.00	0.95	Pass	-16
HE20	MCS0	1	157	5785	Full	0.99	15.12	30.00	0.95	Pass	16
HE20	MCS0	1	157	5785	26/4	8.21	3.42	30.00	0.95	Pass	-26
HE20	MCS0	1	157	5785	52/38	8.21	6.25	30.00	0.95	Pass	-21
HE20	MCS0	1	157	5785	106/53	8.21	8.91	30.00	0.95	Pass	-16
HE20	MCS0	1	165	5825	Full	0.99	15.25	30.00	0.95	Pass	16
HE20	MCS0	1	165	5825	26/8	8.21	2.68	30.00	0.95	Pass	-26
HE20	MCS0	1	165	5825	52/40	8.21	5.37	30.00	0.95	Pass	-21
HE20	MCS0	1	165	5825	106/54	8.21	7.82	30.00	0.95	Pass	-16
HE40	MCS0	1	151	5755	Full	1.04	15.19	30.00	0.95	Pass	16
HE40	MCS0	1	159	5795	Full	1.04	15.25	30.00	0.95	Pass	16
HE80	MCS0	1	155	5775	Full	1.04	15.25	30.00	0.95	Pass	16



Ambient Condition: <u>25</u> °C, <u>45</u> %RH	
According Standard: <u>■Part15E</u>	
Test Date: <u>2023.7.14~2023.8.8</u>	Test Engineer: <u>Long Wu</u>

Emission Bandwidth

Test Result


TestMode	Antenna	Freq(MHz)	26dB EBW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	24.40	5168.00	5192.40	---	---
		5220	27.40	5206.50	5233.90	---	---
		5240	29.30	5225.80	5255.10	---	---
		5260	27.90	5246.40	5274.30	---	---
		5300	30.10	5285.60	5315.70	---	---
		5320	24.40	5308.00	5332.40	---	---
		5500	25.40	5487.50	5512.90	---	---
		5580	26.30	5567.20	5593.50	---	---
		5700	24.70	5688.00	5712.70	---	---
		5745	25.40	5732.00	5757.40	---	---
		5785	25.60	5772.50	5798.10	---	---
5825	25.10	5812.20	5837.30	---	---		
11AX20SISO	Ant1	5180	25.80	5168.10	5193.90	---	---
		5220	26.70	5206.50	5233.20	---	---
		5240	27.00	5227.10	5254.10	---	---
		5260	26.80	5247.40	5274.20	---	---
		5300	29.40	5285.80	5315.20	---	---
		5320	25.30	5307.70	5333.00	---	---
		5500	24.60	5487.90	5512.50	---	---
		5580	27.20	5567.30	5594.50	---	---
		5700	25.40	5687.20	5712.60	---	---
		5745	26.70	5732.50	5759.20	---	---
		5785	25.60	5772.20	5797.80	---	---
5825	24.90	5813.10	5838.00	---	---		
11AX40SISO	Ant1	5190	46.00	5167.80	5213.80	---	---
		5230	48.00	5207.60	5255.60	---	---
		5270	46.40	5247.60	5294.00	---	---
		5310	60.00	5282.80	5342.80	---	---
		5510	47.00	5486.60	5533.60	---	---
		5550	46.60	5527.20	5573.80	---	---



		5670	46.40	5646.80	5693.20	---	---
		5755	46.40	5732.00	5778.40	---	---
		5795	46.40	5772.20	5818.60	---	---
11AX80SISO	Ant1	5210	86.40	5167.60	5254.00	---	---
		5290	88.00	5246.80	5334.80	---	---
		5530	86.40	5487.20	5573.60	---	---
		5775	88.00	5731.00	5819.00	---	---




Test Graphs






11A_Ant1_5240



Date: 8.AUG.2023 15:04:59


11A_Ant1_5260




Date: 8.AUG.2023 15:06:11



11A_Ant1_5300




11A_Ant1_5320






11A_Ant1_5500





Date: 8.AUG.2023 15:08:27

11A_Ant1_5580




Date: 8.AUG.2023 15:09:13








11AX20SISO_Ant1_5180



Date: 8.AUG.2023 15:25:13


11AX20SISO_Ant1_5220



Date: 8.AUG.2023 15:26:03




11AX20SISO_Ant1_5240




Date: 8.AUG.2023 15:26:41

11AX20SISO_Ant1_5260




Date: 8.AUG.2023 15:27:11



11AX20SISO_Ant1_5320




11AX20SISO_Ant1_5500




11AX20SISO_Ant1_5580








11AX20SISO_Ant1_5785




Date: 8.AUG.2023 15:31:34

11AX20SISO_Ant1_5825




Date: 8.AUG.2023 15:32:17






11AX40SISO_Ant1_5270



Date: 8.AUG.2023 15:34:50


11AX40SISO_Ant1_5310



Date: 8.AUG.2023 15:36:21




11AX40SISO_Ant1_5510



Date: 8.AUG.2023 15:52:43


11AX40SISO_Ant1_5550



Date: 8.AUG.2023 15:53:44




11AX40SISO_Ant1_5670



Date: 8.AUG.2023 15:54:43


11AX40SISO_Ant1_5755



Date: 8.AUG.2023 15:55:22




11AX40SISO_Ant1_5795





Date: 8.AUG.2023 15:55:58

11AX80SISO_Ant1_5210



Date: 8.AUG.2023 15:56:58







Occupied channel bandwidth

Test Result


TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	18.222	5170.8891	5189.1109	---	---
		5220	18.342	5210.8492	5229.1908	---	---
		5240	18.382	5230.8092	5249.1908	---	---
		5260	18.222	5250.8092	5269.0310	---	---
		5300	18.462	5290.7692	5309.2308	---	---
		5320	19.141	5310.6494	5329.7902	---	---
		5500	18.701	5490.6494	5509.3506	---	---
		5580	18.661	5570.6494	5589.3107	---	---
		5700	18.342	5690.8092	5709.1508	---	---
		5745	18.422	5735.7293	5754.1508	---	---
		5785	18.382	5775.6893	5794.0709	---	---
5825	18.462	5815.6494	5834.1109	---	---		
11AX20SISO	Ant1	5180	19.62	5170.2098	5189.8302	---	---
		5220	19.62	5210.2098	5229.8302	---	---
		5240	19.58	5230.2098	5249.7902	---	---
		5260	19.62	5250.1698	5269.7902	---	---
		5300	19.74	5290.1299	5309.8701	---	---
		5320	19.78	5310.1299	5329.9101	---	---
		5500	19.9	5490.0500	5509.9500	---	---
		5580	19.94	5570.0500	5589.9900	---	---
		5700	19.9	5690.0500	5709.9500	---	---
		5745	19.9	5735.0100	5754.9101	---	---
		5785	19.78	5775.0500	5794.8302	---	---
5825	19.86	5815.0500	5834.9101	---	---		
11AX40SISO	Ant1	5190	38.521	5170.7393	5209.2607	---	---
		5230	38.601	5210.7393	5249.3407	---	---
		5270	38.601	5250.7393	5289.3407	---	---
		5310	38.761	5290.6593	5329.4206	---	---
		5510	38.681	5490.6593	5529.3407	---	---
		5550	38.681	5530.6593	5569.3407	---	---
		5670	38.761	5650.6593	5689.4206	---	---
		5755	38.681	5735.5794	5774.2607	---	---
5795	38.761	5775.5794	5814.3407	---	---		
11AX80SISO	Ant1	5210	77.842	5171.3187	5249.1608	---	---





		5290	78.322	5250.9990	5329.3207	---	---
		5530	78.641	5490.8392	5569.4805	---	---
		5775	78.482	5735.6793	5814.1608	---	---




Test Graphs









11A_5580




11A_5700




Date: 14.JUL.2023 19:10:47

11A_5745




Date: 14.JUL.2023 19:12:45






11AX20SISO_5180



Date: 14.JUL.2023 20:09:21


11AX20SISO_5220



Date: 14.JUL.2023 20:15:27




11AX20SISO_5240



Date: 14.JUL.2023 20:17:07


11AX20SISO_5260



Date: 14.JUL.2023 20:18:46




11AX20SISO_5300





Date: 14.JUL.2023 20:20:45

11AX20SISO_5320




Date: 14.JUL.2023 20:22:27








11AX20SISO_5785



Date: 14.JUL.2023 20:29:49


11AX20SISO_5825



Date: 14.JUL.2023 20:31:00




11AX40SISO_5190



Date: 14.JUL.2023 20:35:32


11AX40SISO_5230



Date: 14.JUL.2023 20:40:42




11AX40SISO_5270



Date: 14.JUL.2023 20:42:49

11AX40SISO_5310



Date: 14.JUL.2023 21:15:06