

NR SA

Test Mode & Test Freq.[MHz]	Frequency [MHz]	PK+Level [dBm]	PK+Limit [dBm]	PK+Margin [dB]	Polarization	Azimuth [deg]
NR_SA_N25_40M_CH374000_Low	952.975	-39.46	-13.00	26.46	H	0
NR_SA_N25_40M_CH374000_High	3,702.000	-34.81	-13.00	21.81	V	0
	5,553.000	-27.71	-13.00	14.71	V	48.7
	7,404.000	-21.67	-13.00	8.67	H	182.2
	9,255.000	-39.01	-13.00	26.01	V	352.3
	11,106.000	-37.48	-13.00	24.48	H	360
	12,957.000	-35.90	-13.00	22.90	H	8.9
	14,808.000	-34.02	-13.00	21.02	H	0
	16,659.000	-28.55	-13.00	15.55	V	0
NR_SA_N41_100M_CH518598_Low	947.979	-39.08	-25.00	14.08	H	194.9
NR_SA_N41_100M_CH518598_High	5,090.000	-43.86	-25.00	18.86	V	360
	7,635.000	-41.04	-25.00	16.04	V	0
	10,180.000	-50.47	-25.00	25.47	H	90.7
	12,725.000	-49.22	-25.00	24.22	H	360
	15,270.500	-48.05	-25.00	23.05	V	0
	17,815.000	-44.37	-25.00	19.37	H	175.9
NR_SA_N48_40M_CH641666_Low	954.213	-57.58	-40.00	17.58	H	14.2
NR_SA_N48_40M_CH641666_High	7,214.000	-44.09	-40.00	4.09	H	0
	10,821.500	-50.91	-40.00	10.91	V	352.7
	14,428.500	-48.92	-40.00	8.92	V	0
NR_SA_N66_40M_CH346000_Low	950.179	-39.06	-13.00	26.06	H	174.6
NR_SA_N66_40M_CH346000_High	3,422.000	-34.60	-13.00	21.60	V	49.9
	5,133.000	-30.37	-13.00	17.37	V	360
	6,844.000	-24.35	-13.00	11.35	H	360
	8,555.000	-37.70	-13.00	24.70	H	360
	10,266.000	-37.27	-13.00	24.27	H	0
	11,977.000	-36.47	-13.00	23.47	V	244.4
	13,688.000	-35.08	-13.00	22.08	H	115.7
	15,399.000	-32.54	-13.00	19.54	H	0
	17,110.000	-29.61	-13.00	16.61	V	9.5
NR_SA_N70_5M_CH340500_Low	940.417	-39.98	-13.00	26.98	H	102.2
NR_SA_N70_5M_CH340500_High	3,402.000	-34.82	-13.00	21.82	V	202.2
	5,103.000	-31.81	-13.00	18.81	V	296.5
	6,804.000	-36.14	-13.00	23.14	H	0
	8,505.000	-39.07	-13.00	26.07	H	184.1
	10,206.000	-36.99	-13.00	23.99	V	360
	11,907.000	-37.48	-13.00	24.48	V	245.6
	13,608.000	-35.47	-13.00	22.47	H	184.1

	15,309.000	-33.36	-13.00	20.36	V	236.2
	17,010.000	-29.67	-13.00	16.67	V	236.2

Remark: 'Low' indicates a frequency range below 1GHz, and 'High' indicates a frequency range above 1GHz.

NR UL MIMO

Test Mode & Test Freq.[MHz]	Frequency [MHz]	PK+Level [dBm]	PK+Limit [dBm]	PK+Margin [dB]	Polarization	Azimuth [deg]
n41A_100M_CH528000_Low	856.450	-41.20	-25.00	16.20	V	4.6
n41A_100M_CH528000_High	5,182.000	-44.31	-25.00	19.31	V	246
	7,774.000	-38.49	-25.00	13.49	H	149.2
	10,376.000	-51.12	-25.00	26.12	V	0.6
	12,954.500	-49.23	-25.00	24.23	H	360
	15,547.000	-47.74	-25.00	22.74	V	76.5
n48A_40M_CH641666_Low	945.871	-57.52	-40.00	17.52	H	312.2
n48A_40M_CH641666_High	7,214.500	-44.34	-40.00	4.34	V	0
	10,822.000	-51.10	-40.00	11.10	V	63
	14,428.000	-49.86	-40.00	9.86	V	188.6

Remark: 'Low' indicates a frequency range below 1GHz, and 'High' indicates a frequency range above 1GHz.

NR NSA

Test Mode & Test Freq.[MHz]	Frequency [MHz]	PK+Level [dBm]	PK+Limit [dBm]	PK+Margin [dB]	Polarization	Azimuth [deg]
DC_2A_n41_100M_CH509202_Low	938.354	-40.54	-25.00	15.54	H	101.5
DC_2A_n41_100M_CH509202_High	4,995.500	-45.22	-25.00	20.22	H	137.7
	7,494.500	-39.50	-25.00	14.50	H	355
	9,992.000	-50.72	-25.00	25.72	H	246.2
	12,490.000	-49.71	-25.00	24.71	V	0.9
	14,988.000	-48.53	-25.00	23.53	H	360
	17,485.500	-45.29	-25.00	20.29	V	360
DC_7A_n25_25M_CH372500_Low	953.113	-39.70	-13.00	26.70	H	360
DC_7A_n25_25M_CH372500_High	3,737.000	-33.75	-13.00	20.75	H	46.3
	5,603.500	-29.19	-13.00	16.19	V	237.5
	7,473.000	-32.21	-13.00	19.21	V	22.5
	9,340.000	-39.58	-13.00	26.58	V	360
	11,209.000	-37.68	-13.00	24.68	V	353.2
	13,076.000	-36.96	-13.00	23.96	H	360
	14,944.000	-33.55	-13.00	20.55	V	360
	16,813.000	-28.86	-13.00	15.86	H	113.3
DC_7A_n66_15M_CH343500_Low	943.350	-39.98	-13.00	26.98	H	360
DC_7A_n66_15M_CH343500_High	3,442.000	-35.89	-13.00	22.89	H	313.7
	5,163.000	-31.38	-13.00	18.38	H	0
	6,884.000	-35.49	-13.00	22.49	H	0
	8,605.000	-38.22	-13.00	25.22	V	352.7
	10,326.000	-37.52	-13.00	24.52	H	360
	12,047.000	-35.97	-13.00	22.97	V	6.4
	13,768.000	-36.58	-13.00	23.58	V	360
	15,489.000	-32.63	-13.00	19.63	H	360
	17,210.000	-29.83	-13.00	16.83	V	352.7
DC_12A_n25_40M_CH374000_Low	943.213	-39.39	-13.00	26.39	H	114.3
DC_12A_n25_40M_CH374000_High	3,728.000	-34.93	-13.00	21.93	H	0
	5,592.000	-28.85	-13.00	15.85	H	311.4
	7,456.000	-33.45	-13.00	20.45	H	0
	9,320.000	-39.26	-13.00	26.26	V	0
	11,184.000	-37.31	-13.00	24.31	H	6.4
	13,048.000	-36.61	-13.00	23.61	V	353.3
	14,912.000	-34.53	-13.00	21.53	H	0
	16,776.000	-29.27	-13.00	16.27	V	360
DC_12A_n66_40M_CH346000_Low	960.308	-39.76	-13.00	26.76	H	101.4
DC_12A_n66_40M_CH346000_High	3,422.000	-35.60	-13.00	22.60	H	140.6
	5,133.000	-31.10	-13.00	18.10	V	19.5

	6,844.000	-35.95	-13.00	22.95	H	95.1
	8,555.000	-38.69	-13.00	25.69	V	176.6
	10,266.000	-37.90	-13.00	24.90	V	55.4
	11,977.000	-36.69	-13.00	23.69	V	0
	13,688.000	-37.01	-13.00	24.01	H	182.9
	15,399.000	-33.47	-13.00	20.47	V	182.9
	17,110.500	-29.49	-13.00	16.49	V	125.6
DC_13A_n48_40M_CH645332_Low	953.617	-57.18	-40.00	17.18	H	312
DC_13A_n48_40M_CH645332_High	7,324.000	-42.76	-40.00	2.76	H	0
	10,985.500	-51.15	-40.00	11.15	H	360
	14,648.000	-48.87	-40.00	8.87	V	0

Remark: 'Low' indicates a frequency range below 1GHz, and 'High' indicates a frequency range above 1GHz.