

Report No.: ZEWA2310000147RG05

Page: 1 of 29

# TEST REPORT

Application No.: ZEWA2310000147RG

**Applicant:** Quectel Wireless Solutions Co., Ltd.

Address of Applicant: Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road,

Minhang District, Shanghai, China 200233

**Manufacturer:** Quectel Wireless Solutions Co., Ltd.

Address of Manufacturer: Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road,

Minhang District, Shanghai, China 200233

**EUT Description:** 5G Sub-6 GHz M.2 Module

Model No.: RM520N-GL
Trade Mark: Quectel

FCC ID: XMR2023RM520NGLT

Standards: 47 CFR Part 2

47 CFR Part 96

**Date of Receipt:** 2022/05/15 (for report FYCR220600021102)

2023/04/19 (for report ZEWM2306000841RG02) 2023/09/26 (for report ZEWA2310000147RG02) 2023/11/10 (for report ZEWA2310000147RG05)

**Date of Test:** 2022/05/22 to 2022/07/22 (for report FYCR220600021102)

2023/05/09 to 2023/06/19 (for report ZEWM2306000841RG02) 2023/10/04 to 2023/10/30 (for report ZEWA2310000147RG02)

**Date of Issue:** 2023/11/10

Test Result : PASS \*

\* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Authorized Signature:

Keny Xu Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions">https://www.sgs.com/en/Terms-and-Conditions</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sport responsibility is to its Client and this document does not excented parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, foregrey or falsification of the content or appearance of this document is unlauf and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

to the fullest extent or the land, which was sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 83071443, October 1886, Section 1886, Sectio

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 中国・广东・深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057

t (86-755) 26012053 sgs.ch

Report No.: ZEWA2310000147RG05

Page: 2 of 29

## **Version**

|         | Revision Record |            |          |          |  |  |
|---------|-----------------|------------|----------|----------|--|--|
| Version | Chapter         | Date       | Modifier | Remark   |  |  |
| 01      |                 | 2023/11/10 |          | Original |  |  |

| Prepared By | Jack Huang) / Test Engineer         |  |
|-------------|-------------------------------------|--|
| Checked By  | Flora Wang  (Flora Wang) / Reviewer |  |



sgs.china@sgs.com



Report No.: ZEWA2310000147RG05

Page: 3 of 29

## **Contents**

| 1 | Versi | on   | 2  |
|---|-------|--|----|
| 2 | Test  | Summary  | 4  |
|   | 2.1   | NR Band n48  | 4  |
| 3 | Gene  | eral Information   | 7  |
|   | 3.1   | Details of Client  | 7  |
|   | 3.2   | Test Location  | 7  |
|   | 3.3   | Test Facility  | 7  |
|   | 3.4   | General Description of EUT                                 | 8  |
|   | 3.5   | Test Mode  | 10 |
|   | 3.6   | Test Environment   | 10 |
|   | 3.7   | Description of Support Units                               | 10 |
|   | 3.8   | Technical Specification                                    | 11 |
|   | 3.9   | Test Frequencies   | 12 |
|   | ;     | 3.9.1 Reference test frequencies for NR operating band n48 | 12 |
| 4 | Desc  | ription of Tests   | 13 |
|   | 4.1   | Conducted Output Power                                     | 13 |
|   | 4.2   | Effective (Isotropic) Radiated Power of Transmitter        | 14 |
|   | 4.3   | Occupied Bandwidth   | 15 |
|   | 4.4   | Band Edge at Antenna Terminals                             | 16 |
|   | 4.5   | Spurious And Harmonic Emissions at Antenna Terminal        | 17 |
|   | 4.6   | Peak-Average Ratio   | 18 |
|   | 4.7   | Field Strength of Spurious Radiation                       | 19 |
|   | 4.8   | Frequency Stability / Temperature Variation                | 20 |
|   | 4.9   | Test Setups  | 21 |
|   | •     | 4.9.1 Test Setup 1   | 21 |
|   | •     | 4.9.2 Test Setup 2   | 21 |
|   | •     | 4.9.3 Test Setup 3   | 22 |
|   | 4.10  | Test Conditions  | 23 |
| 5 | Main  | Test Instruments   | 25 |
| 6 | Meas  | surement Uncertainty                                       | 26 |
| 7 | Appe  | ndixes   | 29 |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions">https://www.sgs.com/en/Terms-and-Conditions</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from excising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document to unique and printeders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN. Doccheck@sos.com"

邮编: 518057

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86–755) 26012053

中国・广东・深圳市南山区科技园中区M-10栋1号厂房



Report No.: ZEWA2310000147RG05

Page: 4 of 29

#### 2 **Test Summary**

## 2.1 NR Band n48

#### 3550-3700MHz:

| Test Item  | FCC Rule<br>No.    | Requirements  | Test Result                   | Verdict |
|--|--------------------|---|-------------------------------|---------|
| Effective (Isotropic) Radiated Power Output Data | §2.1046,<br>§96.41 | EIRP ≤ 23dBm/10MHz  | Section 1 of<br>Appendix B.50 | Pass    |
| Peak-Average<br>Ratio                            | §96.41             | FCC: Limit≤13 dB  | Section 2 of<br>Appendix B.50 | Pass    |
| Bandwidth  | §2.1049            | OBW: No limit.<br>EBW: No limit.  | Section 3 of<br>Appendix B.50 | Pass    |
| Adjacent Channel<br>Leakage Ratio                | §96.41             | the Adjacent Channel Leakage Ratio for<br>End User Devices shall be at least 30<br>dB.  | Section 4 of<br>Appendix B.50 | Pass    |
| Band Edges<br>Compliance                         | §2.1051,<br>§96.41 | for channel and frequency assignments made by a CBSD to End User Devices, the conducted power of any End User Device emission outside the fundamental emission (whether in or outside of the authorized band) shall not exceed -13 dBm/MHz within 0 to B megahertz (where B is the bandwidth in megahertz of the assigned channel or multiple contiguous channels of the End User Device) above the upper CBSD-assigned channel edge and within 0 to B megahertz below the lower CBSD-assigned channel edge.  | Section 5 of<br>Appendix B.50 | Pass    |
| Spurious Emission<br>at Antenna<br>Terminals     | §2.1051,<br>§96.41 | for channel and frequency assignments made by a CBSD to End User Devices, the conducted power of any End User Device emission outside the fundamental emission (whether in or outside of the authorized band) shall not exceed –13 dBm/MHz within 0 to B megahertz (where B is the bandwidth in megahertz of the assigned channel or multiple contiguous channels of the End User Device) above the upper CBSD-assigned channel edge and within 0 to B megahertz below the lower CBSD-assigned channel edge. At all frequencies greater than B megahertz above the upper CBSD assigned channel edge and less than B megahertz below the lower CBSD-assigned channel edge, the conducted | Section 6 of<br>Appendix B.50 | Pass    |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions">https://www.sgs.com/en/Terms-and-Conditions</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from excising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document to unique and printeders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN. Doccheck@sos.com"

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86–755) 26012053

邮编: 518057 中国・广东・深圳市南山区科技园中区M-10栋1号厂房



# SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: ZEWA2310000147RG05

Page: 5 of 29

|   |                    | power of any End User Device emission shall not exceed -25 dBm/MHz.  (2) Additional protection levels.  Notwithstanding paragraph (e)(1) of this section, for CBSDs and End User Devices, the conducted power of emissions below 3540 MHz or above 3710 MHz shall not exceed -25 dBm/MHz, and the conducted power of emissions below 3530 MHz or above 3720 MHz shall not exceed -40dBm/MHz.   |                               |      |
|---|--------------------|--|-------------------------------|------|
| Field Strength of<br>Spurious Radiation | §2.1053,<br>§96.41 | for channel and frequency assignments made by a CBSD to End User Devices, the conducted power of any End User Device emission outside the fundamental emission (whether in or outside of the authorized band) shall not exceed –13 dBm/MHz within 0 to B megahertz (where B is the bandwidth in megahertz of the assigned channel or multiple contiguous channels of the End User Device) above the upper CBSD-assigned channel edge and within 0 to B megahertz below the lower CBSD-assigned channel edge. At all frequencies greater than B megahertz above the upper CBSD assigned channel edge and less than B megahertz below the lower CBSD-assigned channel edge, the conducted power of any End User Device emission shall not exceed –25 dBm/MHz.  (2) Additional protection levels.  Notwithstanding paragraph (e)(1) of this section, for CBSDs and End User Devices, the conducted power of emissions below 3540 MHz or above 3710 MHz shall not exceed –25 dBm/MHz, and the conducted power of emissions below 3530 MHz or above 3720 MHz shall not exceed –40dBm/MHz. | Section 7 of<br>Appendix B.50 | Pass |
| Frequency Stability                     | §2.1055,<br>§96.41 | Within authorized bands of operation/ frequency block.   | Section 8 of<br>Appendix B.50 | Pass |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions">https://www.sgs.com/en/Terms-and-Conditions</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from excising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refor only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CVD.Doccheck@sos.com"

t (86-755) 26012053

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 中国・广东・深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057

ZEWA2310000147RG05 Report No.:

6 of 29 Page:

Remark for report ZEWM2306000841RG02 issue on 2023/06/21:

This test report (Report No.: ZEWM2306000841RG02 issue on 2023/06/21) is based on the original test report (Report No.: FYCR220600021102 issue on 2022/08/29).

Review this report and original report, this report just changing the parts according to the declaration letter from client.

Considering to the difference, pre-scan were performed on the sample in this report to find the items which can be influential to the result in the original test report for fully retest.

The Effective (Isotropic) Radiated Power Output Data were fully tested in this report, and other items data please refer to the test report FYCR220600021102. The FCC ID is XMR2022RM520NGL has been certified, and the test report issued by Compliance Certification Services (Kunshan) Inc. Shenzhen branch. on 2022/08/29.

Remark for report ZEWA2310000147RG02 issue on 2023/10/31:

This test report (Report No.: ZEWA2310000147RG02 issue on 2023/10/31) is based on the original test report (Report No.: ZEWM2306000841RG02 issue on 2023/06/21).

Review this report and original report, this report just changing the parts according to the declaration letter from client.

Considering to the difference, pre-scan were performed on the sample in this report to find the items which can be influential to the result in the original test report for fully retest.

Therefore in this report the Field Strength of Spurious Radiation of NR Band n48, Power of NR Band n48(SA&MIMO) and all items of NR Band n48(SA&MIMO) 30MHz were tested, and other test data in this report are based on the previous report with report number ZEWM2306000841RG02 issue on 2023/06/21.

Remark for report ZEWA2310000147RG05 issue on 2023/11/10:

This test report (Report No.: ZEWA2310000147RG05 issue on 2023/11/10) is based on the original test report (Report No.: ZEWA2310000147RG02 issue on 2023/10/31).

Review this report and original report, this report just changing FCC ID.

Therefore in this report all items do not need to retest and all test data in this report are based on the previous report with report number ZEWA2310000147RG02 issue on 2023/10/31.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions.">https://www.sgs.com/en/Terms-and-Conditions.</a>
Indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, foregrey or falsification of the content or appearance of this document is unally and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. to the fullest extent of the law. Online was a sample(s) are retained for 3 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 83071443,

Report No.: ZEWA2310000147RG05

Page: 7 of 29

## 3 General Information

## 3.1 Details of Client

| Applicant:   | Quectel Wireless Solutions Co., Ltd.  |  |  |
|--|---|--|--|
| Address of Applicant:  Building 5, Shanghai Business Park Phase III (Area B), No.1016 T Road, Minhang District, Shanghai, China 200233 |   |  |  |
| Manufacturer:  | Quectel Wireless Solutions Co., Ltd.  |  |  |
| Address of Manufacturer:   | Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233 |  |  |

#### 3.2 Test Location

| Company:       | SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch   |
|----------------|---|
| Address:       | No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China |
| Post code:     | 518057  |
| Test engineer: | Jinhua Wei  |

## 3.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

## • A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

#### VCC

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

#### Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

#### FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch has been recognized as an

accredited testing laboratory. Designation Number: CN1336.

Test Firm Registration Number: 787754



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions">https://www.sgs.com/en/Terms-and-Conditions</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's spot responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, foregrey or falsification of the content or appearance of this document is unalula and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

to the fullest extent or the teath of the teath of the fullest extent or the teath of the fullest extent or the teath of the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CN Deccheck@ses.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 中国・广东・深圳市南山区科技园中区M-10株1号厂房 邮编:518057

Report No.: ZEWA2310000147RG05

Page: 8 of 29

## 3.4 General Description of EUT

| EUE D             | 5001000                                  |   |                              |                               |  |
|-------------------|--|---|------------------------------|-------------------------------|--|
| EUT Description:  | 5G Sub-6 GHz I                           | 5G Sub-6 GHz M.2 Module   |                              |                               |  |
| Model No.:        | RM520N-GL                                |   |                              |                               |  |
| Trade Mark:       | Quectel                                  |   |                              |                               |  |
| Hardware Version: | R1.0                                     |   |                              |                               |  |
| Software Version: | RM520NGLAAF                              | R03A01M   | 4G                           |                               |  |
| Power Supply:     | DC 3.7V                                  |   |                              |                               |  |
| IMEI:             | RF Conducted                             | 868371  | 050414016                    |                               |  |
| IIVIEI.           | RSE                                      | RSE 868371050432802   |                              |                               |  |
| Feature:          | UL 2*2 MIMO: NR Band n48                 |   |                              |                               |  |
| Antenna Type:     | PIFA Antenna                             | PIFA Antenna  |                              |                               |  |
|                   | NR Band n48: 1dBi (Ant0) 1dBi (Ant2)     |   |                              | t2)                           |  |
| Antenna Gain:     | Note:<br>The antenna ga<br>manufacturer. | The antenna gain are derived from the gain information report provided by the |                              |                               |  |
|                   | 9kHz ~ 30MHz                             |   |                              | 1000MHz ~ 2000MHz<br>(0.8dB)  |  |
| RF Cable:         | 2000MHz ~ 4000MHz<br>(1.1dB)             |   | 4000MHz ~ 6000MHz<br>(1.8dB) | 6000MHz ~ 12750MHz<br>(2.6dB) |  |
|                   | Above 12750MHz (3.5dB)                   |   |                              | _                             |  |
| Domorke           | -  |   | -                            |                               |  |

Remark:

As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.





Report No.: ZEWA2310000147RG05

Page: 9 of 29

#### **MIMO Model:**

FCC KDB 662911 D01 Multiple Transmitter Output v02r01 If all antennas have the same gain,  $G_{ANT}$ , Directional gain =  $G_{ANT}$  + Array Gain, where Array Gain is as follows

• For power measurements on IEEE 802.11 devices:

Array Gain = 0 dB (i.e., no array gain) for  $N_{ANT} \le 4$ ;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N<sub>ANT</sub>;

Array Gain =  $5 \log(N_{ANT}/N_{SS}=1)$  dB or 3 dB, whichever is less, for 20-MHz channel widths with  $N_{ANT} \ge 5$ .

Unequal antenna gains, with equal transmit powers. For antenna gains given by G1, G2, ..., GN dBi

• If transmit signals are correlated, then

Directional gain = 10 log[(10<sup>G1/20</sup> + 10<sup>G2/20</sup> + ... + 10<sup>GN/20</sup>)<sup>2</sup> /N<sub>ANT</sub>] dBi [Note the "20"s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]

If all transmit signals are completely uncorrelated, then
 Directional gain = 10 log[(10<sup>G1/10</sup> + 10<sup>G2/10</sup> + ... + 10<sup>GN/10</sup>)/N<sub>ANT</sub>] dBi

| Band         | ANT Gain0 | ANT Gain2 | Directional gain |
|--------------|-----------|-----------|------------------|
|              | (dBi)     | (dBi)     | (dBi)            |
| NR Band n48: | 1         | 1         | 1                |



Report No.: ZEWA2310000147RG05

Page: 10 of 29

## 3.5 Test Mode

| Test Mode  | Test Modes Description                |  |  |
|--|---------------------------------------|--|--|
| NR/TM1   | NR system, DFT-s-Pi/2-BPSK modulation |  |  |
| NR/TM2   | NR system, DFT-s-QPSK modulation      |  |  |
| NR/TM3   | NR system, DFT-s-16QAM modulation     |  |  |
| NR/TM4   | NR system, DFT-s-64QAM modulation     |  |  |
| NR/TM5   | NR system, DFT-s-256QAM modulation    |  |  |
| NR/TM6   | NR system, CP-QPSK modulation         |  |  |
| NR/TM7   | NR system, CP-16QAM modulation        |  |  |
| NR/TM8   | NR system, CP-64QAM modulation        |  |  |
| NR/TM9   | NR system, CP-256QAM modulation       |  |  |
| Remark: The test mode(s) are selected according to relevant radio technology specifications. |                                       |  |  |

## 3.6 Test Environment

| Environment Parameter          |  | 101.0 kPa Selected Values During Tests |                                   |  |
|--------------------------------|--|--|-----------------------------------|--|
| Relative Humidity              |  | 44-46 % RH Ambient                     |                                   |  |
| Value                          |  | Temperature(°C)                        | Voltage(V)                        |  |
| NTNV                           |  | 22-23                                  | 3.7                               |  |
| LTLV                           |  | -30                                    | 3.135                             |  |
| LTHV                           |  | -30                                    | 4.4                               |  |
| HTLV                           |  | 50                                     | 3.135                             |  |
| HTHV                           |  | 50                                     | 4.4                               |  |
| Remark:                        |  |  |                                   |  |
| NV: Normal Voltage LV: Low     |  | Extreme Test Voltage                   | HV: High Extreme Test Voltage     |  |
| NT: Normal Temperature LT: Low |  | Extreme Test Temperature               | HT: High Extreme Test Temperature |  |

# 3.7 Description of Support Units

| Description  | Manufacturer | Model No. |  |  |
|--|--------------|-----------|--|--|
| Test auxiliary PCB board   | Quectel      | N/A       |  |  |
| Remark: all above the information of table are provided by client. |              |           |  |  |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions">https://www.sgs.com/en/Terms-and-Conditions</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that Information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from execting all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, foregrey or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CAD Doccheck@sus.com"

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 www.sgsgroup.com.cn

Report No.: ZEWA2310000147RG05

Page: 11 of 29

## 3.8 Technical Specification

| Characteristics   | Description  |                  |          |                  |             |  |
|---|--|------------------|----------|------------------|-------------|--|
| Radio System Type   | ⊠ SA ⊠ NSA   |                  |          |                  |             |  |
|   | Band   | TX               |          | RX               |             |  |
|   | NR Band n48  | 3550 to 3700 MHz |          | 3550 to 3700 MHz |             |  |
| 0 (15   | NR CA:   |                  |          |                  |             |  |
| Supported Frequency Range   | n48A-n66A;n2A-n48A;n5A-n48A;n48A-n70A;n48A-n71A;n25A-n48A;     |                  |          |                  |             |  |
| range   | ENDC:  |                  |          |                  |             |  |
|   | DC_2A_n48A;DC_5A_n48A;DC_13A_n48A;DC_66A_n48A;                 |                  |          |                  |             |  |
|   | DC_48A_n5A; DC_48A_n66A; DC_48A_n25A; DC_48A_n71A; DC_48A_n12A |                  |          |                  | C_48A_n12A; |  |
| Supported Channel   | NR Band n48<br>(3550-3700)                                     | SCS 30kHz:       |          |                  |             |  |
| Bandwidth   |  | ⊠10 MHz          | ⊠20 MHz  | ⊠30 MHz          | ⊠40 MHz     |  |
| Designation of Emissions  | of   |                  | CP-16QAM |                  |             |  |
| (Remark: the  |  | SCS 30kHz:       |          |                  |             |  |
| necessary bandwidth<br>of which is the worst<br>value from the<br>measured occupied<br>bandwidths for each<br>type of channel<br>bandwidth<br>configuration.) | NR Band n48<br>(3550-3700)                                     | 26M8G7D          | 27M8W7D  |                  |             |  |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions">https://www.sgs.com/en/Terms-and-Conditions</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from excising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document to unique and printeders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN. Doccheck@sos.com"

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 中国・广东・深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057



Report No.: ZEWA2310000147RG05

Page: 12 of 29

## 3.9 Test Frequencies

## Reference test frequencies for NR operating band n48

## Test frequencies for NR operating band n48 and SCS 30 kHz

#### 3550-3700:

| CBW<br>[MHz] | Range    |      | Carrier centre<br>[MHz] | Carrier centre<br>[ARFCN] | SS block SCS<br>[kHz] |
|--------------|----------|------|-------------------------|---------------------------|-----------------------|
|              | Downlink | Low  | 3555                    | 637000                    |                       |
| 10           | &        | Mid  | 3624.99                 | 641666                    | 30                    |
|              | Uplink   | High | 3694.98                 | 646332                    |                       |
|              | Downlink | Low  | 3560.01                 | 637334                    | 30                    |
| 20           | &        | Mid  | 3624.99                 | 641666                    |                       |
|              | Uplink   | High | 3690                    | 646000                    |                       |
|              | Downlink | Low  | 3565.02                 | 637668                    |                       |
| 30           | &        | Mid  | 3624.99                 | 641666                    | 30                    |
|              | Uplink   | High | 3684.99                 | 645666                    |                       |
|              | Downlink | Low  | 3570                    | 638000                    |                       |
| 40           | &        | Mid  | 3624.99                 | 641666                    | 30                    |
|              | Uplink   | High | 3679.98                 | 645332                    |                       |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions">https://www.sgs.com/en/Terms-and-Conditions</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from excising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document to unique and printeders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN. Doccheck@sos.com"

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86–755) 26012053 www.sgsgroup.com.cn

邮编: 518057

中国・广东・深圳市南山区科技园中区M-10栋1号厂房

sgs.china@sgs.com

ZEWA2310000147RG05 Report No.:

Page: 13 of 29

# **Description of Tests**

## 4.1 Conducted Output Power

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 5.2.1

The transmitter output was connected to a calibrated coaxial cable, attenuator and power meter, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The power output at the transmitter antenna port was determined by adding the value of the cable insertion loss to the power reading. The tests were performed at three frequencies (low channel, middle channel and high channel) and on the highest power levels, which can be setup on the transmitters.

Remark: Reference test setup 1



Report No.: ZEWA2310000147RG05

Page: 14 of 29

## 4.2 Effective (Isotropic) Radiated Power of Transmitter

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 5.8.4

Calculate power in dBm by the following formula:

ERP (dBm) = Conducted Power (dBm) + antenna gain (dBd)

EIRP(dBm) = Conducted Power (dBm) + antenna gain (dBi)

EIRP=ERP+2.15dB



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions">https://www.sgs.com/en/Terms-and-Conditions</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not excented parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, foregrey or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

to the fullest extent of the law. Unless outcome was applied against the fullest extent of the law. Sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 83071443, see a mail: CAP Descheck@ags.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 中国・广东・深圳市南山区科技园中区■-10栋1号厂房 邮编: 518057

t (86-755) 26012053 t (86-755) 26012053

www.sgsgroup.com.cn sgs.china@sgs.com

Report No.: ZEWA2310000147RG05

Page: 15 of 29

## 4.3 Occupied Bandwidth

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 4.2 & 4.3

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel, middle channel and high channel). The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.

#### Remark: Reference test setup 1

#### Test Settings

- The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
- RBW = 1 5% of the expected OBW
- VBW ≥ 3 x RBW
- Detector = Peak
- Trace mode = max hold
- Sweep = auto couple
- 7. The trace was allowed to stabilize
- 8. If necessary, steps 2 7 were repeated after changing the RBW such that it would be within
  - 1 5% of the 99% occupied bandwidth observed in Step 7



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions.">https://www.sgs.com/en/Terms-and-Conditions.</a>
Indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, foregrey or falsification of the content or appearance of this document is unally and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Report No.: ZEWA2310000147RG05

Page: 16 of 29

## 4.4 Band Edge at Antenna Terminals

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 6.0

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at two frequencies (low channel and high channel).in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of 100kHz or 1% of the emission bandwidth of the fundamental emission of the transmitter may be employed. The EUT emission bandwidth is measured as the width of the signal between two points, outside of which all emission are attenuated at least 26dB below the transmitter power. The video bandwidth of the spectrum analyzer was set at thrice the resolution bandwidth. Detector Mode was set to rms.

#### Remark: Reference test setup 1

#### Test Settings

- 1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
- 2. Span was set large enough so as to capture all out of band emissions near the band edge
- 3. RBW > 1% of the emission bandwidth
- 4. VBW > 3 x RBW
- Detector = RMS
- Number of sweep points ≥ 2 x Span/RBW
- 7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
- 8. Sweep time = auto couple
- 9. The trace was allowed to stabilize



邮编: 518057

Report No.: ZEWA2310000147RG05

Page: 17 of 29

## 4.5 Spurious And Harmonic Emissions at Antenna Terminal

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 6.0

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyzer, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel and high channel). The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

#### Remark: Reference test setup 1

#### **Test Settings**

- 1. Start frequency was set to 9kHz and stop frequency was set to at least 10\* the fundamental frequency(Separated into at least two plots per channel)
- 2. Detector = RMS
- 3. Trace mode = trace average for continuous emissinos, max hold for pulse emissions
- 4. Sweep time = auto couple
- 5. The trace was allowed to stabilize
- 6. Please see test notes below for RBW and VBW settings



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions.">https://www.sgs.com/en/Terms-and-Conditions.</a>
Indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, foregrey or falsification of the content or appearance of this document is unally and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. to the fullest extent of the law. Online was a sample(s) are retained for 3 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 83071443,

Report No.: ZEWA2310000147RG05

Page: 18 of 29

## 4.6 Peak-Average Ratio

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 5.7.2

A peak to average ratio measurement is performed at the conducted port of the EUT. For WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth. The traces are generated with the spectrum analyzer set to zero span mode.

#### Remark: Reference test setup 1

#### Test Settings

- 1. The signal analyzer's CCDF measurement profile is enabled
- 2. Frequency = carrier center frequency
- 3. Measurement BW > Emission bandwidth of signal
- 4. The signal analyzer was set to collect one million samples to generate the CCDF curve
- 5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power



ZEWA2310000147RG05 Report No.:

19 of 29 Page:

## 4.7 Field Strength of Spurious Radiation

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 5.8

#### Below 1GHz test procedure as below:

- 1). The EUT was powered ON and placed on a 80cm high table in the chamber. The antenna of the transmitter was extended to its maximum length.
- 2). The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made.
- 3). Steps 1) and 2) were performed with the EUT and the receive antenna in both vertical and horizontal polarization.
- 4). Test the EUT in the lowest channel, the middle channel, the Highest channel.
- 5). The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, Only the test worst case mode is recorded in the report.
- 6). Repeat above procedures until all frequencies measured was complete.

E (dBμV/m) = Measured amplitude level (dBμV) + (Cable Loss (dB) + Antenna Factor (dB/m) – AMP(dB)) EIRP (dBm) = E (dB $\mu$ V/m) + 20 log D - 104.8; where D is the measurement distance in meters

#### Above 1GHz test procedure as below:

- 1) Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber
- 2) Calculate power in dBm by the following formula:

E (dBμV/m) = Measured amplitude level (dBμV) + (Cable Loss (dB) + Antenna Factor (dB/m) – AMP(dB)) EIRP (dBm) = E (dBμV/m) + 20 log D - 104.8; where D is the measurement distance in meters

- 3). Test the EUT in the lowest channel, the middle channel the Highest channel
- 4). The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, Only the test worst case mode is recorded in the report.
- 5). Repeat above procedures until all frequencies measured was complete

Remark1: Reference test setup 2

Remark2: The emission below 18G were measured at a 3m test distance, while emissions above 18GHz were measured at a 1m test distance. At a measurement distance of 1 meter the limit line was increased by 20\*LOG(3/1) = 9.54 dB.

#### Remark: Reference test setup 2

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & AMP. The basic equation with a sample calculation is as follows:

AF = Antenna Factor(dB/m)

Factor = Cable Factor(dB) - Preamplifier (dB)

Level = Reading Level + AF + Factor -95.26

Margin = Limit - Level

2) Scan from 9kHz to 40GHz, The disturbance between 9KHz to 30MHz and 18GHz to 40GHz was very low, and the harmonics were the highest point could be found when testing, so only the harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

3) All modes have been tested, but only the worst case data displayed in this report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions">https://www.sgs.com/en/Terms-and-Conditions</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exciting all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, foregrey or falsification of the content or appearance of this document is unlauf and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. to the fullest extent of the law. Online was a sample(s) are retained for 3 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 83071443,

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053

中国・广东・深圳市南山区科技园中区M-10栋1号厂房

邮编: 518057 t (86-755) 26012053

Report No.: ZEWA2310000147RG05

Page: 20 of 29

## 4.8 Frequency Stability / Temperature Variation

Measurement Procedure:

Frequency stability testing is performed in accordance with the guidelines of FCC KDB 971168 D01 V03r01; Section 9

- . The frequency stability of the transmitter is measured by:
- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5 ppm) of the center frequency.

#### Time Period and Procedure:

- 1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
- 2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
- 3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Remark: Reference test setup 3




Report No.: ZEWA2310000147RG05


Page: 21 of 29

## 4.9 Test Setups

#### 4.9.1 **Test Setup 1**



#### 4.9.2 **Test Setup 2**





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions">https://www.sgs.com/en/Terms-and-Conditions</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that Information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from execting all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, foregrey or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 83071443, or email: CAD Doccheck@sus.com"


t (86-755) 26012053 www.sgsgroup.com.cn



Report No.: ZEWA2310000147RG05

Page: 22 of 29

#### 4.9.3 **Test Setup 3**





Report No.: ZEWA2310000147RG05

Page: 23 of 29

## 4.10 Test Conditions

|                  | itions   |  |  |  |  |
|------------------|--|--|--|--|--|
|                  | Transmit Output Power Data - Average Power, Total                      |  |  |  |  |
| Test Case        | Test Conditions  |  |  |  |  |
| Test Environment | Ambient Climate & Rated Voltage  |  |  |  |  |
| Test Setup       | Test Setup 1   |  |  |  |  |
| RF Channels (TX) | L, M, H (L= low channel, M= middle channel, H= high channel)           |  |  |  |  |
| Test Mode        | NR/TM1; NR/TM2; NR/TM3; NR/TM4; NR/TM5; NR/TM6; NR/TM7; NR/TM8; NR/TM9 |  |  |  |  |
|                  | Peak-to-Average Ratio  |  |  |  |  |
| Test Case        | Test Conditions  |  |  |  |  |
| Test Environment | Ambient Climate & Rated Voltage  |  |  |  |  |
| Test Setup       | Test Setup 1   |  |  |  |  |
| RF Channels (TX) | L, M, H (L= low channel, M= middle channel, H= high channel)           |  |  |  |  |
| Test Mode        | NR/TM5; NR/TM9   |  |  |  |  |
|                  | Bandwidth - Occupied Bandwidth   |  |  |  |  |
| Test Case        | Test Conditions  |  |  |  |  |
| Test Environment | Ambient Climate & Rated Voltage  |  |  |  |  |
| Test Setup       | Test Setup 1   |  |  |  |  |
| RF Channels (TX) | M (M= middle channel)  |  |  |  |  |
| Test Mode        | NR/TM1; NR/TM2; NR/TM3; NR/TM4; NR/TM5; NR/TM6; NR/TM7; NR/TM8; NR/TM9 |  |  |  |  |
|                  | Bandwidth - Emission Bandwidth   |  |  |  |  |
| Test Case        | Test Conditions  |  |  |  |  |
| Test Environment | Ambient Climate & Rated Voltage  |  |  |  |  |
| Test Setup       | Test Setup 1   |  |  |  |  |
| RF Channels (TX) | M (M= middle channel)  |  |  |  |  |
| Test Mode        | NR/TM1; NR/TM2; NR/TM3; NR/TM4; NR/TM5; NR/TM6; NR/TM7; NR/TM8; NR/TM9 |  |  |  |  |
|                  | Adjacent Channel Leakage Ratio   |  |  |  |  |
| Test Case        | Test Conditions  |  |  |  |  |
| Test Environment | Ambient Climate & Rated Voltage  |  |  |  |  |
| Test Setup       | Test Setup 1   |  |  |  |  |
| RF Channels (TX) | L, M, H (L= low channel, M= middle channel, H= high channel )          |  |  |  |  |
| Test Mode        | NR/TM1   |  |  |  |  |
|                  | Band Edges Compliance  |  |  |  |  |
| Test Case        | Test Conditions  |  |  |  |  |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions">https://www.sgs.com/en/Terms-and-Conditions</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from excising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document to unique and printeders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN. Doccheck@sos.com"

www.sgsgroup.com.cn



Report No.: ZEWA2310000147RG05

Page: 24 of 29

| Test Environment                     | Ambient Climate & Rated Voltage   |  |  |  |
|--------------------------------------|---|--|--|--|
|                                      | · ·   |  |  |  |
| Test Setup                           | Test Setup 1  |  |  |  |
| RF Channels (TX)                     | L, H (L= low channel, H= high channel)  |  |  |  |
| Test Mode                            | NR/TM1; NR/TM6  |  |  |  |
|                                      | Spurious Emission at Antenna Terminals  |  |  |  |
| Test Case                            | Test Conditions   |  |  |  |
| Test Environment                     | Ambient Climate & Rated Voltage   |  |  |  |
| Test Setup                           | Test Setup 1  |  |  |  |
| RF Channels (TX)                     | L, M, H (L= low channel, M= middle channel, H= high channel)  |  |  |  |
| Test Mode                            | NR/TM1  |  |  |  |
| Field Strength of Spurious Radiation |   |  |  |  |
| Test Case                            | Test Conditions   |  |  |  |
| Test Environment                     | Ambient Climate & Rated Voltage   |  |  |  |
| Test Setup                           | Test Setup 2  |  |  |  |
| RF Channels (TX)                     | L, M, H (L= low channel, M= middle channel, H= high channel)  |  |  |  |
| Test Mode                            | NR/TM1 Remark: All bandwidth and modulation of NR have been pre tested, and only the worst results are reflected in the report. |  |  |  |
|                                      | Frequency Stability   |  |  |  |
| Test Case                            | Test Conditions   |  |  |  |
| T4 Fi                                | (1) -30 °C to +50 °C with step 10 °C at Rated Voltage   |  |  |  |
| Test Environment                     | (2) VL, VN and VH of Rated Voltage at Ambient Climate.  |  |  |  |
| Test Setup                           | Test Setup 3  |  |  |  |
| RF Channels (TX)                     | M (M= middle channel)   |  |  |  |
| Test Mode                            | NR/TM1; NR/TM6  |  |  |  |
| rest wode                            | The report only show the bandwidth with the worst case.   |  |  |  |



Report No.: ZEWA2310000147RG05

Page: 25 of 29

#### 5 **Main Test Instruments**

| RF conducted test (for report ZEWM2306000841RG02) |  |                  |                 |                           |                              |
|---|--|------------------|-----------------|---------------------------|------------------------------|
| Test Equipment                                    | Manufacturer                                   | Model No.        | Inventory No.   | Cal. date<br>(yyyy/mm/dd) | Cal.Due date<br>(yyyy/mm/dd) |
| Signal Generator                                  | Rohde &<br>Schwarz                             | SMR20            | SZ-WRG-M-034    | 2022/09/22                | 2023/09/21                   |
| Signal Generator                                  | Keysight                                       | N5182B           | SZ-WRG-M-015    | 2023/02/16                | 2024/02/15                   |
| Spectrum Analyzer                                 | Keysight                                       | N9020A           | SZ-WRG-M-018    | 2022/05/31                | 2023/05/30                   |
| Spectrum Analyzer                                 | Reysignt                                       | N9020A           | 32-VVKG-IVI-016 | 2023/05/25                | 2024/05/24                   |
| Radio<br>Communication<br>Tester                  | Anritsu  | MT8821C          | SZ-WRG-M-014    | 2022/09/22                | 2023/09/21                   |
| Radio<br>Communication<br>Tester                  | Anritsu  | MT8000A          | SZ-WRG-M-013    | 2022/09/22                | 2023/09/21                   |
| DC power supply                                   | HYELEC   | HY3005B          | SZ-WRG-M-024    | 2022/09/22                | 2023/09/21                   |
| Humidity/<br>Temperature<br>Indicator             | Shanghai<br>Meteorological<br>Industry Factory | HTC-1            | SZ-WRG-M-022    | 2023/02/17                | 2024/02/16                   |
| Programmable<br>Temperature &                     | Votsch<br>Industrietechnik                     | VT 4002          | SZ-WRG-M-075    | 2022/06/09                | 2023/06/08                   |
| Humidity Chamber                                  | GmbH   | V 1 4002         | 32-WKG-W-073    | 2023/05/25                | 2024/05/24                   |
| RF Control Unit                                   | Tonscend                                       | JS0806-1         | SZ-WRG-A-019    | NCR                       | NCR                          |
| BandRejectFilter<br>Group                         | Tonscend                                       | JS0806-F         | SZ-WRG-A-020    | NCR                       | NCR                          |
| Test Software                                     | Tonscend                                       | TS1120<br>V2.4.1 | N/A             | NCR                       | NCR                          |
| Signal &Spectrum<br>Analyzer                      | Rohde &<br>Schwarz                             | FSV              | SZ-WRG-M-048    | 2023/02/16                | 2024/02/15                   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions">https://www.sgs.com/en/Terms-and-Conditions</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from excising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document to unique and printeders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN. Doccheck@sos.com"

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86–755) 26012053

中国・广东・深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057



Report No.: ZEWA2310000147RG05

Page: 26 of 29

| RF conducted test (for report ZEWA2310000147RG02) |  |           |               |                           |                              |
|---|--|-----------|---------------|---------------------------|------------------------------|
| Test Equipment                                    | Manufacturer                                   | Model No. | Inventory No. | Cal. date<br>(yyyy/mm/dd) | Cal.Due date<br>(yyyy/mm/dd) |
| Signal Generator                                  | Rohde &<br>Schwarz                             | SMR 20    | SZ-WRG-M-034  | 2023/09/14                | 2024/09/13                   |
| MXG Vector Signal<br>Generator                    | Keysight                                       | N5182B    | SZ-WRG-M-015  | 2023/02/16                | 2024/02/15                   |
| Spectrum Analyzer                                 | Keysight                                       | N9020A    | SZ-WRG-M-018  | 2023/05/25                | 2024/05/24                   |
| Radio<br>Communication<br>Tester                  | Anritsu  | MT8821C   | SZ-WRG-M-014  | 2023/09/14                | 2024/09/13                   |
| Radio<br>Communication<br>Tester                  | Anritsu  | MT8000A   | SZ-WRG-M-013  | 2023/09/14                | 2024/09/13                   |
| Digital Multimeter                                | VICTOR   | VC890C    | 374464013173  | 2023/02/06                | 2024/02/05                   |
| DC power supply                                   | HYELEC   | HY3005B   | SZ-WRG-M-024  | 2023/09/14                | 2024/09/13                   |
| Programmable<br>Temperature &<br>Humidity Chamber | Votsch<br>Industrietechnik<br>GmbH             | VT 4002   | SZ-WRG-M-017  | 2022/12/22                | 2023/12/21                   |
| Humi/ Temp<br>Indicator                           | Shanghai<br>Meteorological<br>Industry Factory | HTC-1     | SZ-WRG-M-022  | 2023/02/17                | 2024/02/16                   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions">https://www.sgs.com/en/Terms-and-Conditions</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from excising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refor only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CVD.Doccheck@sos.com"

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 www.sgsgroup.com.cn



Report No.: ZEWA2310000147RG05

Page: 27 of 29

| Radiated spurious emissions (for report ZEWA2310000147RG02) |                    |                      |               |                           |                              |
|---|--------------------|----------------------|---------------|---------------------------|------------------------------|
| Test Equipment  | Manufacturer       | Model No.            | Inventory No. | Cal. date<br>(yyyy/mm/dd) | Cal.Due date<br>(yyyy/mm/dd) |
| EMI TEST<br>RECEIVER  | Rohde &<br>Schwarz | ESR                  | SZ-WRG-M-047  | 2023/02/16                | 2024/02/15                   |
| Signal &Spectrum<br>Analyzer                                | Rohde &<br>Schwarz | FSV                  | SZ-WRG-M-048  | 2023/02/16                | 2024/02/15                   |
| Low Noise<br>Amplifier<br>9K-3GHz                           | Tonscend           | TAP9K3G32            | SZ-WRG-M-049  | 2023/02/16                | 2024/02/15                   |
| Low Noise<br>Amplifier<br>30M-8GHz                          | Tonscend           | TAP30M8G30           | SZ-WRG-M-050  | 2023/02/16                | 2024/02/15                   |
| Low Noise<br>Amplifier<br>1G-18GHz                          | Tonscend           | TAP01018050          | SZ-WRG-M-051  | 2023/02/16                | 2024/02/15                   |
| Low Noise<br>Amplifier<br>18G-40GHz                         | Tonscend           | TAP18040048          | SZ-WRG-M-052  | 2023/02/16                | 2024/02/15                   |
| Active Loop<br>Antenna<br>9kHz-30MHz                        | SCHWARZBECK        | FMZB 1519B           | SZ-WRG-M-053  | 2022/01/16                | 2024/01/15                   |
| TRILOG<br>Breitband<br>Antenne<br>30MHz-1GHz                | SCHWARZBECK        | VULB 9168            | SZ-WRG-M-054  | 2022/01/16                | 2024/01/15                   |
| Double Ridge<br>Horn Antenna<br>1GHz-18GHz                  | SCHWARZBECK        | BBHA 9120 D          | SZ-WRG-M-055  | 2022/01/16                | 2024/01/15                   |
| SHF-EHF Horn<br>15GHz-40GHz                                 | SCHWARZBECK        | BBHA 9170            | SZ-WRG-M-056  | 2022/01/16                | 2024/01/15                   |
| Radio<br>Communication<br>Tester                            | STARPOINT          | SP9500               | SZ-WRG-M-057  | 2023/01/10                | 2024/01/09                   |
| RSE Test<br>Software  | Tonscend           | JS32-RSE<br>V4.0.0   | SZ-WRG-S-058  | NCR                       | NCR                          |
| RE Test Software  | Tonscend           | JS36-RSE<br>V5.0.0.1 | SZ-WRG-S-059  | NCR                       | NCR                          |
| Radio<br>Communication<br>Tester                            | Anritsu            | MT8821C              | SZ-WRG-M-042  | 2023/05/25                | 2024/05/24                   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions">https://www.sgs.com/en/Terms-and-Conditions</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from excising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refor only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CVD.Doccheck@sos.com"

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86–755) 26012053 www.sgsgroup.com.cn

中国・广东・深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057

Report No.: ZEWA2310000147RG05

Page: 28 of 29

#### **Measurement Uncertainty** 6

For a 95% confidence level (k = 2), the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

| No. | Item                                | Measurement Uncertainty |
|-----|-------------------------------------|-------------------------|
| 1   | Radio Frequency                     | ± 9.84Hz                |
| 2   | Duty cycle                          | ± 0.185%                |
| 3   | Occupied Bandwidth                  | ± 0.20%                 |
| 4   | RF conducted power                  | ± 0.42dB                |
| 5   | RF power density                    | ± 1.97dB                |
| 6   | Conducted Spurious emissions        | ± 0.42dB                |
|     |                                     | ±4.8dB (30MHz-1GHz)     |
| 7   | Radiated Spurious emission test(UE) | ±4.68dB (1GHz-6GHz)     |
| /   |                                     | ±4.52dB (6GHz-18GHz)    |
|     |                                     | ±5.26dB (18GHz-40GHz)   |

The U<sub>lab</sub> (lab Uncertainty) is less than U<sub>cispr/ETSI</sub> (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;

- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



邮编: 518057



Report No.: ZEWA2310000147RG05

Page: 29 of 29

# 7 Appendixes

| Appendix A.3  | WWAN Setup Photos-part96 |
|---------------|--------------------------|
| Appendix B.50 | NR Band n48(3550-3700)   |

---End of Report---



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions">https://www.sgs.com/en/Terms-and-Conditions</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from excising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document to unique and printeders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN. Doccheck@sos.com"