

# RF Exposure Evaluation Report

**APPLICANT** : Quetel Wireless Solutions Co., Ltd.  
**EQUIPMENT** : Wi-Fi & Bluetooth Module  
**BRAND NAME** : Quetel  
**MODEL NAME** : FCS861L  
**FCC ID** : XMR2024FCS861L  
**STANDARD** : 47 CFR Part 2.1091

The product evaluation date was started from Apr. 01, 2024 and completed on Apr. 01, 2024. We, Sporton International Inc. (Kunshan), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Si Zhang

**Sporton International Inc. (Kunshan)**

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China**



## **Table of Contents**

<b>1. ADMINISTRATION DATA</b> .....	<b>4</b>
1.1. Testing Laboratory .....	4
<b>2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)</b> .....	<b>5</b>
<b>3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS</b> .....	<b>6</b>
<b>4. RF EXPOSURE LIMIT INTRODUCTION</b> .....	<b>8</b>
<b>5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION</b> .....	<b>9</b>
5.1. Standalone Power Density Calculation .....	9
5.2. Collocated Power Density Calculation.....	9





## **1. Administration Data**

### **1.1. Testing Laboratory**

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

<b>Testing Laboratory</b>			
<b>Test Firm</b>	Sporton International Inc. (Kunshan)		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	SAR01-KS	CN1257	314309

<b>Applicant</b>	
<b>Company Name</b>	Quectel Wireless Solutions Co., Ltd.
<b>Address</b>	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai 200233, China

<b>Manufacturer</b>	
<b>Company Name</b>	Quectel Wireless Solutions Co., Ltd.
<b>Address</b>	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai 200233, China

## 2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	Wi-Fi & Bluetooth Module
Brand Name	Quectel
Model Name	FCS861L
FCC ID	XMR2024FCS861L
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	WLAN 2.4GHz 802.11b/g WLAN 2.4GHz 802.11n HT20/HT40 WLAN 2.4GHz 802.11ac VHT20/VHT40 WLAN 2.4GHz 802.11ax HE20/HE40 WLAN 5GHz 802.11a WLAN 5GHz 802.11n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 WLAN 5GHz 802.11ax HE20/HE40/HE80 Bluetooth BR/EDR/LE
Antenna Type	Dipole antenna
HW Version	R1.0
SW Version	NA
EUT Stage	Identical Prototype

**Remark:**

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. WLAN2.4GHz /WLAN5GHz all support SISO and MIMO mode, and MIMO mode is only for WLAN 2.4GHz 802.11n/ac/ax HT20/HT40/VHT20/VHT40/HE20/HE40 and WLAN 5GHz 802.11n/ac/ax HT20/HT40/VHT20/VHT40 /VHT80/HE20/HE40/HE80.
3. Chose the maximum RF output tune up power of all antennas among same frequency WLAN/BT bands and the maximum antenna gain to perform MPE calculation conservatively.

**Comments and Explanations:**

1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.

**Antenna Gain:**

WLAN	Ant.0	Ant.1
WLAN2.4GHz	-0.1	-0.1
WLAN5.2GHz	-0.9	-0.9
WLAN5.3GHz	-1.4	-1.4
WLAN5.5GHz	-0.3	-0.3
WLAN5.8GHz	0.4	0.4
BT	BT/WIFI 0 Path	BT Path
Bluetooth	-0.1	-0.1



**3. Maximum RF average output tune up power among production units**

**<Bluetooth>**

Mode	Maximum Average Power (dBm)	
	BT/WIFI 0 Path	BT Path
Bluetooth BR/EDR	9.00	8.00
Bluetooth LE	9.00	3.00

**<2.4GHz WLAN >**

Mode	Maximum Average Power (dBm)			
	Ant.0	Ant.1	Ant.0+1	
2.4GHz	802.11b	23.00	23.00	/
	802.11g	23.00	23.00	/
	802.11n-HT20	13.00	13.00	16.00
	802.11n-HT40	14.00	14.00	17.00
	802.11ac-VHT20	13.00	13.00	16.00
	802.11ac-VHT40	14.00	14.00	17.00
	802.11ax-HE20	13.00	13.00	16.00
	802.11ax-HE40	14.00	14.00	17.00



**<5GHz WLAN >**

Mode		Maximum Average Power (dBm)		
		Ant.0	Ant.1	Ant.0+1
5.2GHz	802.11a	16.00	16.00	/
	802.11n-HT20	15.00	15.00	18.00
	802.11n-HT40	15.00	15.00	18.00
	802.11ac-VHT20	14.00	14.00	17.00
	802.11ac-VHT40	15.00	15.00	18.00
	802.11ac-VHT80	11.00	11.00	14.00
	802.11ax-HE20	14.00	14.00	17.00
	802.11ax-HE40	15.00	15.00	18.00
5.3GHz	802.11a	16.00	16.00	/
	802.11n-HT20	15.00	15.00	18.00
	802.11n-HT40	15.00	15.00	18.00
	802.11ac-VHT20	14.00	14.00	17.00
	802.11ac-VHT40	15.00	15.00	18.00
	802.11ac-VHT80	11.00	11.00	14.00
	802.11ax-HE20	14.00	14.00	17.00
	802.11ax-HE40	15.00	15.00	18.00
5.5GHz	802.11a	17.00	17.00	/
	802.11n-HT20	16.00	16.00	19.00
	802.11n-HT40	16.00	16.00	19.00
	802.11ac-VHT20	16.00	16.00	19.00
	802.11ac-VHT40	16.00	16.00	19.00
	802.11ac-VHT80	15.00	15.00	18.00
	802.11ax-HE20	16.00	16.00	19.00
	802.11ax-HE40	16.00	16.00	19.00
5.8GHz	802.11a	17.00	17.00	/
	802.11n-HT20	16.00	16.00	19.00
	802.11n-HT40	16.00	16.00	19.00
	802.11ac-VHT20	15.00	15.00	18.00
	802.11ac-VHT40	16.00	16.00	19.00
	802.11ac-VHT80	15.00	15.00	18.00
	802.11ax-HE20	15.00	15.00	18.00
	802.11ax-HE40	16.00	16.00	19.00

Note: WLAN2.4GHz 802.11n/ac /ax and WLAN5GHz 802.11n/ac/ax all support SISO/MIMO mode, chose the maximum RF output tune up power of all antennas among same frequency WLAN bands and the maximum antenna gain to perform MPE calculation conservatively.



### 4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

- S = Power Density
- P = Output Power at Antenna Terminals
- G = Gain of Transmit Antenna (linear gain)
- R = Distance from Transmitting Antenna





### 5. Radio Frequency Radiation Exposure Evaluation

#### 5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Power Density / Limit
2.4GHz WLAN	2412.0	-0.10	23.00	22.900	194.984	0.039	1.000	<b>0.039</b>
5.2GHz WLAN	5180.0	-0.90	18.00	17.100	51.286	0.010	1.000	0.010
5.3GHz WLAN	5260.0	-1.40	18.00	16.600	45.709	0.009	1.000	0.009
5.5GHz WLAN	5500.0	-0.30	19.00	18.700	74.131	0.015	1.000	0.015
5.8GHz WLAN	5745.0	0.40	19.00	19.400	87.096	0.017	1.000	<b>0.017</b>
Bluetooth	2402.0	-0.10	9.00	8.900	7.762	0.002	1.000	<b>0.002</b>

**Note:**

- For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
- WLAN2.4GHz and WLAN5GHz chose the higher SISO gain as MIMO gain to perform MPE calculation.
- Chose the maximum RF output tune up power of all antennas among same frequency WLAN/BT bands and the maximum antenna gain to perform MPE calculation conservatively.

#### 5.2. Collocated Power Density Calculation

Bluetooth Power Density / Limit	WLAN 5GHz Power Density / Limit	Σ(Power Density / Limit) of Bluetooth + WLAN 5GHz
0.002	0.017	0.019

Bluetooth Power Density / Limit	WLAN 2.4GHz Power Density / Limit	Σ(Power Density / Limit) of Bluetooth + WLAN 2.4GHz
0.002	0.039	0.041

**Note:**

- According to the EUT characteristic, Bluetooth antennas cannot transmit simultaneously.
- According to the EUT characteristic, WLAN 2.4GHz and WLAN5GHz cannot transmit simultaneously.
- Σ(Power Density / Limit): This is a summation of [(power density for each transmitter/antenna included in the simultaneous transmission) / (corresponding MPE limit)], for Bluetooth +WLAN5GHz, Bluetooth + WLAN2.4GHz.
- Considering all transmitter of the EIRP performance listed in the table above, the aggregated (power density /limit) is smaller than 1.

### Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----