



FCC RF Test Report

APPLICANT : Quectel Wireless Solutions Co., Ltd.
EQUIPMENT : Smart LTE Module
BRAND NAME : Quectel
MODEL NAME : SC200E-AU
FCC ID : XMR2024SC200EAU
STANDARD : 47 CFR Part 22(H), 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter (PCB)
TEST DATE(S) : Aug. 08, 2024 ~ Aug. 20, 2024

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

***No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China***



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	6
1.5 Modification of EUT	6
1.6 Maximum Conducted Power, and Emission Designator	7
1.7 Testing Location	7
1.8 Test Software	7
1.9 Applicable Standards	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System	10
2.3 Support Unit used in test configuration	10
2.4 Measurement Results Explanation Example	11
2.5 Frequency List of Low/Middle/High Channels	11
3 CONDUCTED TEST RESULT.....	12
3.1 Measuring Instruments.....	12
3.2 Test Setup	12
3.3 Test Result of Conducted Test.....	12
3.4 Conducted Output Power and ERP/EIRP	13
3.5 Peak-to-Average Ratio	14
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	15
3.7 Conducted Band Edge	16
3.8 Conducted Spurious Emission	17
3.9 Frequency Stability	18
4 RADIATED TEST ITEMS	19
4.1 Measuring Instruments.....	19
4.2 Test Setup	19
4.3 Test Result of Radiated Test.....	20
4.4 Field Strength of Spurious Radiation Measurement	21
5 LIST OF MEASURING EQUIPMENT	22
6 MEASUREMENT UNCERTAINTY	23
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG480203A	Rev. 01	Initial issue of report	Nov. 29, 2024

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	-	Report Only	-
	§22.913(a)(5)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053; §22.917(a); §24.238(a); §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 29.60 dB at 3765.00 MHz

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Quectel Wireless Solutions Co., Ltd.

Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai 200233, China

1.2 Manufacturer

Quectel Wireless Solutions Co., Ltd.

Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai 200233, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart LTE Module
Brand Name	Quectel
Model Name	SC200E-AU
FCC ID	XMR2024SC200EAU
IMEI Code	Conducted: 866080060008526/866080060008534 Radiation: 866080060009029/866080060009037
HW Version	R1.0
SW Version	SC200EAUDAR12A01
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM/GPRS/EDGE: 850: 824 MHz ~ 849 MHz 1900: 1850MHz ~ 1910MHz WCDMA: Band V: 824 MHz ~ 849 MHz Band II: 1850 MHz ~ 1910 MHz Band IV: 1710 MHz ~ 1755 MHz
Rx Frequency	GSM/GPRS/EDGE: 850: 869 MHz ~ 894 MHz 1900: 1930 MHz ~ 1990 MHz WCDMA: Band V: 869 MHz ~ 894 MHz Band II: 1930 MHz ~ 1990 MHz Band IV: 2110 MHz ~ 2155 MHz
Maximum Output Power to Antenna	GSM/GPRS/EDGE: 850: 33.53 dBm 1900: 31.02 dBm WCDMA: Band V: 24.27 dBm Band II: 24.23 dBm Band IV: 24.33 dBm
Antenna Type	Dipole Antenna
Antenna Gain	Cellular Band: 2.2 dBi PCS Band: 1.59 dBi AWS Band: 2.0 dBi
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: BPSK HSPA: QPSK HSPA+ : 16QAM DC-HSDPA: 64QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Maximum Conducted Power, and Emission Designator

FCC Rule	Frequency Band	Frequency Range (MHz)	Type of Modulation	Maximum Conducted power (W)	Emission Designator
Part 22H	GSM850 (GSM)	824.2 ~ 848.8	GMSK	2.2542	244KGXW
Part 22H	GSM850 (EDGE)	824.2 ~ 848.8	8PSK	0.7261	240KG7W
Part 22H	WCDMA Band V	826.4 ~ 846.6	BPSK	0.2673	4M12F9W
Part 24E	GSM1900 (GSM)	1850.2 ~ 1909.8	GMSK	1.2647	243KGXW
Part 24E	GSM1900 (EDGE)	1850.2 ~ 1909.8	8PSK	0.6486	246KG7W
Part 24E	WCDMA Band II	1852.4 ~ 1907.6	BPSK	0.2649	4M12F9W
Part 27L	WCDMA Band IV	1712.4 ~ 1752.6	BPSK	0.2710	4M11F9W

1.7 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH04-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	SPORTON	Part2224_Ver5.0 200330	5.0
2.	03CH04-KS	AUDIX	E3	210616



1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 22(H), 24(E), 27(L)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.(X-Plane)

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19100 MHz for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GSM Link ■ EDGE 1 Tx slots Link	■ GSM Link ■ EDGE 1 Tx slots Link
GSM 1900	■ GSM Link ■ EDGE 1 Tx slots Link	■ GSM Link ■ EDGE 1 Tx slots Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



The EUT has been configuration operated in a manner tended to maximize its emission characteristics in a typical application.

2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	Test Jig	N/A	N/A	N/A	N/A	N/A
4.	Antenna	N/A	N/A	N/A	N/A	N/A
5.	Adapter	N/A	N/A	N/A	N/A	N/A



2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

The following shows an offset computation example with RF cable loss 5.3 dB.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} \\ &= 5.3 \text{ (dB)}\end{aligned}$$

2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	Channel/Frequency(MHz)	Lowest	Middle	Highest
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6


3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2023	Aug. 08, 2024	Oct. 10, 2024	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	NCR	Aug. 08, 2024	NCR	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 04, 2024	Aug. 08, 2024	Jul. 03, 2025	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY57471079	10Hz~44G,MAX 30dB	Oct. 11, 2023	Aug. 19, 2024~ Aug. 20, 2024	Oct. 10, 2024	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 11 2023	Aug. 19, 2024~ Aug. 20, 2024	Sep. 10, 2024	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz~1GHz	Dec. 06, 2023	Aug. 19, 2024~ Aug. 20, 2024	Dec. 05, 2024	Radiation (03CH04-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 23, 2023	Aug. 19, 2024~ Aug. 20, 2024	Oct. 22, 2024	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 27, 2024	Aug. 19, 2024~ Aug. 20, 2024	Jan. 26, 2025	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	413740	9KHz~1GHz	Jan. 03, 2024	Aug. 19, 2024~ Aug. 20, 2024	Jan. 02, 2025	Radiation (03CH04-KS)
Amplifier	EM	EM18G40G A	060728	18~40GHz	Jan. 02, 2024	Aug. 19, 2024~ Aug. 20, 2024	Jan. 01, 2025	Radiation (03CH04-KS)
high gain Amplifier	EM	EM01G18G A	060840	1Ghz~18Ghz	Oct. 11, 2023	Aug. 19, 2024~ Aug. 20, 2024	Oct. 10, 2024	Radiation (03CH04-KS)
Amplifier	EM	EM01G18G A	060892	1Ghz~18Ghz	Oct. 11, 2023	Aug. 19, 2024~ Aug. 20, 2024	Oct. 10, 2024	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Aug. 19, 2024~ Aug. 20, 2024	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Aug. 19, 2024~ Aug. 20, 2024	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Aug. 19, 2024~ Aug. 20, 2024	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required



6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	±2.26 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.50 dB
Peak to Average Ratio	±0.50 dB
Frequency Stability	±0.04ppm

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.83 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.83 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.82 dB
---	---------

----- THE END -----



Appendix A. Test Results of Conducted Test

Test Engineer :	Simle Wang	Temperature :	22~23°C
		Relative Humidity :	40~42%

Conducted Output Power(Average power) and ERP/EIRP

GSM850

GSM850	Burst Average Power (dBm)			ERP(W)		
TX Channel	128	189	251			
Frequency (MHz)	824.2	836.4	848.8	L	M	H
GSM 1 Tx slot	33.51	33.42	33.53	2.2699	2.2233	2.2803
GPRS 1 Tx slot	33.28	33.24	33.17	2.1528	2.1330	2.0989
GPRS 2 Tx slots	30.12	30.33	30.52	1.0399	1.0914	1.1402
GPRS 3 Tx slots	29.02	29.16	29.04	0.8072	0.8337	0.8110
GPRS 4 Tx slots	27.13	27.38	27.18	0.5224	0.5534	0.5284
EDGE 1 Tx slot	28.54	28.27	28.61	0.7228	0.6792	0.7345
EDGE 2 Tx slots	26.47	26.86	26.55	0.4487	0.4909	0.4571
EDGE 3 Tx slots	25.22	25.39	25.63	0.3365	0.3499	0.3698
EDGE 4 Tx slots	23.52	23.51	23.48	0.2275	0.2270	0.2254

GSM1900

GSM1900	Burst Average Power (dBm)			EIRP(W)		
TX Channel	512	661	810			
Frequency (MHz)	1850.2	1880	1909.8	L	M	H
GSM 1 Tx slot	30.87	31.02	30.81	1.7620	1.8239	1.7378
GPRS 1 Tx slot	30.75	30.95	30.83	1.7140	1.7947	1.7458
GPRS 2 Tx slots	28.52	28.29	28.46	1.0257	0.9727	1.0116
GPRS 3 Tx slots	26.49	26.37	26.54	0.6427	0.6252	0.6501
GPRS 4 Tx slots	24.59	24.56	24.37	0.4150	0.4121	0.3945
EDGE 1 Tx slot	27.69	28.12	28.06	0.8472	0.9354	0.9226
EDGE 2 Tx slots	25.33	25.19	25.32	0.4920	0.4764	0.4909
EDGE 3 Tx slots	24.36	24.39	24.44	0.3936	0.3963	0.4009
EDGE 4 Tx slots	22.45	22.48	22.51	0.2535	0.2553	0.2570



WCDMA_V

Band		WCDMA V			ERP(W)		
TX Channel		4132	4182	4233			
Rx Channel		4357	4407	4458			
Frequency (MHz)		826.4	836.4	846.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	24.17	14.12	24.03	0.2642	0.0261	0.2559
3GPP Rel 99	RMC 12.2Kbps	24.25	24.27	24.11	0.2692	0.2704	0.2606
3GPP Rel 6	HSDPA Subtest-1	24.12	24.01	24.18	0.2612	0.2547	0.2649
3GPP Rel 6	HSDPA Subtest-2	24.03	24.06	24.10	0.2559	0.2576	0.2600
3GPP Rel 6	HSDPA Subtest-3	23.98	23.81	23.79	0.2529	0.2432	0.2421
3GPP Rel 6	HSDPA Subtest-4	23.49	23.54	23.67	0.2259	0.2286	0.2355
3GPP Rel 8	DC-HSDPA Subtest-1	23.51	23.49	23.36	0.2270	0.2259	0.2193
3GPP Rel 8	DC-HSDPA Subtest-2	23.41	23.21	23.48	0.2218	0.2118	0.2254
3GPP Rel 8	DC-HSDPA Subtest-3	23.26	23.19	23.27	0.2143	0.2109	0.2148
3GPP Rel 8	DC-HSDPA Subtest-4	22.37	22.46	22.59	0.1746	0.1782	0.1837
3GPP Rel 6	HSUPA Subtest-1	22.18	22.37	22.30	0.1671	0.1746	0.1718
3GPP Rel 6	HSUPA Subtest-2	23.48	23.26	23.11	0.2254	0.2143	0.2070
3GPP Rel 6	HSUPA Subtest-3	21.37	21.44	21.58	0.1387	0.1409	0.1455
3GPP Rel 6	HSUPA Subtest-4	22.26	22.47	22.33	0.1702	0.1786	0.1730
3GPP Rel 6	HSUPA Subtest-5	22.98	22.76	22.89	0.2009	0.1910	0.1968
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	22.98	23.04	22.90	0.2009	0.2037	0.1972

WCDMA_IV

Band		WCDMA IV			EIRP(W)		
TX Channel		1312	1413	1513			
Rx Channel		1537	1638	1738			
Frequency (MHz)		1712.4	1732.6	1752.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	23.85	23.78	23.65	0.3846	0.3784	0.3673
3GPP Rel 99	RMC 12.2Kbps	24.33	24.26	24.24	0.4295	0.4227	0.4207
3GPP Rel 6	HSDPA Subtest-1	24.13	24.20	24.22	0.4102	0.4169	0.4188
3GPP Rel 6	HSDPA Subtest-2	23.71	23.92	23.61	0.3724	0.3908	0.3639
3GPP Rel 6	HSDPA Subtest-3	23.33	23.29	23.41	0.3412	0.3381	0.3475
3GPP Rel 6	HSDPA Subtest-4	23.52	23.62	23.55	0.3565	0.3648	0.3589
3GPP Rel 8	DC-HSDPA Subtest-1	23.37	23.58	23.44	0.3443	0.3614	0.3499
3GPP Rel 8	DC-HSDPA Subtest-2	23.11	23.15	23.32	0.3243	0.3273	0.3404
3GPP Rel 8	DC-HSDPA Subtest-3	23.49	23.43	23.37	0.3540	0.3491	0.3443
3GPP Rel 8	DC-HSDPA Subtest-4	23.62	23.64	23.79	0.3648	0.3664	0.3793
3GPP Rel 6	HSUPA Subtest-1	23.45	23.33	23.41	0.3508	0.3412	0.3475
3GPP Rel 6	HSUPA Subtest-2	22.06	21.97	22.83	0.2547	0.2495	0.3041
3GPP Rel 6	HSUPA Subtest-3	22.83	22.81	22.74	0.3041	0.3027	0.2979
3GPP Rel 6	HSUPA Subtest-4	21.36	21.24	21.49	0.2168	0.2109	0.2234
3GPP Rel 6	HSUPA Subtest-5	22.73	22.84	22.98	0.2972	0.3048	0.3148
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	22.92	22.90	22.87	0.3105	0.3090	0.3069



WCDMA_II

Band		WCDMA II			EIRP(W)		
TX Channel		9262	9400	9538			
Rx Channel		9662	9800	9938			
Frequency (MHz)		1852.4	1880	1907.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	23.58	23.74	23.89	0.3289	0.3412	0.3532
3GPP Rel 99	RMC 12.2Kbps	23.93	24.12	24.23	0.3565	0.3724	0.3819
3GPP Rel 6	HSDPA Subtest-1	23.82	23.91	23.83	0.3475	0.3548	0.3483
3GPP Rel 6	HSDPA Subtest-2	23.52	23.49	23.13	0.3243	0.3221	0.2965
3GPP Rel 6	HSDPA Subtest-3	23.27	23.45	23.16	0.3062	0.3192	0.2985
3GPP Rel 6	HSDPA Subtest-4	23.55	23.48	23.05	0.3266	0.3214	0.2911
3GPP Rel 8	DC-HSDPA Subtest-1	23.58	23.46	23.15	0.3289	0.3199	0.2979
3GPP Rel 8	DC-HSDPA Subtest-2	23.27	23.39	23.18	0.3062	0.3148	0.2999
3GPP Rel 8	DC-HSDPA Subtest-3	23.54	23.42	23.36	0.3258	0.3170	0.3126
3GPP Rel 8	DC-HSDPA Subtest-4	23.59	23.27	23.22	0.3296	0.3062	0.3027
3GPP Rel 6	HSUPA Subtest-1	23.25	23.32	22.87	0.3048	0.3097	0.2793
3GPP Rel 6	HSUPA Subtest-2	21.36	21.49	21.23	0.1972	0.2032	0.1914
3GPP Rel 6	HSUPA Subtest-3	22.79	22.68	22.54	0.2742	0.2673	0.2588
3GPP Rel 6	HSUPA Subtest-4	21.35	21.64	21.20	0.1968	0.2104	0.1901
3GPP Rel 6	HSUPA Subtest-5	22.81	22.79	22.83	0.2754	0.2742	0.2767
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	22.71	22.85	22.93	0.2692	0.2780	0.2831



GSM

Peak-to-Average Ratio


Mode	GSM850		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	1.01	3.19	PASS
Middle CH	1.01	3.48	
Highest CH	1.04	3.42	

Mode	GSM1900		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.41	3.36	PASS
Middle CH	0.41	3.16	
Highest CH	0.46	3.16	




GSM850 (GSM)

Lowest Channel




GSM850 (EDGE class 8)


Lowest Channel



Middle Channel




Middle Channel



Highest Channel




Highest Channel






GSM1900 (GSM)

Lowest Channel




GSM1900 (EDGE class 8)


Lowest Channel




Middle Channel




Middle Channel



Highest Channel



Highest Channel





26dB Bandwidth


Mode	GSM850(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.315	0.309
Middle CH	0.318	0.313
Highest CH	0.318	0.296

Mode	GSM1900	
Mod.	GSM	EDGE class 8
Lowest CH	0.314	0.313
Middle CH	0.317	0.313
Highest CH	0.313	0.317




GSM850 (GSM)

Lowest Channel




GSM850 (EDGE class 8)


Lowest Channel




Middle Channel




Middle Channel



Highest Channel




Highest Channel





GSM1900 (GSM)


Lowest Channel



Date: 8.AUG.2024 10:20:15


GSM1900 (EDGE class 8)

Lowest Channel




Date: 8.AUG.2024 10:04:21

Middle Channel




Date: 8.AUG.2024 10:20:49

Middle Channel




Date: 8.AUG.2024 10:04:45

Highest Channel



Date: 8.AUG.2024 10:21:12

Highest Channel



Date: 8.AUG.2024 10:05:12



Occupied Bandwidth


Mode	GSM850(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.244	0.239
Middle CH	0.244	0.236
Highest CH	0.241	0.240

Mode	GSM1900(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.240	0.246
Middle CH	0.243	0.246
Highest CH	0.243	0.246



GSM850 (GSM)

Lowest Channel




GSM850 (EDGE class 8)

Lowest Channel




Middle Channel




Middle Channel



Highest Channel




Highest Channel






GSM1900 (GSM)

Lowest Channel



GSM1900 (EDGE class 8)


Lowest Channel




Middle Channel




Middle Channel



Highest Channel





Highest Channel





Conducted Band Edge









GSM1900 (GSM)

Lowest Band Edge




Highest Band Edge




GSM1900 (EDGE class 8)

Lowest Band Edge



Highest Band Edge






Conducted Spurious Emission

GSM850 (GSM)


Lowest Channel



Date: 8.AUG.2024 11:39:27


GSM850 (EDGE class 8)

Lowest Channel




Date: 8.AUG.2024 09:57:26

Middle Channel




Date: 8.AUG.2024 11:39:47

Middle Channel




Date: 8.AUG.2024 09:57:56

Highest Channel



Date: 8.AUG.2024 11:40:09

Highest Channel




Date: 8.AUG.2024 09:59:35




GSM1900 (GSM)

Lowest Channel




GSM1900 (EDGE class 8)


Lowest Channel




Middle Channel




Middle Channel



Highest Channel



Highest Channel



**Frequency Stability**

Test Conditions	Middle Channel	GSM850 (GSM)	GSM850 (EDGE class 8)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0173	0.0129	PASS
40	Normal Voltage	0.0255	0.0171	
30	Normal Voltage	0.0171	0.0237	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0086	0.0165	
0	Normal Voltage	0.0169	0.0143	
-10	Normal Voltage	0.0257	0.0421	
-20	Normal Voltage	0.0343	0.0175	
-30	Normal Voltage	0.0172	0.0291	
20	Maximum Voltage	0.0096	0.0234	
20	Normal Voltage	0.0000	0.0000	
20	Minimum Voltage	0.0271	0.0238	



Test Conditions	Middle Channel	GSM1900 (GSM)	GSM1900 (EDGE class 8)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0245	0.0212	PASS
40	Normal Voltage	0.0196	0.0171	
30	Normal Voltage	0.0129	0.0145	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0234	0.0247	
0	Normal Voltage	0.0157	0.0144	
-10	Normal Voltage	0.0171	0.0157	
-20	Normal Voltage	0.0254	0.0241	
-30	Normal Voltage	0.0098	0.0159	
20	Maximum Voltage	0.0024	0.0175	
20	Normal Voltage	0.0000	0.0000	
20	Minimum Voltage	0.0174	0.0196	

Note:

1. Normal Voltage = 3.8V ; Minimum Voltage =3.55V. ; Maximum Voltage =4.4V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



WCDMA


Peak-to-Average Ratio

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	2.93	2.99	3.07	PASS
Middle CH	2.99	2.99	3.13	
Highest CH	2.93	2.93	3.10	




WCDMA Band V (RMC 12.2Kbps)

Lowest Channel



WCDMA Band II (RMC 12.2Kbps)


Lowest Channel



Middle Channel



Middle Channel




Highest Channel



Highest Channel





WCDMA Band IV (RMC 12.2Kbps)	-																		
Lowest Channel	-																		
Spectrum Ref Level 5.60 dBm Offset 15.60 dB Att 20 dB AQT 2 ms RBW 10 MHz 1Sa View <table><tr><th colspan="6">Complementary Cumulative Distribution Function</th></tr><tr><th>Mean</th><th>Peak</th><th>Crest</th><th>10%</th><th>1%</th><th>0.1%</th></tr><tr><td>23.75 dBm</td><td>27.11 dBm</td><td>3.36 dB</td><td>1.68 dB</td><td>2.64 dB</td><td>3.07 dB</td></tr></table> CF 1.7124 GHz Mean Pwr = 20.00 dB Trace 1 Measuring... Date: 8.AUG.2024 01:49:18	Complementary Cumulative Distribution Function						Mean	Peak	Crest	10%	1%	0.1%	23.75 dBm	27.11 dBm	3.36 dB	1.68 dB	2.64 dB	3.07 dB	-
Complementary Cumulative Distribution Function																			
Mean	Peak	Crest	10%	1%	0.1%														
23.75 dBm	27.11 dBm	3.36 dB	1.68 dB	2.64 dB	3.07 dB														
Middle Channel	-																		
Spectrum Ref Level 5.60 dBm Offset 15.60 dB Att 20 dB AQT 2 ms RBW 10 MHz 1Sa View <table><tr><th colspan="6">Complementary Cumulative Distribution Function</th></tr><tr><th>Mean</th><th>Peak</th><th>Crest</th><th>10%</th><th>1%</th><th>0.1%</th></tr><tr><td>23.72 dBm</td><td>27.16 dBm</td><td>3.45 dB</td><td>1.74 dB</td><td>2.70 dB</td><td>3.13 dB</td></tr></table> CF 1.7326 GHz Mean Pwr = 20.00 dB Trace 1 Measuring... Date: 8.AUG.2024 01:49:38	Complementary Cumulative Distribution Function						Mean	Peak	Crest	10%	1%	0.1%	23.72 dBm	27.16 dBm	3.45 dB	1.74 dB	2.70 dB	3.13 dB	-
Complementary Cumulative Distribution Function																			
Mean	Peak	Crest	10%	1%	0.1%														
23.72 dBm	27.16 dBm	3.45 dB	1.74 dB	2.70 dB	3.13 dB														
Highest Channel	-																		
Spectrum Ref Level 5.60 dBm Offset 15.60 dB Att 20 dB AQT 2 ms RBW 10 MHz 1Sa View <table><tr><th colspan="6">Complementary Cumulative Distribution Function</th></tr><tr><th>Mean</th><th>Peak</th><th>Crest</th><th>10%</th><th>1%</th><th>0.1%</th></tr><tr><td>23.63 dBm</td><td>27.09 dBm</td><td>3.46 dB</td><td>1.68 dB</td><td>2.64 dB</td><td>3.10 dB</td></tr></table> CF 1.7526 GHz Mean Pwr = 20.00 dB Trace 1 Measuring... Date: 8.AUG.2024 01:50:02	Complementary Cumulative Distribution Function						Mean	Peak	Crest	10%	1%	0.1%	23.63 dBm	27.09 dBm	3.46 dB	1.68 dB	2.64 dB	3.10 dB	-
Complementary Cumulative Distribution Function																			
Mean	Peak	Crest	10%	1%	0.1%														
23.63 dBm	27.09 dBm	3.46 dB	1.68 dB	2.64 dB	3.10 dB														




26dB Bandwidth

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.715	4.705	4.695
Middle CH	4.705	4.705	4.685
Highest CH	4.715	4.715	4.685



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 8.AUG.2024 02:26:53


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 8.AUG.2024 01:53:36

Middle Channel




Date: 8.AUG.2024 02:27:25

Middle Channel




Date: 8.AUG.2024 01:54:07

Highest Channel



Date: 8.AUG.2024 02:27:54

Highest Channel




Date: 8.AUG.2024 01:54:50




WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel




Date: 8.AUG.2024 01:27:17

Middle Channel



Date: 8.AUG.2024 01:27:17

Highest Channel



Date: 8.AUG.2024 01:28:32



Occupied Bandwidth

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.106	4.116	4.106
Middle CH	4.106	4.106	4.106
Highest CH	4.116	4.106	4.106