

Radio Exposure Evaluation Report

FCC ID : XN6-SL512X86
Contains FCC ID : 2AS8LATM210
Equipment : 5.1.2 Soundbar System
Brand Name : VIZIO
Model Name : SL512X-0806
Applicant : Zylux Acoustic Corporation
7F, 70, Rui Guang Road,
Neihu District, Taipei 114, Taiwan
Manufacturer : Zylux Acoustic Corporation
7F, 70, Rui Guang Road,
Neihu District, Taipei 114, Taiwan
Standard : 47 CFR FCC Part 2 Subpart J, section 2.1091

The product was received on Mar. 19, 2024, and testing was started from Mar. 23, 2024 and completed on Mar. 23, 2024. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.



Approved by: Jackson Tsai

SPORTON INTERNATIONAL INC. Hsinhua Laboratory
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



Table of Contents

HISTORY OF THIS TEST REPORT3

SUMMARY OF TEST RESULT4

1 GENERAL DESCRIPTION5

1.1 Information.....5

1.2 Applicable Standards6

1.3 Testing Location6

2 MAXIMUM PERMISSIBLE EXPOSURE7

2.1 Limit of Maximum Permissible Exposure7

2.2 RF Exposure Exempt Measurement8

2.3 Multiple RF Sources Exposure9

2.4 MPE Calculation Method10

2.5 Calculated Result and Limit.....11

Photographs of EUT V01



History of this test report

Report No.	Version	Description	Issued Date
FA420501	01	Initial issue of report	Apr. 29, 2024



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

None

Reviewed by: Ben Tseng
Report Producer: Ann Hou

1 General Description

1.1 Information

1.1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK) LE: DSSS (GFSK)

1.1.2 Antenna Information

Ant.	Port	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	1	WIESON	ARY196-4044-002-00	Omni directional	MHF 1	3.61

Note 1: The EUT has one antenna.

For BT function:

Ant. 1 (port 1) could transmit/receive.

1.1.3 Accessories

Accessories			
AC Power Cord (* 2 pcs)	Signal Line	1.5 meter, Non-Shielded cable, without ferrite core	
HDMI Cable (X1 PCS)	Signal Line	1.83 meter, Non-Shielded cable, without ferrite core	
Audio Cable (X 2 PCS) (for Surround Speaker)	Signal Line	8 meter, Non-Shielded cable, without ferrite core	
Surround Speaker (X 2 PCS)	Brand Name	VIZIO	Model Name SL512X-0806 Surround
	Manufacturer	Zylux	
Wireless Subwoofer (X1 PCS)	Brand Name	VIZIO	Model Name SL512X-0806 subwoofer
	Manufacturer	Zylux	

Reminder: Regarding to more detail and other information, please refer to user manual.



1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 2 Subpart J, section 2.1091
- ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ 47 CFR Part 1.1307
- ♦ 47 CFR Part 1.1310

1.3 Testing Location

Test Lab. : Sporton International Inc. Hsinhua Laboratory		
<input checked="" type="checkbox"/>	Hsinhua (TAF: 3785)	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)
		TEL: 886-3-327-3456 FAX: 886-3-327-0973
Test site Designation No. TW3785 with FCC.		

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

Multiple Transmitters Condition

Co-location as simultaneously transmitting (co-transmitting) and the evaluation shall be consider that simultaneous transmissions from co-located devices the individual transmitters are evaluated separately. After sum of the individual value (basic restriction / reference level) are measured/calculated also have to under basic restriction / reference level.

Co-transmitting mode: 5GHz WLAN+Bluetooth

2.2 RF Exposure Exempt Measurement

Option	Refer Std.	Exemption Exposure Thresholds (TL)
A	§1.1307(b)(3)(i)(A)	Available maximum time-averaged power is no more than 1 mW
B	§1.1307(b)(3)(i)(B)	$P_{th}(mW) = \begin{cases} ERP_{20cm} (d / 20cm)^x \rightarrow d \leq 20cm \\ ERP_{20cm} \rightarrow 20cm < d \leq 40cm \end{cases}$ $x = -\log_{10} \left(\frac{60}{ERP_{20cm} \sqrt{f}} \right) \text{ and } f \text{ is in GHz}$ $\begin{cases} ERP_{20cm} : 0.3GHz \leq f < 1.5GHz \rightarrow 2040 f (mW) \\ ERP_{20cm} : 1.5GHz \leq f \leq 6GHz \rightarrow 3060 (mW) \end{cases}$
C	§1.1307(b)(3)(i)(C)	$\begin{cases} 0.3 \sim 1.34MHz \rightarrow ERP(W) = 1920R^2 \\ 1.34 \sim 30MHz \rightarrow ERP(W) = 3450R^2 / f^2 \\ 30 \sim 300MHz \rightarrow ERP(W) = 3.83R^2 \\ 300 \sim 1500MHz \rightarrow ERP(W) = 0.0128R^2 f \\ 1500 \sim 100000MHz \rightarrow ERP(W) = 19.2R^2 \end{cases}$ <p>f is in MHz; R is in m; $R > \lambda / 2\pi$</p>



2.3 Multiple RF Sources Exposure

Refer Std.	Exemption Exposure Thresholds (TL)
§1.1307(b)(3)(ii)(A)	<p>The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required)</p>
§1.1307(b)(3)(ii)(B)	$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k} \leq 1$ <p>a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for P , including existing exempt transmitters and those being added. b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added. c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters. P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive). P_{th,i} = the exemption threshold power (P_{th}) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i. ERP_j = the ERP of fixed, mobile, or portable RF source j. ERP_{th,j} = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π according to the applicable formula of paragraph §1.1307(b)(3)(i)(C) of this section. Evaluated_k = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure. Evaluated Limit_k = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.</p>



2.4 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit. The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.5 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;BT-LE	3.61	8.23	9.69	0.50	10.447	20	B	3060.0	0.0034
2.4G;BT-BR	3.61	8.31	9.77	0.50	10.641	20	B	3060.0	0.0035
2.4G;BT-EDR	3.61	5.81	7.27	0.50	5.984	20	B	3060.0	0.0020

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

Simultaneous Transmission Analysis Mode: WLAN 5GHz+Bluetooth

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
5G	2.80	7.91	8.56	0.50	8.06	20.00	0.00263	1.00000	B	3060.000	0.0026
2.4G;BT-BR	3.61	8.31	9.77	0.50	10.64	20.00	0.00347	1.00000	B	3060.000	0.0035
Sum Ratio	0.00611										
Ratio Limit	1.00000										

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

Note 4: Refer as clause 2.3 Multiple RF Sources Exposure. Please follow below option and sum TL ration table.

Option	Sum TL Ratio_B	Option	Sum TL Ratio_C	Option	Sum TL Ratio_E
B	$\sum_{i=1}^a \frac{P_i}{P_{th,i}}$	C	$\sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}}$	E	$\sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k}$

Note: The above antenna gain was declared by manufacturer.

—————THE END—————