

FCC PART 15C TEST REPORT FOR CERTIFICATION
On Behalf of

Zylux Acoustic Corporation.

HP Roar Plus Wireless Speaker

Model Number: HP SR8250

FCC ID: XN6-SR8250

Prepared for : Zylux Acoustic Corporation.
3F, 22Lane 35, Jihu Road, Neihu Technology Park, Taipei,
114 Taiwan

Prepared By : EST Technology Co., Ltd.
Santun(guantai Road), Houjie Town, DongGuan City,
GuangDong, China.

Tel: 86-769-83081888-808




Report Number: ESTE-R1406037
Date of Test : June 03 ~ June 19, 2014
Date of Report : June 25, 2014

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION.....	3
1. GENERAL INFORMATION.....	5
1.1. Description of Device (EUT).....	5
2. SUMMARY OF TEST.....	6
2.1. Summary of test result.....	6
2.2. Test Facilities.....	7
2.3. Assistant equipment used for test.....	8
2.4. Block Diagram.....	8
2.5. Test mode.....	9
2.6. Channel List for Bluetooth.....	9
2.7. Test Equipment.....	10
3 POWER LINE CONDUCTED EMISSION TEST.....	11
3.1. Limit.....	11
3.2. Block Diagram of Test Setup.....	11
3.3. Test Procedure.....	11
3.4. Test Result.....	11
3.5. Test data.....	12
4 RADIATED EMISSION TEST.....	14
4.1 Limit.....	14
4.2. Test Procedure.....	15
4.3 Block Diagram of Test setup.....	15
4.4 Test Result.....	15
4.5 Test Data.....	16
5 CONDUCTED SPURIOUS EMISSION.....	35
5.1 Limit.....	35
5.2 Test Procedure.....	35
5.3 Test Result.....	35
5.4 Test Data.....	36
6 BAND EDGE COMPLIANCE TEST.....	42
6.1 Limit.....	42
6.2 Test Procedure.....	42
6.3 Test Result.....	42
6.4 Test Data.....	43
7 6dB Bandwidth Test.....	47
7.1 Limit.....	47
7.2 Test Procedure.....	47
7.3 Test Result.....	47
7.4 Test Data.....	48
8 OUTPUT POWER TEST.....	50
8.1 Limit.....	50
8.2 Test Procedure.....	50
8.3 Test Procedure.....	50

8.4	Test Result.....	51
8.5	Test Data	52
9	POWER SPECTRAL DENSITY TEST	54
9.1	Limit	54
9.2	Test Procedure.....	54
9.3	Test Result.....	55
9.4	Test Data	56
10	ANTENNA REQUIREMENTS.....	58
10.1	Limit.....	58
10.2	Result.....	58
11	TEST SETUP PHOTO.....	59
12	PHOTOS OF EUT	61

Test Report Verification

Applicant:	Zylux Acoustic Corporation.		
Address:	3F, 22Lane 35, Jihu Road, Neihu Technology Park, Taipei, 114 Taiwan		
Manufacturer Address:	Zhao Yang ELEC. (SHENZHEN) CO.,LTD. Building 1 & Building 2, De Yong Jia Industrial Park, Guang Qiao Road, Yu Lv Community, Gong Ming Street, Guang Ming New District, Shenzhen		
E.U.T:	HP Roar Plus Wireless Speaker		
Model Number:	HP SR8250		
Power Supply:	DC 3.7V From Internal Battery DC 5.3V From Adapter Input AC 100~240V 50/60Hz		
Test Voltage:	DC 5.3V From Adapter Input AC 120V/60Hz		
Trade Name:	HP	Serial No.:	-----
Date of Receipt:	June 03, 2014	Date of Test:	June 03 ~ 19, 2014
Test Specification:	FCC Rules and Regulations Part 15 Subpart C:2013 ANSI C63.4:2009		
Test Result:	<p>The device described above is tested by EST Technology Co., Ltd.. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the ETSI EN FCC Rules and Regulations Part 15 Subpart C requirements.</p> <p style="text-align: center;">This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.</p> <p style="text-align: right;">Date: June 25, 2014</p>		
Prepared by:	Tested by:	Approved by:	
			
_____ Ada / Assistant	_____ Tony.Tang/ Engineer	_____ IcemanHu / Manager	
Other Aspects:	None.		
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
<i>This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.</i>			

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Product Name	:	HP Roar Plus Wireless Speaker	
Model Number	:	HP SR8250	
FCC ID	:	XN6-SR8250	
Operation frequency	:	2402MHz~2480MHz	
Number of channel	:	79	40
Antenna	:	Internal antenna, 0 dBi gain	
Modulation	:	FHSS (GFSK, $\pi/4$ -DQPSK, 8-DPSK)	BLE GFSK
Sample Type	:	Prototype production	

2. SUMMARY OF TEST

2.1. Summary of test result

Description of Test Item	Standard	Results
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.4:2009	PASS
Radiated Emission	FCC Part 15: 15.209 ANSI C63.4:2009 KDB 558074	PASS
Band Edge Compliance	FCC Part 15: 15.247 ANSI C63.4:2009 KDB 558074	PASS
Conducted spurious emissions	FCC Part 15: 15.247 ANSI C63.4:2009 KDB 558074	PASS
6dB Bandwidth	FCC Part 15: 15.247 ANSI C63.4:2009 KDB 558074	PASS
Peak Output Power	FCC Part 15: 15.247 ANSI C63.4:2009 KDB 558074	PASS
Power Spectral Density	FCC Part 15: 15.247 ANSI C63.4:2009 KDB 558074	PASS
Antenna requirement	FCC Part 15: 15.203	PASS
Note: 558074 D01 DTS Meas Guidance v03r02		

2.2. Test Facilities

EMC Lab	:	Certificated by CNAL, CHINA Registration No.: L5288 Date of registration: October 28, 2011
		Certificated by FCC, USA Registration No.: 989591 Date of registration: November 20, 2013
		Certificated by Industry Canada Registration No.: 46405-9405 Test Side Number: 9405A-1 Date of registration: January 03, 2013
		Certificated by VCCI, Japan Registration No.: R-3663 & C-4103 Date of registration: July 25, 2011
		Certificated by TUV Rheinland, Germany Registration No.: UA 50195514 0001 Date of registration: January 07, 2011
		Certificated by TUV/PS, Shenzhen Registration No.: SCN1017 Date of registration: January 27, 2011
		Certificated by Intertek ETL SEMKO Registration No.: 2011-RTL-L1-18 Date of registration: April 28, 2011
		Certificated by Siemic, Inc. Registration No.: SLCN021 Date of registration: November 8, 2011
		Certificated by Nemko, Hong Kong Registration No.: 175193 Date of registration: May 4, 2011
Name of Firm	:	EST Technology Co., Ltd.
Site Location	:	San Tun Management Zone, Houjie Town, Dongguan, Guangdong, China

2.3. Assistant equipment used for test

2.3.1. Adapter

M/N	:	WAD005
Input	:	AC 100~240V 50/60Hz 0.3A Max
Output	:	DC 5.3V/2.0A

2.4. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 meter high above ground. EUT was set into BT test mode by Bluesuite software before test.



(EUT: HP Roar Plus Wireless Speaker)

2.5. Test mode

A special test software was used to control EUT work in Continuous TX mode(100% duty cycle), and select test channel, wireless mode and data rate.

Mode	Channel	Frequency
BT 4.0-BLE GFSK	Low	2402MHz
	Middle	2440MHz
	High	2480MHz

2.6. Channel List for Bluetooth

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2402	2	2404
3	2406	4	2408
5	2410	6	2412
7	2414	8	2416
9	2418	10	2420
11	2422	12	2424
13	2426	14	2428
15	2430	16	2432
17	2434	18	2436
19	2438	20	2440
21	2442	22	2444
23	2446	24	2448
25	2450	26	2452
27	2454	28	2456
29	2458	30	2460
31	2462	32	2464
33	2466	34	2468
35	2470	36	2472
37	2474	38	2476
39	2478	40	2480

2.7. Test Equipment

2.7.1. For conducted emission test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	832354	July,30,13	1 Year
Artificial Mains Networ	Rohde & Schwarz	ENV216	101260	July,30,13	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	101100	July,25,13	1 Year

2.7.2. For radiated emission test(30-1000MHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESVS10	100004	July,23,13	1 Year
Spectrum Analyzer	Agilent	E4411B	MY5014069 7	July ,23,13	1 Year
Bilog Antenna	Teseq	CBL 6111D	27090	July ,29,13	1 Year
Signal Amplifier	Agilent	310N	187037	July ,23,13	1 Year
RF Cable	Hubersuhner	W10.02	534123	July, 23,13	1 Year

2.7.3. For radiated emission test(above 1GHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Horn Antenna	SCHWARZB ECK	BBHA 9120 D	BBHA9120D1 002	July,29,13	1 Year
Signal Amplifier	SCHWARZB ECK	BBV9718	9718-212	July,23,13	1 Year
Spectrum Analyzer	Agilent	E4408B	MY44211139	July,23,13	1 Year
RF Cable	Hubersuhner	RG 214/U	513423	July,21,13	1 Year


3 POWER LINE CONDUCTED EMISSION TEST

3.1. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.
 2. The lower limit shall apply at the transition frequencies.

3.2. Block Diagram of Test Setup



3.3 Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2009 on Conducted Emission Test.


The bandwidth of test receiver (R & S ESHS30) is set at 10kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Result


PASS. (All emissions not reported below are too low against the prescribed limits.)

3.5. Test data



Site no. : EST Conduction Shielded Room Data no. : 109
 Limit : FCC PART 15B QP LINE Phase : LINE
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : TX Mode

	LISN	Cable	Emission		Limits	Margin	Remark
Freq. (MHz)	Factor (dB/m)	Loss (dB)	Reading (dBuV)	Level (dBuv/m)	(dBuv/m)	(dB)	
1	9.61	9.81	38.60	58.02	65.91	7.89	QP
2	9.61	9.81	21.60	41.02	55.91	14.89	Average
3	9.61	9.80	33.37	52.78	62.66	9.88	QP
4	9.61	9.80	18.37	37.78	52.66	14.88	Average
5	9.61	9.81	28.14	47.56	56.58	9.02	QP
6	9.61	9.81	12.14	31.56	46.58	15.02	Average
7	9.60	9.82	30.16	49.58	56.00	6.42	QP
8	9.60	9.82	11.16	30.58	46.00	15.42	Average
9	9.66	9.86	27.21	46.73	60.00	13.27	QP
10	9.66	9.86	7.21	26.73	50.00	23.27	Average
11	9.66	9.88	23.91	43.45	60.00	16.55	QP
12	9.66	9.88	15.91	35.45	50.00	14.55	Average



Site no. : EST Conduction Shielded Room Data no. : 111
 Limit : FCC PART 15B QP LINE Phase : NEUTRAL
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	0.15	9.48	9.81	37.60	56.89	65.74	8.85	QP
2	0.15	9.48	9.81	19.60	38.89	55.74	16.85	Average
3	0.21	9.60	9.80	33.84	53.24	63.10	9.86	QP
4	0.21	9.60	9.80	18.84	38.24	53.10	14.86	Average
5	0.57	9.61	9.82	30.73	50.16	56.00	5.84	QP
6	0.57	9.61	9.82	14.73	34.16	46.00	11.84	Average
7	0.68	9.63	9.81	27.30	46.74	56.00	9.26	QP
8	0.68	9.63	9.81	14.30	33.74	46.00	12.26	Average
9	3.04	9.63	9.85	22.08	41.56	56.00	14.44	QP
10	3.04	9.63	9.85	9.08	28.56	46.00	17.44	Average
11	9.25	9.69	9.88	27.97	47.54	60.00	12.46	QP
12	9.25	9.69	9.88	17.97	37.54	50.00	12.46	Average

4 RADIATED EMISSION TEST

4.1 Limit

4.1.1 15.209 limits

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

- Remark :
- (1) Emission level $\text{dB}\mu\text{V} = 20 \log$ Emission level $\mu\text{V}/\text{m}$
 - (2) The smaller limit shall apply at the cross point between two frequency bands.
 - (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

4.1.2 15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

4.2. Test Procedure


EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna are set on test.

The bandwidth of the EMI test receiver is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 3MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

The frequency range from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.

4.3 Block Diagram of Test setup



4.4 Test Result

PASS.


All the emissions from 30MHz to 25 GHz were comply with 15.209 limits.

Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

2、 The frequency 2402MHz 、 2440MHz and 2480 MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.

4.5 Test Data


30-1000 MHz



```


Site no.      : 3m Chamber                Data no. : 567
Dis. / Ant.  : 3m 27137                  Ant. pol.: HORIZONTAL
Limit        : FCC PART 15 B
Env. / Ins.  : Temp:25.6%;Humi:56%;Press:101.52kPa
Engineer     : Tony
EUT          : HP Roar Plus Wireless Speaker
Power        : DC 5.3V From Adapter Input AC 120V/60Hz
M/N         : HP SR8250
Test Mode    : GFSK TX 2402MHz
    
```

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission		Margin (dB)	Remark	
				Level (dBuV/m)	Limits (dBuV/m)			
1	155.13	10.67	1.69	21.93	34.29	43.50	9.21	QP
2	168.71	9.31	1.70	16.75	27.76	43.50	15.74	QP
3	221.09	9.26	2.01	15.58	26.85	46.00	19.15	QP
4	247.28	11.36	2.15	17.87	31.38	46.00	14.62	QP
5	310.33	13.20	2.28	11.01	26.49	46.00	19.51	QP
6	361.74	14.53	2.63	8.59	25.75	46.00	20.25	QP




Site no. : 3m Chamber Data no. : 568
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Emission Reading (dBuV)	Emission			Remark
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	30.00	18.51	0.65	12.38	31.54	40.00	8.46	QP
2	56.19	5.21	0.96	20.74	26.91	40.00	13.09	QP
3	133.79	11.36	1.56	21.75	34.67	43.50	8.83	QP
4	155.13	10.67	1.69	21.90	34.26	43.50	9.24	QP
5	218.18	9.00	1.90	20.09	30.99	46.00	15.01	QP
6	261.83	12.96	2.19	11.99	27.14	46.00	18.86	QP




Site no. : 3m Chamber Data no. : 569
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2440MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission		Margin (dB)	Remark
					Level (dBuV/m)	Limits (dBuV/m)		
1	30.00	18.51	0.65	15.63	34.79	40.00	5.21	QP
2	56.19	5.21	0.96	20.52	26.69	40.00	13.31	QP
3	67.83	5.39	1.13	21.28	27.80	40.00	12.20	QP
4	138.64	11.42	1.54	19.45	32.41	43.50	11.09	QP
5	159.98	10.36	1.71	18.15	30.22	43.50	13.28	QP
6	171.62	9.12	1.68	16.70	27.50	43.50	16.00	QP




Site no. : 3m Chamber Data no. : 570
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2440MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission			Margin (dB)	Remark
				Level (dBuV/m)	Limits (dBuV/m)			
1	138.64	11.42	1.54	14.25	27.21	43.50	16.29	QP
2	159.98	10.36	1.71	21.08	33.15	43.50	10.35	QP
3	184.23	8.57	1.71	20.62	30.90	43.50	12.60	QP
4	250.19	11.82	2.11	11.94	25.87	46.00	20.13	QP
5	315.18	13.39	2.42	10.40	26.21	46.00	19.79	QP
6	361.74	14.53	2.63	9.31	26.47	46.00	19.53	QP



Site no. : 3m Chamber Data no. : 571
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2480MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	155.13	10.67	1.69	21.93	34.29	43.50	9.21	QP
2	168.71	9.31	1.70	16.75	27.76	43.50	15.74	QP
3	221.09	9.26	2.01	15.58	26.85	46.00	19.15	QP
4	247.28	11.36	2.15	17.87	31.38	46.00	14.62	QP
5	310.33	13.20	2.28	11.01	26.49	46.00	19.51	QP
6	361.74	14.53	2.63	8.59	25.75	46.00	20.25	QP



Site no. : 3m Chamber Data no. : 572
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Cable		Emission				Remark
		Factor (dB/m)	Loss (dB)	Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	30.00	18.51	0.65	12.38	31.54	40.00	8.46	QP
2	56.19	5.21	0.96	20.74	26.91	40.00	13.09	QP
3	133.79	11.36	1.56	21.75	34.67	43.50	8.83	QP
4	155.13	10.67	1.69	21.90	34.26	43.50	9.24	QP
5	218.18	9.00	1.90	20.09	30.99	46.00	15.01	QP
6	261.83	12.96	2.19	11.99	27.14	46.00	18.86	QP


1000-18000 MHz



Site no. : 3m Chamber Data no. : 535
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2402MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission		Limits (dBuV/m)	Margin (dB)	Remark
				Reading (dBuV)	Level (dBuV/m)			
1	27.61	6.62	34.18	98.16	98.21	74.00	-24.21	Peak
2	31.31	11.92	31.85	34.72	46.10	74.00	27.90	Peak
3	36.54	11.61	31.93	33.77	49.99	74.00	24.01	Peak
4	38.14	11.61	31.76	31.79	49.78	74.00	24.22	Peak
5	41.71	10.92	33.08	32.40	51.95	74.00	22.05	Peak
6	39.80	10.98	33.17	29.86	47.47	74.00	26.53	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 536
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.61	6.62	34.18	95.32	95.37	74.00	-21.37	Peak
2	4804.00	31.25	11.77	31.81	41.13	52.34	74.00	21.66	Peak
3	7324.00	36.55	11.57	31.99	33.13	49.26	74.00	24.74	Peak
4	10129.00	38.33	11.52	32.01	32.79	50.63	74.00	23.37	Peak
5	14039.00	41.49	10.90	33.85	33.57	52.11	74.00	21.89	Peak
6	14498.00	41.88	10.93	33.08	32.51	52.24	74.00	21.76	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 539
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2440MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2440.00	27.60	6.67	34.12	95.77	95.92	74.00	-21.92	Peak
2	4880.00	31.37	12.07	31.90	40.09	51.63	74.00	22.37	Peak
3	8004.00	37.01	11.40	31.22	32.47	49.66	74.00	24.34	Peak
4	10214.00	38.48	11.47	32.17	33.08	50.86	74.00	23.14	Peak
5	14498.00	41.88	10.93	33.08	31.52	51.25	74.00	22.75	Peak
6	17099.00	40.13	10.95	32.96	27.83	45.95	74.00	28.05	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 540
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2440MHz

	Ant.	Cable	Amp	Emission					
Freq. (MHz)	Factor (dB/m)	Loss (dB)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark	
1	27.60	6.67	34.12	94.12	94.27	74.00	-20.27	Peak	
2	31.37	12.07	31.90	38.45	49.99	74.00	24.01	Peak	
3	36.68	11.47	31.40	32.81	49.56	74.00	24.44	Peak	
4	37.98	11.67	31.89	33.87	51.63	74.00	22.37	Peak	
5	39.37	11.12	34.10	32.69	49.08	74.00	24.92	Peak	
6	41.88	10.93	33.08	31.51	51.24	74.00	22.76	Peak	


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 541
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2480MHz

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission		Margin (dB)	Remark
						Level (dBUV/m)	Limits (dBUV/m)		
1	2480.00	27.58	6.71	34.03	94.05	94.31	74.00	-20.31	Peak
2	4960.00	31.49	12.44	31.97	39.92	51.88	74.00	22.12	Peak
3	7358.00	36.56	11.58	31.99	33.88	50.03	74.00	23.97	Peak
4	8684.00	37.32	11.45	32.43	34.32	50.66	74.00	23.34	Peak
5	10673.00	39.17	11.30	33.04	32.74	50.17	74.00	23.83	Peak
6	14498.00	41.88	10.93	33.08	31.56	51.29	74.00	22.71	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 542
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2480MHz

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission		Margin (dB)	Remark
						Level (dBUV/m)	Limits (dBUV/m)		
1	2480.00	27.58	6.71	34.03	95.15	95.41	74.00	-21.41	Peak
2	4927.00	31.45	12.29	31.95	33.36	45.15	74.00	28.85	Peak
3	7868.00	36.74	11.46	31.35	33.15	50.00	74.00	24.00	Peak
4	9959.00	38.13	11.60	31.77	32.57	50.53	74.00	23.47	Peak
5	11234.00	39.37	11.12	34.10	32.50	48.89	74.00	25.11	Peak
6	14328.00	41.74	10.92	32.98	31.22	50.90	74.00	23.10	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


18000-25000 MHz



Site no. : 3m Chamber Data no. : 545
 Dis. / Ant. : 3m ANT ABVOE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission		Margin (dB)	Remark
						Level (dBuV/m)	Limits (dBuV/m)		
1	20023.00	46.10	19.69	36.68	17.93	47.04	74.00	26.96	Peak
2	23369.00	45.67	21.48	33.46	17.10	50.79	74.00	23.21	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.       : 3m Chamber                Data no. : 546
Dis. / Ant.   : 3m ANT ABOVE 18G         Ant. pol. : VERTICAL
Limit         : FCC PART 15C PEAK
Env. / Ins.   : Temp:25.6';Humi:56%;Press:101.52kPa
Engineer      : Tony
EUT           : HP Roar Plus Wireless Speaker
Power         : DC 5.3V From Adapter Input AC 120V/60Hz
M/N           : HP SR8250
Test Mode     : GFSK TX 2402MHz
    
```

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	18658.00	45.06	18.12	35.55	18.41	46.04	74.00	27.96	Peak
2	21374.00	46.08	20.29	35.46	17.41	48.32	74.00	25.68	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 546
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2402MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission		Margin (dB)	Remark	
					Level (dBUV/m)	Limits (dBUV/m)			
1	18658.00	45.06	18.12	35.55	18.41	46.04	74.00	27.96	Peak
2	21374.00	46.08	20.29	35.46	17.41	48.32	74.00	25.68	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 547
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2440MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission			Margin (dB)	Remark
					Level (dBuV/m)	Limits (dBuV/m)			
1	20688.00	46.11	19.99	36.07	15.94	45.97	74.00	28.03	Peak
2	22613.00	45.75	20.92	34.24	15.44	47.87	74.00	26.13	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 548
 Dis. / Ant. : 3m ANT ABVOE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2440MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission			Remark
					Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1 19274.00	45.68	18.86	36.08	16.00	44.46	74.00	29.54	Peak
2 20688.00	46.11	19.99	36.07	16.75	46.78	74.00	27.22	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 549
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2480MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission		Limits (dBuV/m)	Margin (dB)	Remark
				Reading (dBuV)	Level (dBuV/m)			
1 20373.00	46.03	19.85	36.36	15.81	45.33	74.00	28.67	Peak
2 22578.00	45.77	20.90	34.30	15.61	47.98	74.00	26.02	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 550
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	20723.00	46.14	20.01	36.05	15.01	45.11	74.00	28.89	Peak
2	21143.00	46.21	20.19	35.67	16.08	46.81	74.00	27.19	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

5 CONDUCTED SPURIOUS EMISSION

5.1 Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

5.2 Test Procedure



The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz for frequency range from 30MHz to 1000 MHz; The resolution bandwidth is set to 1 MHz, The video bandwidth is set to 3 MHz for frequency range from 1000MHz to 25000 MHz..



5.3 Test Result

PASS (The testing data was attached in the next pages.)



5.4 Test Data


Test Mode: BT 4.0-BLE GFSK 2402MHz









Test Mode: BT 4.0-BLE GFSK 2440MHz





Test Mode: BT 4.0-BLE GFSK 2480MHz





6 BAND EDGE COMPLIANCE TEST

6.1 Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits

6.2 Test Procedure


1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=1MHz; VBW=3MHz; Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz; VBW=10Hz; Sweep=AUTO

6.3 Test Result

Pass (The testing data was attached in the next pages.)

- Note:
- 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.
 - 2、 The frequency 2402MHz and 2480 MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.

6.4 Test Data




```

Site no.      : 3m Chamber           Data no. : 537
Dis. / Ant.  : 3m ANT 1-18G         Ant. pol.: HORIZONTAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : Temp:25.6';Humi:56%;Press:101.52kPa
Engineer     : Tony
EUT          : HP Roar Plus Wireless Speaker
Power        : DC 5.3V From Adapter Input AC 120V/60Hz
M/N          : HP SR8250
Test Mode    : GFSK TX 2402MHz
    
```

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission			Margin (dB)	Remark	
				Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)			
1	2331.79	27.73	6.54	34.23	35.11	35.15	74.00	38.85	Peak
2	2390.00	27.64	6.62	34.19	33.94	34.01	74.00	39.99	Peak
3	2402.19	27.61	6.62	34.18	94.86	94.91	74.00	-20.91	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 538
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2402MHz

	Ant.	Cable	Amp	Emission					
Freq. (MHz)	Factor (dB/m)	Loss (dB)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark	
1	27.73	6.54	34.23	34.83	34.87	74.00	39.13	Peak	
2	27.64	6.62	34.19	33.79	33.86	74.00	40.14	Peak	
3	27.61	6.62	34.18	99.41	99.46	74.00	-25.46	Peak	


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official



Site no. : 3m Chamber Data no. : 543
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2479.98	27.58	6.71	34.03	101.14	101.40	74.00	-27.40	Peak
2	2483.50	27.58	6.71	34.03	41.12	41.38	74.00	32.62	Peak
3	2491.98	27.58	6.73	34.03	37.76	38.04	74.00	35.96	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 544
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : HP Roar Plus Wireless Speaker
 Power : DC 5.3V From Adapter Input AC 120V/60Hz
 M/N : HP SR8250
 Test Mode : GFSK TX 2480MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission		Margin (dB)	Remark
					Level (dBuV/m)	Limits (dBuV/m)		
1	27.58	6.71	34.03	99.23	99.49	74.00	-25.49	Peak
2	27.58	6.71	34.03	40.45	40.71	74.00	33.29	Peak
3	27.58	6.71	34.03	36.33	36.59	74.00	37.41	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

7 6dB Bandwidth Test

7.1 Limit

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

7.2 Test Procedure


- 1, Connected the EUT's antenna port to spectrum analyzer device.
- 2, Follow the test procedure as described in KDB 558074
 - (1). Set resolution bandwidth (RBW) = 100 kHz.
 - (2). Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
 - (3). Detector = Peak.
 - (4). Trace mode = max hold.
 - (5). Sweep = auto couple.
 - (6). Allow the trace to stabilize.
 - (7). Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3 Test Result


EUT: HP Roar Plus Wireless Speaker			
M/N: HP SR8250			
Test date: June 17, 2014		Tested by: Tony.Tang	Test site: RF Site
Test Mode	CH	6dB bandwidth (MHz)	Limit (KHz)
BT 4.0-BLE GFSK	CH1	0.744	>500
	CH20	0.753	>500
	CH40	0.751	>500
Conclusion : PASS			

7.4 Test Data

Test Mode: BT 4.0-BLE GFSK 2402MHz



Test Mode: BT 4.0-BLE GFSK 2440MHz



Test Mode: BT 4.0-BLE GFSK 2480MHz

Agilent

Ch Freq 2.48 GHz Trig Free

Occupied Bandwidth

Ref 10 dBm Atten 20 dB

Center 2.48 GHz Span 10 MHz
 #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)

Occupied Bandwidth		Occ BW % Pwr	99.00 %
1.0644 MHz		x dB	-6.00 dB
Transmit Freq Error	-21.288 kHz		
x dB Bandwidth	751.253 kHz		

Freq/Channel

Center Freq
2.48000000 GHz

Start Freq
2.47500000 GHz

Stop Freq
2.48500000 GHz

CF Step
1.00000000 MHz
Auto Man

Freq Offset
0.00000000 Hz

Signal Track
On Off

8 OUTPUT POWER TEST

8.1 Limit

For systems using digital modulation in the 2400—2483.5MHz, The Peak out put Power shall not exceed 1W(30dBm)

8.2 Test Procedure

8.3 Test Procedure

- 1, Connected the EUT's antenna port to spectrum analyzer device.
- 2, Follow the test procedure as described in KDB 558074
 - (1). Set the RBW \geq DTS bandwidth.
 - (2). Set VBW \geq 3 x RBW.
 - (3). Set span \geq 3 x RBW.
 - (4). Sweep time = auto couple.
 - (5). Detector = peak.
 - (6). Trace mode = max hold.
 - (7). Allow trace to fully stabilize.
 - (8). Use peak marker function to determine the peak amplitude level.


Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

8.4 Test Result


EUT: HP Roar Plus Wireless Speaker			
M/N:HP SR8250			
Test date: June 17,2014		Test site: 3m Chamber	Tested by: Tony Tang
Pass			
Test Mode	CH	Peak output Power (dBm)	Limit (dBm)
BT 4.0-BLE GFSK	CH1	1.87	30
	CH20	2.57	30
	CH40	2.45	30
Conclusion : PASS			

8.5 Test Data


Test Mode: BT 4.0-BLE GFSK 2402MHz



Test Mode: BT 4.0-BLE GFSK 2440MHz



Test Mode: BT 4.0-BLE GFSK 2480MHz



9 POWER SPECTRAL DENSITY TEST

9.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

9.2 Test Procedure

- 1, Connected the EUT's antenna port to spectrum analyzer device.


- 2, Follow the test procedure as described in KDB 558074
 - (1). Set analyzer center frequency to DTS channel center frequency.
 - (2). Set the span to 1.5 times the DTS bandwidth.
 - (3). Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
 - (4). Set the VBW $\geq 3 \text{ RBW}$.
 - (5). Detector = peak.
 - (6). Sweep time = auto couple.
 - (7). Trace mode = max hold.
 - (8). Allow trace to fully stabilize.
 - (9). Use the peak marker function to determine the maximum amplitude level.
 - (10). If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

9.3 Test Result


EUT: HP Roar Plus Wireless Speaker			
M/N: HP SR8250			
Test date: June 17, 2014		Test site: 3m Chamber	Tested by: Tony Tang
Pass			
Test Mode	CH	Power density (dBm/3kHz)	Limit (dBm/3kHz)
BT 4.0-BLE GFSK	CH1	-16.89	8
	CH20	-15.79	8
	CH40	-14.19	8
Conclusion : PASS			

9.4 Test Data


Test Mode: BT 4.0-BLE GFSK 2402MHz



Test Mode: BT 4.0-BLE GFSK 2440MHz



Test Mode: BT 4.0-BLE GFSK 2480MHz



10 ANTENNA REQUIREMENTS

10.1 Limit



For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

10.2 Result


The antennas used for this product are integral Patch Antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 0 dBi.

11 TEST SETUP PHOTO


Conducted Test



Radiated Test (30-1000 MHz)




Radiated Test (1000-25000 MHz)




12 PHOTOS OF EUT


External Photos
M/N: HP SR8250




External Photos
M/N: HP SR8250




External Photos
M/N: HP SR8250





Internal Photos
M/N: HP SR8250





Internal Photos
M/N: HP SR8250



Internal Photos
M/N: HP SR8250





Internal Photos
M/N: HP SR8250




Bluetooth
Antenna

Internal Photos
M/N: HP SR8250



Internal Photos
M/N: HP SR8250



Adapter Photos

