	А	В	С	D		E		\square
5	3RD ANGLE PROJECTION					⁻ 16 ±0.05±0. 16 ⁻ 63 ±0.1±0.2 3 ⁻ 150 ±0.1±0.2 0 ⁻ 250 ±0.2±0.3	$\pm 0.5 \pm 0.8 \pm 30^{\circ}$	- 5
4		S/N:MMYYXX Sirius TTR1 Rad Model: TTR1 Input: AC100V-2: 50/60Hz 0.7A Ma	io 40V subject to the following (1) this device may not interference, and (2) this device must ac interference received, interference that may co operation.	Operation is g two conditions: tt cause harmful ccept any including				4
3	Made in China ECCIDXN6SIRTIRI LISTED I.I.F TOLEARAGE FOR EACH DIMENSIONS NOT BOOK REPER TO TABLE < TABLE FOR TOLEARAGE FOR EACH DIMENSIONS NOT SHOW, REPER TO TABLE < TABLE PRE TOLEARAGE FOR EACH DIMENSIONS NOT SHOW, REPER TO TABLE < TABLE PRE TOLEARAGE FOR EACH DIMENSIONS A.U.NACCEPTRALE CONDITIONS FLASH, BUILDENSIONS, S.O. REPERSENTS CHITICAL AREAS TO BE HEASLERDA.L. OTHER DIMENSIONS THAT CAN'T BE CHARAGE FOR REPEAR TO BE HEASLERDA.L. OTHER DIMENSIONS THAT CAN'T BE CHARAGE FOR REPEAR. S.M.I.EMENSIONS, A.U.DEREMENTS REPIERATE CHITICAL DIMENSIONS THAT CAN'T BE CHARAGE FOR REPEAR TO REPEAR. MONTH YEAR PRODUCT SERIAL NO.							3
2								2
	(REFERENCE FILE*QNI-F40-01*) E D		TITLE. PRODUCT LABEL	REV SHEET A 1/1	HODED.	DOODOOIAA DATE.	09.07.28 FIT	
1			MATERIAL. 25#消銀龍 M	N0.K1203-0002658	APPROVAL.	CHECKED.	DESIGN.	1
	B PROTOTYPE-A4 09.07.28 JIANJUN	COLOR. N/A DRAWER. JIANJUN		DAVEYLEE	YONG	JIANJUN	1	
	ISS CHANGE RECORDS DATE REVISER							
	A	В	С	C D		E		\searrow