

# FCC Test Report

**FCC ID** : XNAHWA03  
**Equipment** : Withings Steel HR  
**Model No.** : HWA03  
**Brand Name** : Withings  
**Applicant** : Withings  
**Address** : Karaportti 3 Espoo FI-02610 Finland  
**Standard** : 47 CFR FCC Part 15.247  
**Received Date** : Jul. 28, 2016  
**Tested Date** : Aug. 08 ~ Aug. 12, 2016

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

  
\_\_\_\_\_  
Gary Chang / Manager



---

## Table of Contents

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1	Information.....	5
1.2	Local Support Equipment List .....	7
1.3	Test Setup Chart .....	7
1.4	Test Equipment List and Calibration Data.....	8
1.5	Test Standards .....	9
1.6	Measurement Uncertainty .....	9
<b>2</b>	<b>TEST CONFIGURATION.....</b>	<b>10</b>
2.1	Testing Condition .....	10
2.2	The Worst Test Modes and Channel Details .....	10
<b>3</b>	<b>TRANSMITTER TEST RESULTS.....</b>	<b>11</b>
3.1	Conducted Emissions.....	11
3.2	6dB and Occupied Bandwidth .....	14
3.3	RF Output Power .....	16
3.4	Power Spectral Density .....	18
3.5	Emissions in Restricted Frequency Bands.....	20
3.6	Emissions in non-restricted Frequency Bands .....	32
<b>4</b>	<b>TEST LABORATORY INFORMATION .....</b>	<b>35</b>

---

## Release Record

Report No.	Version	Description	Issued Date
FR672802	Rev. 01	Initial issue	Sep. 07, 2016

## Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	AC Power Line Conducted Emissions	[dBuV]: 0.393MHz 36.45 (Margin -11.54dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 4804.00MHz 51.79 (Margin -2.21dB) - AV	Pass
15.247(b)(3)	Maximum Output Power	Power [dBm]: -3.69	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

# 1 General Description

## 1.1 Information

### 1.1.1 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Bluetooth Mode	Ch. Freq. (MHz)	Channel Number	Data Rate
2400-2483.5	V4.0 LE	2402-2480	0-39 [40]	1 Mbps
Note 1: Bluetooth LE (Low energy) uses GFSK modulation.				

### 1.1.2 Antenna Details

Ant. No.	Brand	Model	Type	Gain (dBi)	Connector
1	ethertronics	1001312	Ceramic	1.72	N/A

### 1.1.3 Power Supply Type of Equipment under Test (EUT)

<b>Power Supply Type</b>	3.7Vdc from Rechargeable li-ion battery 5Vdc from host
--------------------------	---

### 1.1.4 Accessories

Accessories		
No.	Equipment	Description
1	Rechargeable li-ion battery	Brand Name: Routejade Model Name: PD2430C1 Rating: 3.7Vdc, 110mAh
2	USB cable (for charging use only)	1m shielded cable without core.

### 1.1.5 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
37	2402	9	2422	18	2442	28	2462
0	2404	10	2424	19	2444	29	2464
1	2406	38	2426	20	2446	30	2466
2	2408	11	2428	21	2448	31	2468
3	2410	12	2430	22	2450	32	2470
4	2412	13	2432	23	2452	33	2472
5	2414	14	2434	24	2454	34	2474
6	2416	15	2436	25	2456	35	2476
7	2418	16	2438	26	2458	36	2478
8	2420	17	2440	27	2460	39	2480

### 1.1.6 Test Tool and Duty Cycle

Test tool	nRFGo Studio
Duty cycle of test signal (%)	64.27%
Duty Factor (dB)	1.92


### 1.1.7 Power Setting

Modulation Mode	Test Frequency (MHz)		
	2402	2440	2480
GFSK/1Mbps	Default	Default	Default


## 1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Signal cable / Length (m)
1	Notebook	DELL	Latitude E6440	DoC	---

## 1.3 Test Setup Chart



Note: The support console cable and Notebook are disconnected from EUT and removed from test table when EUT is set to transmit/receive continuously.



## 1.4 Test Equipment List and Calibration Data

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
EMC Receiver	R&S	ESCS 30	100169	Oct. 21, 2015	Oct. 20, 2016
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 13, 2015	Nov. 12, 2016
RF Cable-CON	EMC	EMCCFD300-BM-BM-6000	50821	Dec. 21, 2015	Dec. 20, 2016
Measurement Software	AUDIX	e3	6.120210k	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	Radiated Emission				
Test Site	966 chamber 2 / (03CH02-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101499	Dec. 17, 2015	Dec. 16, 2016
Receiver	R&S	ESR3	101657	Jan. 12, 2016	Jan. 11, 2017
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-523	Nov. 09, 2015	Nov. 08, 2016
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1095	Oct. 07, 2015	Oct. 06, 2016
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 04, 2015	Nov. 03, 2016
Preamplifier	Burgeon	BPA-530	100218	Nov. 03, 2015	Nov. 02, 2016
Preamplifier	Agilent	83017A	MY39501309	Sep. 22, 2015	Sep. 21, 2016
Preamplifier	EMC	EMC184045B	980192	Sep. 01, 2015	Aug. 31, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16140/4	Dec. 10, 2015	Dec. 09, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16018/4	Dec. 10, 2015	Dec. 09, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16015/4	Dec. 10, 2015	Dec. 09, 2016
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-003	Dec. 10, 2015	Dec. 09, 2016
LF cable 10M	EMCC	CFD400-E	CFD400-001	Dec. 10, 2015	Dec. 09, 2016
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 17, 2016	Feb. 16, 2017
Power Meter	Anritsu	ML2495A	1241002	Sep. 21, 2015	Sep. 20, 2016
Power Sensor	Anritsu	MA2411B	1207366	Sep. 21, 2015	Sep. 20, 2016
Signal Generator	R&S	SMB100A	175727	Oct. 05, 2015	Oct. 04, 2016
DC POWER SOURCE	GW INSTRON	GPC-3060D	EM884797	Oct. 20, 2015	Oct. 19, 2016
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA

Note: Calibration Interval of instruments listed above is one year.



## 1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2013

FCC KDB 558074 D01 DTS Meas Guidance v03r05

## 1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ( $k=2$ ))

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	$\pm 34.134$ Hz
Conducted power	$\pm 0.808$ dB
Power density	$\pm 0.463$ dB
Conducted emission	$\pm 2.670$ dB
AC conducted emission	$\pm 2.90$ dB
Radiated emission $\leq 1$ GHz	$\pm 3.87$ dB
Radiated emission $> 1$ GHz	$\pm 5.60$ dB

## 2 Test Configuration

### 2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	21°C / 60%	Howard Huang
Radiated Emissions	03CH02-WS	22°C / 64%	Vincent Yeh
RF Conducted	TH01-WS	23°C / 66%	Alex Huang

➤ FCC site registration No.: 181692

➤ IC site registration No.: 10807A-2

### 2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate	Test Configuration
AC Power Line Conducted Emissions	Charging	---	---	2
Radiated Emissions ≤ 1GHz	BT LE	2480	1Mbps	1
Radiated Emissions ≤ 1GHz	Charging	---	---	2
Radiated Emissions > 1GHz	BT LE	2402, 2440, 2480	1Mbps	1
Maximum Output Power	BT LE	2402, 2440, 2480	1Mbps	1
6dB bandwidth				
Power spectral density				

**NOTE:**

- The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **X-plane** result was found as the worst case and was shown in this report.
- The device can be operated under battery mode and charging mode. Each mode was selected for related test items as below configuration.
  - Configuration 1: Battery mode , X-plane
  - Configuration 2: Charging mode, X-plane

## 3 Transmitter Test Results

### 3.1 Conducted Emissions

#### 3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: \* Decreases with the logarithm of the frequency.

#### 3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50  $\Omega$  LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz


#### 3.1.3 Test Setup




Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

### 3.1.4 Test Result of Conducted Emissions

Power Phase	Line	Test Configuration	2																																																																																																																					
 <p>The graph shows the conducted emission level in dBuV versus frequency in MHz. The y-axis ranges from 0 to 80 dBuV, and the x-axis ranges from 0.15 to 30 MHz. Two red limit lines are shown: CISPR/CNS/VCCI-B (upper) and CISPR/CNS/VCCI-B AV (lower). A blue test result line is plotted, with several peaks labeled with circled numbers 2, 4, 5, 6, 8, 9, 10, and 12. Peak 7 is highlighted with a box in the table below.</p>																																																																																																																								
<table border="1"> <thead> <tr> <th></th> <th>Freq MHz</th> <th>Level dBuV</th> <th>Limit Line dBuV</th> <th>Over Limit dB</th> <th>Read Level dBuV</th> <th>LISN factor dB</th> <th>cable loss dB</th> <th>Remark</th> </tr> </thead> <tbody> <tr><td>1</td><td>0.156</td><td>39.89</td><td>55.65</td><td>-15.76</td><td>39.76</td><td>0.11</td><td>0.02</td><td>Average</td></tr> <tr><td>2</td><td>0.156</td><td>50.42</td><td>65.65</td><td>-15.23</td><td>50.29</td><td>0.11</td><td>0.02</td><td>QP</td></tr> <tr><td>3</td><td>0.174</td><td>38.43</td><td>54.77</td><td>-16.34</td><td>38.30</td><td>0.11</td><td>0.02</td><td>Average</td></tr> <tr><td>4</td><td>0.174</td><td>47.07</td><td>64.77</td><td>-17.70</td><td>46.94</td><td>0.11</td><td>0.02</td><td>QP</td></tr> <tr><td>5</td><td>0.234</td><td>37.38</td><td>52.30</td><td>-14.92</td><td>37.25</td><td>0.11</td><td>0.02</td><td>Average</td></tr> <tr><td>6</td><td>0.234</td><td>46.00</td><td>62.30</td><td>-16.30</td><td>45.87</td><td>0.11</td><td>0.02</td><td>QP</td></tr> <tr><td>7</td><td>0.393</td><td>36.45</td><td>47.99</td><td>-11.54</td><td>36.29</td><td>0.13</td><td>0.03</td><td>Average</td></tr> <tr><td>8</td><td>0.393</td><td>38.02</td><td>57.99</td><td>-19.97</td><td>37.86</td><td>0.13</td><td>0.03</td><td>QP</td></tr> <tr><td>9</td><td>7.893</td><td>33.90</td><td>50.00</td><td>-16.10</td><td>33.52</td><td>0.23</td><td>0.15</td><td>Average</td></tr> <tr><td>10</td><td>7.893</td><td>42.41</td><td>60.00</td><td>-17.59</td><td>42.03</td><td>0.23</td><td>0.15</td><td>QP</td></tr> <tr><td>11</td><td>21.830</td><td>36.82</td><td>50.00</td><td>-13.18</td><td>36.23</td><td>0.39</td><td>0.20</td><td>Average</td></tr> <tr><td>12</td><td>21.830</td><td>44.27</td><td>60.00</td><td>-15.73</td><td>43.68</td><td>0.39</td><td>0.20</td><td>QP</td></tr> </tbody> </table>					Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark	1	0.156	39.89	55.65	-15.76	39.76	0.11	0.02	Average	2	0.156	50.42	65.65	-15.23	50.29	0.11	0.02	QP	3	0.174	38.43	54.77	-16.34	38.30	0.11	0.02	Average	4	0.174	47.07	64.77	-17.70	46.94	0.11	0.02	QP	5	0.234	37.38	52.30	-14.92	37.25	0.11	0.02	Average	6	0.234	46.00	62.30	-16.30	45.87	0.11	0.02	QP	7	0.393	36.45	47.99	-11.54	36.29	0.13	0.03	Average	8	0.393	38.02	57.99	-19.97	37.86	0.13	0.03	QP	9	7.893	33.90	50.00	-16.10	33.52	0.23	0.15	Average	10	7.893	42.41	60.00	-17.59	42.03	0.23	0.15	QP	11	21.830	36.82	50.00	-13.18	36.23	0.39	0.20	Average	12	21.830	44.27	60.00	-15.73	43.68	0.39	0.20	QP
	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark																																																																																																																
1	0.156	39.89	55.65	-15.76	39.76	0.11	0.02	Average																																																																																																																
2	0.156	50.42	65.65	-15.23	50.29	0.11	0.02	QP																																																																																																																
3	0.174	38.43	54.77	-16.34	38.30	0.11	0.02	Average																																																																																																																
4	0.174	47.07	64.77	-17.70	46.94	0.11	0.02	QP																																																																																																																
5	0.234	37.38	52.30	-14.92	37.25	0.11	0.02	Average																																																																																																																
6	0.234	46.00	62.30	-16.30	45.87	0.11	0.02	QP																																																																																																																
7	0.393	36.45	47.99	-11.54	36.29	0.13	0.03	Average																																																																																																																
8	0.393	38.02	57.99	-19.97	37.86	0.13	0.03	QP																																																																																																																
9	7.893	33.90	50.00	-16.10	33.52	0.23	0.15	Average																																																																																																																
10	7.893	42.41	60.00	-17.59	42.03	0.23	0.15	QP																																																																																																																
11	21.830	36.82	50.00	-13.18	36.23	0.39	0.20	Average																																																																																																																
12	21.830	44.27	60.00	-15.73	43.68	0.39	0.20	QP																																																																																																																
<p>Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).            2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).</p>																																																																																																																								

Power Phase	Neutral	Test Configuration	2																																																																																																																					
 <p>The graph displays the measured level in dBuV against frequency in MHz on a logarithmic scale. Two red limit lines are shown: CISPR/CNS/VCCI-B (upper) and CISPR/CNS/VCCI-B AV (lower). The blue trace represents the measured signal, with several peaks labeled 1 through 12. The x-axis ranges from 0.1502 to 30 MHz, and the y-axis ranges from 0 to 80 dBuV.</p>																																																																																																																								
<table border="1"> <thead> <tr> <th></th> <th>Freq MHz</th> <th>Level dBuV</th> <th>Limit Line dBuV</th> <th>Over Limit dB</th> <th>Read Level dBuV</th> <th>LISN factor dB</th> <th>cable loss dB</th> <th>Remark</th> </tr> </thead> <tbody> <tr><td>1</td><td>0.156</td><td>38.91</td><td>55.65</td><td>-16.74</td><td>38.76</td><td>0.13</td><td>0.02</td><td>Average</td></tr> <tr><td>2</td><td>0.156</td><td>48.36</td><td>65.65</td><td>-17.29</td><td>48.21</td><td>0.13</td><td>0.02</td><td>QP</td></tr> <tr><td>3</td><td>0.234</td><td>38.61</td><td>52.30</td><td>-13.69</td><td>38.48</td><td>0.11</td><td>0.02</td><td>Average</td></tr> <tr><td>4</td><td>0.234</td><td>46.69</td><td>62.30</td><td>-15.61</td><td>46.56</td><td>0.11</td><td>0.02</td><td>QP</td></tr> <tr><td>5</td><td>0.313</td><td>30.51</td><td>49.88</td><td>-19.37</td><td>30.35</td><td>0.13</td><td>0.03</td><td>Average</td></tr> <tr><td>6</td><td>0.313</td><td>38.23</td><td>59.88</td><td>-21.65</td><td>38.07</td><td>0.13</td><td>0.03</td><td>QP</td></tr> <tr><td>7</td><td>0.994</td><td>25.20</td><td>46.00</td><td>-20.80</td><td>25.01</td><td>0.13</td><td>0.06</td><td>Average</td></tr> <tr><td>8</td><td>0.994</td><td>38.20</td><td>56.00</td><td>-17.80</td><td>38.01</td><td>0.13</td><td>0.06</td><td>QP</td></tr> <tr><td>9</td><td>6.352</td><td>26.67</td><td>50.00</td><td>-23.33</td><td>26.31</td><td>0.22</td><td>0.14</td><td>Average</td></tr> <tr><td>10</td><td>6.352</td><td>33.99</td><td>60.00</td><td>-26.01</td><td>33.63</td><td>0.22</td><td>0.14</td><td>QP</td></tr> <tr><td>11</td><td>21.946</td><td>31.83</td><td>50.00</td><td>-18.17</td><td>31.21</td><td>0.42</td><td>0.20</td><td>Average</td></tr> <tr><td>12</td><td>21.946</td><td>43.03</td><td>60.00</td><td>-16.97</td><td>42.41</td><td>0.42</td><td>0.20</td><td>QP</td></tr> </tbody> </table>					Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark	1	0.156	38.91	55.65	-16.74	38.76	0.13	0.02	Average	2	0.156	48.36	65.65	-17.29	48.21	0.13	0.02	QP	3	0.234	38.61	52.30	-13.69	38.48	0.11	0.02	Average	4	0.234	46.69	62.30	-15.61	46.56	0.11	0.02	QP	5	0.313	30.51	49.88	-19.37	30.35	0.13	0.03	Average	6	0.313	38.23	59.88	-21.65	38.07	0.13	0.03	QP	7	0.994	25.20	46.00	-20.80	25.01	0.13	0.06	Average	8	0.994	38.20	56.00	-17.80	38.01	0.13	0.06	QP	9	6.352	26.67	50.00	-23.33	26.31	0.22	0.14	Average	10	6.352	33.99	60.00	-26.01	33.63	0.22	0.14	QP	11	21.946	31.83	50.00	-18.17	31.21	0.42	0.20	Average	12	21.946	43.03	60.00	-16.97	42.41	0.42	0.20	QP
	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark																																																																																																																
1	0.156	38.91	55.65	-16.74	38.76	0.13	0.02	Average																																																																																																																
2	0.156	48.36	65.65	-17.29	48.21	0.13	0.02	QP																																																																																																																
3	0.234	38.61	52.30	-13.69	38.48	0.11	0.02	Average																																																																																																																
4	0.234	46.69	62.30	-15.61	46.56	0.11	0.02	QP																																																																																																																
5	0.313	30.51	49.88	-19.37	30.35	0.13	0.03	Average																																																																																																																
6	0.313	38.23	59.88	-21.65	38.07	0.13	0.03	QP																																																																																																																
7	0.994	25.20	46.00	-20.80	25.01	0.13	0.06	Average																																																																																																																
8	0.994	38.20	56.00	-17.80	38.01	0.13	0.06	QP																																																																																																																
9	6.352	26.67	50.00	-23.33	26.31	0.22	0.14	Average																																																																																																																
10	6.352	33.99	60.00	-26.01	33.63	0.22	0.14	QP																																																																																																																
11	21.946	31.83	50.00	-18.17	31.21	0.42	0.20	Average																																																																																																																
12	21.946	43.03	60.00	-16.97	42.41	0.42	0.20	QP																																																																																																																
<p>Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).            2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).</p>																																																																																																																								

## 3.2 6dB and Occupied Bandwidth

### 3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

### 3.2.2 Test Procedures


#### 6dB Bandwidth

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

#### Occupied Bandwidth


1. Set resolution bandwidth (RBW) = 20 kHz, Video bandwidth = 100 kHz.
2. Detector = Sample, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

### 3.2.3 Test Setup



### 3.2.4 Test Result of 6dB and Occupied Bandwidth

Mode	Freq. (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit of 6dB Bandwidth (kHz)
BT LE	2402	0.691	1.05	500
BT LE	2440	0.696	1.05	500
BT LE	2480	0.696	1.05	500



## 3.3 RF Output Power

### 3.3.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.


- Antenna gain  $\leq$  6dBi, no any corresponding reduction is in output power limit.
- Antenna gain  $>$  6dBi
  - Non Fixed, point to point operations.  
The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB
  - Fixed, point to point operations  
Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

### 3.3.2 Test Procedures

- Maximum Peak Conducted Output Power
  - Spectrum analyzer**
    1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
    2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
    3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.
  - Power meter**
    1. A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
- Maximum Conducted Average Output Power ( For reference only)
  - Power meter**
    1. A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

### 3.3.3 Test Setup





### 3.3.4 Test Result of Maximum Output Power

Mode	Freq. (MHz)	Peak Power			Antenna gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
		Power (mW)	Power (dBm)	Limit (dBm)			
BT LE	2402	0.42	-3.75	30	1.72	-2.03	36
BT LE	2440	0.42	-3.76	30	1.72	-2.04	36
BT LE	2480	0.43	<b>-3.69</b>	30	1.72	-1.97	36

Mode	Freq. (MHz)	AV Power (mW)	AV Power (dBm)	Limit (dBm)
BT LE	2402	0.41	-3.82	---
BT LE	2440	0.41	-3.83	---
BT LE	2480	0.42	<b>-3.76</b>	---

Note: Average power is for reference only

## 3.4 Power Spectral Density


### 3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

### 3.4.2 Test Procedures


- Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
  1. Set the RBW = 3kHz, VBW = 10kHz.
  2. Detector = Peak, Sweep time = auto couple.
  3. Trace mode = max hold, allow trace to fully stabilize.
  4. Use the peak marker function to determine the maximum amplitude level.
- Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
  1. Set the RBW = 100kHz, VBW = 300 kHz.
  2. Detector = RMS, Sweep time = auto couple.
  3. Set the sweep time to:  $\geq 10 \times (\text{number of measurement points in sweep}) \times (\text{maximum data rate per stream})$ .
  4. Perform the measurement over a single sweep.
  5. Use the peak marker function to determine the maximum amplitude level.

### 3.4.3 Test Setup



### 3.4.4 Test Result of Power Spectral Density

Mode	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
BT LE	2402	-19.87	8
BT LE	2440	-20.00	8
BT LE	2480	-19.78	8



## 3.5 Emissions in Restricted Frequency Bands

### 3.5.1 Limit of Emissions in Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

**Note 1:**  
Quasi-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

**Note 2:**  
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

### 3.5.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

### 3.5.3 Test Setup


#### Radiated Emissions below 1 GHz




#### Radiated Emissions above 1 GHz



### 3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2480																																																																													
Polarization	Horizontal	Test Configuration	1																																																																													
																																																																																
	<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission level</th> <th>Limit</th> <th>Margin</th> <th>SA reading</th> <th>Factor</th> <th>Remark</th> <th>ANT High cm</th> <th>Turn Table deg</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>46.49</td> <td>18.78</td> <td>40.00</td> <td>-21.22</td> <td>30.42</td> <td>-11.64</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>2</td> <td>148.34</td> <td>19.45</td> <td>43.50</td> <td>-24.05</td> <td>31.43</td> <td>-11.98</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>3</td> <td>279.29</td> <td>18.97</td> <td>46.00</td> <td>-27.03</td> <td>30.57</td> <td>-11.60</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>4</td> <td>370.47</td> <td>21.57</td> <td>46.00</td> <td>-24.43</td> <td>31.03</td> <td>-9.46</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>5</td> <td>511.12</td> <td>24.76</td> <td>46.00</td> <td>-21.24</td> <td>31.07</td> <td>-6.31</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>6</td> <td>675.05</td> <td>27.37</td> <td>46.00</td> <td>-18.63</td> <td>30.97</td> <td>-3.60</td> <td>Peak</td> <td>---</td> </tr> </tbody> </table>	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg	MHz	dBuV/m	dBuV/m	dB	dBuV	dB				1	46.49	18.78	40.00	-21.22	30.42	-11.64	Peak	---	2	148.34	19.45	43.50	-24.05	31.43	-11.98	Peak	---	3	279.29	18.97	46.00	-27.03	30.57	-11.60	Peak	---	4	370.47	21.57	46.00	-24.43	31.03	-9.46	Peak	---	5	511.12	24.76	46.00	-21.24	31.07	-6.31	Peak	---	6	675.05	27.37	46.00	-18.63	30.97	-3.60	Peak	---							
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB																																																																											
1	46.49	18.78	40.00	-21.22	30.42	-11.64	Peak	---																																																																								
2	148.34	19.45	43.50	-24.05	31.43	-11.98	Peak	---																																																																								
3	279.29	18.97	46.00	-27.03	30.57	-11.60	Peak	---																																																																								
4	370.47	21.57	46.00	-24.43	31.03	-9.46	Peak	---																																																																								
5	511.12	24.76	46.00	-21.24	31.07	-6.31	Peak	---																																																																								
6	675.05	27.37	46.00	-18.63	30.97	-3.60	Peak	---																																																																								
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)            *Factor includes antenna factor , cable loss and amplifier gain            Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).            Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.</p>																																																																																

<b>Modulation</b>	GFSK	<b>Test Freq. (MHz)</b>	2480
<b>Polarization</b>	Vertical	<b>Test Configuration</b>	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	41.64	20.66	40.00	-19.34	32.42	-11.76	Peak	---	---
2	160.95	20.71	43.50	-22.79	32.44	-11.73	Peak	---	---
3	268.62	20.13	46.00	-25.87	32.21	-12.08	Peak	---	---
4	437.40	22.60	46.00	-23.40	30.42	-7.82	Peak	---	---
5	608.12	25.50	46.00	-20.50	29.98	-4.48	Peak	---	---
6	728.40	28.94	46.00	-17.06	31.67	-2.73	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

<b>Modulation</b>	---	<b>Test Freq. (MHz)</b>	---
<b>Polarization</b>	Horizontal	<b>Test Configuration</b>	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	70.74	34.61	40.00	-5.39	49.15	-14.54	Peak	---	---
2	98.87	29.99	43.50	-13.51	46.80	-16.81	Peak	---	---
3	232.73	28.79	46.00	-17.21	42.40	-13.61	Peak	---	---
4	299.66	30.44	46.00	-15.56	41.56	-11.12	Peak	---	---
5	431.58	28.35	46.00	-17.65	36.30	-7.95	Peak	---	---
6	575.14	28.34	46.00	-17.66	33.45	-5.11	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.



<b>Modulation</b>	---	<b>Test Freq. (MHz)</b>	---
<b>Polarization</b>	Vertical	<b>Test Configuration</b>	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	70.74	27.51	40.00	-12.49	42.05	-14.54	Peak	---	---
2	98.87	29.34	43.50	-14.16	46.15	-16.81	Peak	---	---
3	143.49	25.36	43.50	-18.14	37.51	-12.15	Peak	---	---
4	364.65	28.08	46.00	-17.92	37.70	-9.62	Peak	---	---
5	431.58	28.60	46.00	-17.40	36.55	-7.95	Peak	---	---
6	575.14	27.42	46.00	-18.58	32.53	-5.11	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

### 3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK

<b>Modulation</b>	GFSK	<b>Test Freq. (MHz)</b>	2402
<b>Polarization</b>	Horizontal	<b>Test Configuration</b>	1




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.94	54.00	-16.06	41.00	-3.06	Average	100	318
2	2390.00	50.14	74.00	-23.86	53.20	-3.06	Peak	100	318
3	4804.00	51.79	54.00	-2.21	47.58	4.21	Average	100	15
4	4804.00	57.39	74.00	-16.61	53.18	4.21	Peak	100	15
5	12010.00	43.53	54.00	-10.47	29.66	13.87	Average	100	321
6	12010.00	55.05	74.00	-18.95	41.18	13.87	Peak	100	321

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	GFSK	<b>Test Freq. (MHz)</b>	2402
<b>Polarization</b>	Vertical	<b>Test Configuration</b>	1




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.68	54.00	-16.32	40.74	-3.06	Average	100	58
2	2390.00	49.57	74.00	-24.43	52.63	-3.06	Peak	100	58
3	4804.00	42.83	54.00	-11.17	38.62	4.21	Average	100	15
4	4804.00	49.33	74.00	-24.67	45.12	4.21	Peak	100	15
5	12010.00	43.33	54.00	-10.67	29.46	13.87	Average	100	285
6	12010.00	55.10	74.00	-18.90	41.23	13.87	Peak	100	285

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	GFSK	<b>Test Freq. (MHz)</b>	2440
<b>Polarization</b>	Horizontal	<b>Test Configuration</b>	1




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.98	54.00	-16.02	41.04	-3.06	Average	100	330
2	2390.00	50.16	74.00	-23.84	53.22	-3.06	Peak	100	330
3	2483.50	38.06	54.00	-15.94	40.75	-2.69	Average	100	330
4	2483.50	50.29	74.00	-23.71	52.98	-2.69	Peak	100	330
5	4880.00	50.64	54.00	-3.36	46.23	4.41	Average	100	22
6	4880.00	56.74	74.00	-17.26	52.33	4.41	Peak	100	22
7	7320.00	42.55	54.00	-11.45	33.32	9.23	Average	100	296
8	7320.00	52.41	74.00	-21.59	43.18	9.23	Peak	100	296

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	GFSK	<b>Test Freq. (MHz)</b>	2440
<b>Polarization</b>	Vertical	<b>Test Configuration</b>	1




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	37.89	54.00	-16.11	40.95	-3.06	Average	100	65
2	2390.00	49.49	74.00	-24.51	52.55	-3.06	Peak	100	65
3	2483.50	38.16	54.00	-15.84	40.85	-2.69	Average	100	65
4	2483.50	49.81	74.00	-24.19	52.50	-2.69	Peak	100	65
5	4880.00	44.89	54.00	-9.11	40.48	4.41	Average	100	18
6	4880.00	51.81	74.00	-22.19	47.40	4.41	Peak	100	18
7	7320.00	42.61	54.00	-11.39	33.38	9.23	Average	134	104
8	7320.00	53.17	74.00	-20.83	43.94	9.23	Peak	134	104

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	GFSK	<b>Test Freq. (MHz)</b>	2480
<b>Polarization</b>	Horizontal	<b>Test Configuration</b>	1




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	38.24	54.00	-15.76	40.93	-2.69	Average	100	316
2	2483.50	55.53	74.00	-18.47	58.22	-2.69	Peak	100	316
3	4960.00	49.61	54.00	-4.39	44.99	4.62	Average	115	8
4	4960.00	56.61	74.00	-17.39	51.99	4.62	Peak	115	8
5	7440.00	43.02	54.00	-10.98	33.55	9.47	Average	100	279
6	7440.00	52.86	74.00	-21.14	43.39	9.47	Peak	100	279

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	GFSK	<b>Test Freq. (MHz)</b>	2480
<b>Polarization</b>	Vertical	<b>Test Configuration</b>	1



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	38.14	54.00	-15.86	40.83	-2.69	Average	100	85
2	2483.50	50.18	74.00	-23.82	52.87	-2.69	Peak	100	85
3	4960.00	44.15	54.00	-9.85	39.53	4.62	Average	100	6
4	4960.00	51.07	74.00	-22.93	46.45	4.62	Peak	100	6
5	7440.00	43.95	54.00	-10.05	34.48	9.47	Average	275	104
6	7440.00	53.96	74.00	-20.04	44.49	9.47	Peak	275	104

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

## 3.6 Emissions in non-restricted Frequency Bands

### 3.6.1 Emissions in non-restricted frequency bands limit

The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

### 3.6.2 Test Procedures


#### Reference Level Measurement

1. Set the RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Set Sweep time = auto couple, Trace mode = max hold.
3. Allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

#### Unwanted Emissions Level Measurement


1. Set RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Trace Mode = max hold, Sweep = auto couple.
3. Allow the trace to stabilize.
4. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

### 3.6.3 Test Setup






### 3.6.4 Test Result of Emissions in non-restricted Frequency Bands




**TX Freq 2480MHz / 30MHz~25GHz (down 20dBc)**

---



---



---

## 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <http://www.icertifi.com.tw>.

### **Linkou**

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin  
Kou District, New Taipei City,  
Taiwan, R.O.C.

### **Kwei Shan**

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,  
Kwei Shan District, Tao Yuan City  
333, Taiwan, R.O.C.

### **Kwei Shan Site II**

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd  
St., Kwei Shan District, Tao Yuan  
City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: [ICC\\_Service@icertifi.com.tw](mailto:ICC_Service@icertifi.com.tw)

==END==