



FCC RADIO TEST REPORT

Applicant : Withings

Address : 2 Rue Maurice Hartmann Issy-les-Moulineaux
92130 France

Equipment : Withings Thermo™

Model No. : SCT01

Trade Name : Withings


FCC ID : XNASCT01


I HEREBY CERTIFY THAT :

The sample was received on Dec. 10, 2015 and the testing was carried out on Dec. 11, 2015 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Tested by:


 Steven Wang
 Manager


 Spree Yei
 Engineer

Laboratory Accreditation:

CerpPASS Technology Corporation Test Laboratory



CerpPASS Technology(SuZhou) Co., Ltd.





Contents

1. Summary of Test Procedure and Test Results.....	5
1.1 Applicable Standards	5
2. Test Configuration of Equipment under Test.....	6
2.1 Feature of Equipment under Test.....	6
2.2 Carrier Frequency of Channels.....	6
2.3 Test Mode and Test Software.....	7
2.4 Description of Test System.....	7
2.5 General Information of Test.....	8
3. Test Equipment and Ancillaries Used for Tests	9
4. Antenna Requirements.....	10
4.1 Standard Applicable	10
4.2 Antenna Construction and Directional Gain.....	10
5. Test of AC Power Line Conducted Emission	11
6. Test of Spurious Emission (Radiated)	12
6.1 Test Limit	12
6.2 Test Procedures	12
6.3 Typical Test Setup	13
6.4 Test Result and Data (9KHz ~ 30MHz)	14
6.5 Test Result and Data (30MHz ~ 1GHz).....	14
6.6 Test Result and Data (1GHz ~ 25GHz).....	20
6.7 Restricted Bands of Operation	26
6.8 Restrict Band Emission Measurement Data	27
6.9 Test Photographs (30MHz ~ 1GHz).....	30
6.10 Test Photographs (1GHz ~ 25GHz)	31
7. Test of Spurious Emission (Conducted).....	32
7.1 Test Limit	32
7.2 Test Procedure	32
7.3 Test Setup Layout	32
7.4 Test Result and Data	32
8. 6dB Bandwidth Measurement Data	36
8.1 Test Limit	36
8.2 Test Procedures	36
8.3 Test Setup Layout	36
8.4 Test Result and Data	36
9. Maximum Peak and Average Output Power	39
9.1 Test Limit	39
9.2 Test Procedures	39
9.3 Test Setup Layout	39
9.4 Test Result and Data	40
10. Power Spectral Density	41
10.1 Test Limit	41
10.2 Test Procedures	41
10.3 Test Setup Layout	41



10.4 Test Result and Data.....41



1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

ANSI C63.4: 2009

FCC Rules and Regulations Part 15 Subpart C §15.247

KDB558074

KDB662911

FCC Rule	Description of Test	Result
15.203	Antenna Requirement	Pass
15.207	AC Power Line Conducted Emission	N/A
15.209 15.205	Spurious Emission(Radiated)	Pass
15.247(d)	Spurious Emission(Conducted)	Pass
15.247(a)(2)	6dB Bandwidth	Pass
15.247(b)	Maximum Peak Output Power	Pass
15.247(e)	Power Spectral Density	Pass

This EUT has been also tested and compiled with the requirement of FCC Part 15, Subpart B, recorded in a separate test report.



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Modulation Type	DSSS, OFDM, GFSK
Frequency Range	802.11b/g/n: 2412 - 2462 MHz BT-LE: 2402 – 2480 MHz
Channel Number	802.11 b/g/n: 01 ~ 11 BT-LE: 01 ~ 39
Data Rate	802.11b: 11Mbps 802.11g: 54Mbps 802.11n HT20: 65Mbps
RF Output Power	802.11b/g/n: 9.25 dBm BT-LE: -5.88 dBm
Antenna Type/ gain	802.11 b/g/n: Omnidirectional Antenna / 2.8 dBi BT-LE: Omnidirectional Antenna / 2.8 dBi
Power Source	2 x 1.5V (LR03 AAA Battery)

2.2 Carrier Frequency of Channels

802.11b, 802.11g, 802.11n HT 20 (2412MHz~2462MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
*01	2412	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	*11	2462
*06	2437	---	---

Note: Channels remarked * are selected to perform test.



2.3 Test Mode and Test Software

- a. During testing, the interface cables and equipment positions were varied according to ANSI C63.4.
- b. The complete test system included Notebook and EUT for RF test.
- c. An executive program, "TeraTerm" under WIN 7 was executed to transmit and receive data via WLAN and Bluetooth.
- d. Pre-Scanned RF Power:

802.11b mode								
Date Rate (Mbps)	11	5.5	2	1	---	---	---	---
Peak Power Output (dBm)	4.87	4.99	5.21	5.33				
Avg. Power Output (dBm)	2.56	2.52	2.49	2.44				

802.11g mode								
Date Rate (Mbps)	54	48	36	24	18	12	9	6
Peak Power Output (dBm)	8.43	8.58	8.74	8.99	9.05	9.11	9.17	9.25
Avg. Power Output (dBm)	-2.15	-2.27	-2.09	-1.88	-1.08	0.85	1.37	1.74

802.11n HT20 mode								
Date Rate (Mbps)	65/7	58.8/6	52/5	39/4	26/3	19.5/2	13/1	6.5/0
Peak Power Output (dBm)	8.22	8.44	8.63	8.78	8.99	9.04	9.22	9.25
Avg. Power Output (dBm)	-2.89	-2.55	-2.07	-1.87	-1.39	1.01	1.47	1.67

*The highest powers were chosen for the full test.

- e. XYZ 3 axis of the EUT have been tested, only the worst axis was reported.
- f. The following test modes were performed for radiation test:
 Test Mode 1. 802.11b (1Mbps)
 Test Mode 2. 802.11g (6Mbps)
 Test Mode 3. 802.11n HT20 (6.5Mbps)
 For radiation (30MHz-1GHz) test, caused "Test Mode 3" generated the worst case, it was reported as the final data.
 For radiation (1GHz-25GHz) test, caused "Test Mode 1" generated the worst case, it was reported as the final data.

2.4 Description of Test System

Device	Manufacturer	Model No.	Description
Notebook	DELL	LatitudeE5450/5450	Power Cable, Unshielding, 1.8m



2.5 General Information of Test

<input checked="" type="checkbox"/> Test Site	CerpPASS Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel:+886-3-3226-888 Fax:+886-3-3226-881 Address: No.68-1, Shihbachongsi, Shihding Township, New Taipei City 223, Taiwan, R.O.C. Tel: +886-2-2663-8582	
	FCC	TW1079, TW1061,390316, 228391, 641184
	IC	4934E-1, 4934E-2
	VCCI	T-2205 for Telecommunication Test C-4663 for Conducted emission test R-3428, R-4218 for Radiated emission test G-812, G-813 for radiated disturbance above 1GHz
<input type="checkbox"/> Test Site	CerpPASS Technology (Suzhou) Co.,Ltd Address: No.66,Tangzhuang Road, Suzhou Industrial Park, Jiangsu 215006, China Tel: +86-512-6917-5888 Fax: +86-512-6917-5666	
	FCC	916572, 331395
	IC	7290A-1, 7290A-2
	VCCI	T-343 for Telecommunication Test C-2919 for Conducted emission test R-2670 for Radiated emission test G-227 for radiated disturbance above 1GHz
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 25000MHz	
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.	



3. Test Equipment and Ancillaries Used for Tests

Instrument	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
EMI RECEIVER	R&S	ESCI 3	100443	2015/03/30	2016/03/29
Bilog Antenna	Schwarzbeck	VULB9168	275	2015/09/03	2016/09/02
Preamplifier	QuieTek	AP-0100A	CHM0906075	2015/09/17	2016/09/16
SPECTRUM ANALYZER	R&S	FSP40	100219	2015/09/01	2016/08/31
HORN ANTENNA	EMCO	3115	31589	2015/03/09	2016/03/08
PREAMPLIFIER	AGILENT	8449B	3008A01954	2015/03/05	2016/03/04
HORN ANTENNA	EMCO	3116	31970	2015/03/05	2016/03/04
HORN ANTENNA	EMCO	3116	31974	2015/09/07	2016/09/06
SPECTRUM ANALYZER	R&S	FSP40	100047	2015/03/07	2016/03/06
PREAMPLIFIER	AGILENT	8449B	3008A01954	2015/03/05	2016/03/04
HIGH PASS FILTER	HP	84300-80038	002	N/A	N/A
SERIES POWER METER	ANRITSU	ML2495A	1224005	2015/03/05	2016/03/04
POWER SENSOR	ANRITSU	MA2411B	1207295	2015/03/05	2016/03/04
Bluetooth Tester	R&S	CBT	101133	2015/03/12	2016/03/11



4. Antenna Requirements

4.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.2 Antenna Construction and Directional Gain

Antenna Type	Antenna Gain
Omnidirectional Antenna	2.8 dBi



5. Test of AC Power Line Conducted Emission

The power supply is DC source, so this item doesn't require testing.



6. Test of Spurious Emission (Radiated)

6.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3


6.2 Test Procedures

- The EUT was placed on a rotatable table top 0.8 meter above ground.
- The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- The table was rotated 360 degrees to determine the position of the highest radiation.
- The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- “Cone of radiation” has been considered to be 3dB bandwidth of the measurement antenna.




6.3 Typical Test Setup


Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup






6.4 Test Result and Data (9KHz ~ 30MHz)

The 9kHz - 30MHz spurious emission is under limit 20dB more.

6.5 Test Result and Data (30MHz ~ 1GHz)

Power	: DC Source	Pol/Phase	: VERTICAL
Test Mode 3	: 802.11n HT20 CH01	Temperature	: 24°C
Test Date	: Dec. 10, 2015	Humidity	: 49%
Memo	:	Atmospheric Pressure	: 1008 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (°)	P/F
1	43.5800	-18.00	49.22	31.22	40.00	-8.78	QP	105	211	P
2	143.4900	-18.79	46.83	28.04	43.50	-15.46	peak	200	0	P
3	198.7800	-20.86	51.10	30.24	43.50	-13.26	peak	200	0	P
4	276.3800	-18.18	45.27	27.09	46.00	-18.91	peak	200	0	P
5	553.8000	-11.19	40.04	28.85	46.00	-17.15	peak	200	0	P
6	623.6400	-9.63	39.26	29.63	46.00	-16.37	peak	200	0	P


Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



Power	: DC Source	Pol/Phase	: HORIZONTAL
Test Mode 3	: 802.11n HT20 CH01	Temperature	: 24°C
Test Date	: Dec. 10, 2015	Humidity	: 49%
Memo	:	Atmospheric Pressure	: 1008 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (°)	P/F
1	47.4600	-18.12	46.28	28.16	40.00	-11.84	peak	100	0	P
2	143.4900	-18.79	49.33	30.54	43.50	-12.96	peak	100	0	P
3	198.7800	-20.86	54.58	33.72	43.50	-9.78	peak	100	0	P
4	312.2700	-17.10	50.59	33.49	46.00	-12.51	peak	100	0	P
5	415.0900	-14.35	44.65	30.30	46.00	-15.70	peak	100	0	P
6	831.2199	-5.78	38.02	32.24	46.00	-13.76	peak	100	0	P


Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



Power	: DC Source	Pol/Phase	: VERTICAL
Test Mode 3	: 802.11n HT20 CH06	Temperature	: 24°C
Test Date	: Dec. 10, 2015	Humidity	: 49%
Memo	:	Atmospheric Pressure	: 1008 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (°)	P/F
1	41.6400	-18.03	49.08	31.05	40.00	-8.95	QP	105	200	P
2	143.4900	-18.79	49.17	30.38	43.50	-13.12	peak	200	0	P
3	198.7800	-20.86	52.03	31.17	43.50	-12.33	peak	200	0	P
4	482.9900	-12.83	49.11	36.28	46.00	-9.72	peak	200	0	P
5	551.8600	-11.24	50.66	39.42	46.00	-6.58	peak	200	0	P
6	623.6400	-9.63	44.05	34.42	46.00	-11.58	peak	200	0	P


Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



Power	: DC Source	Pol/Phase	: HORIZONTAL
Test Mode 3	: 802.11n HT20 CH06	Temperature	: 24°C
Test Date	: Dec. 10, 2015	Humidity	: 49%
Memo	:	Atmospheric Pressure	: 1008 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (°)	P/F
1	47.4600	-18.12	46.73	28.61	40.00	-11.39	peak	100	0	P
2	144.4600	-18.77	48.67	29.90	43.50	-13.60	peak	100	0	P
3	198.7800	-20.86	55.14	34.28	43.50	-9.22	peak	100	0	P
4	324.8800	-16.77	52.48	35.71	46.00	-10.29	peak	100	0	P
5	415.0900	-14.35	47.57	33.22	46.00	-12.78	peak	100	0	P
6	828.3100	-5.84	42.05	36.21	46.00	-9.79	peak	100	0	P


Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



Power	: DC Source	Pol/Phase	: VERTICAL
Test Mode 3	: 802.11n HT20 CH11	Temperature	: 24°C
Test Date	: Dec. 10, 2015	Humidity	: 49%
Memo	:	Atmospheric Pressure	: 1008 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (°)	P/F
1	42.6100	-18.00	48.57	30.57	40.00	-9.43	QP	100	236	P
2	118.2700	-21.00	51.15	30.15	43.50	-13.35	peak	200	0	P
3	275.4100	-18.21	48.99	30.78	46.00	-15.22	peak	200	0	P
4	324.8800	-16.77	47.83	31.06	46.00	-14.94	peak	200	0	P
5	416.0600	-14.32	48.33	34.01	46.00	-11.99	peak	200	0	P
6	551.8600	-11.24	48.50	37.26	46.00	-8.74	peak	200	0	P


Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



Power	: DC Source	Pol/Phase	: HORIZONTAL
Test Mode 3	: 802.11n HT20 CH11	Temperature	: 24°C
Test Date	: Dec. 10, 2015	Humidity	: 49%
Memo	:	Atmospheric Pressure	: 1008 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (°)	P/F
1	47.4600	-18.12	46.53	28.41	40.00	-11.59	peak	100	0	P
2	144.4600	-18.77	48.89	30.12	43.50	-13.38	peak	100	0	P
3	198.7800	-20.86	54.76	33.90	43.50	-9.60	peak	100	0	P
4	276.3800	-18.18	53.50	35.32	46.00	-10.68	peak	100	0	P
5	321.9700	-16.85	50.52	33.67	46.00	-12.33	peak	100	0	P
6	414.1200	-14.37	45.29	30.92	46.00	-15.08	peak	100	0	P

Note: Level = Reading + Factor


Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



6.6 Test Result and Data (1GHz ~ 25GHz)

Power	: DC Source	Pol/Phase	: VERTICAL
Test Mode 1	: 802.11b CH01	Temperature	: 22.3°C
Test Date	: Dec. 10, 2015	Humidity	: 49%
Memo	:	Atmospheric Pressure	: 1008 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (°)	P/F
1	4816.000	-17.49	58.34	40.85	74.00	-33.15	peak	200	0	P
2	7240.000	-11.91	52.02	40.11	74.00	-33.89	peak	200	0	P
3	9640.000	-6.40	52.72	46.32	74.00	-27.68	peak	200	0	P


Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



Power	: DC Source	Pol/Phase	: HORIZONTAL
Test Mode 1	: 802.11b CH01	Temperature	: 22.3°C
Test Date	: Dec. 10, 2015	Humidity	: 49%
Memo	:	Atmospheric Pressure	: 1008 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (°)	P/F
1	4816.000	-17.49	56.52	39.03	74.00	-34.97	peak	100	0	P
2	7240.000	-11.91	50.74	38.83	74.00	-35.17	peak	100	0	P
3	9640.000	-6.40	50.83	44.43	74.00	-29.57	peak	100	0	P


Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



Power	: DC Source	Pol/Phase	: VERTICAL
Test Mode 1	: 802.11b CH06	Temperature	: 22.3°C
Test Date	: Dec. 10, 2015	Humidity	: 49%
Memo	:	Atmospheric Pressure	: 1008 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (°)	P/F
1	4864.000	-17.34	61.04	43.70	74.00	-30.30	peak	100	0	P
2	7312.000	-11.46	55.22	43.76	74.00	-30.24	peak	100	0	P
3	9736.000	-6.26	51.85	45.59	74.00	-28.41	peak	100	0	P


Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



Power	: DC Source	Pol/Phase	: HORIZONTAL
Test Mode 1	: 802.11b CH06	Temperature	: 22.3°C
Test Date	: Dec. 10, 2015	Humidity	: 49%
Memo	:	Atmospheric Pressure	: 1008 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (°)	P/F
1	4864.000	-17.34	59.18	41.84	74.00	-32.16	peak	200	0	P
2	7312.000	-11.46	54.67	43.21	74.00	-30.79	peak	200	0	P
3	9736.000	-6.26	52.57	46.31	74.00	-27.69	peak	200	0	P


Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



Power	: DC Source	Pol/Phase	: VERTICAL
Test Mode 1	: 802.11b CH11	Temperature	: 22.3°C
Test Date	: Dec. 10, 2015	Humidity	: 49%
Memo	:	Atmospheric Pressure	: 1008 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (°)	P/F
1	4912.000	-17.18	58.45	41.27	74.00	-32.73	peak	200	0	P
2	7384.000	-11.00	54.93	43.93	74.00	-30.07	peak	200	0	P
3	9856.000	-6.10	54.24	48.14	74.00	-25.86	peak	200	0	P


Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



Power	: DC Source	Pol/Phase	: HORIZONTAL
Test Mode 1	: 802.11b CH11	Temperature	: 22.3°C
Test Date	: Dec. 10, 2015	Humidity	: 49%
Memo	:	Atmospheric Pressure	: 1008 hpa



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (°)	P/F
1	4912.000	-17.18	58.45	41.27	74.00	-32.73	peak	100	0	P
2	7384.000	-11.00	55.19	44.19	74.00	-29.81	peak	100	0	P
3	9856.000	-6.10	51.54	45.44	74.00	-28.56	peak	100	0	P

Note: Level = Reading + Factor

Margin = Level – Limit

Factor= Antenna Factor + Cable Loss - Amplifier Factor



6.7 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz



6.8 Restrict Band Emission Measurement Data

Test Date: Dec. 10, 2015

Temperature: 23 °C

Atmospheric pressure: 1008 hPa

Humidity: 49 %

Modulation Standard: IEEE 802.11b

Duty cycle: 0.9838

AVG Compensate = 10Log(1/duty cycle) = 0.07

Channel 1						Fundamental Frequency: 2412 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2385.99	V	60.16	-12.44	47.72	Peak	74	54	-26.28	0	2.00
---	V	---	---	---	Ave	74	54	---	---	---
2384.46	H	62.66	-12.44	50.22	Peak	74	54	-23.78	0	1.00
---	H	---	---	---	Ave	74	54	---	---	---
Channel 11						Fundamental Frequency: 2462 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2487.76	V	59.17	-11.96	47.21	Peak	74	54	-26.79	0	2.00
---	V	---	---	---	Ave	74	54	---	---	---
2487.91	H	62.75	-11.96	50.79	Peak	74	54	-23.21	0	1.00
---	H	---	---	---	Ave	74	54	---	---	---



Modulation Standard: IEEE 802.11g

Duty cycle: 0.9156

AVG Compensate = 10Log(1/duty cycle)=0.38

Channel 1						Fundamental Frequency: 2412 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2338.96	V	69.75	-12.65	57.1	Peak	74	54	-16.9	192	1.05
2338.96	V	46.15	-12.27	33.88	Ave	74	54	-20.12	192	1.05
2347.74	V	72.16	-12.6	59.56	Peak	74	54	-14.44	192	1.05
2347.74	V	45.50	-12.13	35.28	Ave	74	54	-18.72	192	1.05
2368.03	V	71.36	-12.51	58.85	Peak	74	54	-15.15	192	1.05
2368.03	V	50.31	-12.13	38.18	Ave	74	54	-14.16	192	1.05
2385.99	V	74.21	-12.44	61.77	Ave	74	54	-12.23	192	1.05
2385.99	V	56.04	-12.06	43.98	Peak	74	54	-8.36	192	1.05
2337.13	H	72.28	-12.67	59.61	Ave	74	54	-14.36	104	1.10
2337.13	H	46.47	-12.29	34.18	Peak	74	54	-18.16	104	1.10
2356.20	H	72.89	-12.57	60.32	Ave	74	54	-13.68	104	1.10
2356.20	H	49.07	-12.19	36.88	Peak	74	54	-15.46	104	1.10
2371.30	H	74.32	-12.5	61.82	Ave	74	54	-12.18	104	1.10
2371.30	H	50.38	-12.12	38.26	Peak	74	54	-14.08	104	1.10
2390.00	H	79.58	-12.41	67.17	Ave	74	54	-6.83	104	1.10
2390.00	H	58.21	-12.03	46.18	Peak	74	54	-6.16	104	1.10

Channel 11						Fundamental Frequency: 2462 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2484.95	V	63.35	-11.98	51.37	Peak	74	54	-22.63	0	2.00
---	V	---	---	---	Ave	74	54	---	---	---
2483.73	H	67.90	-11.98	55.92	Peak	74	54	-18.08	195	1.11
2483.73	H	48.48	-11.98	36.5	Peak	74	54	-17.50	195	1.11



Modulation Standard: IEEE 802.11n HT20

Duty cycle: 0.6258

AVG Compensate = 10Log(1/duty cycle) =2.04

Channel 1						Fundamental Frequency: 2412 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2388.74	V	77.56	-12.42	65.14	Peak	74	54	-8.86	143	1.05
2388.74	V	59.12	-10.38	48.74	Ave	74	54	-5.26	143	1.05
2390.00	H	76.01	-12.41	63.6	Peak	74	54	-10.4	288	1.05
2390.00	H	58.91	-10.37	48.54	Ave	74	54	-5.46	288	1.05
Channel 11						Fundamental Frequency: 2462 MHz				
Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result (dBuV/m)	Remark	Limit (dBuV/m)		Margin (dB)	Table Deg.	Ant High (m)
						Peak	Ave			
2485.21	V	61.64	-11.98	49.66	Peak	74	54	-24.34	0	2.00
---	V	---	---	---	Ave	74	54	---	---	---
2483.73	H	65.40	-11.98	53.42	Peak	74	54	-20.58	0	1.00
---	H	---	---	---	Ave	74	54	---	---	---

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3 MHz (detector peak mode) for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3 MHz (detector sample mode) for Average detection at frequency above 1GHz.



7. Test of Spurious Emission (Conducted)


7.1 Test Limit

Below -20dB of the highest emission level of operating band (In 100 kHz Resolution Bandwidth)

7.2 Test Procedure

- a. The transmitter output was connected to the spectrum analyzer via a low lose cable.
- b. Set RBW of spectrum analyzer to 100 KHz and VBW of spectrum analyzer to 300 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- c. Peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20dB relative to the maximum measured in-band peak PSD level.
- d. The band edges was measured and recorded.

7.3 Test Setup Layout




7.4 Test Result and Data

Test Date	: Dec. 11, 2015	Temperature	: 22°C
Atmospheric pressure	: 1022 hPa	Humidity	: 54%
Test Result	: PASS		




Note: Test plots refers to the following pages.



Modulation Type: 802.11b
CH01







CH11






Modulation Type: 802.11g
CH01

CH11








Modulation Type: 802.11n HT20
CH01



CH11





8. 6dB Bandwidth Measurement Data


8.1 Test Limit

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

8.2 Test Procedures

- a. The transmitter output was connected to the spectrum analyzer.
- b. Set RBW of spectrum analyzer to 1~5% of the emission bandwidth and VBW ≥ 3x RBW.
- c. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.
- d. The 6dB Bandwidth was measured and recorded.

8.3 Test Setup Layout




8.4 Test Result and Data

Test Date : Dec. 11, 2015 Temperature : 22°C
 Atmospheric pressure : 1022 hPa Humidity : 54%


Modulation Type	Channel	Frequency (MHz)	6dB Bandwidth (MHz)
IEEE 802.11b (1Mbps)	01	2412	9.50
	06	2437	9.20
	11	2462	8.60
IEEE 802.11g (6Mbps)	01	2412	16.20
	06	2437	16.00
	11	2462	16.30
IEEE 802.11n HT20 (6.5Mbps)	01	2412	17.60
	06	2437	17.60
	11	2462	17.60




Modulation Type: 802.11b
CH01




Modulation Type: 802.11g
CH01




CH06




CH06



CH11




CH11







Modulation Type: 802.11n HT20
CH01



CH06



CH11





9. Maximum Peak and Average Output Power

9.1 Test Limit


The Maximum Peak Output Power Measurement is 30dBm.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi

9.2 Test Procedures

The antenna port (RF output) of the EUT was connected to the input (RF input) of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

9.3 Test Setup Layout





9.4 Test Result and Data

Test Date : Dec. 11, 2015 Temperature : 22°C
 Atmospheric pressure : 1022 hPa Humidity : 54%

Modulation Standard	Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Power Output(mW)
802.11b (1Mbps)	01	2412	5.33	3.41
	06	2437	1.33	1.36
	11	2462	-2.44	0.57
802.11g (6Mbps)	01	2412	9.25	8.41
	06	2437	5.66	3.68
	11	2462	2.24	1.67
802.11n HT20 (6.5Mbps)	01	2412	9.25	8.41
	06	2437	6.06	4.04
	11	2462	2.11	1.63

Modulation Standard	Channel	Frequency (MHz)	Avg. Power Output (dBm)	Avg. Power Output (mW)
802.11b (1Mbps)	01	2412	2.44	1.75
	06	2437	-0.87	0.82
	11	2462	-4.73	0.34
802.11g (6Mbps)	01	2412	1.74	1.49
	06	2437	-1.65	0.68
	11	2462	-5.34	0.29
802.11n HT20 (6.5Mbps)	01	2412	1.67	1.47
	06	2437	-1.88	0.65
	11	2462	-5.63	0.27



10. Power Spectral Density

10.1 Test Limit


The Maximum of Power Spectral Density Measurement is 8dBm.

If transmitting antennas of directional gain greater than 6 dBi are used, the power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi

10.2 Test Procedures

- a. The transmitter output was connected to spectrum analyzer.
- b. The spectrum analyzer’s resolution bandwidth were set at 3KHz RBW and 30KHz VBW as that of the fundamental frequency. Set the sweep time=auto couple.
- c. The power spectral density was measured and recorded.

10.3 Test Setup Layout




10.4 Test Result and Data

Test Date : Dec. 11, 2015 Temperature : 22°C
 Atmospheric pressure : 1022 hPa Humidity : 54%


Modulation Standard	Channel	Frequency (MHz)	Maximum Power Density of 3 kHz Bandwidth (dBm)
802.11b (1Mbps)	01	2412	-19.91
	06	2437	-24.93
	11	2462	-28.11
802.11g (6Mbps)	01	2412	-25.16
	06	2437	-28.24
	11	2462	-32.38
802.11n HT20 (6.5Mbps)	01	2412	-23.71
	06	2437	-29.10
	11	2462	-32.28




Modulation Type: 802.11b
CH01




Modulation Type: 802.11g
CH01




CH06




CH06



CH11




CH11






Modulation Type: 802.11n HT20
CH01



CH06



CH11

