

FCC Test Report

FCC ID : XNAWBS06S
Equipment : Body
Model No. : WBS06S
Brand Name : Withings
Applicant : Withings
Address : 2 rue Maurice Hartmann
92130 Issy-Les-Moulineaux
France
Standard : 47 CFR FCC Part 15.247
Received Date : Mar. 03, 2022
Tested Date : Mar. 17 ~ Mar. 28, 2022

We, International Certification Corporation, would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:

Approved by:



Along Chen / Assistant Manager



Gary Chang / Manager

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	The Equipment List	8
1.5	Test Standards	9
1.6	Reference Guidance	9
1.7	Deviation from Test Standard and Measurement Procedure.....	9
1.8	Measurement Uncertainty	9
2	TEST CONFIGURATION	10
2.1	Testing Facility.....	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS.....	11
3.1	6dB and Occupied Bandwidth	11
3.2	RF Output Power.....	16
3.3	Power Spectral Density	19
3.4	Unwanted Emissions into Restricted Frequency Bands	24
3.5	Emissions in Non-Restricted Frequency Bands.....	46
4	TEST LABORATORY INFORMATION	50

Release Record

Report No.	Version	Description	Issued Date
FR230302AC	Rev. 01	Initial issue	Apr. 28, 2022

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	Note ¹	N/A
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 7311.00MHz 53.53 (Margin -0.47dB) - AV	Pass
15.247(b)(3)	Maximum Output Power	Max Power [dBm]: 23.01	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

N/A means Not Applicable.

Note¹: The EUT consumes DC power from battery, so the test is not required.

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	Data Rate / MCS
2400-2483.5	b	2412-2462	1-11 [11]	1	1-11 Mbps
2400-2483.5	g	2412-2462	1-11 [11]	1	6-54 Mbps
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	1	MCS 0-7

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.
 Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.
 Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.

1.1.2 Antenna Details

Ant. No.	Brand	Model	Type	Connector	Gain (dBi)
1	BROADCOM	BCM9Fractal64	PCB	NA	2.8

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	4x1.5V AAA battery
--------------------------	--------------------

1.1.4 Accessories

N/A

1.1.5 Test Sample Information

MAC ID of Test Sample	Radiated Emission: 0024E4EDFEE4 Antenna Port Conducted: 0024E4EE9C7E
------------------------------	---

1.1.6 Channel List

Channel	Frequency(MHz)
1	2412
2	2417
3	2422
4	2427
5	2432
6	2437
7	2442
8	2447
9	2452
10	2457
11	2462

1.1.7 Test Tool and Duty Cycle

Test Tool	Tera Term, V4.94		
Duty Cycle and Duty Factor	Mode	Duty Cycle (%)	Duty Factor (dB)
	11b	99.66%	0.01
	11g	94.23%	0.26
	HT20	93.81%	0.28

1.1.8 Power Index of Test Tool


Modulation Mode	Test Frequency (MHz)	Power Index
11b	2412	14
11b	2437	14
11b	2462	14
11g	2412	13
11g	2437	13
11g	2462	13
HT20	2412	13
HT20	2437	13
HT20	2462	13

1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Remarks
1	Notebook	DELL	Latitude E5470	DoC	---
2	Fixture	---	---	---	Provided by applicant.
3	USB Cable	ICC	mini to A	---	---

Note: The support notebook, USB Cable and fixture are disconnected from EUT and removed from test table after sending command to EUT to control EUT to transmit continuously.

1.3 Test Setup Chart



1.4 The Equipment List

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Tested Date	Mar. 17, 2022				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101657	Mar. 15, 2022	Mar. 14, 2023
Spectrum Analyzer	R&S	FSV40	101498	Nov. 29, 2021	Nov. 28, 2022
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 08, 2021	Nov. 07, 2022
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jun. 30, 2021	Jun. 29, 2022
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 03, 2021	Dec. 02, 2022
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170508	Jan. 11, 2022	Jan. 10, 2023
Preamplifier	EMC	EMC02325	980225	Jun. 29, 2021	Jun. 28, 2022
Preamplifier	Agilent	83017A	MY39501308	Sep. 28, 2021	Sep. 27, 2022
Preamplifier	EMC	EMC184045B	980192	Jul. 14, 2021	Jul. 13, 2022
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 05, 2021	Oct. 04, 2022
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 05, 2021	Oct. 04, 2022
LF cable 11M	EMC	EMCCFD400-NW-N W-11000	200801	Oct. 05, 2021	Oct. 04, 2022
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	160502	Oct. 05, 2021	Oct. 04, 2022
RF Cable	EMC	EMC104-35M-35M- 8000	210920	Oct. 05, 2021	Oct. 04, 2022
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Oct. 05, 2021	Oct. 04, 2022
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Mar. 28, 2022				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101498	Nov. 29, 2021	Nov. 28, 2022
Power Meter	Anritsu	ML2495A	1241002	Nov. 07, 2021	Nov. 06, 2022
Power Sensor	Anritsu	MA2411B	1207366	Nov. 07, 2021	Nov. 06, 2022
Measurement Software	Sporton	SENSE-15247_DTS	V5.10	NA	NA

Note: Calibration Interval of instruments listed above is one year.

1.5 Test Standards

47 CFR FCC Part 15.247

ANSI C63.10-2013

1.6 Reference Guidance

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

1.7 Deviation from Test Standard and Measurement Procedure

None

1.8 Measurement Uncertainty

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$)).

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 34.130 Hz
Conducted power	± 0.808 dB
Power density	± 0.583 dB
Conducted emission	± 2.715 dB
AC conducted emission	± 2.92 dB
Radiated emission ≤ 1 GHz	± 3.41 dB
Radiated emission > 1 GHz	± 4.59 dB

2 Test Configuration

2.1 Testing Facility

Test Laboratory	International Certification Corporation
Test Site	03CH01-WS, TH01-WS
Address of Test Site	No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Dist., Tao Yuan City 33381, Taiwan (R.O.C.)

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- ISED#: 10807A
- CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate	Test Configuration
Radiated Emissions ≤1GHz	11g	2462	6 Mbps	---
Radiated Emissions >1GHz	11b	2412 / 2437 / 2462	1 Mbps	---
Maximum Output Power	11g	2412 / 2437 / 2462	6 Mbps	
6dB bandwidth	HT20	2412 / 2437 / 2462	MCS 0	
Power spectral density				

3 Transmitter Test Results

3.1 6dB and Occupied Bandwidth

3.1.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.1.2 Test Procedures


6dB Bandwidth

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

1. Set resolution bandwidth (RBW) = 1% ~ 5 % of OBW, Video bandwidth = 3 x RBW
2. Detector = Sample, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

3.1.3 Test Setup



3.1.4 Test Result of 6dB and Occupied Bandwidth

Ambient Condition	21°C / 67%	Tested By	Aska Huang
--------------------------	------------	------------------	------------

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
802.11b_Nss1,(1Mbps)_1TX	8.551M	13.965M	14M0G1D	8.043M	13.965M
802.11g_Nss1,(6Mbps)_1TX	15.072M	16.353M	16M4D1D	15.072M	16.281M
802.11n HT20_Nss1,(MCS0)_1TX	15.072M	17.511M	17M5D1D	13.913M	17.438M

Max-N dB = Maximum 6dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;

Result


Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
802.11b_Nss1,(1Mbps)_1TX	-	-	-	-
2412MHz	Pass	500k	8.551M	13.965M
2437MHz	Pass	500k	8.043M	13.965M
2462MHz	Pass	500k	8.551M	13.965M
802.11g_Nss1,(6Mbps)_1TX	-	-	-	-
2412MHz	Pass	500k	15.072M	16.353M
2437MHz	Pass	500k	15.072M	16.281M
2462MHz	Pass	500k	15.072M	16.353M
802.11n HT20_Nss1,(MCS0)_1TX	-	-	-	-
2412MHz	Pass	500k	15.072M	17.438M
2437MHz	Pass	500k	13.913M	17.511M
2462MHz	Pass	500k	15.072M	17.438M

Port X-N dB = Port X 6dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;

802.11b_Nss1,(1Mbps)_1TX

EBW


2412MHz



802.11b_Nss1,(1Mbps)_1TX

EBW


2437MHz



802.11b_Nss1,(1Mbps)_1TX

EBW

2462MHz




802.11g_Nss1,(6Mbps)_1TX


EBW

2412MHz

CF
2.412GHz
Span
50MHz
RBW
100kHz
VBW
300kHz
Sweep Time
1.08ms
Detector Type
Peak



CF
2.412GHz
Span
50MHz
RBW
200kHz
VBW
1MHz
Sweep Time
1.02ms
Detector Type
Sample




6dB(Hz)	Fl-6dB(Hz)	Fh-6dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
15.072M	2.404464G	2.419536G	16.353M	2.403823G	2.420177G	500k	1

802.11g_Nss1,(6Mbps)_1TX


EBW

2437MHz

CF
2.437GHz
Span
50MHz
RBW
100kHz
VBW
300kHz
Sweep Time
1.08ms
Detector Type
Peak



CF
2.437GHz
Span
50MHz
RBW
200kHz
VBW
1MHz
Sweep Time
1.02ms
Detector Type
Sample




6dB(Hz)	Fl-6dB(Hz)	Fh-6dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
15.072M	2.429464G	2.444536G	16.281M	2.428823G	2.445104G	500k	1

802.11g_Nss1,(6Mbps)_1TX


EBW

2462MHz

CF
2.462GHz
Span
50MHz
RBW
100kHz
VBW
300kHz
Sweep Time
1.08ms
Detector Type
Peak



CF
2.462GHz
Span
50MHz
RBW
200kHz
VBW
1MHz
Sweep Time
1.02ms
Detector Type
Sample




6dB(Hz)	Fl-6dB(Hz)	Fh-6dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
15.072M	2.454464G	2.469536G	16.353M	2.453823G	2.470177G	500k	1

802.11n HT20_Nss1,(MCS0)_1TX

EBW


2412MHz



802.11n HT20_Nss1,(MCS0)_1TX

EBW


2437MHz



802.11n HT20_Nss1,(MCS0)_1TX

EBW

2462MHz



3.2 RF Output Power

3.2.1 Limit of RF Output Power


Conducted power shall not exceed 1Watt.

Antenna gain $\leq 6\text{dBi}$, no any corresponding reduction is in output power limit.

3.2.2 Test Procedures

A broadband RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.2.3 Test Setup



3.2.4 Test Result of Maximum Output Power

Ambient Condition	21°C / 67%	Tested By	Aska Huang
--------------------------	------------	------------------	------------

Summary of Peak Conducted Output Power

Mode	Total Power (dBm)	Total Power (W)
2.4-2.4835GHz	-	-
802.11b_Nss1,(1Mbps)_1TX	16.85	0.04842
802.11g_Nss1,(6Mbps)_1TX	23.01	0.19999
802.11n HT20_Nss1,(MCS0)_1TX	22.92	0.19588

Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Total Power (dBm)	Power Limit (dBm)	EIRP (dBm)	EIRP Limit (dBm)
802.11b_Nss1,(1Mbps)_1TX	-	-	-	-	-	-	-
2412MHz	Pass	2.80	16.62	16.62	30.00	19.42	36.00
2437MHz	Pass	2.80	16.79	16.79	30.00	19.59	36.00
2462MHz	Pass	2.80	16.85	16.85	30.00	19.65	36.00
802.11g_Nss1,(6Mbps)_1TX	-	-	-	-	-	-	-
2412MHz	Pass	2.80	22.46	22.46	30.00	25.26	36.00
2437MHz	Pass	2.80	22.83	22.83	30.00	25.63	36.00
2462MHz	Pass	2.80	23.01	23.01	30.00	25.81	36.00
802.11n HT20_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
2412MHz	Pass	2.80	22.42	22.42	30.00	25.22	36.00
2437MHz	Pass	2.80	22.88	22.88	30.00	25.68	36.00
2462MHz	Pass	2.80	22.92	22.92	30.00	25.72	36.00

DG = Directional Gain; **Port X** = Port X output power

Summary of Conducted (Average) Output Power

Mode	Total Power (dBm)	Total Power (W)
2.4-2.4835GHz	-	-
802.11b_Nss1,(1Mbps)_1TX	14.47	0.02799
802.11g_Nss1,(6Mbps)_1TX	14.31	0.02698
802.11n HT20_Nss1,(MCS0)_1TX	14.11	0.02576

Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Total Power (dBm)	Power Limit (dBm)	EIRP (dBm)	EIRP Limit (dBm)
802.11b_Nss1,(1Mbps)_1TX	-	-	-	-	-	-	-
2412MHz	Pass	2.80	14.31	14.31	-	17.11	-
2437MHz	Pass	2.80	14.46	14.46	-	17.26	-
2462MHz	Pass	2.80	14.47	14.47	-	17.27	-
802.11g_Nss1,(6Mbps)_1TX	-	-	-	-	-	-	-
2412MHz	Pass	2.80	14.02	14.02	-	16.82	-
2437MHz	Pass	2.80	14.18	14.18	-	16.98	-
2462MHz	Pass	2.80	14.31	14.31	-	17.11	-
802.11n HT20_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
2412MHz	Pass	2.80	14.01	14.01	-	16.81	-
2437MHz	Pass	2.80	14.05	14.05	-	16.85	-
2462MHz	Pass	2.80	14.11	14.11	-	16.91	-

DG = Directional Gain; Port X = Port X output power

Note : Conducted average output power is for reference only

3.3 Power Spectral Density

3.3.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.3.2 Test Procedures

Peak PSD

1. Set the RBW = 3 kHz, VBW = 10 kHz.
2. Detector = Peak, Sweep time = auto couple.
3. Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.


Average PSD, duty cycle \geq 98%

1. Set the RBW = 30 kHz, VBW = 100 kHz.
2. Detector = RMS, Sweep time = auto couple.
3. Sweep time = auto couple.
4. Employ trace averaging (RMS) mode over a minimum of 100 traces.
5. Use the peak marker function to determine the maximum amplitude level.

Average PSD, duty cycle $<$ 98%

1. Set the RBW = 30 kHz, VBW = 100 kHz. Detector = RMS.
2. Set the sweep time to: ≥ 10 (number of measurement points in sweep) x (total on/off period of the transmitted signal).
3. Perform the measurement over a single sweep.
4. Use the peak marker function to determine the maximum amplitude level.
5. Add $10 \log (1/x)$, where x is the duty cycle.

3.3.3 Test Setup



3.3.4 Test Result of Power Spectral Density

Ambient Condition	21°C / 67%	Tested By	Aska Huang
--------------------------	------------	------------------	------------

Summary

Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
802.11b_Nss1,(1Mbps)_1TX	-8.42
802.11g_Nss1,(6Mbps)_1TX	-10.69
802.11n HT20_Nss1,(MCS0)_1TX	-9.65

RBW= 3 kHz

Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)
802.11b_Nss1,(1Mbps)_1TX	-	-	-	-	-
2412MHz	Pass	2.80	-8.47	-8.47	8.00
2437MHz	Pass	2.80	-8.90	-8.90	8.00
2462MHz	Pass	2.80	-8.42	-8.42	8.00
802.11g_Nss1,(6Mbps)_1TX	-	-	-	-	-
2412MHz	Pass	2.80	-10.81	-10.81	8.00
2437MHz	Pass	2.80	-10.69	-10.69	8.00
2462MHz	Pass	2.80	-11.12	-11.12	8.00
802.11n HT20_Nss1,(MCS0)_1TX	-	-	-	-	-
2412MHz	Pass	2.80	-9.65	-9.65	8.00
2437MHz	Pass	2.80	-10.48	-10.48	8.00
2462MHz	Pass	2.80	-10.40	-10.40	8.00

DG = Directional Gain;


PD = Power density; **Port X** = Port X power density;

RBW= 3 kHz

802.11b_Nss1,(1Mbps)_1TX

PSD

2412MHz




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-8.47	-8.47	-8.47

802.11b_Nss1,(1Mbps)_1TX

PSD

2437MHz




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-8.90	-8.90	-8.90

802.11b_Nss1,(1Mbps)_1TX

PSD

2462MHz




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-8.42	-8.42	-8.42

802.11g_Nss1,(6Mbps)_1TX

PSD


2412MHz



802.11g_Nss1,(6Mbps)_1TX

PSD


2437MHz



802.11g_Nss1,(6Mbps)_1TX

PSD


2462MHz



802.11n HT20_Nss1,(MCS0)_1TX

PSD


2412MHz



802.11n HT20_Nss1,(MCS0)_1TX

PSD


2437MHz



802.11n HT20_Nss1,(MCS0)_1TX

PSD

2462MHz



3.4 Unwanted Emissions into Restricted Frequency Bands

3.4.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Quasi-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.4.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.4.3 Test Setup


Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz




3.4.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	11g	Test Freq. (MHz)	2462																																																																																																																																			
Polarization	Horizontal																																																																																																																																					
Test By : Roger Lu Temperature(°C):24 Humidity(%):67																																																																																																																																						
																																																																																																																																						
	<table border="1"> <thead> <tr> <th>1</th> <th>2</th> <th>3</th> <th>4</th> <th>5</th> <th>6</th> </tr> </thead> <tbody> <tr> <td>38.73</td> <td>160.95</td> <td>271.53</td> <td>376.29</td> <td>468.44</td> <td>574.17</td> </tr> <tr> <td>21.84</td> <td>21.08</td> <td>23.45</td> <td>24.43</td> <td>29.21</td> <td>28.64</td> </tr> <tr> <td>40.00</td> <td>43.50</td> <td>46.00</td> <td>46.00</td> <td>46.00</td> <td>46.00</td> </tr> <tr> <td>-18.16</td> <td>-22.42</td> <td>-22.55</td> <td>-21.57</td> <td>-16.79</td> <td>-17.36</td> </tr> <tr> <td>30.71</td> <td>29.86</td> <td>32.49</td> <td>30.73</td> <td>33.20</td> <td>30.45</td> </tr> <tr> <td>-8.87</td> <td>-8.78</td> <td>-9.04</td> <td>-6.30</td> <td>-3.99</td> <td>-1.81</td> </tr> <tr> <td>Peak</td> <td>Peak</td> <td>Peak</td> <td>Peak</td> <td>Peak</td> <td>Peak</td> </tr> <tr> <td>---</td> <td>---</td> <td>---</td> <td>---</td> <td>---</td> <td>---</td> </tr> <tr> <td>---</td> <td>---</td> <td>---</td> <td>---</td> <td>---</td> <td>---</td> </tr> </tbody> </table>	1	2	3	4	5	6	38.73	160.95	271.53	376.29	468.44	574.17	21.84	21.08	23.45	24.43	29.21	28.64	40.00	43.50	46.00	46.00	46.00	46.00	-18.16	-22.42	-22.55	-21.57	-16.79	-17.36	30.71	29.86	32.49	30.73	33.20	30.45	-8.87	-8.78	-9.04	-6.30	-3.99	-1.81	Peak	Peak	Peak	Peak	Peak	Peak	---	---	---	---	---	---	---	---	---	---	---	---	<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission level</th> <th>Limit</th> <th>Margin</th> <th>SA reading</th> <th>Factor</th> <th>Remark</th> <th>ANT High cm</th> <th>Turn Table deg</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB/m</th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>38.73</td> <td>21.84</td> <td>40.00</td> <td>-18.16</td> <td>30.71</td> <td>-8.87</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>2</td> <td>160.95</td> <td>21.08</td> <td>43.50</td> <td>-22.42</td> <td>29.86</td> <td>-8.78</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>3</td> <td>271.53</td> <td>23.45</td> <td>46.00</td> <td>-22.55</td> <td>32.49</td> <td>-9.04</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>4</td> <td>376.29</td> <td>24.43</td> <td>46.00</td> <td>-21.57</td> <td>30.73</td> <td>-6.30</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>5</td> <td>468.44</td> <td>29.21</td> <td>46.00</td> <td>-16.79</td> <td>33.20</td> <td>-3.99</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>6</td> <td>574.17</td> <td>28.64</td> <td>46.00</td> <td>-17.36</td> <td>30.45</td> <td>-1.81</td> <td>Peak</td> <td>---</td> </tr> </tbody> </table>	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m				1	38.73	21.84	40.00	-18.16	30.71	-8.87	Peak	---	2	160.95	21.08	43.50	-22.42	29.86	-8.78	Peak	---	3	271.53	23.45	46.00	-22.55	32.49	-9.04	Peak	---	4	376.29	24.43	46.00	-21.57	30.73	-6.30	Peak	---	5	468.44	29.21	46.00	-16.79	33.20	-3.99	Peak	---	6	574.17	28.64	46.00	-17.36	30.45	-1.81	Peak	---
1	2	3	4	5	6																																																																																																																																	
38.73	160.95	271.53	376.29	468.44	574.17																																																																																																																																	
21.84	21.08	23.45	24.43	29.21	28.64																																																																																																																																	
40.00	43.50	46.00	46.00	46.00	46.00																																																																																																																																	
-18.16	-22.42	-22.55	-21.57	-16.79	-17.36																																																																																																																																	
30.71	29.86	32.49	30.73	33.20	30.45																																																																																																																																	
-8.87	-8.78	-9.04	-6.30	-3.99	-1.81																																																																																																																																	
Peak	Peak	Peak	Peak	Peak	Peak																																																																																																																																	
---	---	---	---	---	---																																																																																																																																	
---	---	---	---	---	---																																																																																																																																	
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m																																																																																																																																	
1	38.73	21.84	40.00	-18.16	30.71	-8.87	Peak	---																																																																																																																														
2	160.95	21.08	43.50	-22.42	29.86	-8.78	Peak	---																																																																																																																														
3	271.53	23.45	46.00	-22.55	32.49	-9.04	Peak	---																																																																																																																														
4	376.29	24.43	46.00	-21.57	30.73	-6.30	Peak	---																																																																																																																														
5	468.44	29.21	46.00	-16.79	33.20	-3.99	Peak	---																																																																																																																														
6	574.17	28.64	46.00	-17.36	30.45	-1.81	Peak	---																																																																																																																														
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m). Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.																																																																																																																																						

Modulation	11g	Test Freq. (MHz)	2462
Polarization	Vertical		

Test By :Roger Lu Temperature(°C):24 Humidity(%):67



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	38.73	22.81	40.00	-17.19	31.68	-8.87	Peak	---	---
2	160.95	21.42	43.50	-22.08	30.20	-8.78	Peak	---	---
3	288.99	22.78	46.00	-23.22	31.18	-8.40	Peak	---	---
4	362.71	23.96	46.00	-22.04	30.57	-6.61	Peak	---	---
5	468.44	28.24	46.00	-17.76	32.23	-3.99	Peak	---	---
6	549.92	27.74	46.00	-18.26	30.20	-2.46	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)


*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.4.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11b


Modulation	11b	Test Freq. (MHz)	2412						
Polarization	Horizontal								
Test By : Roger Lu Temperature(°C):24 Humidity(%):67									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		cm	deg
1	2390.00	41.89	54.00	-12.11	44.64	-2.75	Average	225	98
2	2390.00	53.77	74.00	-20.23	56.52	-2.75	Peak	225	98
3	4824.00	43.78	54.00	-10.22	39.64	4.14	Average	100	265
4	4824.00	49.73	74.00	-24.27	45.59	4.14	Peak	100	265
5	12060.00	42.91	54.00	-11.09	29.12	13.79	Average	100	30
6	12060.00	55.96	74.00	-18.04	42.17	13.79	Peak	100	30
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

Modulation	11b	Test Freq. (MHz)	2412						
Polarization	Vertical								
Test By :Roger Lu Temperature(°C):24 Humidity(%):67									
									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2390.00	39.11	54.00	-14.89	41.86	-2.75	Average	100	183
2	2390.00	51.38	74.00	-22.62	54.13	-2.75	Peak	100	183
3	4824.00	46.00	54.00	-8.00	41.86	4.14	Average	100	357
4	4824.00	51.20	74.00	-22.80	47.06	4.14	Peak	100	357
5	12060.00	43.04	54.00	-10.96	29.25	13.79	Average	100	40
6	12060.00	56.15	74.00	-17.85	42.36	13.79	Peak	100	40
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

Modulation	11b	Test Freq. (MHz)	2437						
Polarization	Horizontal								
Test By : Roger Lu		Temperature(°C): 24	Humidity(%): 67						
									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		cm	deg
1	2390.00	38.98	54.00	-15.02	41.73	-2.75	Average	252	96
2	2390.00	51.37	74.00	-22.63	54.12	-2.75	Peak	252	96
3	2483.50	39.42	54.00	-14.58	42.12	-2.70	Average	252	96
4	2483.50	51.86	74.00	-22.14	54.56	-2.70	Peak	252	96
5	4874.00	43.27	54.00	-10.73	39.14	4.13	Average	100	262
6	4874.00	48.52	74.00	-25.48	44.39	4.13	Peak	100	262
7	7311.00	46.57	54.00	-7.43	37.29	9.28	Average	100	41
8	7311.00	54.99	74.00	-19.01	45.71	9.28	Peak	100	41
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

Modulation	11b	Test Freq. (MHz)	2437
Polarization	Vertical		

Test By :Roger Lu Temperature(°C):24 Humidity(%):67



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2390.00	37.92	54.00	-16.08	40.67	-2.75	Average	100	185
2	2390.00	51.14	74.00	-22.86	53.89	-2.75	Peak	100	185
3	2483.50	38.37	54.00	-15.63	41.07	-2.70	Average	100	185
4	2483.50	51.32	74.00	-22.68	54.02	-2.70	Peak	100	185
5	4874.00	45.29	54.00	-8.71	41.16	4.13	Average	100	329
6	4874.00	49.59	74.00	-24.41	45.46	4.13	Peak	100	329
7	7311.00	53.53	54.00	-0.47	44.25	9.28	Average	202	353
8	7311.00	60.93	74.00	-13.07	51.65	9.28	Peak	202	353


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11b	Test Freq. (MHz)	2462
Polarization	Horizontal		

Test By :Roger Lu Temperature(°C):24 Humidity(%):67



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2483.50	40.95	54.00	-13.05	43.65	-2.70	Average	225	100
2	2483.50	53.89	74.00	-20.11	56.59	-2.70	Peak	225	100
3	4924.00	41.17	54.00	-12.83	37.11	4.06	Average	100	266
4	4924.00	47.21	74.00	-26.79	43.15	4.06	Peak	100	266
5	7386.00	45.16	54.00	-8.84	35.91	9.25	Average	100	44
6	7386.00	53.06	74.00	-20.94	43.81	9.25	Peak	100	44


Note 1: Emission Level (dBUV/m) = SA Reading (dBUV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	11b	Test Freq. (MHz)	2462
Polarization	Vertical		

Test By :Roger Lu Temperature(°C):24 Humidity(%):67



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2483.50	38.42	54.00	-15.58	41.12	-2.70	Average	100	186
2	2483.50	51.52	74.00	-22.48	54.22	-2.70	Peak	100	186
3	4924.00	43.32	54.00	-10.68	39.26	4.06	Average	100	330
4	4924.00	48.64	74.00	-25.36	44.58	4.06	Peak	100	330
5	7386.00	51.94	54.00	-2.06	42.69	9.25	Average	173	349
6	7386.00	58.81	74.00	-15.19	49.56	9.25	Peak	173	349

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.4.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11g

Modulation	11g	Test Freq. (MHz)	2412						
Polarization	Horizontal								
Test By : Roger Lu Temperature(°C):24 Humidity(%):67									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		cm	deg
1	2390.00	45.47	54.00	-8.53	48.22	-2.75	Average	224	93
2	2390.00	61.85	74.00	-12.15	64.60	-2.75	Peak	224	93
3	4824.00	34.39	54.00	-19.61	30.25	4.14	Average	100	269
4	4824.00	47.81	74.00	-26.19	43.67	4.14	Peak	100	269
5	12060.00	42.93	54.00	-11.07	29.14	13.79	Average	100	30
6	12060.00	55.97	74.00	-18.03	42.18	13.79	Peak	100	30
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

Modulation	11g	Test Freq. (MHz)	2412
Polarization	Vertical		

Test By :Roger Lu Temperature(°C):24 Humidity(%):67



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2390.00	41.81	54.00	-12.19	44.56	-2.75	Average	102	188
2	2390.00	57.83	74.00	-16.17	60.58	-2.75	Peak	102	188
3	4824.00	36.63	54.00	-17.37	32.49	4.14	Average	100	355
4	4824.00	50.42	74.00	-23.58	46.28	4.14	Peak	100	355
5	12060.00	43.00	54.00	-11.00	29.21	13.79	Average	100	40
6	12060.00	56.17	74.00	-17.83	42.38	13.79	Peak	100	40


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2437
Polarization	Horizontal		

Test By :Roger Lu Temperature(°C):24 Humidity(%):67



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2390.00	39.98	54.00	-14.02	42.73	-2.75	Average	225	95
2	2390.00	52.93	74.00	-21.07	55.68	-2.75	Peak	225	95
3	2483.50	40.20	54.00	-13.80	42.90	-2.70	Average	225	95
4	2483.50	53.05	74.00	-20.95	55.75	-2.70	Peak	225	95
5	4874.00	33.69	54.00	-20.31	29.56	4.13	Average	100	265
6	4874.00	47.01	74.00	-26.99	42.88	4.13	Peak	100	265
7	7311.00	41.12	54.00	-12.88	31.84	9.28	Average	100	45
8	7311.00	54.53	74.00	-19.47	45.25	9.28	Peak	100	45


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2437
Polarization	Vertical		

Test By :Roger Lu Temperature(°C):24 Humidity(%):67



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2390.00	37.83	54.00	-16.17	40.58	-2.75	Average	100	188
2	2390.00	51.04	74.00	-22.96	53.79	-2.75	Peak	100	188
3	2483.50	37.45	54.00	-16.55	40.15	-2.70	Average	100	188
4	2483.50	51.56	74.00	-22.44	54.26	-2.70	Peak	100	188
5	4874.00	35.99	54.00	-18.01	31.86	4.13	Average	100	357
6	4874.00	49.67	74.00	-24.33	45.54	4.13	Peak	100	357
7	7311.00	48.10	54.00	-5.90	38.82	9.28	Average	188	351
8	7311.00	63.79	74.00	-10.21	54.51	9.28	Peak	188	351


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2462
Polarization	Horizontal		

Test By :Roger Lu Temperature(°C):24 Humidity(%):67



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2483.50	42.73	54.00	-11.27	45.43	-2.70	Average	224	93
2	2483.50	64.45	74.00	-9.55	67.15	-2.70	Peak	224	93
3	4924.00	33.21	54.00	-20.79	29.15	4.06	Average	100	260
4	4924.00	45.75	74.00	-28.25	41.69	4.06	Peak	100	260
5	7386.00	39.40	54.00	-14.60	30.15	9.25	Average	100	39
6	7386.00	52.84	74.00	-21.16	43.59	9.25	Peak	100	39


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11g	Test Freq. (MHz)	2462
Polarization	Vertical		

Test By :Roger Lu Temperature(°C):24 Humidity(%):67



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2483.50	39.89	54.00	-14.11	42.59	-2.70	Average	100	188
2	2483.50	60.67	74.00	-13.33	63.37	-2.70	Peak	100	188
3	4924.00	34.32	54.00	-19.68	30.26	4.06	Average	100	354
4	4924.00	46.44	74.00	-27.56	42.38	4.06	Peak	100	354
5	7386.00	45.83	54.00	-8.17	36.58	9.25	Average	186	355
6	7386.00	61.68	74.00	-12.32	52.43	9.25	Peak	186	355

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

3.4.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT20

Modulation	HT20	Test Freq. (MHz)	2412						
Polarization	Horizontal								
Test By : Roger Lu Temperature(°C):24 Humidity(%):67									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		cm	deg
1	2390.00	45.81	54.00	-8.19	48.56	-2.75	Average	225	95
2	2390.00	61.63	74.00	-12.37	64.38	-2.75	Peak	225	95
3	4824.00	34.25	54.00	-19.75	30.11	4.14	Average	100	267
4	4824.00	47.69	74.00	-26.31	43.55	4.14	Peak	100	267
5	12060.00	43.02	54.00	-10.98	29.23	13.79	Average	100	50
6	12060.00	56.11	74.00	-17.89	42.32	13.79	Peak	100	50
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

Modulation	HT20	Test Freq. (MHz)	2412
Polarization	Vertical		

Test By :Roger Lu Temperature(°C):24 Humidity(%):67



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2390.00	41.47	54.00	-12.53	44.22	-2.75	Average	105	183
2	2390.00	57.71	74.00	-16.29	60.46	-2.75	Peak	105	183
3	4824.00	36.45	54.00	-17.55	32.31	4.14	Average	100	353
4	4824.00	50.77	74.00	-23.23	46.63	4.14	Peak	100	353
5	12060.00	43.03	54.00	-10.97	29.24	13.79	Average	100	20
6	12060.00	56.24	74.00	-17.76	42.45	13.79	Peak	100	20


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Horizontal		

Test By :Roger Lu Temperature(°C):24 Humidity(%):67



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2390.00	39.81	54.00	-14.19	42.56	-2.75	Average	222	93
2	2390.00	52.70	74.00	-21.30	55.45	-2.75	Peak	222	93
3	2483.50	40.05	54.00	-13.95	42.75	-2.70	Average	222	93
4	2483.50	52.96	74.00	-21.04	55.66	-2.70	Peak	222	93
5	4874.00	33.61	54.00	-20.39	29.48	4.13	Average	100	263
6	4874.00	46.81	74.00	-27.19	42.68	4.13	Peak	100	263
7	7311.00	40.96	54.00	-13.04	31.68	9.28	Average	100	41
8	7311.00	54.37	74.00	-19.63	45.09	9.28	Peak	100	41


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Vertical		

Test By :Roger Lu Temperature(°C):24 Humidity(%):67



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2390.00	37.65	54.00	-16.35	40.40	-2.75	Average	100	186
2	2390.00	50.81	74.00	-23.19	53.56	-2.75	Peak	100	186
3	2483.50	37.35	54.00	-16.65	40.05	-2.70	Average	100	186
4	2483.50	51.28	74.00	-22.72	53.98	-2.70	Peak	100	186
5	4874.00	35.78	54.00	-18.22	31.65	4.13	Average	100	355
6	4874.00	49.42	74.00	-24.58	45.29	4.13	Peak	100	355
7	7311.00	48.19	54.00	-5.81	38.91	9.28	Average	188	351
8	7311.00	63.52	74.00	-10.48	54.24	9.28	Peak	188	351


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Horizontal		

Test By :Roger Lu Temperature(°C):24 Humidity(%):67



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2483.50	43.16	54.00	-10.84	45.86	-2.70	Average	226	90
2	2483.50	64.78	74.00	-9.22	67.48	-2.70	Peak	226	90
3	4924.00	33.08	54.00	-20.92	29.02	4.06	Average	100	262
4	4924.00	45.65	74.00	-28.35	41.59	4.06	Peak	100	262
5	7386.00	39.50	54.00	-14.50	30.25	9.25	Average	100	42
6	7386.00	52.89	74.00	-21.11	43.64	9.25	Peak	100	42


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	2462
Polarization	Vertical		

Test By :Roger Lu Temperature(°C):24 Humidity(%):67



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2483.50	39.73	54.00	-14.27	42.43	-2.70	Average	106	187
2	2483.50	60.45	74.00	-13.55	63.15	-2.70	Peak	106	187
3	4924.00	34.17	54.00	-19.83	30.11	4.06	Average	100	355
4	4924.00	46.49	74.00	-27.51	42.43	4.06	Peak	100	355
5	7386.00	45.67	54.00	-8.33	36.42	9.25	Average	187	352
6	7386.00	61.36	74.00	-12.64	52.11	9.25	Peak	187	352

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.5 Emissions in Non-Restricted Frequency Bands

3.5.1 Emissions in Non-Restricted Frequency Bands Limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.5.2 Test Procedures


Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

Emission level measurement




1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level


3.5.3 Test Setup



3.5.4 Unwanted Emissions into Non-Restricted Frequency Bands

Ambient Condition	21°C / 67%	Tested By	Aska Huang
-------------------	------------	-----------	------------






802.11g_Nss1,(6Mbps)_1TX

2462MHz

CSE NdB


802.11n HT20_Nss1,(MCS0)_1TX
2412MHz

CSE NdB




802.11n HT20_Nss1,(MCS0)_1TX
2437MHz

CSE NdB



802.11n HT20_Nss1,(MCS0)_1TX
2462MHz

CSE NdB



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No.30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan
(R.O.C.)

Kwei Shan

Tel: 886-3-271-8666

No.3-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)
No.2-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

Kwei Shan Site II

Tel: 886-3-271-8640

No.14-1, Lane 19, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 333, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0345

Email: ICC_Service@icertifi.com.tw

==END==