

ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT

INTENTIONAL RADIATOR CERTIFICATION TO FCC PART 15 SUBPART C REQUIREMENT

0F **Product Name: Blood Pressure Monitor Brand Name:** N/A Model No.: **BP-801 Model Difference:** N/A FCC ID: XNAWPM02 **Report No.:** EF/2013/80006 **Issue Date:** Aug. 14, 2013 **FCC Rule Part:** §15.247, Cat: DTS Withings **Prepared for:** 20 rue Rouget de Lisle, Issy-les-Moulineaux, France SGS Taiwan Ltd. **Electronics & Communication Laboratory** No.134, Wu Kung Road, New Taipei Industrial **Prepared by:** Park, Wuku District, New Taipei City, Taiwan 24803



Note: This report shall not be reproduced except in full, without the written approval of SGS Taiwan Ltd. This document may be altered or revised by SGS Taiwan Ltd. personnel only, and shall be noted in the revision section of the

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

WeifS of all weights and the results and set of the formation of the set of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law SGS Taiwan Ltd.



VERIFICATION OF COMPLIANCE

Applicant:	Withings 20 rue Rouget de Lisle, Issy-les-Moulineaux, France
Product Name:	Blood Pressure Monitor
Brand Name:	N/A
Model No.:	BP-801
Model Difference:	N/A
FCC ID:	XNAWPM02
File Number:	EF/2013/80006
Date of test:	Jul. 29, 2013 ~ Aug. 09, 2013
Date of EUT Received:	Jul. 29, 2013

We hereby certify that:

The above equipment was tested by SGS Taiwan Ltd. Electronics & Communication Laboratory The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4:2009 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247.

The test results of this report relate only to the tested sample identified in this report.

Test By:	Niele	Lin	Date	Aug. 14, 2013	
	Nick Lin / I	Engineer			
Prepared By:	Judy	Hen	Date	Aug. 14, 2013	
Approved By:		/Clerk Ch ang	Date	Aug. 14, 2013	

Jim Chang / Supervisor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Version

Version No.	Date	Description
00	Aug. 14, 2013	Initial creation of document



Table of Contents

1	GEN	ERAL INFORMATION	.6
	1.1	Product Description	6
	1.2	Related Submittal(s) / Grant (s)	7
	1.3	Test Methodology	7
	1.4	Test Facility	7
	1.5	Special Accessories	
	1.6	Equipment Modifications	7
2	SYS	TEM TEST CONFIGURATION	.8
	2.1	EUT Configuration	8
	2.2	EUT Exercise	
	2.3	Test Procedure	8
	2.4	Configuration of Tested System	9
3	SUM	MARY OF TEST RESULTS1	10
4	DES	CRIPTION OF TEST MODES 1	10
5	MEA	SUREMENT UNCERTAINTY1	1
6	CON	DUCTED EMISSION TEST1	12
	6.1	Standard Applicable:	
	6.2	Measurement Equipment Used:	
	6.3	EUT Setup:	
	6.4	Test SET-UP (Block Diagram of Configuration)	
	6.5	Measurement Procedure:	
	6.6	Measurement Result:	13
7	PEA	K OUTPUT POWER MEASUREMENT1	
	7.1	Standard Applicable:	
	7.2	Measurement Equipment Used:	15
	7.3	Test Set-up:	15
	7.4	Measurement Procedure:	16
	7.5	Measurement Result:	17
8	6dB 2	BANDWIDTH1	18
	8.1	Standard Applicable:	18
	8.2	Measurement Equipment Used:	18
	8.3	Test Set-up:	18
	8.4	Measurement Procedure:	19
	8.5	Measurement Result:	19



9	BANI	D EDGES MEASUREMENT	22
	9.1	Standard Applicable:	22
	9.2	Measurement Equipment Used:	22
	9.3	Test SET-UP:	24
	9.4	Measurement Procedure:	25
	9.5	Field Strength Calculation:	26
	9.6	Measurement Result:	26
10	SPUR	RIOUS RADIATED EMISSION TEST	30
	10.1	Standard Applicable	30
	10.2	Measurement Equipment Used:	31
	10.3	Test SET-UP:	31
	10.4	Measurement Procedure:	32
	10.5	Field Strength Calculation	32
	10.6	Measurement Result:	32
11	PEAF	K POWER SPECTRAL DENSITY	
	11.1	Standard Applicable:	42
	11.2	Measurement Equipment Used:	42
	11.3	Test Set-up:	42
	11.4	Measurement Procedure: (following the measurement procedure 10.2 of KDB558074):	42
	11.5	Measurement Result:	43
12	ANTI	ENNA REQUIREMENT	46
	12.1	Standard Applicable:	
	12.2	Antenna Connected Construction:	46



GENERAL INFORMATION 1

1.1 **Product Description**

General:

Product Name:	Blood Pressure Monitor
Brand Name:	N/A
Model No.:	BP-801
Model difference:	N/A
Hardware Version:	N/A
Software Version:	N/A
Power Supply:	1.5Vdc from AAA battery*4

Bluetooth:

Frequency Range:	2402 – 2480MHz
Bluetooth Version:	V4.0 dual mode
Channel number:	40 channels
Modulation type:	GFSK
Transmit Power:	4.39dBm (Peak)
Antenna Designation:	Ceramic Antenna, 1.72dBi

This test report applies for Bluetooth function.

This report applies for Bluetooth V4.0 mode, and complies with FCC rule part 15C.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



1.2 **Related Submittal(s) / Grant (s)**

This submittal(s) (test report) is intended for FCC ID: XNAWPM02 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules. The composite system (digital device) is compliance with Subpart B is authorized under a DoC procedure.

1.3 **Test Methodology**

Both conducted and radiated testing was performed according to the procedures in ANSI C63.4:2009. Radiated testing was performed at an antenna to EUT distance 3 meters.

Tested in accordance with Apr 2013 KDB558074 D01 V03 for compliance to FCC 47CFR 15.247 requirements.

Test Facility 1.4

The measurement facilities used to collect the 3m Radiated Emission and AC power line conducted data are located on the address of SGS Taiwan Ltd. Electronics & Communication Laboratory No.134, Wu Kung Road, Wuku Industrial Zone, Taipei County, Taiwan which are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2009.. FCC Registration Number are: 990257, Canada Registration Number: 4620A-4.

The 10 m Open Area Test Sites located on the address of SGS Taiwan Ltd. Electronics & Communication Laboratory No. 29, Pau-Tou-Tsuo Valley Chia-Pau Tsuen, Linkou Hsiang, Taipei county, which is constructed and calibrated to meet the CISPR 22/EN 55022 requirements. SGS Site No. 1(3 &10 meters) and FCC Registration Number: 94644.

1.5 **Special Accessories**

There are no special accessories used while test was conducted.

Equipment Modifications 1.6

There was no modification incorporated into the EUT.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



2 SYSTEM TEST CONFIGURATION

2.1 **EUT Configuration**

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 **EUT Exercise**

An engineering test mode (software/firmware) that applicant provided was utilized to manipulate the EUT into transmit, selection of the test channel, and modulation scheme.

2.3 **Test Procedure**

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the general criterion in Section 7.1 of ANSI C63.4:2009.Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz, and the measurement procedure 7.3 in ANSI 63.4:2009 is followed to carry out the test. The CISPR Quasi-Peak and Average detector mode is employed according to §15.107

2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna. according to the requirements in Section 8 and 13 and of ANSI C63.4:2009,.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

Chino Solution and Solution a tronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is frawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law



2.4 **Configuration of Tested System**

Fig. 2-1 Radiated Emission




Fig. 2-2 Conducted (Antenna Port) Configuration




Table 2-1	Equipment	Used in	Tested	System
-----------	-----------	---------	--------	--------

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Data Cable	Power Cord
1.	Bluetooth test software	Tera Term VT	N/A	N/A	N/A	N/A
2.	Notebook	DELL	D505	20995915456	Shielded	N/A
3.	DC Power Supply	HP	E3640A	MY40005907	Shielded	N/A

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



FCC Rules	Description Of Test	Result
§15.207(a)	AC Power Line Conducted Emission	Compliant
§15.247(b) (3)	Peak Output Power	Compliant
§15.247(a)(2)	6dB Bandwidth	Compliant
§15.247(d)	100 KHz Bandwidth Of Frequency Band Edges	Compliant
§15.247(d)	Spurious Emission	Compliant
§15.247(e)	Peak Power Density	Compliant
§15.203	Antenna Requirement	Compliant

3 SUMMARY OF TEST RESULTS

DESCRIPTION OF TEST MODES 4

The EUT has been tested under operating condition.

Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low (2402MHz) v mid (2442MHz) and high (2480MHz) with BT4.0 mode is chosen for full testing.

The field strength of radiation emission was measured as EUT stand-up position (H mode) and lie down position (E1, E2 mode) for BT4.0 mode Transmitter for channel Low, Mid and High, the worst case E2 position was reported.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



5 **MEASUREMENT UNCERTAINTY**

Test Items	Uncertainty
AC Power Line Conducted Emission	+/- 2.586 dB
Peak Output Power	+/- 1.42 dB
6dB Bandwidth	+/- 123.36 Hz
100 KHz Bandwidth Of Frequency Band Edges	+/- 1.55 dB
Peak Power Density	+/- 1.55 dB
Temperature	+/- 0.8 °C
Humidity	+/- 4.7 %
DC / AC Power Source	DC= +/- 1%, AC=+/- 0.2%

Radiated Spurious Emission:

Measurement uncertainty (Polarization : Vertical)	30MHz - 180MHz: +/- 3.37dB
	180MHz -417MHz: +/- 3.19dB
	0.417GHz-1GHz: +/- 3.19dB
	1GHz - 18GHz: +/- 4.04dB
	18GHz - 40GHz: +/- 4.04dB

	30MHz - 167MHz: +/- 4.22dB
Measurement uncertainty	167MHz -500MHz: +/- 3.44dB
(Polarization : Horizontal)	0.5GHz-1GHz: +/- 3.39dB
	1GHz - 18GHz: +/- 4.08dB
	18GHz - 40GHz: +/- 4.08dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



CONDUCTED EMISSION TEST 6

6.1 **Standard Applicable:**

According to §15.207, frequency range within 150KHz to 30MHz shall not exceed the Limit table as below.

Frequency range	Limits dB(uV)					
MHz	Quasi-peak Average					
0.15 to 0.50	66 to 56	56 to 46				
0.50 to 5	56	46				
5 to 30	60	50				
Note						
1. The lower limit shall apply at the transition frequencies						
2. The limit decreases linearly with t	he logarithm of the frequency in the ra	ange 0.15 MHz to 0.50 MHz.				

Measurement Equipment Used: 6.2

Conducted Emission Test Site								
EQUIPMENT	EQUIPMENT MFR MODEL SERIAL							
TYPE		NUMBER	NUMBER	CAL.				
EMI Test Receiver	R&S	ESCI7	100759	02/08/2013	02/07/2014			
EMI Receiver	R&S	ESCS 30	828985/004	09/23/2012	09/22/2013			
LISN	Rolf-Heine	NNB-2/16Z	99012	03/23/2013	03/22/2014			
LISN	FCC	FCC-LISN-50/250-2 5-2-01	04034	03/23/2013	03/22/2014			
Coaxial Cables	N/A	WK CE Cable	N/A	01/05/2013	01/04/2014			

6.3 **EUT Setup:**


- 1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.4:2009.
- 2. The AC/DC Power adaptor of EUT was plug-in LISN. The EUT was placed flushed with the rear of the table.
- 3. The LISN was connected with 120Vac/60Hz power source.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

でいたいでは、 除非另有就明,此報告結果僅對測試之樣品負責,同時此樣品僅保留知天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for elec-tronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms</u> e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law SGS Taiwan Ltd.



6.4 Test SET-UP (Block Diagram of Configuration)



6.5 **Measurement Procedure:**

- 1. The EUT was placed on a table which is 0.8m above ground plane.
- 2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3. Repeat above procedures until all phases of power being supplied by given UE are completed

Measurement Result: 6.6

N/A. The device is powered by DC battery.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

7 PEAK OUTPUT POWER MEASUREMENT

7.1 Standard Applicable:

According to §15.247 (b)

(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and

5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



7.2 **Measurement Equipment Used:**

Conducted Emission Test Site								
EQUIPMENT	MFR	MODEL	SERIAL	LAST	CAL DUE.			
ТҮРЕ		NUMBER	NUMBER	CAL.				
Power Meter	Anritsu	ML2495A	1005007	02/08/2012	02/07/2014			
Power Sensor	Anritsu	MA2411B	917032	02/08/2012	02/07/2014			
Spectrum Analyzer	Agilent	E4446A	MY51100003	05/30/2013	05/29/2014			
Spectrum Analyzer	Agilent	E4440A	MY45304525	03/15/2013	03/14/2014			
DC Block	Mini-Circuits	BLK-18-S+	1	02/28/2013	02/27/2014			
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA	N/A	01/05/2013	01/04/2014			
Attenuator	Mini-Circuit	BW-S10W2+	002	02/28/2013	02/27/2014			
Splitter	Agilent	11636B	N/A	02/28/2013	02/27/2014			

7.3 **Test Set-up:**



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



7.4 **Measurement Procedure:**


1. Place the EUT on the table and set it in transmitting mode.

2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter or spectrum. (Peak power setting on Spectrum: Channel power function, RBW = 1MHz, VBW = 3MHz, Span: 30/60MHz, Detector =peak, Sweep = Auto. Setting on spectrum is adjusted based on the mandatory procedure in 9.1.2 of the KDB558074). Power Meter is used as the auxiliary test equipment to conduct the output power measurement. 9.1.3 in KDB558074 is followed.

(Avg. power setting on Spectrum: Channel power function, RBW = 1MHz, VBW = 3MHz, Span: 30/60MHz, Detector =Avg., Trace avg =100, Sweep = Auto, Setting on spectrum is adjusted based on the mandatory procedure in 9.2.2.4 of the KDB558074). Power Meter is used as the auxiliary test equipment to conduct the output power measurement. 9.2.3, option 3 in KDB558074 is followed.

3. Record the max. Reading as observed from Spectrum or Power Meter.

4. Repeat above procedures until all test default channel measured was complete.



Duty Factor:

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Re非另有說明,此報告結果僅對測試之樣品負責、同時此樣品僅保留90天。本報告未經本公司書面許可,不可的份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms_and_conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134 號



7.5 **Measurement Result:**

BT4.0 mode:

СН	Frequency	Peak Power Output(dBm)	Required Limit	
	(MHz)			
0	2402	1.55	1 Watt = 30 dBm	
20	2442	3.15	1 Watt = 30 dBm	
39	2480	4.39	1 Watt = 30 dBm	

СН	Frequency	Average Power Output(dBm)	Required Limit
	(MHz)		
0	2402	-0.44	1 Watt = 30 dBm
20	2442	1.16	1 Watt = 30 dBm
39	2480	2.43	1 Watt = 30 dBm

*Note: Measured by power meter, cable loss as 1dB that offsets on the power meter in Peak *Note: Measured by power meter, as cable loss+ Duty cycle factor that offsets on the power meter

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



8 **6dB BANDWIDTH**


8.1 **Standard Applicable:**

According to §15.247(a)(2), Systems using digital modulation techniques may operate in the 902 - 928 MHz,2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500kHz.

8.2 **Measurement Equipment Used:**

Conducted Emission Test Site								
EQUIPMENT	MFR	MODEL	SERIAL	LAST	CAL DUE.			
ТҮРЕ		NUMBER	NUMBER	CAL.				
Power Meter	Anritsu	ML2495A	1005007	02/08/2012	02/07/2014			
Power Sensor	Anritsu	MA2411B	917032	02/08/2012	02/07/2014			
Spectrum Analyzer	Agilent	E4446A	MY51100003	05/30/2013	05/29/2014			
Spectrum Analyzer	Agilent	E4440A	MY45304525	03/15/2013	03/14/2014			
DC Block	Mini-Circuits	BLK-18-S+	1	02/28/2013	02/27/2014			
Low Loss Cable	HUBER+SUHNER	SUCOFLEX 104PEA	N/A	01/05/2013	01/04/2014			
Attenuator	Mini-Circuit	BW-S10W2+	002	02/28/2013	02/27/2014			
Splitter	Agilent	11636B	N/A	02/28/2013	02/27/2014			

Test Set-up: 8.3



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



8.4 **Measurement Procedure:**

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as RBW = 100 kHz, VBW = 3*RBW, Span = 5MHz, Detector=Peak, Sweep=auto, the setting on spectrum is adjusted based on the procedure as guide in 8.1 option 1 of KDB558074.
- 4. Mark the peak frequency and –6dB (upper and lower) frequency.
- 5. Repeat above procedures until all test default channel measured were complete.

8.5 **Measurement Result:**

Frequency (MHz)			Result
2402	678.735	> 500	PASS
2442	675.923	> 500	PASS
2480	686.616	> 500	PASS

BT4.0 mode

* Cable loss as 1dB that offsets on the spectrum.


* Note: The arrow "->" reveals X decibel level

Note: Refer to next page for plots.


Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



BT4.0 mode 6dB Band Width Test Data CH-Low




6dB Band Width Test Data CH-Mid



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



6dB Band Width Test Data CH-High



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



9 **BAND EDGES MEASUREMENT**

9.1 **Standard Applicable:**

According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in15.209(a).

9.2 **Measurement Equipment Used:**

9.2.1 **Conducted Emission at antenna port:**

Refer to section 7.2 for details.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




9.2.2 Radiated emission:

966 Chamber								
EQUIPMENT	MFR	MODEL	SERIAL	LAST	CAL DUE.			
ТҮРЕ		NUMBER	NUMBER	CAL.				
EMI Test Receiver	R&S	ESCI7	100759	02/08/2013	02/07/2014			
Spectrum Analyzer	Agilent	E4446A	MY51100003	05/30/2013	05/29/2014			
EXA Spectrum Analyzer	Agilent	N9010A	MY50420195	02/06/2013	02/07/2014			
Spectrum Analyzer	R&S	FSV-30	101398	10/18/2011	10/17/2013			
Bilog Antenna	SCHWAZBECK	VULB9168	378	01/10/2012	01/09/2014			
Horn antenna	ETS.LINDGREN	3117	123995	05/31/2013	05/30/2014			
Horn Antenna	Schwarzbeck	BBHA9170	184	01/17/2012	01/16/2014			
Pre-Amplifier	Agilent	8447D	2944A07676	01/04/2013	01/03/2014			
Pre-Amplifier	EMC Instruments Corp.	EMC0126530	980038	01/04/2013	01/03/2014			
Filter 2400-2483.5 MHz	EWT	EWT-14-0166	M2	02/28/2013	02/28/2014			
Attenuator	Mini-Circuit	BW-S10W2+	004	02/28/2013	02/27/2014			
Turn Table	HD	DT420	N/A	N.C.R	N.C.R			
Antenna Tower	HD	MA240-N	240/657	N.C.R	N.C.R			
Controller	HD	HD100	N/A	N.C.R	N.C.R			
Low Loss Cable	Huber Suhner	966_Rx	9	01/04/2013	01/03/2014			
3m Site NSA	SGS	966 chamber	N/A	07/15/2013	07/14/2014			




9.3 **Test SET-UP:**

9.3.1 **Conducted Emission at antenna port:**




9.3.2 Radiated emission:

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



9.4 Measurement Procedure:

Unwanted Emissions into Non-Restricted Frequency Bands, Measurement Procedure followed by 11.1 of KDB558074 D01

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set start to edge frequency, and stop frequency of spectrum analyzer so as to encompass the spectrum to be examined.
- 4. Set the spectrum analyzer as RBW, VBW=300KHz, Detector = Peak, Sweep = auto
- 5. Mark the highest reading of the emission as the reference level measurement.
- 6. Set DL as the limit = reading on marker 1 20dBm
- 7. Marker on frequency, 2.3999GHz and 2.4836GHz, and examine shall 100 KHz immediately outside the authorized (2400~2483.5) be attenuated by 20dB at least relative to the maximum emission of power.
- 8. Repeat above procedures until all default test channel (low, middle, and high) was complete.

Unwanted Emission falling into Restricted Frequency Bands, Measurement Procedure followed by 11.1 of KDB558074:

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
- 3.EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
- 4. When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna.
- 5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 6. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 7.On spectrum, following 8.1.2, and RBW = 1MHz, VBW = 3MHz, & Marker 2390MHz, and 2483.5MHz (Peak Measurement). Average Measurement: following 8.2 with the modification span to 1MHz, &RBW = 1MHz, VBW = 3MHz and peak marker function to obtain the highest reading on 2390, and 2483.5MHz.

Repeat above procedures until all default test channel (low, middle, and high) was complete

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



9.5 **Field Strength Calculation:**

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

9.6 **Measurement Result:**


Note: Refer to next page spectrum analyzer data chart and tabular data sheets.


Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



BT4.0 mode **Band Edges Test Data CH-Low**







Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Report No.: EF/2013/80006 **Issue Date: Aug. 14, 2013** Page: 28 of 46

Radiated Emission: BT4.0 mode:

Operation Band Fundamental Frequency	:BT4.0 :2402 MHz	Test Date Temp./Humi.	:2013-08-01 :26 deg_C / 60 RH
Operation Mode	:Bandedge LOW	Engineer	:Allen
EUT Pol.	:E2 Plan	Measurement Antenna Pol.	:VERTICAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

 $Factor(dB) = Antenna Factor(dB\mu V/m) + Cable Loss(dB) - Pre_Amplifier Gain(dB)$

"F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency. Note :

"E": denotes Band Edge Frequency.; "S": denotes Spurious Frequency.

"---": denotes Noise Floor.

The trace on RE(radiation emission) plot is as colored blue, and the detection manner we've employed is peak detector.

Freq.	Note	Detector	Spectrum	Factor	Actual	Limit	Margin
		Mode	Reading Level		FS	@3m	
MHz	F/H/E/S	PK/QP/AV	dBμV	dB	dBµV/m	dBµV/m	dB
2390.00	Е	Average	30.37	2.51	32.88	54.00	-21.12
2390.00	Е	Peak	42.94	2.51	45.45	74.00	-28.55

Operation Band	:BT4.0	Test Date	:2013-08-01
Fundamental Frequency	:2402 MHz	Temp./Humi.	:26 deg_C / 60 RH
Operation Mode	:Bandedge LOW	Engineer	:Allen
EUT Pol.	:E2 Plan	Measurement Antenna Pol.	:HORIZONTAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

 $Factor(dB) = Antenna Factor(dB\mu V/m) + Cable Loss(dB) - Pre_Amplifier Gain(dB)$

"F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency. Note :

"E" : denotes Band Edge Frequency. ; "S" : denotes Spurious Frequency.

"---": denotes Noise Floor.

The trace on RE(radiation emission) plot is as colored blue, and the detection manner we've employed is peak detector.

Freq.	Note	Detector	Spectrum	Factor	Actual	Limit	Margin
		Mode	Reading Level		FS	@3m	
MHz	F/H/E/S	PK/QP/AV	dBμV	dB	dBµV/m	dBµV/m	dB
2390.00	S	Average	30.42	3.13	33.55	54.00	-20.45
2390.00	S	Peak	43.39	3.13	46.52	74.00	-27.48

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Report No.: EF/2013/80006 **Issue Date: Aug. 14, 2013** Page: 29 of 46

Operation Band	:BT4.0	Test Date	:2013-08-01
Fundamental Frequency	:2480 MHz	Temp./Humi.	:26 deg_C / 60 RH
Operation Mode	:Bandedge HIGH	Engineer	:Allen
EUT Pol.	:E2 Plan	Measurement Antenna Pol.	:VERTICAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

 $Factor(dB) = Antenna Factor(dB\mu V/m) + Cable Loss(dB) - Pre_Amplifier Gain(dB)$

Note : "F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency.

"E": denotes Band Edge Frequency.; "S": denotes Spurious Frequency.

"---": denotes Noise Floor.

The trace on RE(radiation emission) plot is as colored blue, and the detection manner we've employed is peak detector.

Freq.	Note	Detector	Spectrum	Factor	Actual	Limit	Margin
		Mode	Reading Level		FS	@3m	
MHz	F/H/E/S	PK/QP/AV	dBμV	dB	dBµV/m	dBµV/m	dB
2483.50	Е	Average	30.09	2.87	32.96	54.00	-21.04
2483.50	Е	Peak	43.97	2.87	46.84	74.00	-27.16

Operation Band	:BT4.0	Test Date	:2013-08-01
Fundamental Frequency	:2480 MHz	Temp./Humi.	:26 deg_C / 60 RH
Operation Mode	:Bandedge HIGH	Engineer	:Allen
EUT Pol.	:E2 Plan	Measurement Antenna Pol.	:HORIZONTAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

 $Factor(dB) = Antenna Factor(dB\mu V/m) + Cable Loss(dB) - Pre_Amplifier Gain(dB)$

"F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency. Note :

"E": denotes Band Edge Frequency.; "S": denotes Spurious Frequency.

"---": denotes Noise Floor.

The trace on RE(radiation emission) plot is as colored blue, and the detection manner we've employed is peak detector.

Freq.	Note	Detector	Spectrum	Factor	Actual	Limit	Margin
		Mode	Reading Level		FS	@3m	
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
2483.50	E	Average	30.15	3.90	34.05	54.00	-19.95
2483.50	E	Peak	44.80	3.90	48.70	74.00	-25.30

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



10 SPURIOUS RADIATED EMISSION TEST 10.1 Standard Applicable

According to §15.247(d),

Emission at antenna port:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Radiated Spurious Emission

Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

And according to §15.33(a) (1), for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



10.2 Measurement Equipment Used:

10.2.1 Conducted Emission at antenna port:

Refer to section 7.2 for details.

10.2.2 Radiated emission:

Refer to section 9.2.2 for details.

10.3 Test SET-UP:

10.3.1 Conducted Emission at antenna port:

Refer to section 8.3 for details.

10.3.2 Radiated emission:

Refer to section 9.3.2 for details.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



10.4 Measurement Procedure:

Radiated Emission:

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
- 4. When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna.
- 5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 6. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. On spectrum, change spectrum mode in linear display mode, and reduce VBW = 10Hz if average reading is measured.
- 7. Repeat above procedures until all default test channel measured were complete.

Conducted Emission:

- 1. To connect Antenna Port of EUT to Spectrum.
- 2. Set RBW = 100K & VBW = 300K on Spectrum.
- Sweep the frequency to determine spurious emission as seen on spectrum from span of 30 to 3G, 3G to 8G, 8G to 13G, 13G to 18G and 18G to 26.5GHz, 18G to 40GHz (applicable if operation mode is 5GHz)
- 4. Via Software, combine 5 spans of frequency range into one plot
- 5. Repeat above procedures until all default test channel measured were complete.

10.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

10.6 Measurement Result:


Note: Refer to next page spectrum analyzer data chart and tabular data sheets.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。


This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sqs.com/terms and conditions.htm</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sqs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is advised to the fullest extent of the law. SGS Taiwan Ltd. No.134, WuKungRoad, NewTaipeilndustrialPark, WukuDistrict, NewTaipeiCity, Taiwan 24803/新北市五股區新北產業園區五工路 134 號






Conducted Spurious Emission Measurement Result (BT4.0 mode) Ch Low 30MHz – 3GHz






Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Ch Mid 30MHz - 3GHz




Ch Mid 3GHz – 26.5GHz




Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Ch High 30MHz – 3GHz



Ch High 3GHz – 26.5GHz



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Radiated Spurious Emission Measurement Result (BT4.0 mode)

Operation Band	:BT4.0	Test Date	:2013-08-03
Fundamental Frequency	:2402 MHz	Temp./Humi.	:26 deg_C / 60 RH
Operation Mode	:TX LOW	Engineer	:Allen
EUT Pol.	:E2 Plan	Measurement Antenna Pol.	:VERTICAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

 $Factor(dB) = Antenna Factor(dB\mu V/m) + Cable Loss(dB) - Pre_Amplifier Gain(dB)$

Note : "F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency.

"E": denotes Band Edge Frequency.; "S": denotes Spurious Frequency.

"---": denotes Noise Floor.

Freq.	Note	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
	1,11,1,0	111.21/111	012 pt 1			<i>az p + j ===</i>	ub
144.46	S	Peak	31.11	-12.42	18.69	43.50	-24.81
239.52	S	Peak	33.58	-14.02	19.56	46.00	-26.44
335.55	S	Peak	34.77	-11.64	23.13	46.00	-22.87
448.07	S	Peak	28.43	-9.56	18.87	46.00	-27.13
760.41	S	Peak	27.71	-4.08	23.63	46.00	-22.37
898.15	S	Peak	27.35	-2.51	24.84	46.00	-21.16
4804.00	Н	Average	43.71	7.24	50.95	54.00	-3.05
4804.00	Н	Peak	52.83	7.24	60.07	74.00	-13.93
7206.00	Н						
9608.00	Н						
12010.00	Н						
14412.00	Н						
16814.00	Н						
19216.00	Н						
21618.00	Н						
24020.00	Н						

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Report No.: EF/2013/80006 **Issue Date: Aug. 14, 2013** Page: 37 of 46

Operation Band	:BT4.0	Test Date	:2013-08-03
Fundamental Frequency	:2402 MHz	Temp./Humi.	:26 deg_C / 60 RH
Operation Mode	:TX LOW	Engineer	:Allen
EUT Pol.	:E2 Plan	Measurement Antenna Pol.	:HORIZONTAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

 $Factor(dB) = Antenna Factor(dB\mu V/m) + Cable Loss(dB) - Pre_Amplifier Gain(dB)$

"F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency. Note :

"E": denotes Band Edge Frequency.; "S": denotes Spurious Frequency.

"---": denotes Noise Floor.

Freq.	Note	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
WIIIZ	1/11/12/0		ασμγ	uD	<i>abµ ()</i> III	αυμ γ π	uD
95.96	S	Peak	34.55	-16.89	17.66	43.50	-25.84
288.02	S	Peak	36.36	-12.60	23.76	46.00	-22.24
336.52	S	Peak	34.70	-11.62	23.08	46.00	-22.92
431.58	S	Peak	35.31	-9.95	25.36	46.00	-20.64
766.23	S	Peak	28.95	-4.01	24.94	46.00	-21.06
903.00	S	Peak	32.05	-2.42	29.63	46.00	-16.37
4804.00	Н	Average	39.24	7.28	46.52	54.00	-7.48
4804.00	Н	Peak	45.45	7.28	52.73	74.00	-21.27
7206.00	Н						
9608.00	Н						
12010.00	Н						
14412.00	Н						
16814.00	Н						
19216.00	Н						
21618.00	Н						
24020.00	Н						

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Report No.: EF/2013/80006 **Issue Date: Aug. 14, 2013** Page: 38 of 46

Operation Band	:BT4.0	Test Date	:2013-08-03
Fundamental Frequency	:2442 MHz	Temp./Humi.	:26 deg_C / 60 RH
Operation Mode	:TX MID	Engineer	:Allen
EUT Pol.	:E2 Plan	Measurement Antenna Pol.	:VERTICAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

 $Factor(dB) = Antenna Factor(dB\mu V/m) + Cable Loss(dB) - Pre_Amplifier Gain(dB)$

"F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency. Note :

"E": denotes Band Edge Frequency.; "S": denotes Spurious Frequency.

"---": denotes Noise Floor.

24420.00

Η

Note	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
F/H/E/S		0	dB			dB
					· ·	
S	Peak	33.37	-14.15	19.22	40.00	-20.78
S	Peak	35.06	-16.61	18.45	43.50	-25.05
S	Peak	34.90	-11.64	23.26	46.00	-22.74
S	Peak	31.39	-9.95	21.44	46.00	-24.56
S	Peak	27.42	-3.89	23.53	46.00	-22.47
S	Peak	27.62	-2.41	25.21	46.00	-20.79
Н	Average	42.91	7.50	50.41	54.00	-3.59
Н	Peak	52.26	7.50	59.76	74.00	-14.24
Н						
Н	Average	33.16	13.56	46.72	54.00	-7.28
Н	Peak	47.23	13.56	60.79	74.00	-13.21
Н						
Н						
Н						
Н						
Н						
	F/H/E/S S S S S H H H H H H H H H H H H	Mode F/H/E/S Mode F/H/E/S PK/QP/AV S Peak A Peak B Peak A Peak H Peak <t< td=""><td>Mode Reading Level F/H/E/S PK/QP/AV dBµV S Peak 33.37 S Peak 35.06 S Peak 34.90 S Peak 31.39 S Peak 27.42 S Peak 27.42 S Peak 27.62 H Average 42.91 H Peak 52.26 H 1 H Peak 47.23 H 1 H 1 H 1 H 1 H 1 H 1 H 1 H 1 H 1 H 1 H 1 H 1 H</td><td>Mode Reading Level F/H/E/S PK/QP/AV dBµV dB S Peak 33.37 -14.15 S Peak 35.06 -16.61 S Peak 34.90 -11.64 S Peak 31.39 -9.95 S Peak 27.42 -3.89 S Peak 27.62 -2.41 H Average 42.91 7.50 H Peak 52.26 7.50 H Peak 47.23 13.56 H Peak</td><td>Mode Reading Level FS F/H/E/S PK/QP/AV dBµV dB dBµV/m S Peak 33.37 -14.15 19.22 S Peak 35.06 -16.61 18.45 S Peak 34.90 -11.64 23.26 S Peak 31.39 -9.95 21.44 S Peak 27.42 -3.89 23.53 S Peak 27.62 -2.41 25.21 H Average 42.91 7.50 50.41 H Peak 52.26 7.50 59.76 H H Average 33.16 13.56 60.79 H H H </td><td>ModeReading LevelFS@3mFH/E/SPK/QP/AV$dB\mu V$$dB$$dB\mu V/m$$dB\mu V/m$SPeak$33.37$$-14.15$$19.22$$40.00$SPeak$35.06$$-16.61$$18.45$$43.50$SPeak$34.90$$-11.64$$23.26$$46.00$SPeak$31.39$$-9.95$$21.44$$46.00$SPeak$27.42$$-3.89$$23.53$$46.00$SPeak$27.62$$-2.41$$25.21$$46.00$HAverage$42.91$$7.50$$50.41$$54.00$HPeak$52.26$$7.50$$59.76$$74.00$HPeak$47.23$$13.56$$46.72$$54.00$H$$$$$$$$$$$$H$$$$$$$$$$$$H$$$$$$$$$$H$$$$$$$$$$H$$$$$$$$$$H$$$$$$$$$$H$$$$$$$$$$H$$$$$$$$$$H$$$$$$$$H$$$$$$$$H$$$$$$$$H$$<td< td=""></td<></td></t<>	Mode Reading Level F/H/E/S PK/QP/AV dBµV S Peak 33.37 S Peak 35.06 S Peak 34.90 S Peak 31.39 S Peak 27.42 S Peak 27.42 S Peak 27.62 H Average 42.91 H Peak 52.26 H 1 H Peak 47.23 H 1 H 1 H 1 H 1 H 1 H 1 H 1 H 1 H 1 H 1 H 1 H 1 H	Mode Reading Level F/H/E/S PK/QP/AV dBµV dB S Peak 33.37 -14.15 S Peak 35.06 -16.61 S Peak 34.90 -11.64 S Peak 31.39 -9.95 S Peak 27.42 -3.89 S Peak 27.62 -2.41 H Average 42.91 7.50 H Peak 52.26 7.50 H Peak 47.23 13.56 H Peak	Mode Reading Level FS F/H/E/S PK/QP/AV dBµV dB dBµV/m S Peak 33.37 -14.15 19.22 S Peak 35.06 -16.61 18.45 S Peak 34.90 -11.64 23.26 S Peak 31.39 -9.95 21.44 S Peak 27.42 -3.89 23.53 S Peak 27.62 -2.41 25.21 H Average 42.91 7.50 50.41 H Peak 52.26 7.50 59.76 H H Average 33.16 13.56 60.79 H H H	ModeReading LevelFS@3mFH/E/SPK/QP/AV $dB\mu V$ dB $dB\mu V/m$ $dB\mu V/m$ SPeak 33.37 -14.15 19.22 40.00 SPeak 35.06 -16.61 18.45 43.50 SPeak 34.90 -11.64 23.26 46.00 SPeak 31.39 -9.95 21.44 46.00 SPeak 27.42 -3.89 23.53 46.00 SPeak 27.62 -2.41 25.21 46.00 HAverage 42.91 7.50 50.41 54.00 HPeak 52.26 7.50 59.76 74.00 HPeak 47.23 13.56 46.72 54.00 H $$ $$ $$ $$ $$ $$ H $$ $$ $$ $$ $$ $$ H $$ <td< td=""></td<>

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Report No.: EF/2013/80006 **Issue Date: Aug. 14, 2013** Page: 39 of 46

Operation Band	:BT4.0	Test Date	:2013-08-03
Fundamental Frequency	:2442 MHz	Temp./Humi.	:26 deg_C / 60 RH
Operation Mode	:TX MID	Engineer	:Allen
EUT Pol.	:E2 Plan	Measurement Antenna Pol.	:HORIZONTAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

 $Factor(dB) = Antenna Factor(dB\mu V/m) + Cable Loss(dB) - Pre_Amplifier Gain(dB)$

"F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency. Note :

"E": denotes Band Edge Frequency.; "S": denotes Spurious Frequency.

"---": denotes Noise Floor.

21978.00

24420.00

Η

Η

Freq.	Note	Detector	Spectrum	Factor	Actual	Limit	Margin
		Mode	Reading Level		FS	@3m	
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
95.96	S	Peak	34.54	-16.89	17.65	43.50	-25.85
144.46	S	Peak	32.43	-12.42	20.01	43.50	-23.49
288.02	S	Peak	36.10	-12.60	23.50	46.00	-22.50
431.58	S	Peak	35.67	-9.95	25.72	46.00	-20.28
724.52	S	Peak	29.77	-4.50	25.27	46.00	-20.73
903.97	S	Peak	28.43	-2.41	26.02	46.00	-19.98
4884.00	Н	Average	39.26	7.44	46.70	54.00	-7.30
4884.00	Н	Peak	43.68	7.44	51.12	74.00	-22.88
7326.00	Н						
9768.00	Н	Average	30.28	13.48	43.76	54.00	-10.24
9768.00	Н	Peak	43.73	13.48	57.21	74.00	-16.79
12210.00	Н	Average	33.65	18.66	52.31	54.00	-1.69
12210.00	Н	Peak	47.51	18.66	66.17	74.00	-7.83
14652.00	Н						
17094.00	Н						
19536.00	Н						

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Report No.: EF/2013/80006 **Issue Date: Aug. 14, 2013** Page: 40 of 46

Operation Band	:BT4.0	Test Date	:2013-08-03
Fundamental Frequency	:2480 MHz	Temp./Humi.	:26 deg_C / 60 RH
Operation Mode	:TX HIGH	Engineer	:Allen
EUT Pol.	:E2 Plan	Measurement Antenna Pol.	:VERTICAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

 $Factor(dB) = Antenna Factor(dB\mu V/m) + Cable Loss(dB) - Pre_Amplifier Gain(dB)$

"F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency. Note :

"E": denotes Band Edge Frequency.; "S": denotes Spurious Frequency.

"---": denotes Noise Floor.

Freq.	Note	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
71.71	S	Peak	33.49	-16.50	16.99	40.00	-23.01
240.49	S	Peak	31.37	-13.99	17.38	46.00	-28.62
335.55	S	Peak	34.91	-11.64	23.27	46.00	-22.73
431.58	S	Peak	31.51	-9.95	21.56	46.00	-24.44
743.92	S	Peak	28.96	-4.26	24.70	46.00	-21.30
921.43	S	Peak	28.24	-2.10	26.14	46.00	-19.86
4960.00	Н	Average	42.01	7.64	49.65	54.00	-4.35
4960.00	Н	Peak	50.85	7.64	58.49	74.00	-15.51
7440.00	Н						
9920.00	Н	Average	38.38	14.03	52.41	54.00	-1.59
9920.00	Н	Peak	52.97	14.03	67.00	74.00	-7.00
12400.00	Н						
14880.00	Н						
17360.00	Н						
19840.00	Н						
22320.00	Н						
24800.00	Н						

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Report No.: EF/2013/80006 **Issue Date: Aug. 14, 2013** Page: 41 of 46

Operation Band	:BT4.0	Test Date	:2013-08-03
Fundamental Frequency	:2480 MHz	Temp./Humi.	:26 deg_C / 60 RH
Operation Mode	:TX HIGH	Engineer	:Allen
EUT Pol.	:E2 Plan	Measurement Antenna Pol.	:HORIZONTAL

Actual FS($dB\mu V/m$) = SPA. Reading level($dB\mu V$) + Factor(dB)

 $Factor(dB) = Antenna Factor(dB\mu V/m) + Cable Loss(dB) - Pre_Amplifier Gain(dB)$

"F" : denotes Fundamental Frequency. ; "H" : denotes Harmonic Frequency. Note :

"E": denotes Band Edge Frequency.; "S": denotes Spurious Frequency.

"---": denotes Noise Floor.

24800.00

Η

Freq.	Note	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MII-	E/II/E/C		0	٦Ŀ			JD
MHz	F/H/E/S	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
43.58	S	Peak	27.66	-13.59	14.07	40.00	-25.93
288.02	S	Peak	36.06	-12.60	23.46	46.00	-22.54
386.96	S	Peak	30.44	-10.92	19.52	46.00	-26.48
561.56	S	Peak	28.31	-7.58	20.73	46.00	-25.27
739.07	S	Peak	28.92	-4.33	24.59	46.00	-21.41
912.70	S	Peak	27.48	-2.25	25.23	46.00	-20.77
4960.00	Н	Average	38.25	7.49	45.74	54.00	-8.26
4960.00	Н	Peak	43.94	7.49	51.43	74.00	-22.57
7440.00	Н						
9920.00	Н	Average	37.16	14.06	51.22	54.00	-2.78
9920.00	Н	Peak	51.46	14.06	65.52	74.00	-8.48
12400.00	Н						
14880.00	Н						
17360.00	Н						
19840.00	Н						
22320.00	Н						

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

11 PEAK POWER SPECTRAL DENSITY

11.1 Standard Applicable:

According to \$15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

11.2 Measurement Equipment Used:

Refer to section 7.2 for details.

11.3 Test Set-up:

Refer to section 8.3 for details.

11.4 Measurement Procedure: (following the measurement procedure 10.2 of KDB558074):

- 1. Set analyzer center frequency to DTS channel center frequency.
- 2. Set the span to 1.5 times the DTS channel bandwidth.
- 3. Set the RBW \geq 3 kHz.
- 4. Set the VBW \geq 3 x RBW.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



11.5 Measurement Result:

BT4.0 mode

Frequency	RF Power Density	Maximum Limit	Result
MHz	Reading (dBm)	(dBm)	
2402	-6.18	8	PASS
2442	-4.71	8	PASS
2480	-2.94	8	PASS

NOTE: cable loss as 1dB that offsets in the spectrum

Note: Refer to next page for plots.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測试之樣品負責,同時此樣品僅保留別天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for elec-tronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Inis document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or ap-pearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. SCET taken I to I and Wink unaPrad NewTainel/astr MukruPistrict NewTainel/City Taiwan2/4803/% th TAT SEG & th A SEG & TAT 31.24 &

SGS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134號



Report No.: EF/2013/80006 **Issue Date: Aug. 14, 2013** Page: 44 of 46

BT4.0 mode **Power Spectral Density Test Plot (CH-Low)**




Power Spectral Density Test Plot (CH-Mid)



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Power Spectral Density Test Plot (CH-High)



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Unless otherwise stated the results shown in this test report feiter only to the sample(s) tested and such sample(s) are relatined to so days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>www.sgs.com/terms and conditions.htm</u> and, for elec-tronic format documents, subject to Terms and Conditions for Electronic Documents at <u>www.sgs.com/terms e-document.htm</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

GS Taiwan Ltd. No.134,WuKungRoad,NewTaipeiIndustrialPark,WukuDistrict,NewTaipeiCity,Taiwan24803/新北市五股區新北產業園區五工路 134號

12 ANTENNA REQUIREMENT

12.1 Standard Applicable:

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than furnished by the responsible party shall be used with the device.

12.2 Antenna Connected Construction:

The directional gains of antenna used for transmitting is 1.72dBi, and the antenna connector is designed with unique type RF connector and no consideration of replacement. Please see EUT photo and antenna spec. for details.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.