

FCC Test Report

FCC ID : XNAWPM06
Equipment : Withings BPM Connect Pro
Model No. : WPM06
Brand Name : Withings
Applicant : Withings SA
Address : 2 rue Maurice Hartmann
92130 Issy-Les-Moulineaux
France
Standard : 47 CFR FCC Part 15.247
Received Date : Mar. 31, 2021
Tested Date : Apr. 19 ~ Apr. 27, 2021

We, International Certification Corporation, would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:



Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	8
1.3	Test Setup Chart	8
1.4	The Equipment List	9
1.5	Test Standards	10
1.6	Reference Guidance	10
1.7	Deviation from Test Standard and Measurement Procedure.....	10
1.8	Measurement Uncertainty	10
2	TEST CONFIGURATION.....	11
2.1	Testing Facility	11
2.2	The Worst Test Modes and Channel Details	11
3	TRANSMITTER TEST RESULTS	12
3.1	Conducted Emissions.....	12
3.2	Unwanted Emissions into Restricted Frequency Bands	15
3.3	Unwanted Emissions into Non-Restricted Frequency Bands	34
3.4	Conducted Output Power	42
3.5	Number of Hopping Frequency	45
3.6	20dB and Occupied Bandwidth.....	49
3.7	Channel Separation.....	56
3.8	Number of Dwell Time.....	63
4	TEST LABORATORY INFORMATION	68

Release Record

Report No.	Version	Description	Issued Date
FR133101AD	Rev. 01	Initial issue	May 11, 2021

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.796MHz 28.30 (Margin -17.70dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 31.26MHz 31.86 (Margin -8.14dB) - PK	Pass
15.247(d)	Band Edge	Meet the requirement of limit	Pass
15.247(b)(1)	Conducted Output Power	Power [dBm]: -1.22	Pass
15.247(a)(1)(iii)	Number of Hopping Channels	Meet the requirement of limit	Pass
15.247(a)(1)	Hopping Channel Separation	Meet the requirement of limit	Pass
15.247(a)(1)(iii)	Dwell Time	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number	Data Rate
2400-2483.5	BR	2402-2480	0-78 [79]	1 Mbps
2400-2483.5	EDR	2402-2480	0-78 [79]	2 Mbps
2400-2483.5	EDR	2402-2480	0-78 [79]	3 Mbps

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.
 Note 2: Bluetooth BR uses a GFSK.
 Note 3: Bluetooth EDR uses a combination of $\pi/4$ -DQPSK and 8DPSK.

1.1.2 Antenna Details

Ant. No.	Brand / Model	Type	Connector	Gain (dBi)
1	Brand: BROADCOM Model: BCM9Fractal	PCB	NA	2.8

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	From battery Brand: CEL ; Model: 652265, 1000mAh, 3.7V
--------------------------	---

1.1.4 Accessories

Accessories		
No.	Equipment	Description
1	USB cable	0.58m non-shielded without core

1.1.5 Test Sample Information

MAC Number of Test Sample	Radiated Emission: 0024E4C52360 AC Power Line Conducted Emission: 0024E4C52360 Antenna Port Conducted: 0024E4D3E8BD
----------------------------------	---

1.1.6 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	---	---

1.1.7 Test Tool and Duty Cycle

Test Tool	Tera Term+CMW270, V4.74	
Modulation Mode	Duty Cycle Of Test Signal (%)	Duty Factor (dB)
DH5	78.76%	1.04
2DH5	79.15%	1.02
3DH5	77.69%	1.10

1.1.8 Power Index of Test Tool



Modulation Mode	Test Frequency (MHz)		
	2402	2441	2480
GFSK/1Mbps	Default	Default	Default
$\pi/4$ -DQPSK /2Mbps	Default	Default	Default
8DPSK/3Mbps	Default	Default	Default

1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Remarks
1	Notebook	DELL	Latitude E5470	DoC	---
2	Fixture	---	---	---	Provided by applicant.

Note: The support notebook and fixture were disconnected from EUT and were removed from test table after sending command from support notebook to control EUT to transmit continuously.

1.3 Test Setup Chart



1.4 The Equipment List

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Tested Date	Apr. 27, 2021				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101658	Feb. 08, 2021	Feb. 07, 2022
LISN	R&S	ENV216	101579	Mar. 17, 2021	Mar. 16, 2022
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Dec. 29, 2020	Dec. 28, 2021
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Oct. 21, 2020	Oct. 20, 2021
50 ohm terminal (Support Unit)	NA	50	04	Jun. 05, 2020	Jun. 04, 2021
Measurement Software	AUDIX	e3	6.120210k	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Tested Date	Apr. 19 ~ Apr. 20, 2021				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101657	Mar. 12, 2021	Mar. 11, 2022
Spectrum Analyzer	R&S	FSV40	101498	Dec. 04, 2020	Dec. 03, 2021
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 17, 2020	Nov. 16, 2021
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 10, 2020	Jul. 09, 2021
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 11, 2020	Dec. 10, 2021
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 06, 2020	Nov. 05, 2021
Preamplifier	EMC	EMC02325	980225	Jul. 03, 2020	Jul. 02, 2021
Preamplifier	Agilent	83017A	MY39501308	Sep. 26, 2020	Sep. 25, 2021
Preamplifier	EMC	EMC184045B	980192	Jul. 21, 2020	Jul. 20, 2021
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 06, 2020	Oct. 05, 2021
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 06, 2020	Oct. 05, 2021
LF cable 11M	EMC	EMCCFD400-NW-N W-11000	200801	Oct. 06, 2020	Oct. 05, 2021
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	160502	Oct. 06, 2020	Oct. 05, 2021
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Oct. 06, 2020	Oct. 05, 2021
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Oct. 06, 2020	Oct. 05, 2021
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Apr. 27, 2021				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Apr. 30, 2020	Apr. 29, 2021
Power Meter	Anritsu	ML2495A	1241002	Nov. 04, 2020	Nov. 03, 2021
Power Sensor	Anritsu	MA2411B	1207366	Nov. 04, 2020	Nov. 03, 2021
Wireless connectivity tester	R&S	CMW270	100856	Nov. 02, 2020	Nov. 01, 2021
Measurement Software	--	SENSE-15247_FS	V5.10.7.11	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

47 CFR FCC Part 15.247
ANSI C63.10-2013

1.6 Reference Guidance

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

1.7 Deviation from Test Standard and Measurement Procedure

None

1.8 Measurement Uncertainty

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	±34.130 Hz
Conducted power	±0.808 dB
Power density	±0.583 dB
Conducted emission	±2.715 dB
AC conducted emission	±2.92 dB
Radiated emission ≤ 1GHz	±3.41 dB
Radiated emission > 1GHz	±4.59 dB
Time	±0.1%

2 Test Configuration

2.1 Testing Facility

Test Laboratory	International Certification Corporation
Test Site	CO01-WS, 03CH01-WS, TH01-WS
Address of Test Site	No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Dist., Tao Yuan City 33381, Taiwan (R.O.C.)

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- ISED#: 10807A
- CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate (Mbps)	Test Configuration
Conducted Emissions	GFSK	2402	1Mbps	2
Radiated Emissions ≤ 1GHz	GFSK	2402	1Mbps	1, 2
Radiated Emissions > 1GHz	GFSK	2402, 2441, 2480	1Mbps	1
	8DPSK	2402, 2441, 2480	3Mbps	
Conducted Output Power	GFSK	2402, 2441, 2480	1Mbps	1
	π/4 DQPSK	2402, 2441, 2480	2Mbps	
	8DPSK	2402, 2441, 2480	3Mbps	
Number of Hopping Channels	GFSK	2402~2480	1Mbps	1
	π/4 DQPSK	2402~2480	2Mbps	
	8DPSK	2402~2480	3Mbps	
Hopping Channel Separation 20dB and Occupied bandwidth	GFSK	2402, 2441, 2480	1Mbps	1
	π/4 DQPSK	2402, 2441, 2480	2Mbps	
	8DPSK	2402, 2441, 2480	3Mbps	
Dwell Time	GFSK	2402	1Mbps	1
	π/4 DQPSK	2402	2Mbps	
	8DPSK	2402	3Mbps	

NOTE:

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** results were found as the worst case and were shown in this report.
2. The device can be operated under battery mode and adapter mode. Each mode was selected for related test items as below configuration.
Configuration 1: Battery mode
Configuration 2: Adapter mode

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures


1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz

3.1.3 Test Setup




- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions

Modulation Mode	GFSK	Test Freq. (MHz)	2402																																																																																																																					
Power Phase	Line																																																																																																																							
<p>Test by : Alex Tsai Temperature: 22°C Humidity: 60%</p>																																																																																																																								
																																																																																																																								
<table border="1"> <thead> <tr> <th></th> <th>Freq MHz</th> <th>Level dBuV</th> <th>Limit Line dBuV</th> <th>Over Limit dB</th> <th>Read Level dBuV</th> <th>Factor dB</th> <th>Cable loss dB</th> <th>Remark</th> </tr> </thead> <tbody> <tr><td>1</td><td>0.230</td><td>24.57</td><td>52.44</td><td>-27.87</td><td>14.66</td><td>9.85</td><td>0.06</td><td>Average</td></tr> <tr><td>2</td><td>0.230</td><td>39.44</td><td>62.44</td><td>-23.00</td><td>29.53</td><td>9.85</td><td>0.06</td><td>QP</td></tr> <tr><td>3</td><td>0.358</td><td>18.63</td><td>48.78</td><td>-30.15</td><td>8.67</td><td>9.88</td><td>0.08</td><td>Average</td></tr> <tr><td>4</td><td>0.358</td><td>31.87</td><td>58.78</td><td>-26.91</td><td>21.91</td><td>9.88</td><td>0.08</td><td>QP</td></tr> <tr><td>5*</td><td>0.796</td><td>28.30</td><td>46.00</td><td>-17.70</td><td>18.22</td><td>9.97</td><td>0.11</td><td>Average</td></tr> <tr><td>6</td><td>0.796</td><td>36.40</td><td>56.00</td><td>-19.60</td><td>26.32</td><td>9.97</td><td>0.11</td><td>QP</td></tr> <tr><td>7</td><td>1.229</td><td>17.59</td><td>46.00</td><td>-28.41</td><td>7.46</td><td>9.99</td><td>0.14</td><td>Average</td></tr> <tr><td>8</td><td>1.229</td><td>26.79</td><td>56.00</td><td>-29.21</td><td>16.66</td><td>9.99</td><td>0.14</td><td>QP</td></tr> <tr><td>9</td><td>4.622</td><td>15.65</td><td>46.00</td><td>-30.35</td><td>5.29</td><td>10.05</td><td>0.31</td><td>Average</td></tr> <tr><td>10</td><td>4.622</td><td>24.51</td><td>56.00</td><td>-31.49</td><td>14.15</td><td>10.05</td><td>0.31</td><td>QP</td></tr> <tr><td>11</td><td>9.253</td><td>20.58</td><td>50.00</td><td>-29.42</td><td>10.09</td><td>10.10</td><td>0.39</td><td>Average</td></tr> <tr><td>12</td><td>9.253</td><td>30.05</td><td>60.00</td><td>-29.95</td><td>19.56</td><td>10.10</td><td>0.39</td><td>QP</td></tr> </tbody> </table>					Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	Factor dB	Cable loss dB	Remark	1	0.230	24.57	52.44	-27.87	14.66	9.85	0.06	Average	2	0.230	39.44	62.44	-23.00	29.53	9.85	0.06	QP	3	0.358	18.63	48.78	-30.15	8.67	9.88	0.08	Average	4	0.358	31.87	58.78	-26.91	21.91	9.88	0.08	QP	5*	0.796	28.30	46.00	-17.70	18.22	9.97	0.11	Average	6	0.796	36.40	56.00	-19.60	26.32	9.97	0.11	QP	7	1.229	17.59	46.00	-28.41	7.46	9.99	0.14	Average	8	1.229	26.79	56.00	-29.21	16.66	9.99	0.14	QP	9	4.622	15.65	46.00	-30.35	5.29	10.05	0.31	Average	10	4.622	24.51	56.00	-31.49	14.15	10.05	0.31	QP	11	9.253	20.58	50.00	-29.42	10.09	10.10	0.39	Average	12	9.253	30.05	60.00	-29.95	19.56	10.10	0.39	QP
	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	Factor dB	Cable loss dB	Remark																																																																																																																
1	0.230	24.57	52.44	-27.87	14.66	9.85	0.06	Average																																																																																																																
2	0.230	39.44	62.44	-23.00	29.53	9.85	0.06	QP																																																																																																																
3	0.358	18.63	48.78	-30.15	8.67	9.88	0.08	Average																																																																																																																
4	0.358	31.87	58.78	-26.91	21.91	9.88	0.08	QP																																																																																																																
5*	0.796	28.30	46.00	-17.70	18.22	9.97	0.11	Average																																																																																																																
6	0.796	36.40	56.00	-19.60	26.32	9.97	0.11	QP																																																																																																																
7	1.229	17.59	46.00	-28.41	7.46	9.99	0.14	Average																																																																																																																
8	1.229	26.79	56.00	-29.21	16.66	9.99	0.14	QP																																																																																																																
9	4.622	15.65	46.00	-30.35	5.29	10.05	0.31	Average																																																																																																																
10	4.622	24.51	56.00	-31.49	14.15	10.05	0.31	QP																																																																																																																
11	9.253	20.58	50.00	-29.42	10.09	10.10	0.39	Average																																																																																																																
12	9.253	30.05	60.00	-29.95	19.56	10.10	0.39	QP																																																																																																																
<p>Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB). 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).</p>																																																																																																																								

Modulation Mode	GFSK	Test Freq. (MHz)	2402
Power Phase	Neutral		

Test by : Alex Tsai Temperature: 22°C Humidity: 60%



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	Factor dB	Cable loss dB	Remark
1	0.168	24.10	55.08	-30.98	14.23	9.82	0.05	Average
2*	0.168	41.40	65.08	-23.68	31.53	9.82	0.05	QP
3	0.322	21.40	49.66	-28.26	11.49	9.84	0.07	Average
4	0.322	35.35	59.66	-24.31	25.44	9.84	0.07	QP
5	0.716	19.96	46.00	-26.04	9.98	9.87	0.11	Average
6	0.716	28.80	56.00	-27.20	18.82	9.87	0.11	QP
7	0.809	17.67	46.00	-28.33	7.69	9.87	0.11	Average
8	0.809	25.25	56.00	-30.75	15.27	9.87	0.11	QP
9	4.622	18.97	46.00	-27.03	8.68	9.98	0.31	Average
10	4.622	31.00	56.00	-25.00	20.71	9.98	0.31	QP
11	19.532	13.58	50.00	-36.42	2.61	10.31	0.66	Average
12	19.532	19.31	60.00	-40.69	8.34	10.31	0.66	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 Unwanted Emissions into Restricted Frequency Bands

3.2.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.2.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. Radiated emission above 1GHz / Peak value
RBW=1MHz, VBW=3MHz and Peak detector
Radiated emission above 1GHz / Average value for harmonics
The average value is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula for DH5 packet type which has worst duty factor:
3.
$$20\log(\text{Duty cycle}) = 20\log \frac{1\text{s} / 1600 * 5}{100\text{ ms}} = -30.1\text{dB}$$
4. Radiated emission above 1GHz / Average value for other emissions
RBW=1MHz, VBW=1/T and Peak detector

3.2.3 Test Setup


Radiated Emissions below 1 GHz



Radiated Emissions above 1 GHz




3.2.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	GFSK	Test Freq. (MHz)	2402					
Polarization	Horizontal	Test Configuration	1					
Test By :Akun Chung Temperature(°C):24 Humidity(%):64								
								
	Freq.	Emission Limit	Margin	SA	Factor	Remark	ANT	Turn
	MHz	level		reading			High	Table
		dBuV/m	dBuV/m	dB	dBuV	dB/m	cm	deg
1	31.58	24.33	40.00	-15.67	33.94	-9.61	Peak	---
2	60.85	23.45	40.00	-16.55	32.58	-9.13	Peak	---
3	162.75	20.44	43.50	-23.06	29.37	-8.93	Peak	---
4	437.52	24.98	46.00	-21.02	29.60	-4.62	Peak	---
5	467.82	26.93	46.00	-19.07	30.82	-3.89	Peak	---
6	483.57	28.23	46.00	-17.77	31.88	-3.65	Peak	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	1

Test By :Akun Chung Temperature(°C):24 Humidity(%):64



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	31.21	28.74	40.00	-11.26	38.46	-9.72	Peak	---	---
2	38.54	25.11	40.00	-14.89	33.90	-8.79	Peak	---	---
3	57.63	23.81	40.00	-16.19	32.75	-8.94	Peak	---	---
4	395.45	34.42	46.00	-11.58	40.24	-5.82	Peak	---	---
5	467.22	29.63	46.00	-16.37	33.52	-3.89	Peak	---	---
6	481.83	32.63	46.00	-13.37	36.28	-3.65	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Horizontal	Test Configuration	2

Test By :Akun Chung Temperature(°C):24 Humidity(%):64



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	31.25	24.88	40.00	-15.12	34.58	-9.70	Peak	---	---
2	67.25	24.45	40.00	-15.55	34.67	-10.22	Peak	---	---
3	114.88	21.93	43.50	-21.57	33.08	-11.15	Peak	---	---
4	154.23	20.85	43.50	-22.65	29.74	-8.89	Peak	---	---
5	269.87	22.36	46.00	-23.64	31.55	-9.19	Peak	---	---
6	483.36	27.95	46.00	-18.05	31.60	-3.65	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical	Test Configuration	2

Test By :Akun Chung Temperature(°C):24 Humidity(%):64



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	31.26	31.86	40.00	-8.14	41.56	-9.70	Peak	---	---
2	47.52	30.42	40.00	-9.58	38.75	-8.33	Peak	---	---
3	128.54	27.21	43.50	-16.29	37.19	-9.98	Peak	---	---
4	131.66	27.95	43.50	-15.55	37.61	-9.66	Peak	---	---
5	467.54	30.85	46.00	-15.15	34.74	-3.89	Peak	---	---
6	481.87	33.22	46.00	-12.78	36.87	-3.65	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.


3.2.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK

Modulation	GFSK	Test Freq. (MHz)	2402						
Polarization	Horizontal								
Test By : Roger Lu Temperature(°C):24 Humidity(%):65									
									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		cm	deg
1	2390.00	37.26	54.00	-16.74	40.05	-2.79	Average	100	299
2	2390.00	50.35	74.00	-23.65	53.14	-2.79	Peak	100	299
3	4804.00	15.53	54.00	-38.47	12.03	3.50	Average	100	355
4	4804.00	45.63	74.00	-28.37	42.13	3.50	Peak	100	355
5	12010.00	25.61	54.00	-28.39	11.34	14.27	Average	100	22
6	12010.00	55.71	74.00	-18.29	41.44	14.27	Peak	100	22

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		

Test By :Roger Lu Temperature(°C):24 Humidity(%):65



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2390.00	37.69	54.00	-16.31	40.48	-2.79	Average	100	73
2	2390.00	50.67	74.00	-23.33	53.46	-2.79	Peak	100	73
3	4804.00	15.66	54.00	-38.34	12.16	3.50	Average	100	217
4	4804.00	45.76	74.00	-28.24	42.26	3.50	Peak	100	217
5	12010.00	25.76	54.00	-28.24	11.49	14.27	Average	100	80
6	12010.00	55.86	74.00	-18.14	41.59	14.27	Peak	100	80


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Horizontal		

Test By :Roger Lu Temperature(°C):24 Humidity(%):65



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2390.00	37.36	54.00	-16.64	40.15	-2.79	Average	100	291
2	2390.00	49.37	74.00	-24.63	52.16	-2.79	Peak	100	291
3	2483.50	37.58	54.00	-16.42	40.32	-2.74	Average	100	291
4	2483.50	49.67	74.00	-24.33	52.41	-2.74	Peak	100	291
5	4882.00	14.61	54.00	-39.39	11.14	3.47	Average	100	357
6	4882.00	44.71	74.00	-29.29	41.24	3.47	Peak	100	357
7	7323.00	20.10	54.00	-33.90	11.07	9.03	Average	100	20
8	7323.00	50.20	74.00	-23.80	41.17	9.03	Peak	100	20


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Vertical		

Test By :Roger Lu Temperature(°C):24 Humidity(%):65




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2390.00	37.47	54.00	-16.53	40.26	-2.79	Average	100	75
2	2390.00	49.55	74.00	-24.45	52.34	-2.79	Peak	100	75
3	2483.50	37.73	54.00	-16.27	40.47	-2.74	Average	100	75
4	2483.50	49.81	74.00	-24.19	52.55	-2.74	Peak	100	75
5	4882.00	16.75	54.00	-37.25	13.28	3.47	Average	100	219
6	4882.00	46.85	74.00	-27.15	43.38	3.47	Peak	100	219
7	7323.00	20.18	54.00	-33.82	11.15	9.03	Average	100	50
8	7323.00	50.28	74.00	-23.72	41.25	9.03	Peak	100	50

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Horizontal		

Test By :Roger Lu Temperature(°C):24 Humidity(%):65



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2483.50	38.19	54.00	-15.81	40.93	-2.74	Average	100	299
2	2483.50	50.05	74.00	-23.95	52.79	-2.74	Peak	100	299
3	4960.00	18.06	54.00	-35.94	14.38	3.68	Average	100	356
4	4960.00	48.16	74.00	-25.84	44.48	3.68	Peak	100	356
5	7440.00	20.21	54.00	-33.79	11.23	8.98	Average	100	23
6	7440.00	50.31	74.00	-23.69	41.33	8.98	Peak	100	23


Note 1: Emission Level (dBUV/m) = SA Reading (dBUV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical		

Test By :Roger Lu Temperature(°C):24 Humidity(%):65




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2483.50	38.21	54.00	-15.79	40.95	-2.74	Average	100	74
2	2483.50	50.14	74.00	-23.86	52.88	-2.74	Peak	100	74
3	4960.00	18.14	54.00	-35.86	14.46	3.68	Average	100	220
4	4960.00	48.24	74.00	-25.76	44.56	3.68	Peak	100	220
5	7440.00	20.27	54.00	-33.73	11.29	8.98	Average	100	40
6	7440.00	50.37	74.00	-23.63	41.39	8.98	Peak	100	40

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


3.2.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 8DPSK

Modulation	8DPSK	Test Freq. (MHz)	2402						
Polarization	Horizontal								
Test By : Roger Lu Temperature(°C):24 Humidity(%):65									
									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		cm	deg
1	2390.00	37.61	54.00	-16.39	40.40	-2.79	Average	100	288
2	2390.00	49.70	74.00	-24.30	52.49	-2.79	Peak	100	288
3	4804.00	14.47	54.00	-39.53	10.97	3.50	Average	100	358
4	4804.00	44.57	74.00	-29.43	41.07	3.50	Peak	100	358
5	12010.00	25.68	54.00	-28.32	11.41	14.27	Average	100	18
6	12010.00	55.78	74.00	-18.22	41.51	14.27	Peak	100	18

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		

Test By :Roger Lu Temperature(°C):24 Humidity(%):65



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2390.00	37.78	54.00	-16.22	40.57	-2.79	Average	100	74
2	2390.00	49.85	74.00	-24.15	52.64	-2.79	Peak	100	74
3	4804.00	14.55	54.00	-39.45	11.05	3.50	Average	100	205
4	4804.00	44.65	74.00	-29.35	41.15	3.50	Peak	100	205
5	12010.00	25.81	54.00	-28.19	11.54	14.27	Average	100	70
6	12010.00	55.91	74.00	-18.09	41.64	14.27	Peak	100	70


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2441
Polarization	Horizontal		

Test By :Roger Lu Temperature(°C):24 Humidity(%):65



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2390.00	37.62	54.00	-16.38	40.41	-2.79	Average	100	287
2	2390.00	49.98	74.00	-24.02	52.77	-2.79	Peak	100	287
3	2483.50	37.62	54.00	-16.38	40.36	-2.74	Average	100	287
4	2483.50	49.79	74.00	-24.21	52.53	-2.74	Peak	100	287
5	4882.00	14.53	54.00	-39.47	11.06	3.47	Average	100	354
6	4882.00	44.63	74.00	-29.37	41.16	3.47	Peak	100	354
7	7323.00	20.14	54.00	-33.86	11.11	9.03	Average	100	25
8	7323.00	50.24	74.00	-23.76	41.21	9.03	Peak	100	25


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2441
Polarization	Vertical		

Test By :Roger Lu Temperature(°C):24 Humidity(%):65




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2390.00	37.77	54.00	-16.23	40.56	-2.79	Average	100	75
2	2390.00	50.06	74.00	-23.94	52.85	-2.79	Peak	100	75
3	2483.50	37.73	54.00	-16.27	40.47	-2.74	Average	100	75
4	2483.50	49.90	74.00	-24.10	52.64	-2.74	Peak	100	75
5	4882.00	14.68	54.00	-39.32	11.21	3.47	Average	100	207
6	4882.00	44.78	74.00	-29.22	41.31	3.47	Peak	100	207
7	7323.00	20.21	54.00	-33.79	11.18	9.03	Average	100	80
8	7323.00	50.31	74.00	-23.69	41.28	9.03	Peak	100	80

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal		

Test By :Roger Lu Temperature(°C):24 Humidity(%):65



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2483.50	37.18	54.00	-16.82	39.92	-2.74	Average	100	299
2	2483.50	49.61	74.00	-24.39	52.35	-2.74	Peak	100	299
3	4960.00	15.57	54.00	-38.43	11.89	3.68	Average	100	351
4	4960.00	45.67	74.00	-28.33	41.99	3.68	Peak	100	351
5	7440.00	20.16	54.00	-33.84	11.18	8.98	Average	100	18
6	7440.00	50.26	74.00	-23.74	41.28	8.98	Peak	100	18


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		

Test By :Roger Lu Temperature(°C):24 Humidity(%):65



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	2483.50	37.35	54.00	-16.65	40.09	-2.74	Average	100	76
2	2483.50	49.75	74.00	-24.25	52.49	-2.74	Peak	100	76
3	4960.00	15.79	54.00	-38.21	12.11	3.68	Average	100	209
4	4960.00	45.89	74.00	-28.11	42.21	3.68	Peak	100	209
5	7440.00	20.25	54.00	-33.75	11.27	8.98	Average	100	70
6	7440.00	50.35	74.00	-23.65	41.37	8.98	Peak	100	70

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.3 Unwanted Emissions into Non-Restricted Frequency Bands

3.3.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.3.2 Test Procedures


Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

Emission level measurement


1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

3.3.3 Test Setup



3.3.4 Unwanted Emissions into Non-Restricted Frequency Bands


Ambient Condition	23°C / 63%	Tested By	Brad Wu
-------------------	------------	-----------	---------



BT-BR(1Mbps)

CSEndB-FS


2480MHz



BT-EDR(2Mbps)

CSEndB-FS


2402MHz



BT-EDR(2Mbps)

CSENdB-FS


2441MHz



BT-EDR(2Mbps)

CSENdB-FS


2480MHz



BT-EDR(3Mbps)

CSEndB-FS


2402MHz




BT-EDR(3Mbps)

CSEndB-FS

2441MHz






BT-BR(1Mbps)

2402MHz


Hopping Ch Bandedge (Non-restricted Band)



BT-EDR(2Mbps)

2402MHz


Hopping Ch Bandedge (Non-restricted Band)



BT-EDR(3Mbps)

2402MHz

Hopping Ch Bandedge (Non-restricted Band)



3.4 Conducted Output Power


3.4.1 Limit of Conducted Output Power

- 1 Watt
For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band.
- 0.125 Watt
For all other frequency hopping systems in the 2400–2483.5 MHz band.
- 0.125 Watt
For Frequency hopping systems operating in the 2400–2483.5 MHz band have hopping channel carrier frequencies that are separated by two-thirds of the 20 dB bandwidth of the hopping channel.

3.4.2 Test Procedures

1. A wideband power meter is used for power measurement. Bandwidth of power sensor and meter is 50MHz
2. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power

3.4.3 Test Setup



3.4.4 Test Result of Conducted Output Power

Ambient Condition	23°C / 63%	Tested By	Brad Wu
--------------------------	------------	------------------	---------

Summary of Peak Conducted Output Power

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	-1.22	0.00076
BT-EDR(2Mbps)	-4.11	0.00039
BT-EDR(3Mbps)	-4.01	0.00040

Result

Mode	Result	Antenna Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	2.80	-1.22	21.00
2441MHz	Pass	2.80	-1.25	21.00
2480MHz	Pass	2.80	-1.86	21.00
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	2.80	-4.53	21.00
2441MHz	Pass	2.80	-4.65	21.00
2480MHz	Pass	2.80	-4.11	21.00
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	2.80	-4.52	21.00
2441MHz	Pass	2.80	-4.59	21.00
2480MHz	Pass	2.80	-4.01	21.00

Summary of Conducted (Average) Output Power

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	-1.71	0.00067
BT-EDR(2Mbps)	-8.03	0.00016
BT-EDR(3Mbps)	-8.01	0.00016

Result

Mode	Result	Antenna Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	2.80	-1.71	-
2441MHz	Pass	2.80	-1.85	-
2480MHz	Pass	2.80	-2.50	-
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	2.80	-8.50	-
2441MHz	Pass	2.80	-8.72	-
2480MHz	Pass	2.80	-8.03	-
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	2.80	-8.44	-
2441MHz	Pass	2.80	-8.67	-
2480MHz	Pass	2.80	-8.01	-

Note: Average power is for reference only.

3.5 Number of Hopping Frequency


3.5.1 Limit of Number of Hopping Frequency

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

3.5.2 Test Procedures

1. Set RBW = 100kHz, VBW = 300kHz, Sweep time = Auto, Detector = Peak Trace max hold.
2. Allow trace to stabilize.

3.5.3 Test Setup



3.5.4 Test Result of Number of Hopping Frequency

Ambient Condition	23°C / 63%	Tested By	Brad Wu
--------------------------	------------	------------------	---------

Summary


Mode	Max-Hop No
2.4-2.4835GHz	-
BT-BR(1Mbps)	79
BT-EDR(2Mbps)	79
BT-EDR(3Mbps)	79

Result

Mode	Result	Hopping No	Limit
BT-BR(1Mbps)	-	-	-
2402MHz	Pass	79	15
BT-EDR(2Mbps)	-	-	-
2402MHz	Pass	79	15
BT-EDR(3Mbps)	-	-	-
2402MHz	Pass	79	15


BT-BR(1Mbps)
2402MHz

Hopping-FS




BT-EDR(2Mbps)
2402MHz

Hopping-FS



BT-EDR(3Mbps)
2402MHz

Hopping-FS



3.6 20dB and Occupied Bandwidth

3.6.1 Test Procedures


20dB Bandwidth

1. Set RBW=20kHz, VBW=100kHz, Sweep time = Auto, Detector=Peak , Trace max hold
2. Allow trace to stabilize
3. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

1. Set RBW=20kHz, VBW=100kHz, Sweep time = Auto, Detector=Sample , Trace max hold
2. Allow trace to stabilize
3. Use Occupied bandwidth function of spectrum analyzer to measuring 99% occupied bandwidth

3.6.2 Test Setup



3.6.3 Test result of 20dB and Occupied Bandwidth

Ambient Condition	23°C / 63%	Tested By	Brad Wu
--------------------------	------------	------------------	---------

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-BR(1Mbps)	855.072k	893.632k	894KF1D	855.072k	875.543k
BT-EDR(2Mbps)	1.333M	1.226M	1M23G1D	1.322M	1.216M
BT-EDR(3Mbps)	1.333M	1.219M	1M22G1D	1.261M	1.216M

Max-N dB = Maximum 20dB down bandwidth; Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 20dB down bandwidth; Min-OBW = Minimum 99% occupied bandwidth

Result


Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	Inf	855.072k	893.632k
2441MHz	Pass	Inf	855.072k	890.014k
2480MHz	Pass	Inf	855.072k	875.543k
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	Inf	1.322M	1.226M
2441MHz	Pass	Inf	1.33M	1.219M
2480MHz	Pass	Inf	1.333M	1.216M
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	Inf	1.264M	1.216M
2441MHz	Pass	Inf	1.333M	1.219M
2480MHz	Pass	Inf	1.261M	1.216M

Port X-N dB = Port X 20dB down bandwidth;
Port X-OBW = Port X 99% occupied bandwidth

BT-BR(1Mbps)

EBW-FS


2402MHz



BT-BR(1Mbps)

EBW-FS


2441MHz



BT-BR(1Mbps)

EBW-FS


2480MHz



BT-EDR(2Mbps)

EBW-FS


2402MHz



BT-EDR(2Mbps)

EBW-FS


2441MHz



BT-EDR(2Mbps)

EBW-FS


2480MHz



BT-EDR(3Mbps)

EBW-FS


2402MHz



BT-EDR(3Mbps)


EBW-FS

2441MHz




BT-EDR(3Mbps)

2480MHz



EBW-FS



20dB(Hz)	Fl-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
1.261M	2.479333G	2.480594G	1.216M	2.479363G	2.480579G	Inf	1

3.7 Channel Separation


3.7.1 Limit of Channel Separation

- Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
- Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.7.2 Test Procedures

1. Set RBW=30kHz, VBW=100kHz, Sweep time = Auto, Detector=Peak Trace max hold
2. Allow trace to stabilize
3. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The EUT shall show compliance with the appropriate regulatory limit

3.7.3 Test Setup



3.7.4 Test result of Channel Separation

Ambient Condition	23°C / 63%	Tested By	Brad Wu
--------------------------	------------	------------------	---------

Summary

Mode	Max-Space (Hz)	Min-Space (Hz)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	1M	1M
BT-EDR(2Mbps)	1.004348M	1M
BT-EDR(3Mbps)	1M	1M

Result

Mode	Result	Fl (Hz)	Fh (Hz)	Ch.Space (Hz)	Limit (Hz)
BT-BR(1Mbps)	-	-	-	-	-
2402MHz	Pass	2.402143G	2.403143G	1M	569.477952k
2441MHz	Pass	2.441143G	2.442143G	1M	569.477952k
2480MHz	Pass	2.479139G	2.480139G	1M	569.477952k
BT-EDR(2Mbps)	-	-	-	-	-
2402MHz	Pass	2.401987G	2.402987G	1M	880.452k
2441MHz	Pass	2.440983G	2.441987G	1.004348M	885.78k
2480MHz	Pass	2.478983G	2.479983G	1M	887.778k
BT-EDR(3Mbps)	-	-	-	-	-
2402MHz	Pass	2.402143G	2.403143G	1M	841.824k
2441MHz	Pass	2.441143G	2.442143G	1M	887.778k
2480MHz	Pass	2.479139G	2.480139G	1M	839.826k

BT-BR(1Mbps)

Channel Separation-FS

2.402G/2.403GHz



BT-BR(1Mbps)

Channel Separation-FS

2.441G/2.442GHz



BT-BR(1Mbps)

Channel Separation-FS


2.48G/2.479GHz



BT-EDR(2Mbps)

Channel Separation-FS


2.402G/2.403GHz



BT-EDR(2Mbps)

Channel Separation-FS


2.441G/2.442GHz



BT-EDR(2Mbps)

Channel Separation-FS


2.48G/2.479GHz



BT-EDR(3Mbps)

Channel Separation-FS


2.402G/2.403GHz



BT-EDR(3Mbps)


Channel Separation-FS

2.441G/2.442GHz



BT-EDR(3Mbps)
2.48G/2.479GHz

Channel Separation-FS



3.8 Number of Dwell Time


3.8.1 Limit of Dwell time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.8.2 Test Procedures

1. Set RBW=300 kHz, VBW=1 MHz, Sweep time=8 ms, Detector=Peak, Span=0 Hz, Trace max hold.
2. Enable gating and trigger function of spectrum analyzer to measure burst on time.
3. Set RBW=300 kHz, VBW=1 MHz, Sweep time=5 s / 2 s, Detector=Peak, Span=0 Hz, Trace max hold.
4. Enable gating and trigger function of spectrum analyzer to measure burst on number of transmission.
5. Set RBW=300 kHz, VBW=1 MHz, Sweep time=31.6 s / 8 s, Detector=Peak, Span=0 Hz, Trace max hold.
6. Enable gating and trigger function of spectrum analyzer to measure burst on number of transmission of entire time cycle.

3.8.3 Test Setup



3.8.4 Test Result of Dwell Time

Ambient Condition	23°C / 63%	Tested By	Brad Wu
--------------------------	------------	------------------	---------

Summary

Mode	Max-Dwell (s)
2.4-2.4835GHz	-
BT-BR(1Mbps)	314.20828m_DH5
BT-EDR(2Mbps)	351.44414m_DH5
BT-EDR(3Mbps)	351.6843m_DH5
BT-BR-AFH(1Mbps)	292.475m_DH5-AFH
BT-EDR-AFH(2Mbps)	304.408m_DH5-AFH
BT-EDR-AFH(3Mbps)	304.538m_DH5-AFH

Result/ Non AFH mode

Mode	Result	Period (s)	Dwell (s)	Limit (s)	Tx On (ms)	Number of transmission in a 5 s
BT-BR(1Mbps)	-	-	-	-	-	-
2402MHz_DH5	PASS	31.6	0.31421	0.4	2.92450	17
BT-EDR(2Mbps)	-	-	-	-	-	-
2402MHz_DH5	PASS	31.6	0.35144	0.4	2.92675	19
BT-EDR(3Mbps)	-	-	-	-	-	-
2402MHz_DH5	PASS	31.6	0.35168	0.4	2.92875	19

Note 1: Dwell time =Number of transmission in a 5 second x Tx On Time x 6.32

Note 2: DH5 was the worst mode.

Result/ AFH mode

Mode	Result	Period (s)	Dwell (s)	Limit (s)	Tx On (ms)	Number of transmission in a 2 s
BT-BR-AFH(1Mbps)	-	-	-	-	-	-
2402MHz_DH5	PASS	8	0.29248	0.4	2.92475	25
BT-EDR-AFH(2Mbps)	-	-	-	-	-	-
2402MHz_DH5	PASS	8	0.30441	0.4	2.92700	26
BT-EDR-AFH(3Mbps)	-	-	-	-	-	-
2402MHz_DH5	PASS	8	0.30454	0.4	2.92825	26

Note 1: Dwell time =Number of transmission in a 2 second x Tx On Time x 4

Note 2: DH5 was the worst mode.

BT-BR(1Mbps)

Dwell-FS

2402MHz



BT-EDR(2Mbps)

Dwell-FS

2402MHz



BT-EDR(3Mbps)

Dwell-FS

2402MHz



BT-BR-AFH(1Mbps)

Dwell-FS


2402MHz



BT-EDR-AFH(2Mbps)

Dwell-FS


2402MHz



BT-EDR-AFH(3Mbps)

Dwell-FS

2402MHz



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No.30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan
(R.O.C.)

Kwei Shan

Tel: 886-3-271-8666

No.3-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)
No.2-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

Kwei Shan Site II

Tel: 886-3-271-8640

No.14-1, Lane 19, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 333, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0345

Email: ICC_Service@icertifi.com.tw

==END==