



The University of Michigan  
Radiation Laboratory  
3228 EECS Building  
Ann Arbor, MI 48109-2122  
Tel: (734) 764-0500  
Fax: (734) 647-2106

Measured Radio Frequency Emissions  
From

**Evigia Systems, Inc. Transponder**  
**FCC ID: XND-ECX-1**  
**IC: 8519A- ECX1**


Test Report No. 417124-527  
October 14, 2009

Copyright © 2009

For:  
Evigia Systems, Inc.  
3810 Varsity Drive  
Ann Arbor, MI 48108-2224  
Contact: Robert W. Hower  
webinfo@evigia.com  
Phone: 734-302-1140  
Fax: 734-372-6435

Measurements made by: Valdis V. Liepa

Testing supervised by:  
Report Approved by:

  
Valdis V. Liepa  
Research Scientist

Test report written by: Joseph D. Brunett

---

## Summary

Tests for compliance with FCC Regulations, CFR 47, Part 15 and with Industry Canada RSS-210/Gen, were performed on a Evigia, FCC ID: XND-ECX-1, IC: 8519A-ECX1. This device under test (DUT) is subject to the rules and regulations as a Transceiver.

In testing completed on September 19, 2009, the DUT tested meets the allowed specifications for intentional radiated emissions by 2.4 dB. Harmonic radiated emissions meet the regulations by more than 9.6 dB. The FCC Class A digital emissions limit pass by more than 20 dB. Power line conducted emissions are not subject to regulation as the DUT is powered by a 3.6 VDC battery.

## **Table of Contents**

1.	Introduction.....	3
2.	Equipment Used.....	3
3.	Device Under Test .....	4
3.1	Description & Block Diagram .....	4
3.2	Variants and Samples.....	4
3.3	Modes of Operation .....	4
3.4	Exemptions .....	4
3.5	EMC Relevant Modifications .....	4
4.	Emissions Limits.....	5
4.1	Radiated Emissions Limits.....	5
4.2	Power Line Conducted Emissions Limits .....	6
5.	Measurement Procedures .....	6
5.1	Semi-Anechoic Chamber Radiated Emissions.....	6
5.2	Outdoor Radiated Emissions.....	6
5.3	Radiated Field Computations.....	7
5.4	Indoor Power Line Conducted Emissions.....	7
5.5	Supply Voltage Variation.....	7
6.	Test Results.....	8
6.1	Radiated Emissions.....	8
6.1.1	Correction for Pulse Operation .....	8
6.1.2	Emission Spectrum .....	8
6.1.3	Emission Bandwidth .....	8
6.1.4	Supply Voltage and Supply Voltage Variation.....	8
6.2	Conducted Emissions.....	8

## 1. Introduction

These Evigia Transponders were tested for compliance with FCC Regulations, Part 15, adopted under Docket 87-389, April 18, 1989 as subsequently amended, and with Industry Canada RSS-210/Gen, Issue 7, June 2007. Tests were performed at the University of Michigan Radiation Laboratory Willow Run Test Range following the procedures described in ANSI C63.4-2003 "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz". The Site description and attenuation characteristics of the Open Site facility are on file with FCC Laboratory, Columbia, Maryland (FCC Reg. No: 91050) and with Industry Canada, Ottawa, ON (File Ref. No: IC 2057A-1).

## 2. Equipment Used

The test equipment commonly used in our facility is listed in Table 2.1. Except where indicated as a pre-test, monitoring, or support device; all equipment listed below is a part of the University of Michigan Radiation Laboratory (UMRL) quality system. This quality system has been established to ensure all equipment has a clearly identifiable classification, calibration expiry date, and that all calibrations are traceable to national standards.

**Table 2.1 Test Equipment.**

Test Instrument	Used	Manufacturer/Model	Q Number
Spectrum Analyzer (9kHz-26GHz)	<input checked="" type="checkbox"/>	Hewlett-Packard 8593E, SN: 3412A01131	HP8593E1
Spectrum Analyzer (9kHz-6.5GHz)	<input checked="" type="checkbox"/>	Hewlett-Packard 8595E, SN: 3543A01546	JDB8595E
Power Meter	<input type="checkbox"/>	Hewlett-Packard, 432A	HP432A1
Harmonic Mixer (26-40 GHz)	<input type="checkbox"/>	Hewlett-Packard 11970A, SN: 3003A08327	HP11970A1
Harmonic Mixer (40-60 GHz)	<input type="checkbox"/>	Hewlett-Packard 11970U, SN: 2332A00500	HP11970U1
Harmonic Mixer (75-110 GHz)	<input type="checkbox"/>	Hewlett-Packard 11970W, SN: 2521A00179	HP11970W1
Harmonic Mixer (140-220 GHz)	<input type="checkbox"/>	Pacific Millimeter Prod., GMA, SN: 26	PMPGMA1
S-Band Std. Gain Horn	<input type="checkbox"/>	S/A, Model SGH-2.6	SBAND1
C-Band Std. Gain Horn	<input type="checkbox"/>	University of Michigan, NRL design	CBAND1
XN-Band Std. Gain Horn	<input type="checkbox"/>	University of Michigan, NRL design	XNBAND1
X-Band Std. Gain Horn	<input type="checkbox"/>	S/A, Model 12-8.2	XBAND1
X-band horn (8.2- 12.4 GHz)	<input type="checkbox"/>	Narda 640	XBAND2
X-band horn (8.2- 12.4 GHz)	<input type="checkbox"/>	Scientific Atlanta , 12-8.2, SN: 730	XBAND3
K-band horn (18-26.5 GHz)	<input type="checkbox"/>	FXR, Inc., K638KF	KBAND1
Ka-band horn (26.5-40 GHz)	<input type="checkbox"/>	FXR, Inc., U638A	KABAND1
U-band horn (40-60 GHz)	<input type="checkbox"/>	Custom Microwave, HO19	UBAND1
W-band horn(75-110 GHz)	<input type="checkbox"/>	Custom Microwave, HO10	WBAND1
G-band horn (140-220 GHz)	<input type="checkbox"/>	Custom Microwave, HO5R	GBAND1
Bicone Antenna (30-250 MHz)	<input checked="" type="checkbox"/>	University of Michigan, RLBC-1	LBBIC1
Bicone Antenna (200-1000 MHz)	<input checked="" type="checkbox"/>	University of Michigan, RLBC-2	HBBIC1
Dipole Antenna Set (30-1000 MHz)	<input checked="" type="checkbox"/>	University of Michigan, RLDP-1,-2,-3	UMDIP1
Dipole Antenna Set (30-1000 MHz)	<input type="checkbox"/>	EMCO 3121C, SN: 992 (Ref. Antennas)	EMDIP1
Active Rod Antenna (30 Hz-50 MHz)	<input type="checkbox"/>	EMCO 3301B, SN: 3223	EMROD1
Active Loop Antenna (30 Hz-50 MHz)	<input type="checkbox"/>	EMCO 6502, SN:2855	EMLOOP1
Ridge-horn Antenna (300-5000 MHz)	<input checked="" type="checkbox"/>	University of Michigan	UMRH1
Amplifier (5-1000 MHz)	<input checked="" type="checkbox"/>	Avantek, A11-1, A25-1S	AVAMP1
Amplifier (5-4500 MHz)	<input checked="" type="checkbox"/>	Avantek	AVAMP2
Amplifier (4.5-13 GHz)	<input type="checkbox"/>	Avantek, AFT-12665	AVAMP3
Amplifier (6-16 GHz)	<input type="checkbox"/>	Trek	TRAMP1
Amplifier (16-26 GHz)	<input type="checkbox"/>	Avantek	AVAMP4
LISN Box	<input type="checkbox"/>	University of Michigan	UMLISN1
Signal Generator	<input type="checkbox"/>	Hewlett-Packard 8657B	HPSG1

### 3. Device Under Test

#### 3.1 Description & Block Diagram

The DUT is a 433.9 MHz FSK, active RFID Transponder designed for cargo tracking applications. These devices are housed in plastic cases and employ a 3.6 V lithium battery. The DUT is designed and manufactured by Evigia Systems, Inc., 3810 Varsity Drive, Ann Arbor, MI 48108-2224.

Transponder	[Make], Model	[S/N],P/N	EMC Consideration
Container Security	[Evigia], EV3-CST	[18713172574612]	FCC 15.231, 15.240 IC RSS-210 2.7, A5

Cable	[Make], Model	Length	EMC Consideration
USB	[Generic]	1 m	Class A PC Interface (programming)

#### 3.2 Variants and Samples

There is only a single variant of the DUT; one sample was provided for testing. An Evigia engineer programmed the device into CW, modulated, and Rx only modes for testing.

#### 3.3 Modes of Operation

This transponder is capable of only a single mode of operation, and qualifies for certification under two rule parts (FCC 15.231/RSS-210 2.7 and FCC 15.240/RSS-210 A5). When interrogated by an associated reader, these transponders reply with a single control/data packet. The reader device verifies the integrity of the packet sent before requesting a new packet. Both the transponder and any associated reader employ the ISO 18000-7:2008 RFID protocol.

#### 3.4 Exemptions

Since these devices are sold only for commercial use, they are subject only to Class A digital emissions verification. They are not used for residential purposes.

The transponder included in this application always operates within the rules of FCC Part 15.231. Thus, it is not necessary to notify the FCC OET about use of this transponder in a specific location as prescribed

#### 3.5 EMC Relevant Modifications

No EMI Relevant Modifications were performed by this test laboratory.

#### 4. Emissions Limits

##### 4.1 Radiated Emissions Limits

The DUT tested falls under the category of an Intentional Radiator. The applicable testing frequencies and corresponding emission limits set by both the FCC and IC are given in Tables 4.1 and 4.2 below.

**Table 4.1. TX Emission Limits (FCC: 15.231(b), .205(a); IC: RSS-210 2.7 T4).**

Frequency (MHz)	Fundamental Ave. E <sub>lim</sub> (3m)		Spurious** Ave. E <sub>lim</sub> (3m)	
	(μV/m)	dB (μV/m)	(μV/m)	dB (μV/m)
260.0-470.0	3750-12500*		375-1250	
315	6042	75.6	604.2	55.6
433.9	10966	80.8	1096.6	60.8
322-335.4 399.9-410 608-614	Restricted Bands		200	46.0
960-1240/1427(IC) 1300-1427 1435-1626.5 1645.5-1646.5 (IC) 1660-1710 1718.9-1722.2 2200-2300	Restricted Bands		500	54.0

\* Linear interpolation, formula:  $E = -7083 + 41.67 * f$  (MHz)

\*\* Measure up to tenth harmonic; 120 kHz BW up to 1 GHz, 1 MHz BW above 1 GHz

**Table 4.1(b). TX Emission Limits (FCC: 15.240; IC: RSS-210 A5).**

Frequency (MHz)	Fundamental Ave. E <sub>lim</sub> (3m)		Spurious** Ave. E <sub>lim</sub> (3m)	
	(μV/m)	dB (μV/m)	(μV/m)	dB (μV/m)
433.5-434.5	11000	80.8	200 < 1 GHz 500 > 1 GHz	46.0 54.0

\* Linear interpolation, formula:  $E = -7083 + 41.67 * f$  (MHz)

\*\* Measure up to tenth harmonic; 120 kHz BW up to 1 GHz, 1 MHz BW above 1 GHz

**Table 4.2. Spurious Emission Limits (FCC: 15.33, .35, .109/209; IC: RSS-210 2.7, T2)**

Freq. (MHz)	E <sub>lim</sub> (3m) μV/m	E <sub>lim</sub> dB(μV/m)
30-88	100	40.0
88-216	150	43.5
216-960	200	46.0
960-2000	500	54.0

Note: Average readings apply above 1000 MHz (1 MHz BW), Quasi-Peak readings apply to 1000 MHz (120 kHz RBW), PRF of intentional emissions > 20 Hz for QPK to apply.

## 4.2 Power Line Conducted Emissions Limits

**Table 4.3 Emission Limits (FCC:15.107 (CISPR); IC: RSS-Gen, 7.2.2 T2).**

Frequency (MHz)	Class A (dBμV)		Class B (dBμV)	
	Quasi-peak	Average	Quasi-peak	Average
.150 - 0.50	79	66	66 - 56*	56 - 46*
0.50 - 5	73	60	56	46
5 - 30	73	60	60	50

Notes:

1. The lower limit shall apply at the transition frequency
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15-0.50 MHz:  
\*Class B Quasi-peak:  $\text{dB}\mu\text{V} = 50.25 - 19.12 \cdot \log(f)$   
\*Class B Average:  $\text{dB}\mu\text{V} = 40.25 - 19.12 \cdot \log(f)$
3. 9 kHz RBW

## 5. Measurement Procedures

### 5.1 Semi-Anechoic Chamber Radiated Emissions

To become familiar with the radiated emission behavior of the DUT, the device is first studied and measured in our shielded semi-anechoic chamber. In the chamber there is a set-up similar to that of an outdoor 3-meter site, with a turntable, an antenna mast, and a ground plane. Instrumentation includes spectrum analyzers and other equipment as needed.

The DUT is laid on the test table as shown in the included block diagram and/or photographs. A shielded loop antenna is employed when studying emissions from 9 kHz to 30 MHz. Above 30 MHz and below 250 MHz a biconical antenna is employed. Above 250 MHz a ridge or standard gain horn antennas are used. The spectrum analyzer resolution and video bandwidths are set so as to measure the DUT emission without decreasing the emission bandwidth (EBW) of the device. Emissions are studied for all orientations (3-axes) of the DUT and all test antenna polarizations. In the chamber, spectrum and modulation characteristics of intentional carriers are recorded. Receiver spurious emissions are measured with an appropriate carrier signal applied. Associated test data is presented in subsequent sections.

### 5.2 Outdoor Radiated Emissions

After measurements are performed indoors, emissions on our outdoor 3-meter Open Area Test Site (OATS) are made. If the DUT connects to auxiliary equipment and is table or floor standing, the configurations prescribed in ANSI C63.4 are employed. Alternatively, an on-table layout more representative of actual use may be employed if the resulting emissions appear to be worst-case in such a configuration. Any intentionally radiating elements are placed on the test table flat, on their side, and on their end (3-axes) and worst case emissions are recorded. For each configuration the DUT is rotated 360 degrees about its azimuth and the receive antenna is raised and lowered between 1 and 4 meters to maximize radiated emissions from the device. Receiver spurious emissions are measured with an appropriate carrier signal applied. For devices with intentional emissions below 30 MHz, our shielded loop antenna at a 1 meter received height is used. Low frequency field extrapolation to the regulatory limit distance is employed as needed. Emissions between 30 MHz and 1 GHz are measured using tuned dipoles and/or biconical antennas. Care is taken to ensure that the RBW and VBW used meet the regulatory requirements, and that the EBW of the DUT is not reduced. The Photographs included in this report show the DUT on the OATS.

### **5.3 Radiated Field Computations**

To convert the dBm values measured on the spectrum analyzer to dB( $\mu$ V/m), we use expression

$$E3(\text{dB}\mu\text{V/m}) = 107 + \text{PR} + \text{KA} - \text{KG} + \text{KE} - \text{CF}$$

where      PR = power recorded on spectrum analyzer, dBm, measured at 3 m  
             KA = antenna factor, dB/m  
             KG = pre-amplifier gain, including cable loss, dB  
             KE = duty correction factor, dB  
             CF = distance conversion (employed only if limits are specified at alternate distance), dB

When presenting the data at each frequency, the highest measured emission under all of the possible DUT orientations (3-axes) is given.

### **5.4 Indoor Power Line Conducted Emissions**

When applicable, power line conducted emissions are measured in our semi-anechoic chamber. If the DUT connects to auxiliary equipment and is table or floor standing, the configurations prescribed in ANSI C63.4 are employed. Alternatively, an on-table layout more representative of actual use may be employed if the resulting emissions appear to be worst-case in such a configuration.

The conducted emissions measured with the spectrum analyzer and recorded (in dB $\mu$ V) from 0-2 MHz and 2-30 MHz for both the ungrounded (Hi) and grounded (Lo) conductors. The spectrum analyzer is set to peak-hold mode in order to record the highest peak throughout the course of functional operation. Only when the emission exceeds or is near the limit are quasi-peak and average detection used.

### **5.5 Supply Voltage Variation**

Measurements of the variation in the fundamental radiated emission were performed with the supply voltage varied by no less than 85% and 115% of the nominal rated value. For battery operated equipment, tests were performed using a new battery, and worst case emissions are re-checked employing a new battery.

## **6. Test Results**

### **6.1 Radiated Emissions**

#### **6.1.1 Correction for Pulse Operation**

These transponder devices are firmware encoded to limit transmitted packet length, measured at 25.5 ms, with a minimum measured packet period of 96.5 ms. Each transponder is capable of transmitting only a single FSK data packet in response to an automatic activation from an associated reader unit (not included in this certification). See Figure 6.1. Computing the duty factor results in:

$$K_E = 25.5 \text{ ms} / 96.5 \text{ ms} = 0.264 \text{ or } -11.6 \text{ dB.}$$

#### **6.1.2 Emission Spectrum**

The relative DUT emission spectrum is recorded and is shown in Figure 6.2.

#### **6.1.3 Emission Bandwidth**

The emission bandwidth of the signal is shown in Figure 6.3. The allowed 99% bandwidth is 0.25% of 433.9 MHz, or 1.085 MHz. From the plot we see that the EBW is 245.0 kHz, and the center frequency is 433.92 MHz.

#### **6.1.4 Supply Voltage and Supply Voltage Variation**

The DUT has been designed to be powered by a 3.6 VDC battery. For this test, relative radiated power was measured at the fundamental as the voltage was varied from 2.5 to 4.0 volts. The emission variation is shown in Figure 6.4.

Batteries:	before testing	$V_{oc} = 3.60 \text{ V}$
	after testing	$V_{oc} = 3.49 \text{ V}$
Ave. current from batteries		$I = 22.1 \text{ mA (cw)}$

### **6.2 Conducted Emissions**

These tests do not apply, since the DUT is powered from a 3.6 VDC battery.

The University of Michigan  
Radiation Laboratory  
3228 EECS Building  
Ann Arbor, MI 48109-2122  
Tel: (734) 764-0500  
Fax: (734) 647-2106

**Table 6.1 Radiated Emissions**

<b>Fundamental &amp; Harmonic Emissions</b>											Evigia EV3-CST; FCC/IC
#	Freq. MHz	Ant. Used	Ant. Pol.	Pr dBm	Det. Used	Ka dB/m	Kg dB	E3* dBμV/m	E3lim** dBμV/m	Pass dB	Comments
1	433.9	Dip	H	-24.6	Pk	21.2	19.5	72.5	80.8	8.3	end
2	433.9	Dip	V	-18.7	Pk	21.2	19.5	78.4	80.8	2.4	flat
3	867.8	Dip	H	-83.3	Pk	27.4	16.1	23.4	46.0	22.6	max all, noise
4	867.8	Dip	V	-81.6	Pk	27.4	16.1	25.1	46.0	20.9	max all, noise
5	1301.8	Horn	H	-52.4	Pk	20.7	28.1	35.6	54.0	18.4	side
6	1735.7	Horn	H	-61.9	Pk	21.9	28.1	27.3	54.0	26.7	end
7	2169.6	Horn	H	-53.7	Pk	22.9	26.5	38.1	54.0	15.9	side
8	2603.5	Horn	H	-53.7	Pk	24.1	25.7	40.1	54.0	13.9	end
9	3037.4	Horn	H	-55.0	Pk	25.5	23.9	41.9	54.0	12.1	side
10	3471.4	Horn	H	-59.4	Pk	26.8	23.2	39.6	54.0	14.4	end
11	3905.3	Horn	H	-59.0	Pk	28.1	22.4	42.2	54.0	11.8	end
12	4339.2	Horn	H	-64.2	Pk	29.5	16.2	44.4	54.0	9.6	flat
13											
14	* includes 11.6 dB duty factor										
15	** Harmonic Emissions Limit is 60.8 dBuV/m under 15.231, 46 dBuV/m - 54 dBuV/m under 15.240.										
16											
<b>Spurious Digital Emissions (Class A)</b>											
#	Freq. MHz	Ant. Used	Ant. Pol.	Pr dBm	Det. Used	Ka dB/m	Kg dB	E3 dBμV/m	E3lim dBμV/m	Pass dB	Comments
17											
18											
19											
20	Digital emission more than 20 dB below FCC/IC Class B limit.										
21											
22											
23											
24											
25											
26											
<b>Spurious Receiver Emissions (Class B)</b>											
#	Freq. MHz	Ant. Used	Ant. Pol.	Pr dBm	Det. Used	Ka dB/m	Kg dB	E3 dBμV/m	E3lim dBμV/m	Pass dB	Comments
27	433.89	SBic	H	-82.1	Pk	21.9	19.5	27.3	46.0	18.7	LO, noise
28	433.95	SBic	H	-83.0	Pk	21.9	19.5	26.4	46.0	19.6	LO, noise
29	867.77	SBic	H	-82.9	Pk	28.6	16.1	36.6	46.0	9.4	2 x LO, noise
30	867.91	SBic	V	-82.4	Pk	28.6	16.1	37.1	46.0	8.9	2 x LO, noise
31											
32											
33											

Meas. 09/02/2009; U of Mich.




Figure 6.1. Transmission characteristics, (top) single packet length,  
(bottom) minimum packet period when the DUT is automatically for a second transmission




Figure 6.2. Emission spectrum of the DUT (pulsed emission). Amplitudes are only indicative (not corrected).




Figure 6.3. Measured emission bandwidth of the DUT (pulsed).





Figure 6.4. Relative emission at fundamental vs. supply voltage (pulsed).



**Photograph 6.5. DUT on OATS (one of three axes tested)**



**Photograph 6.6. Close-up of DUT on OATS (one of three axes tested)**



**Photograph 6.7. Digital Emissions Test Setup on OATS**