

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant: Shenzhen QiyueOptronics Company Limited
Address of applicant: Flat3,Tower 3, Excellence Meilin Center Plaza, Zhongkang Road
128, Shangmeilin, Futian District, Shenzhen, China

Manufacturer: SHENZHEN QIYUE OPTRONICS COMPANY LIMITED BRANCH
SEIYU INDUSTRIAL PARK,DA SAN VILLAGE,DA SHUI
Address of manufacturer: KENG,GUANLAN TOWN,LONGHUA NEW DISTRICT,
SHENZHEN,P.R.C

General Description of EUT:

Product Name: 86 INCH SMART 4K UHD TV
Trade Name: RCA smarTVirtuoso,RCA, PROSCAN, RCA SCENIUM,
TECHNICOLOR, SYLVANIA
Model No.: RNSMU8615
Adding Model(s): XXXXXXXXXXXXXXXXXXXX86XXXXXXXXXXXXXXXXXXXXX
(Where "X" can be any alphanumeric of A-Z or 0-9 or blank or -,
indicates different client)
FCC ID: XOMD86D18
Rated Voltage: AC 100-240V

Technical Characteristics of EUT:

Support Standards: 802.11b, 802.11g, 802.11n
Frequency Range: 2412-2462MHz for 802.11b/g/n(HT20)
2422-2452MHz for 802.11n(HT40)
Max RF Output Power: 23.52dBm (Conducted)
Type of Modulation: DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM
Type of Antenna: Integral Antenna
Antenna Gain: ANT1:4.44 dBi, ANT2:4.44dBi
Device Category: Mobile Device

Note 2: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model RNSMU8615, but the circuit and the electronic construction do not change, declared by the manufacturer.

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30 * P * G) / (377 * R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

Maximum output power: 23.52(dBm)

Maximum peak output power at antenna input terminal: 224.92 (mW)

Prediction distance: >20(cm)

Prediction frequency: 2412 (MHz)

Antenna gain: 7.45 (dBi)

Directional gain (numeric gain): 5.56

The worst case is power density at prediction frequency at 20cm: 0.25(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Result: Pass

Note: Directional gain = $G_{ANT} + 10 \log(N_{ANT}) = 7.45\text{dBi}$