

## MPE Calculation

FCC ID: XOMIPD32P619

Remark: Average  $\leq$  Peak, which means that calculating the power density applying Peak power is worst case. The worst case operation mode generating the highest power in each frequency range is taken for calculation.

*For WiFi 11b/g/n(HT20):*

Frequency range: **2412-2462** MHz Typical use distance:  $d \geq 20$  cm

Power density limit for mobile devices at 2.4 GHz:  $S \leq 1$  mW/cm<sup>2</sup>

Maximum measured conducted power (Peak):  $P_{\text{conducted}} = \mathbf{20.57}$  dBm = 114.02 mW

Antenna Gain:  $G = \mathbf{2.55}$  dBi = 1.8 on the linear scale

Calculation:  $P_{\text{radiated}} = P_{\text{conducted}} + G_{\text{linear}} = 20.57$  dBm + 2.55 dBi = 23.12 dBm = 205.12 mW

Power density  $S = (P_{\text{radiated}}) / (4\pi \times d^2) = 205.12 / 5026 = 0.0408$  mW/cm<sup>2</sup> < 1 => below limit

*For WiFi 11n(HT40):*

Frequency range: **2452-2452** MHz Typical use distance:  $d \geq 20$  cm

Power density limit for mobile devices at 2.4 GHz:  $S \leq 1$  mW/cm<sup>2</sup>

Maximum measured conducted power (Peak):  $P_{\text{conducted}} = \mathbf{19.64}$  dBm = 92.04 mW

Antenna Gain:  $G = \mathbf{2.55}$  dBi = 1.8 on the linear scale

Calculation:  $P_{\text{radiated}} = P_{\text{conducted}} + G_{\text{linear}} = 19.64$  dBm + 2.55 dBi = 22.19 dBm = 165.58 mW

Power density  $S = (P_{\text{radiated}}) / (4\pi \times d^2) = 165.58 / 5026 = 0.0329$  mW/cm<sup>2</sup> < 1 => below limit