



Maximum Permissible Exposure Report For

Shenzhen Qiyue Optronics Company Limited

Flat3,Tower 3, Excellence Meilin Center Plaza, Zhongkang Road 128, Shangmeilin,
Futian District, Shenzhen, China

FCC ID: XOMIRTUOXOXX60XX

FCC Rule(s):	<u>FCC 47CFR Part 2.019</u>
Product Description:	<u>60" SMART 4K UHD TV</u>
Tested Model:	<u>D60A114-U-A-I RNSMU6036</u> <u>XXXXXXXXXXXXXXXXXX60XXXXXXXXXXXX</u> <u>(Where "X" can be any alphanumeric of a-z,</u> <u>A-Z or 0-9 or blank & "-".)</u>
Report No.:	<u>WTG19G01003938W-2</u>
Sample Receipt Date:	<u>January 19, 2019</u>
Tested Date:	<u>January 19 ~ February 26, 2019</u>
Issued Date:	<u>February 26, 2019</u>
Tested By:	<u>Jason Su / Engineer</u> <i>Jason Su</i>
Reviewed By:	<u>Silin Chen / EMC Manager</u> <i>Silin Chen</i>
Approved & Authorized By:	<u>Jandy So / PSQ Manager</u> <i>Jandy So</i>
Prepared By:	Shenzhen SEM Test Technology Co. Ltd 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, 518101,China Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn



TABLE OF CONTENTS

1. GENERAL INFORMATION3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)3

2. MAXIMUM PERMISSIBLE EXPOSURE5
2.1 APPLICABLE STANDARD5

3. MPE CALCULATION METHOD6

4.CONDUCTED POWER RESULT7
4.1 ANTENNA 17
4.2 ANTENNA 27

5. CALCULATED RESULT AND LIMIT8
5.1 ANTENNA 18
5.2 ANTENNA 28
5.3 ANTENNA 1+29



1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information	
Applicant:	Shenzhen Qiyue Optronics Company Limited
Address of applicant:	Flat3,Tower 3, Excellence Meilin Center Plaza, Zhongkang Road 128, Shangmeilin, Futian District, Shenzhen, China
Manufacturer:	SHENZHEN QIYUE OPTRONICS COMPANY LIMITED BRANCH
Address of manufacturer:	SEIYU INDUSTRIAL PARK, DA SAN VILLAGE, DA SHUI KENG, GUANLAN TOWN, LONGHUA NEW DISTRICT, SHENZHEN, P.R.C

General Description of EUT	
Product Name:	60" SMART 4K UHD TV
Trade Name:	RCA SMARTVIRTUOSO
Model No.:	D60A114-U-A-I RNSMU6036 XXXXXXXXXXXXXXXX60XXXXXXXXXXXX (Where "X"can be any alphanumeric of a-z, A-Z or 0-9 or blank &"-".)
Adding Model(s):	N/A
Rated Voltage:	Input: AC 100-120V, 60Hz, 98W Output: USB DC 5V, 500mA
Power Adapter Model:	N/A
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	IEEE 802.11b/ g / nHT20: 2412MHz~2462MHz IEEE802.11nHT40: 2422MHz~2452MHz
Modulation:	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK)



Quantity of Channels:	11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)
Type of Antenna:	Wi-Fi Antenna
Antenna Gain:	Antenna 1: 3 dBi Antenna 2: 3 dBi
	Note: 11b,g,n uses Antenna 1 / Antenna 2 11n uses MIMO

2. Maximum Permissible Exposure

2.1 Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2, H 2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)

Frequency Range (MHz)	Electric Field Strength E (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2, H 2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	842/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

3. MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, $d=0.2\text{m}$, as well as the gain of the used antenna, the RF power density can be obtained

4. Conducted Power Result

4.1 Antenna 1

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	15.77	37.8	15±1	3.0	2.0
	2437	15.53	35.7	15±1	3.0	2.0
	2462	15.59	36.2	15±1	3.0	2.0
IEEE 802.11g	2412	10.29	10.7	10±1	3.0	2.0
	2437	10.02	10.0	10±1	3.0	2.0
	2462	10.52	11.3	10±1	3.0	2.0
IEEE 802.11n HT20	2412	9.66	9.2	9±1	3.0	2.0
	2437	10.12	10.3	10±1	3.0	2.0
	2462	9.55	9.0	9±1	3.0	2.0
IEEE 802.11n HT40	2422	8.09	6.4	8±1	3.0	2.0
	2437	7.72	5.9	7±1	3.0	2.0
	2452	7.41	5.5	7±1	3.0	2.0

4.2 Antenna 2

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	15.07	32.1	15±1	3.0	2.0
	2437	14.82	30.3	14±1	3.0	2.0
	2462	15.02	31.8	15±1	3.0	2.0
IEEE 802.11g	2412	10.22	10.5	10±1	3.0	2.0
	2437	9.81	9.6	9±1	3.0	2.0
	2462	10.81	12.1	10±1	3.0	2.0
IEEE 802.11n HT20	2412	9.35	8.6	9±1	3.0	2.0
	2437	10.31	10.7	10±1	3.0	2.0
	2462	9.82	9.6	9±1	3.0	2.0
IEEE 802.11n HT40	2422	7.08	5.1	7±1	3.0	2.0
	2437	7.73	5.9	7±1	3.0	2.0
	2452	7.05	5.1	7±1	3.0	2.0

5. Calculated Result and Limit

5.1 Antenna 1

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW /cm ²)	Limited of Power Density (S) (mW /cm ²)	Test Result
		(dBi)	(Linear)			
WiFi						
IEEE 802.11b	16	3.0	2.0	0.0158	1	Compiles
IEEE 802.11g	11	3.0	2.0	0.0050	1	Compiles
IEEE 802.11n HT20	11	3.0	2.0	0.0050	1	Compiles
IEEE 802.11n HT40	9	3.0	2.0	0.0031	1	Compiles

5.2 Antenna 2

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW /cm ²)	Limited of Power Density (S) (mW /cm ²)	Test Result
		(dBi)	(Linear)			
WiFi						
IEEE 802.11b	16	3.0	2.0	0.0158	1	Compiles
IEEE 802.11g	11	3.0	2.0	0.0050	1	Compiles
IEEE 802.11n HT20	11	3.0	2.0	0.0050	1	Compiles
IEEE 802.11n HT40	8	3.0	2.0	0.0025	1	Compiles

5.3 Antenna 1+2

Mode	Power Density (S) (mW/cm ²) Antenna 1	Power Density (S) (mW/cm ²) Antenna 2	Power Density (S) (mW/cm ²) Total	Limited of Power Density (S) (mW/cm ²)	Test Result
WiFi					
IEEE 802.11n HT20	0.0050	0.0050	0.0100	1	Compiles
IEEE 802.11n HT40	0.0031	0.0025	0.0056	1	Compiles