



LS Research, LLC



Testing Cert. # 1255.01

W66 N220 Commerce Court • Cedarburg, WI 53012 • USA

Phone: 262.375.4400 • Fax: 262.375.4248

[www.lsr.com](http://www.lsr.com)

**ENGINEERING TEST REPORT # 310090-Multitech Smartcard  
LSR Job #: C-864**

Compliance Testing of:  
Multitech with WPR

Test Date(s):  
May 17<sup>th</sup>, July 6<sup>th</sup>, August 18<sup>th</sup>, and September 27<sup>th</sup> 2010

Prepared For:



Ingersoll-Rand Company  
11819 N. Pennsylvania St.  
Carmel, IN 46074.

In accordance with:  
**Federal Communications Commission (FCC)**  
**Part 15, Subpart C, Section 15.225, 15.109 and 15.107**  
**Industry Canada (IC)**  
**RSS 210 Annex 2 and section 2.7**

**General Operating Requirements for Low-Power License-Exempt Transceivers**

This Test Report is issued under the Authority of:  
Thomas T. Smith, Manager EMC Test Services

Signature: *Thomas T. Smith* Date: 10/5/2010

**Test Report Reviewed by:**  
Thomas T. Smith, Manager EMC Test Services  
Signature: *Thomas T. Smith* Date: 10/5/10

**Authorized/Tested by:**  
Khairul Aidi Zainal, Senior EMC Engineer  
Signature: *Khairul Aidi Zainal* Date: 09/27/2010

*This Test Report may not be reproduced, except in full, without written approval of LS Research, LLC.*

## TABLE OF CONTENTS (page 1 of 2)

Description	Page
<b>EXHIBIT 1: INTRODUCTION</b>	
1.1 Scope	4
1.2 Normative References	5
1.3 LS Research, LLC Test Facility	6
1.4 Location of Testing	6
1.5 Test Equipment Utilized	6
<b>EXHIBIT 2: PERFORMANCE ASSESSMENT</b>	
2.1 Client Information	7
2.2 Equipment Under Test (EUT) Information	7
2.3 Associated Antenna Description	7
2.4 EUT's Technical Specifications	8
2.5 Product Description	9
<b>EXHIBIT 3: EUT OPERATING CONDITIONS &amp; CONFIGURATIONS DURING TESTS</b>	
3.1 Climate Test Conditions	10
3.2 Applicability & Summary of EMC Emission Test Results	10
3.3 Modifications Incorporated in the EUT for Compliance Purposes	10
3.4 Deviations & Exclusions from Test Specifications	10
<b>EXHIBIT 4: DECLARATION OF CONFORMITY</b>	
11	
<b>EXHIBIT 5: RADIATED EMISSIONS TESTING</b>	
12	
5.1 Test Setup	12
5.2 Test Procedure	12
5.3 Test Equipment Utilized	13
5.4 Test Results	13
5.5 Calculation of Radiated Emissions Limits	14
5.6 Radiated Emissions Test Data Chart	15
5.7 Test Setup Photo(s) – Radiated Emissions Test	18
5.8 Screen Captures – Radiated Emissions Test	20
<b>EXHIBIT 6: CONDUCTED EMISSIONS TEST, AC POWER LINE</b>	
24	
6.1 Test Setup	24
6.2 Test Procedure	24
6.3 Test Equipment Utilized	24
6.4 Test Results	25
6.5 FCC Limits of Conducted Emissions at the AC Mains Ports	25
6.6 Conducted Emissions Test Data Chart	26
6.7 Test Setup Photo(s) – Conducted Emissions Test	27
6.8 Screen Captures – Conducted Emissions Test	28

## **TABLE OF CONTENTS** (Page 2 of 2)

Description	Page
<b>EXHIBIT 7: OCCUPIED BANDWIDTH</b>	
7.1 Limits	29
7.2 Method of Measurements	29
7.3 Test Data	29
7.4 Screen Captures – Occupied Bandwidth	30
<b>EXHIBIT 8: BAND-EDGE MEASUREMENT</b>	
8.1 Test Criterion	31
8.2 Screen Captures	31
<b>APPENDICES</b>	
APPENDIX A: TEST EQUIPMENT LIST	32
APPENDIX B: TEST STANDARDS – RADIO	33
APPENDIX C: UNCERTAINTY STATEMENT	34

## EXHIBIT 1. INTRODUCTION

### 1.1 SCOPE

<b>References:</b>	FCC Part 15, Subpart C, Section 15.225
<b>Title:</b>	Telecommunication – Code of Federal Regulations, CFR 47, Part 15
<b>Purpose of Test:</b>	To gain FCC Certification Authorization for Low-Power License-Exempt Transmitters.

<b>References:</b>	RSS 210 Annex 2, Section A2.6
<b>Title:</b>	Low-power License-exempt Radiocommunication Devices (All Frequency Bands): Category I equipment.
<b>Purpose of Test:</b>	To gain IC Certification Authorization for Low-Power License-Exempt Transmitters.

<b>References:</b>	RSS GEN
<b>Title:</b>	General requirements and Information for the Certification of Radiocommunication Equipment.
<b>Purpose of Test:</b>	To gain IC Certification Authorization for Low-Power License-Exempt Transmitters.

<b>Test Procedures:</b>	Both conducted and radiated emissions measurements were conducted in accordance with American National Standards Institute ANSI C63.4 – American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.
<b>Environmental Classification:</b>	<ul style="list-style-type: none"><li>• Commercial, Industrial or Business</li><li>• Residential</li></ul>

Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 4 of 34</b>

## 1.2 NORMATIVE REFERENCES

Publication	Year	Title
47 CFR, Parts 0-15 (FCC)	2009	Code of Federal Regulations - Telecommunications
RSS 210 Annex 2	2007	Low-power License-exempt Radiocommunication Devices (All Frequency Bands): Category I equipment.
RSS GEN	2007	General requirements and information for the certification of Radiocommunication Equipment.
ANSI C63.4	2009	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.
CISPR 16-1-1	2006-03 A1: 2006-09 A2: 2007-07	Specification for radio disturbance and immunity measuring apparatus and methods. Part 1-1: Measuring Apparatus.
CISPR 16-2-1	2003 A1: 2004-04 A2: 2007-07	Specification for radio disturbance and immunity measuring apparatus and methods. Part 201: Conducted disturbance measurement.

Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 5 of 34</b>

### 1.3 LS Research, LLC TEST FACILITY

LS Research, LLC is accredited by A2LA (American Association for Laboratory Accreditation) to conform to ISO/IEC 17025, 2005 “General Requirements for the Competence of Calibration and Testing Laboratories”.

LS Research, LLC’s scope of accreditation includes all test methods listed herein, unless otherwise noted. A copy of the accreditation may be accessed on our web site: [www.lsr.com](http://www.lsr.com). Accreditation status can be verified at A2LA’s web site: [www.a2la2.net](http://www.a2la2.net).

### 1.4 LOCATION OF TESTING

All testing was performed at LS Research, LLC, W66 N220 Commerce Court, Cedarburg, Wisconsin, 53012 USA, utilizing the facilities listed below, unless otherwise noted.

List of Facilities Located at LS Research, LLC:

- Compact Chamber
- Semi-Anechoic Chamber
- Open Area Test Site (OATS)

### 1.5 TEST EQUIPMENT UTILIZED

A complete list of equipment utilized in testing is provided in Appendix A of this test report. Calibration dates are indicated in Appendix A. All test equipment is calibrated in accordance with A2LA standards.

Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 6 of 34</b>

## EXHIBIT 2. PERFORMANCE ASSESSMENT

### 2.1 CLIENT INFORMATION

<b>Manufacturer Name:</b>	<b>Ingersoll-Rand Company</b>
<b>Address:</b>	<b>11819 N. Pennsylvania St. Carmel, IN 46074</b>
<b>Contact Person:</b>	<b>Frank Nardelli</b>
<b>Contact Phone:</b>	317-810-3191
<b>Contact Email:</b>	fnardelli@irco.com

### 2.2 EQUIPMENT UNDER TEST (EUT) INFORMATION

*The following information has been supplied by the applicant.*

<b>Product Name:</b>	Multitech with WPR
<b>Model Number:</b>	23536758
<b>Serial Number:</b>	N/A

### 2.3 ASSOCIATED ANTENNA DESCRIPTION

There are three antennas associated with the EUT:

1. The antenna for the 125 kHz transmitter is a loop antenna made from 33 gauge wire. The coil is in series with a 1500pH tuning inductance.
2. The antenna for the 13.56 MHz transmitter is a 2 baluns, 2turn loop antenna terminated to ground and 180° out of phase. The antenna is a PCB trace around the PCB.
3. The antenna for the c0-located 900MHz modular radio is a PCB trace inverted L antenna.

Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 7 of 34</b>

## 2.4 EUT'S TECHNICAL SPECIFICATIONS

### Additional Information:

Frequency Range (in MHz)	13.56MHz
RF Power in Watts (Near-field measurement at 3 meters)	13.56 MHz transmitter: 0.00000217 Watts (Note: Every other part of the fundamental within the band were more than 40dB below the limit)
Conducted Output Power (in dBm)	Could not be measured.
Field Strength at 3 meters	13.56 MHz transmitter: 68.6 dB $\mu$ V/m
Occupied Bandwidth (99% BW)	13.56 MHz transmitter: 161.5 kHz
Type of Modulation	Un-modulated when scanning. AM when reading.
Emission Designator	13.56 MHz transmitter: 162KA1D
Transmitter Spurious (worst case) at 3 meters	34.8 dB $\mu$ V/m at 108.5 MHz
Microprocessor Model # (if applicable)	PIC24F128GB106.
EUT will be operated under FCC Rule Part(s)	CFR 47 part 15.225 and 15.109
Antenna Information:	
a) Antenna Type	1. 2 (Two) 2-turn PCB loop antennas 180° out of phase. 2. Loop antenna made from 33 gauge wire.
b) Detachable/Non-Detachable	Non-detachable.
c) Antenna Gain (in dBi)	Not available.
Modular Filing	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Portable or Mobile?	Mobile


Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 8 of 34</b>



## 2.5 PRODUCT DESCRIPTION

The Multitech reader is one of IR's ACP (Access Control Point) that can be paired with any of IR's access point modules. The Multitech ACP in this case is paired with a WPR which provides a wireless link with access point modules. The WPR implements a modular RF transceiver operating in the 902 to 928 MHz ISM band. Information contained in the user credential is read by the Multitech reader via either 125 kHz (PROX) or 13.56 MHz (SmartCard) signal and relayed by the WPR to access point modules which control lock functions and maintains audit trails of the credential used.

The Multitech gets its power from the WPR which runs on a rechargeable battery. The WPR can only supply power to the Multitech reader when it is switched to the battery operated mode and not while it is in the charging mode.



WPR (Left) and Multitech reader (Right)

Multitech reader attached to WPR

WPR AC to Dc converter.



Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 9 of 34</b>

## EXHIBIT 3. EUT OPERATING CONDITIONS & CONFIGURATIONS DURING TESTS

### 3.1 CLIMATE TEST CONDITIONS

Temperature:	71° Fahrenheit
Humidity:	44%
Pressure:	743 mmHg

### 3.2 APPLICABILITY & SUMMARY OF EMC EMISSION TEST RESULTS

FCC Paragraph	Test Requirements	Compliance (yes/no)
FCC : 15.107 IC : RSS GEN 7.2.2	Power Line Conducted Emissions Measurements	Yes
IC: RSS GEN 4.6	Occupied Bandwidth	Yes
FCC : 15.109 IC : RSS 210 2.6	Un-Intentional Radiated Emissions	Yes
FCC : 15.225 (a) IC : RSS 210 A2.6 (a)	Maximum RF Output Power	Yes
FCC : 15.225 (d) IC : RSS 210 A2	Maximum RF Spurious Emissions	Yes
FCC : 15.209 & 15.205 IC : RSS 210 A2 and 2.6	Transmitter General Radiated Emissions	Yes
FCC: 15.225 (d)	Band edge requirements	Yes

### 3.3 MODIFICATIONS INCORPORATED IN THE EUT FOR COMPLIANCE PURPOSES

None  Yes (explain below)

### 3.4 DEVIATIONS & EXCLUSIONS FROM TEST SPECIFICATIONS

None  Yes (explain below)

Note:

The radio was also tested for **co-location** phenomenon since there would be a case where the Multitech reader is transmitting at the same time as the 900MHz modular transceiver.

**There will be no instance when the 125 kHz and 13.56 MHz transmitter is transmitting simultaneously therefore co-location phenomenon was not tested for between these two transmitters.**

Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	Page 10 of 34

## EXHIBIT 4. DECLARATION OF CONFORMITY

The EUT was found to **MEET** the requirements as described within the specification of FCC Title 47, CFR Part 15.225, and Industry Canada RSS-210, Issue 7 (2007), Annex A2.6 for a Low-Power License-Exempt Transmitters, as well as the specification of FCC Title 47, CFR Part 15.109, Part 15.107 and Industry Canada RSS-210, Issue 7 (2007), Section 7 for non-intentional radiators.

If some emissions are seen to be within 3 dB of their respective limits:

As these levels are within the tolerances of the test equipment and site employed, there is a possibility that this unit, or a similar unit selected out of production may not meet the required limit specification if tested by another agency.

LS Research, LLC certifies that the data contained herein was taken under conditions that meet or exceed the requirements of the test specifications. The results in this Test Report apply only to the item(s) tested on the above-specified dates. Any modifications made to the EUT subsequent to the indicated test date(s) will invalidate the data herein, and void this certification.

Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 11 of 34</b>

## EXHIBIT 5. RADIATED EMISSIONS TEST

### 5.1 Test Setup

The test setup was assembled in accordance with Title 47, CFR FCC Part 15, RSS GEN and ANSI C63.4. The Multitech with the WPR, henceforth referred to as the EUT, was placed on an 80cm high non-conductive pedestal, centered on a flush mounted 2-meter diameter turntable inside a 3 meter Semi-Anechoic, FCC listed Chamber.

**Testing of the Multitech reader was performed on a reader that includes a keypad since this configuration was deemed to have worse emission characteristics compared to the Multitech reader without keypad. The radio portion of Multitech with keypad reader is exactly the same as that of the Multitech reader with no keypad. The difference lies in the components involving the keypad itself.**

**Testing was also performed to investigate the effects of a co-located 900MHz modular transceiver on the RF characteristics of the Multitech.**

**In addition, the emissions of the WPR while in charging mode was also investigated.**

For the first test, the EUT was set in a configuration where it continuously transmits at 13.56 MHz. Its operation was then validated using a card set to work at the selected mode. In addition, the EUT was also set in a configuration where the Multitech and the 900MHz modular transceiver were simultaneously transmitting. Initial measurements were performed at 3m separation to identify the emissions below 30MHz and all identified emissions were then re-measured at a 10m separation distance.

For the second test, the WPR was connected to the AC mains and the switch was positioned to the charging mode.

### 5.2 Test Procedure

Radiated RF measurements were performed on the EUT in a 3 meter Semi-Anechoic, FCC listed Chamber. The frequency range from 10 kHz to 1000 MHz was scanned and investigated. In cases where emissions below 30MHz were found, measurements of those emissions were repeated on the OATS at a 10m measurement distance. The radiated RF emission levels were manually noted at the various fixed degree settings of azimuth on the turntable and antenna height. The EUT was placed on a non-conductive pedestal in the 3 meter Semi-Anechoic Chamber, with the antenna mast placed such that the antenna was 3 meters from the EUT. A Biconical Antenna was used to measure emissions from 30 MHz to 300 MHz, and a Log Periodic Antenna was used to measure emissions from 300 MHz to 1000 MHz. For emissions below 30 MHz, an active loop antenna was used. This loop antenna was set at a height of 1m above the conducting ground plane and it was rotated about its vertical and horizontal axes (while utilizing the turntable to rotate the EUT) in order to measure the maximum radiated RF emissions. The maximum radiated RF emissions above 30MHz were found by raising and lowering the antenna between 1 and 4 meters in height, using both horizontal and vertical antenna polarities and rotating the EUT using the turntable.

The receiver was operated with the resolution bandwidth set at 200 Hz for measurements between 9kHz and 150kHz, 9kHz for measurements between 150kHz and 30MHz and 120kHz for measurements between 30MHz and 1000 MHz.

Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 12 of 34</b>

### **5.3 Test Equipment Utilized**

A list of the test equipment and antennas utilized for the Radiated Emissions test can be found in Appendix A. This list includes calibration information and equipment descriptions. All equipment is calibrated and used according to the operation manuals supplied by the manufacturers. All calibrations of the antennas used were performed at an N.I.S.T. traceable site. In addition, the Connecting Cables were measured for losses using a calibrated Signal Generator and an Agilent E4445A/N9039A EMI System. The resulting correction factors and the cable loss factors from these calibrations were entered into the EMI Receiver database. As a result, the data taken from the EMI Receiver accounts for the antenna correction factor as well as cable loss or other corrections, and can therefore be entered into the database as a corrected meter reading. The EMI Receiver was operated with resolution bandwidths as prescribed in ANSI C63.4.

### **5.4 Test Results**

The Multitech and WPR were found to **MEET** the Radiated Emissions requirements of Title 47 CFR, FCC Part 15.225 [Canada RSS-210, Issue 7 (2007), Annex 2 A2.6] and part 15.109. The frequencies with significant RF signal strength were recorded and plotted as shown in the Data Charts and Graphs.

The voltage variation test revealed that the EUT showed no variation in power and frequency. The power was then cycled On/Off to observe system response. No unusual response was observed, the emission characteristics were within compliant parameters, and the system returned to the same state of operation as before the power cycle.

**The EUT also did not cause or have adverse phenomenon when the 900MHz modular transmitter was transmitting simultaneously.**

Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 13 of 34</b>

## 5.5 CALCULATION OF RADIATED EMISSIONS LIMITS

### Transmitter Limits

The maximum peak output power of an intentional radiator in the 13.553-13.56 MHz band, as specified in Title 47 CFR 15.225 and RSS 210 Annex A2.6, is described below. The harmonic and spurious RF emissions, with appropriate receiver bandwidths, as specified in 15.225 (d) and section 2.7 of RSS 210, shall be below the measured power of the desired signal, and must also meet the requirements described in 15.209 and 15.205(c) for FCC and table 1 of RSS 210 where applicable.

At 30m, the fundamental field strength shall not exceed 15848  $\mu\text{V}/\text{m}$  or 84  $\text{dB}\mu\text{V}/\text{m}$ .

At 3m, a correction factor of 20dB ( $20\log(30\text{m}/3\text{m})$ ) is used to adjust the limit which becomes:

Field strength = 104  $\text{dB}\mu\text{V}/\text{m}$  at 3m.

At 10m, a correction factor of 9.54dB ( $20\log(30\text{m}/10\text{m})$ ) is used to adjust the limit which becomes:

Field strength = 93.5  $\text{dB}\mu\text{V}/\text{m}$  at 10m.

The following table depicts the general radiated emission limits. These limits are obtained from Title 47 CFR, Part 15.209, for radiated emissions measurements and are comparable to that of table 3 in RSS 210 section 2.7. These limits were applied to the spurious emission of the intentional radiator as well as all other significant spurious signals.

Frequency (MHz)	Limit $\mu\text{V}/\text{m}$	Limit ( $\text{dB}\mu\text{V}/\text{m}$ )	Measurement Distance (m)
0.009-0.490	2400/F (kHz)	Note 1	300
0.490-1.705	24000/F (kHz)		30
1.705-30.0	30		30
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
960-24,000	500	54.0	3

#### Note 1: Sample calculation for the Fundamental Emission of a transmitter:

For Example:

If a transmitter operates at a fundamental frequency of 25 kHz, the emission limit may be calculated:

$2400/F = 2400/25 = 96.0 \mu\text{V}/\text{m}$  if measured at 300 meters separation.

Expressed in decibels:  $20 \log_{10} (96.0) = 39.64 \text{ dB}\mu\text{V}/\text{m}$  at 300 m separation.

At 3 meters separation, the limit may be extrapolated by the addition of 40 dB/decade per 47CFR 15.31(f)(2)

Limit for the fundamental emission =  $39.64 \text{ dB}\mu\text{V}/\text{m} + 80 \text{ dB} = 119.6 \text{ dB}\mu\text{V}/\text{m}$  at 3 meters

#### Sample conversion from field strength $\mu\text{V}/\text{m}$ to $\text{dB}\mu\text{V}/\text{m}$ :

$$\begin{aligned} \text{dB}\mu\text{V}/\text{m} &= 20 \log_{10} (100) \\ &= 40 \text{ dB}\mu\text{V}/\text{m} \text{ (from 30-88 MHz)} \end{aligned}$$

Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 14 of 34</b>

## 5.6

**RADIATED EMISSIONS DATA CHART**

Measurements of Electromagnetic Radiated Emissions

Frequency Range Inspected: 9 kHz to 1000 MHz

Manufacturer:	Ingersoll-Rand Company				
Date(s) of Test:	May 17 <sup>th</sup> , July 6 <sup>th</sup> , and August 18 <sup>th</sup> 2010				
Project Engineer:	Khairul Aidi Zainal				
Test Engineer(s):	Khairul Aidi Zainal				
Voltage:	12.0 VDC (Multitech) and 120 VAC				
Operation Mode:	Continuous transmit (Multitech) and charging (WPR)				
Environmental Conditions in the Lab:	Temperature: 20 – 25° C Relative Humidity: 30 – 60 %				
EUT Power:	√	Single Phase 120VAC		3 Phase ___ VAC	
	√	Rechargeable Battery		Other:	
EUT Placement:	√	80cm non-conductive table		10cm Spacers	
EUT Test Location:	√	3 Meter Semi-Anechoic FCC Listed Chamber	√	10m OATS	
Measurements:		Pre-Compliance		Preliminary	√ Final
Detectors Used:	√	Peak	√	Quasi-Peak	√ Average

Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 15 of 34</b>

The following tables depict the level of significant fundamental and spurious radiated RF emissions found:

**A. 13.56 MHz transmitter (SmartCard) emissions.**

Due to the nature of the device, transmit and receive functions could not be isolated, hence the data presented below are for both transmit and receive mode:

i. 3 meter measurement

Frequency MHz	Antenna	EUT	Height (m)	Azimuth (0° - 360°)	Peak (dBuV/m)	Q.Peak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Notes
13.6	V	V	1.00	358	68.6	68.6	68.6	104.0	35.4	Note 4
27.1	V	V	1.00	258	32.3	28.9	19.4	69.5	40.6	
40.7	V	V	1.03	99	34.8	27.8	15.3	40.0	12.2	
54.2	V	V	1.08	96	29.7	23.7	13.6	40.0	16.3	
67.8	V	V	1.00	288	31.1	24.9	14.0	40.0	15.1	
81.4	V	V	1.00	100	29.4	24.7	13.8	40.0	15.3	
94.9	V	V	1.00	87	31.1	26.2	14.8	43.5	17.3	
108.5	H	F	1.00	92	35.7	34.8	21.1	43.5	8.7	
122.0	V	S	1.05	65	22.3	19.4	9.5	43.5	24.1	
135.6	V	S	1.00	19	22.3	18.6	9.3	43.5	24.9	
216.9	H	S	1.30	272	33.8	32.0	21.2	46.0	14.0	

Notes:

- 1) An Average and quasi peak Detector function was used in measurements below 30 MHz, a Quasi-Peak Detector was used in measurements between 30 MHz and 1 GHz.
- 2) H = Horizontal; V = Vertical; S = Side; F = Flat
- 3) Measurements below 30MHz were performed at 3m and 10m separation distance. The limits were corrected to reflect the change in measurement distance.
- 4) Data represents peak emission of the fundamental. All other parts of the fundamental emission within the allowed band are more than 40dB below the limit.

ii. 10 meter measurement

Frequency MHz	Antenna	EUT	Height (m)	Azimuth (0° - 360°)	Peak (dBuV/m)	Q.Peak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Notes
13.6	V	V	1.00	7	45.2	45.2	45.2	93.5	48.3	Note 5
27.1										Note 3

Notes:

- 1) An Average and quasi peak Detector function was used in measurements below 30 MHz, a Quasi-Peak Detector was used in measurements between 30 MHz and 1 GHz.
- 2) H = Horizontal; V = Vertical; S = Side; F = Flat
- 3) Emission buried within system noise floor.
- 4) Measurements below 30MHz were performed at 3m and 10m separation distance. The limits were corrected to reflect the change in measurement distance.
- 5) Data represents peak emission of the fundamental. All other parts of the fundamental emission within the allowed band are more than 40dB below the limit.

Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	Page 16 of 34



**B. WPR charging mode emissions.**

Frequency MHz	Antenna	EUT	Height (m)	Azimuth (0° - 360°)	Peak (dBuV/m)	Q.Peak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)
994.9	Note 3				36.6	29.7	23.1	54.0	24.3
693.2	Note 3				31.8	25.5	19.0	46.0	20.5
284.7	Note 3				30.6	23.8	17.3	46.0	22.2
80.0	V	V	1.00	131	33.7	29.2	20.3	40.0	10.8
42.5	V	V	1.00	118	43.0	39.6	30.9	40.0	0.4
39.3	V	V	1.00	67	39.1	34.5	35.7	40.0	5.6


Notes:

- 1) An Average and quasi peak Detector function was used in measurements below 30 MHz, a Quasi-Peak Detector was used in measurements between 30 MHz and 1 GHz.
- 2) H = Horizontal; V = Vertical; S = Side; F = Flat
- 3) Recorded data is that of the system noise floor at the corresponding frequency.

Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 17 of 34</b>

## 5.7 Test Setup Photo(s) – Radiated Emissions Test

### A. Multitech Emissions testing setup.



Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 18 of 34</b>

B. WPR charging mode emissions testing setup.



Vertical (V) orientation



Side (S) orientation



Flat (F) orientation



Rear view of EUT


Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 19 of 34</b>

## 5.8 Screen Captures - Radiated Emissions Testing

These screen captures represent Peak Emissions. For radiated emission measurements, a Quasi-Peak or Average detector function is utilized when measuring frequencies below 1 GHz.


The signature scans shown here are from worst-case emissions with the sense antenna in either vertical or horizontal polarity for worst case presentations.

### A. 13.56 MHz transmitter (SmartCard)




Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 20 of 34</b>

### 150 kHz-1MHz, at 3m




### 1 MHz to 30 MHz, at 3m




Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #: 310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	Page 21 of 34



### 30 MHz to 300 MHz, at 3m



### 300 MHz to 1000 MHz, at 3m




It was also determined that while both the 900MHz modular radio and the 13.56 MHz transmitter were simultaneously transmitting, there were no unexpected RF anomalies within the 30 MHz to 1000 MHz range.


Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	Page 22 of 34

B. WPR charging mode.

30 MHz to 300 MHz, at 3m



300 MHz to 1000 MHz, at 3m



## EXHIBIT 6. CONDUCTED EMISSIONS TEST, AC POWER LINE

### 6.1 Test Setup

The test area and setup are in accordance with ANSI C63.4 and with Title 47 CFR, FCC Part 15 (Industry Canada RSS-210, Issue 7, 2007). The EUT was placed on a non-conductive wooden table, with a height of 80 cm above the reference ground plane. The EUT's power cable was plugged into a 50Ω (ohm), 50/250 μH Line Impedance Stabilization Network (LISN). The AC power supply of 120V was provided via an appropriate broadband EMI Filter, and then to the LISN line input. Final readings were then taken and recorded. After the EUT was setup and connected to the LISN, the RF Sampling Port of the LISN was connected to a 10 dB Attenuator-Limiter, and then to the Agilent E4445A/N9039A EMI System. The EMCO LISN used has the ability to terminate the unused port with a 50Ω (ohm) load when switched to either L1 (line) or L2 (neutral).

### 6.2 Test Procedure

The WPR **charging mode** was investigated for this portion of the testing. The WPR was powered by the supplied 12VDC AC to DC adaptor which was connected to the Mains network via a calibrated LISN. The WPR was then switched to the '**charging mode**' via a switch on the WPR. The appropriate frequency range and bandwidths were selected on the EMI Receiver, and measurements were made. The bandwidth used for these measurements is 9 kHz, as specified in CISPR 16-1 Section 1, Table 1, for Quasi-Peak and Average detectors in the frequency range of 150 kHz to 30MHz. Final readings were then taken and recorded.

### 6.3 Test Equipment Utilized

A list of the test equipment and accessories utilized for the Conducted Emissions test is provided in Appendix A. This list includes calibration information and equipment descriptions. All equipment is calibrated and used according to the operation manuals supplied by the manufacturers. Calibrations of the LISN and Limiter are traceable to N.I.S.T. All cables are calibrated and checked periodically for conformance. The emissions are measured on the Agilent E4445A/N9039A EMI System, which has automatic correction for all factors stored in memory and allows direct readings to be taken.

Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 24 of 34</b>



#### 6.4 Test Results

The EUT was found to **MEET** the Conducted Emission requirements of FCC Part 15.107 and RSS GEN 7.2.2 Conducted Emissions. See the Data Charts and Graphs for more details of the test results.

#### 6.5 FCC Limits of Conducted Emissions at the AC Mains Ports

Frequency Range (MHz)	Class B Limits (dB $\mu$ V)		Measuring Bandwidth
	Quasi-Peak	Average	
0.150 -0.50 *	66-56	56-46	RBW = 9 kHz VBW $\geq$ 9 kHz for QP VBW = 1 Hz for Average
0.5 – 5.0	56	46	
5.0 – 30	60	50	
* The limit decreases linearly with the logarithm of the frequency in this range.			

## 6.6

**CONDUCTED EMISSIONS – TEST DATA CHART**


Frequency Range inspected: 150 KHz to 30 MHz

Manufacturer:	Ingersoll-Rand Company				
Date(s) of Test:	September 27 <sup>th</sup>				
Test Engineer:	Khairul Aidi Zainal				
Voltage:	120 VAC				
Operation Mode:	Charging				
Environmental Conditions in the Lab:	Temperature: 20 – 25° C Relative Humidity: 30 – 60 %				
Test Location:	√	AC mains test bench			Chamber
EUT Placed On:	√	40cm from Vertical Ground Plane	√		10cm Spacers
	√	80cm above Ground Plane			Other:
Measurements:		Pre-Compliance		Preliminary	√ Final
Detectors Used:		Peak	√	Quasi-Peak	√ Average

Frequency (MHz)	Line	<u>QUASI-PEAK</u>			<u>AVERAGE</u>		
		Q-Peak Reading (dBμV)	Q-Peak Limit (dBμ V)	Quasi-Peak Margin (dB)	Average Reading (dBμV)	Average Limit (dBμ V)	Average Margin (dB)
0.350	1.0	48.3	59.0	10.7	33.8	49.0	15.1
0.557	1.0	42.8	56.0	13.2	30.6	46.0	15.4
1.498	1.0	43.9	56.0	12.2	28.2	46.0	17.8
0.252	2.0	44.3	61.7	17.4	27.4	51.7	24.3
0.283	2.0	37.2	60.7	23.5	24.8	50.7	25.9
0.597	2.0	37.4	56.0	18.6	21.9	46.0	24.1

Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 26 of 34</b>

6.7 Test Setup Photo(s) – Conducted Emissions Test




Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 27 of 34</b>


## 6.8 Screen Captures – Conducted Emissions Test

These screen captures represent Peak Emissions. For conducted emission measurements, both a Quasi-Peak detector function and an Average detector function are utilized. The emissions must meet both the Quasi-peak limit and the Average limit as described in 47 CFR 15.107 and RSS GEN 7.2.2.

### Line 1



### Line 2



## EXHIBIT 7. OCCUPIED BANDWIDTH

### 7.1 Limits

There are no stated limits for the occupied bandwidth for devices operating under 47CFR Part 15.225. However it is required by Industry Canada per RSS GEN 4.6

### 7.2 Method of Measurements

ANSI C63.4, FCC and IC standard procedures were adhered to in these measurements.

The transmitter output was placed in normal operation mode. The bandwidth of the fundamental frequency was measured via radiated measurement with the Spectrum Analyzer using RBW=9kHz and VBW=91 kHz for the 13.56MHz transmitter.


### 7.3 Test Data

Mode	Center Frequency (MHz)	Measured -20 dBc Occ.Bw (kHz)
13.56 MHz reader.	13.560	161.5

Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 29 of 34</b>

## 7.4 Screen Captures - OCCUPIED BANDWIDTH

### -20 dBc Occupied Bandwidth



Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 30 of 34</b>


## EXHIBIT 8. BAND EDGE MEASUREMENT.

### 8.1 Test Criterion

FCC 15.225() requires a measurement of spurious emission levels to be no higher than the general radiated emissions limits in 15.209, in particular at the Band-Edges where the intentional radiator operates.

### 8.2 Screen captures.


#### 13.56 MHz (SmartCard) transmitter.




Screen capture shows that outside of the band of operation, the emissions are below the general emissions limit as stated in Title 47 CFR Part 15 section 209.

Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	Page 31 of 34

## APPENDIX A

 <b>LS RESEARCH LLC</b> Wireless Product Development Equipment Calibration		Date : 6-Jul-2010		Type Test : Radiated emissions		Job # : C-864		
		Prepared By: Aidi		Customer : Ingersoll Rand		Quote #: 310090		
No.	Asset #	Description	Manufacturer	Model #	Serial #	Cal Date	Cal Due Date	Equipment Status
1	EE 960158	RF Preselector	Agilent	N9039A	MY46520110	6/7/2010	6/7/2011	Active Calibration
2	EE 960157	3Hz-13.2GHz Spectrum Analyzer	Agilent	E4445A	MY48250225	6/7/2010	6/7/2011	Active Calibration
3	AA 960078	Log Periodic Antenna	EMCO	93146	9701-4855	10/16/2009	10/16/2010	Active Calibration
4	AA 960150	Bicon Antenna	ETS	3110B	0003-3346	11/3/2009	11/3/2010	Active Calibration
5	AA 960006	Active Loop Antenna	EMCO	6502	9205-2753	9/14/2009	9/14/2011	Active Calibration
Project Engineer: Aidi			Quality Assurance: Tom Smith					

 <b>LS RESEARCH LLC</b> Wireless Product Development Equipment Calibration		Date : 6-Jul-2010		Type Test : Conducted Emissions		Job # : C-864		
		Prepared By: Aidi		Customer : Ingersoll Rand		Quote #: 310090		
No.	Asset #	Description	Manufacturer	Model #	Serial #	Cal Date	Cal Due Date	Equipment Status
1	EE 960153	RF Preselector	Agilent	N9039A	MY46520110	6/7/2010	6/7/2011	Active Calibration
2	EE 960157	3Hz-13.2GHz Spectrum Analyzer	Agilent	E4445A	MY48250225	6/7/2010	6/7/2011	Active Calibration
3	AA 960008	LISN	EMCO	3816/2NM	9701-1057	12/15/2009	12/15/2010	Active Calibration
4	AA 960031	Transient Limiter	HP	11947A	3107A01708	9/15/2009	9/15/2010	Active Calibration
Project Engineer: Aidi			Quality Assurance: Tom Smith					

Prepared For: Ingersoll-Rand Company	Model #: 23536758	LS Research, LLC
EUT: Multitech with WPR	IC: 8053B-ADMULTI	Template: 15.209 - v1 10-22-09
Report #:310090-Multitech Smartcard	FCC ID #: XPB-ADMULTI	<b>Page 32 of 34</b>





**APPENDIX C**  
**Uncertainty Statement**

This uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level, using a coverage factor of k=2.

*Table of Expanded Uncertainty Values, (K=2) for Specified Measurements*

Measurement Type	Particular Configuration	Uncertainty Values
Radiated Emissions	3 – Meter chamber, Biconical Antenna	4.24 dB
Radiated Emissions	3-Meter Chamber, Log Periodic Antenna	4.8 dB
Radiated Emissions	10-Meter OATS, Biconical Antenna	4.18 dB
Radiated Emissions	10-Meter OATS, Log Periodic Antenna	3.92 dB
Conducted Emissions	Shielded Room/EMCO LISN	1.60 dB
Radiated Immunity	3 Volts/Meter in 3-Meter Chamber	1.128 Volts/Meter
Conducted Immunity	3 Volts level	1.0 V