

Willow Run (WR) Test Labs, Inc. 7117 Fieldcrest Drive Brighton, MI 48116 Phone: (734) 252-9785, e-mail: info@wrtest.com

## **RF EXPOSURE CALCULATIONS**

## **Requirement:**

According to USA CFR 15 §1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. For Canada, RSS-102 sets out the requirements and measurement techniques used to evaluate radio frequency (RF) exposure compliance of radiocommunication apparatus designed to be used within the vicinity of the human body.

## Maximum Permissible Exposure Calculations:

	Meas. Distance:	3 meters
	EUT Mode:	Worst Case
Min. Sep. Distance: 20 cm (Mobile)	EUT:	Allegion RC11
IC REF: RSS-102 Issue 5, Safety Code 6	Test Engineer:	Joseph Brunett
USA REF: 1.1310, 2.1091/1093, 447498 D01 General RF Exposure Guidance v06	Test Date:	18-Dec-19

					Canada ISED RSS-102 MPE			USA FCC 1.1310 MPE		MPE
Mode	Freq.	Worst Case E3(Avg)*	E20cm(Avg)	H20cm(Avg)	SC6 Limit (E20cm)	SC6 Limit (H20cm)	Worst Case MPE Ratio	E20cm Limit***	H20cm Limit***	Worst Case MPE Ratio
	MHz	dBuV/m	dBuV/m	dBuA/m	dBuV/m	dBuA/m		dBuV/m	dBuA/m	
LF Entry	0.12500	70.2	117.2	65.9		135.3	0.0003	175.8	124.2	0.0012
LF Entry	13.56000	64.0	111.0	59.7	148.8	97.2	0.0133	155.7	104.2	0.0060
Mode	Freq.	Worst Case EIRP(Avg)**	E20cm(Avg)	S20cm(Avg)****		SC6 Limit (S20cm)	MPE Ratio		S Limit	MPE Ratio
	MHz	dBm	dBuV/m	mW/cm2		mW/cm2			mW/cm2	
BLE (module)	2400-2483.5	11.15000	129.87183	0.00259		5.47422	0.0005		1.00000	0.0026
						MPE Total (<1):	.014		MPE Total (<1):	.010
						Complies?	Yes		Complies?	Yes

As Measured / Computed from highest fundamental emission, see fundamental emission section of this report.

\*\*EIRP, as computed from Modular Device RF Exposure Exhibits. \*\*\* For FCC MPE, use of 300 kHz limit at 125 kHz as previously allowed by FCC. \*\*\*\* EIRP (mW) = S (mW/cm<sup>2</sup>) x 4 x PI x 20cm<sup>2</sup>

## Summary:

The EUT with all transmitters is compliant with both the FCC power density limit and the ISED Exposure Evaluation limits.