ONE WORLD OUR APPROVAL



## Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

- P = power input to the antenna
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at device output terminal: _ Cable and Jumper loss:	<u>22.94</u> dBm 0.0 dB
Maximum peak output power at antenna input terminal:	22.94 dBm
	196.788629 mW
Single Antenna gain (typical):	<u>9</u> dBi
Number of Antennae:	1
Total Antenna gain (typical):	<u> </u>
	7.943282347 (numeric)
Prediction distance:	<u>20</u> cm
Prediction frequency:	<u>2402</u> MHz
MPE limit for uncontrolled exposure at prediction frequency:	<u>1</u> mW/cm <sup>2</sup>
Power density at prediction frequency:	0.310978 mW/cm <sup>2</sup>
Power density at prediction frequency:	
Power density at prediction frequency: Tx On time:	<b>0.310978 mW/cm<sup>2</sup></b> 3.109783 W/m <sup>2</sup> 1.000000 ms
Tx On time:	3.109783 W/m <sup>2</sup> 1.000000 ms
	3.109783 W/m <sup>2</sup> 1.000000 ms
Tx On time: Tx period time:	3.109783 W/m <sup>2</sup> 1.000000 ms 1.000000 ms
Tx On time: Tx period time: Average Factor:	3.109783 W/m <sup>2</sup> 1.000000 ms 1.000000 ms 100.000000 %