

InterLab[®]

RF Exposure and Maximum ERP/EIRP Assessment

For

EMMY-W163

FCC ID XPYEMMYW163

IC: 8595A-EMMYW163

Assessment Reference: MDE_UBLOX_1551_MPEb

Test Laboratory:

7layers GmbH
Borsigstrasse 11
40880 Ratingen
Germany



Note:

The following test results relate only to the devices specified in this document. This report shall not be reproduced in parts without the written approval of the test laboratory.

7layers GmbH

Borsigstraße 11
40880 Ratingen, Germany
T +49 (0) 2102 749 0
F +49 (0) 2102 749 350

Geschäftsführer/
Managing Directors:
Frank Spiller
Bernhard Retka
Alexandre Norré-Oudard

Registergericht/registered:
Düsseldorf HRB 75554
USt-Id.-Nr./VAT-No. DE203159652
Steuer-Nr./TAX-No. 147/5869/0385

*a Bureau Veritas
Group Company*

www.7layers.com

Table of Contents

0	Summary	3
0.1	Technical Report Summary	3
1	Administrative Data	4
1.1	Testing Laboratory	4
1.2	Project Data	4
1.3	Applicant Data	4
1.4	Manufacturer Data	4
2	Test object Data	5
2.1	General EUT Description	5
2.2	EUT Main components	6
2.3	Ancillary Equipment	7
2.4	Auxiliary Equipment	7
3	Evaluation Results	8
3.1	RF Exposure Evaluation	8
3.2	RF Exposure Evaluation for multiple transmitters in co-location	11

0 Summary

0.1 Technical Report Summary

Type of Report

RF Exposure and Maximum ERP/EIRP Assessment for a UMTS/LTE radio module. Including RF Exposure for use with co-located radios on generic host device.

Applicable FCC Rules

For RF Exposure:

OET Bulletin 65 Edition 97-01 August 1997

FCC 47 CFR §1.1307

FCC 47 CFR §1.1310

RSS-102 Issue 5 – March 2015

Report version control			
Version	Release date	Changes	Version validity
000	2016-08-18	Initial version	Valid

Responsible for
Accreditation Scope:



Responsible
for Report:



1 Administrative Data

1.1 Testing Laboratory

Company Name: 7Layers GmbH
Address Borsigstr. 11
40880 Ratingen
Germany

This facility has been fully described in a report submitted to the FCC and accepted under the registration number 96716.

The test facility is also accredited by the following accreditation organisation:
Laboratory accreditation no.: DAKKS D-PL-12140-01-01

Responsible for Accreditation Scope: Dipl.-Ing. Bernhard Retka
Dipl.-Ing. Robert Machulec
Dipl.-Ing. Andreas Petz
Dipl.-Ing. Marco Kullik

Report Template Version: 2016-05-15

1.2 Project Data

Responsible for assessment and report: Mr. Patrick Lomax
Date of Report: 2016-08-10

1.3 Applicant Data

Company Name: u-blox AG
Address: Zürcherstrasse 68,
CH-8800 Thalwil
Switzerland
Contact Person: Giulio Comar

1.4 Manufacturer Data

Company Name: please see applicant data
Address:
Contact Person:

2 Test object Data

2.1 General EUT Description

Kind of Device product description	WLAN 2.4 GHz, 5 GHz, BT, NFC, SRD (5.8 GHz) - Single Antenna
Product name	Host-based multiradio module with Wi-Fi, Bluetooth and NFC
Type	EMMY-W161
Declared EUT data by the supplier	
Voltage Type	DC
Voltage Level	normal: 3.3 V DC low: 3.0 V DC high: 3.6 V DC
Modulation Type	Bluetooth LE: GFSK, Bluetooth GFSK, pi/4-DQPSK, 8DPSK WLAN: DSSS, OFDM, HT20 MCS0 – MCS7, HT40 MCS0 –MCS7 please see each test protocol
General product description	EMMY-W161 and EMMY-W163 are ultra-compact multi-radio modules providing Wi-Fi, Classic Bluetooth, Bluetooth low energy and NFC mode of operation. It is designed for both simultaneous and independent operations of: <ul style="list-style-type: none"> • Wi-Fi IEEE 802.11ac and a/b/g/n • Dual-mode Bluetooth 4.2 • NFC
Specific product description for the EUT	EMMY-W163: Shielded module, separate antenna pins for WLAN 802.11 ac/a/b/g/n and Bluetooth communication
The EUT provides the following ports:	- DC power supply - antenna port - signal ports
Data rates	Bluetooth LE, GFSK: 1 Mbit/s BDR, BT GFSK (1-DH1) BDR, BT GFSK (1-DH5) EDR 2, BT pi/4 DQPSK (2-DH1) EDR 3, BT 8-DPSK (3-DH1) WLAN b: please see chapter WLAN g: please see chapter WLAN n 20 MHz: please see chapter WLAN n 40 MHz: please see chapter WLAN ac 20: please see chapter WLAN ac 40: please see chapter WLAN ac 80: please see chapter

2.2 EUT Main components

Type, S/N, Short Descriptions etc. used in this Test Report

Sample Name	Sample Code		Description		
DE1015032da01	da01		Conducted Sample "#4"		
Sample Parameter	Value				
Antenna	Antenna connector on evaluation board (target platform): The following antennas are designated for 2.4 and 5 GHz WLAN transmission on EMMY-W161, as well as Bluetooth on EMMY-W161. - Table 2 of Test Object Specification:				
			Peak gain [dBi]		
#	Manufacturer	Part number	Antenna type	2.4 GHz band	5 GHz band
W1	Antenova	A10194 [1]	SMD chip antenna 10x10x0.9 [mm]	1.8	4.1
W2	Linx	ANT-DB1-RAF-RPS [4]	Dual-band dipole antenna	2.5	4.6
W3	Taoglas	GW.40.2153	Dual-band dipole antenna	3.74	2.5
W4	Taoglas	GW.59.3153 [5]	Dual-band dipole antenna	2.37	2.93
W5	Walsin	RFDPA870900SBLB8G1	Dual-band dipole antenna	2	3
W6	Linx	ANT-2.4-CW-RCT-RP [3]	Single-band dipole antenna	2.2	N/A
W7	Delock	88395 [6]	Dual-band dipole antenna	1.5	2.1
Serial No.	-				
HW Version	03				
SW Version	N/A				
Comment	-				
Sample Name	Sample Code		Description		
DE1015032ca01	bb01		Conducted Sample "#3"		
Sample Parameter	Value				
Integral Antenna	Antenna on evaluation board (target platform): Antenova, Type A10194, SMD chip antenna, 1.8 dBi Peak gain in 2.4 GHz band, 4.1 dBi Peak gain in 5 GHz band				
Serial No.	-				
HW Version	03				
SW Version	N/A				
Comment	-				

NOTE: The short description is used to simplify the identification of the EUT in this test report.

2.3 Ancillary Equipment

For the purposes of this test report, ancillary equipment is defined as equipment which is used in conjunction with the EUT to provide operational and control features to the EUT. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Ancillary Equipment can influence the test results.

Device	Details (Manufacturer, Type Model, OUT Code)	Description
Evaluation board (target platform)	u-blox , 03, -, -	u-blox EVB-W16

2.4 Auxiliary Equipment

For the purposes of this test report, auxiliary equipment is defined as equipment which is used temporarily to enable operational and control features especially used for the tests of the EUT which is not used during normal operation or equipment that is used during the tests in combination with the EUT but is not subject of this test report. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Auxiliary Equipment can influence the test results.

Device	Details (Manufacturer, HW, SW, S/N)	Description
AC/DC power supply (115 V 60 Hz)	PeakTech, -, -, 081062045	PeakTech 6005D

3 Evaluation Results

3.1 RF Exposure Evaluation

Standards
OET Bulletin 65 Edition 97-01 August 1997
FCC 47 CFR §1.1307
FCC 47 CFR §1.1310
RSS-102 Issue 5 – March 2015

3.1.1 Test limits

As specified in Table 1B of 47 CFR 1.1310 – Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure.

Frequency range (MHz)	Power density (mW/cm ²)
300 – 1,500	f/1500
1,500 – 100,000	1.0

Limits specified per RSS-102, Issue 5.

Frequency range (MHz)	Power density (W/m ²)	Power density (mW/cm ²)
300 – 6000	0.02619 f ^{0.6834}	mW/cm ² = W/m ² * 0.1

Equation OET bulletin 65, page 18, edition 97-01:
$$S = \frac{PG}{4\pi R^2} = \frac{EIRP}{4\pi R^2}$$

Where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

3.1.2 Test Protocol

The below table is to determine the MPE values using the maximum gain values for this product.

Table for FCC Limits

Band	Mode	Duty Cycle	Frequency (MHZ)	Maximum Conducted output power (dBm)	Equivalent conducted output power (mW)	FCC MPE Limit (mW/cm ²)	MPE Value using Max gain	Separation distance (cm)	Verdict
WLAN b-Mode; 20 MHz	DSSS, 11 Mbps	50.0%	2437.0	23.6	229.09	1.0000	0.1078	20	Pass
WLAN g-Mode; 20 MHz	OFDM, 36 Mbps	50.0%	2437.0	24.9	309.03	1.0000	0.1455	20	Pass
WLAN n-Mode; 20 MHz	OFDM, MCS3	100.0%	2437.0	25.4	346.74	1.0000	0.1632	20	Pass
WLAN n-Mode; 40 MHz	OFDM, MCS4	100.0%	2437.0	26	398.11	1.0000	0.1874	20	Pass
Bluetooth	GFSK 1-DH1	100.0%	2441.0	11.1	5.37	1.0000	0.0025	20	Pass
WLAN a-Mode; 20 MHz	6 Mbit/s	100.0%	5260.0	16.5	44.67	1.0000	0.0256	20	Pass
WLAN n-Mode; 20 MHz	6,5 Mbit/s MCS0	100.0%	5220.0	16.5	44.67	1.0000	0.0256	20	Pass
WLAN n-Mode; 40 MHz	13,5 Mbit/s MCS0	100.0%	5230.0	16.6	45.71	1.0000	0.0262	20	Pass
WLAN ac-Mode	20 MHz; 6,5 Mbit/s MCS0	100.0%	5220.0	16.3	42.66	1.0000	0.0245	20	Pass
WLAN ac-Mode	40 MHz; 13,5 Mbit/s MCS0	100.0%	5230.0	16.6	45.71	1.0000	0.0262	20	Pass
WLAN ac-Mode	80 MHz; 433 Mbit/s MCS0	100.0%	5210.0	9.7	9.33	1.0000	0.0054	20	Pass

Table for IC Limits

Band	Mode	Duty Cycle	Frequency (MHZ)	Maximum Conducted output power (dBm)	Equivalent conducted output power (mW)	IC MPE Limit (mW/cm ²)	MPE Value using Max gain	Separation distance (cm)	Verdict
WLAN b-Mode; 20 MHz	DSSS, 11 Mbps	50%	2437.0	23.6	229.09	0.5404	0.1078	20	PASS
WLAN g-Mode; 20 MHz	OFDM, 36 Mbps	50%	2437.0	24.9	309.03	0.5404	0.1455	20	PASS
WLAN n-Mode; 20 MHz	OFDM, MCS3	100.0%	2437.0	25.4	346.74	0.5404	0.1632	20	PASS
WLAN n-Mode; 40 MHz	OFDM, MCS4	100.0%	2437.0	26	398.11	0.5404	0.1874	20	PASS
Bluetooth	GFSK 1-DH1	100.0%	2441.0	11.1	5.37	0.5410	0.0025	20	PASS
WLAN a-Mode; 20 MHz	6 Mbit/s	100.0%	5260.0	16.5	44.67	0.9142	0.0256	20	PASS
WLAN n-Mode; 20 MHz	6,5 Mbit/s MCS0	100.0%	5220.0	16.5	44.67	0.9095	0.0256	20	PASS
WLAN n-Mode; 40 MHz	13,5 Mbit/s MCS0	100.0%	5230.0	16.6	45.71	0.9107	0.0262	20	PASS
WLAN ac-Mode	20 MHz; 6,5 Mbit/s MCS0	100.0%	5220.0	16.3	42.66	0.9095	0.0245	20	PASS
WLAN ac-Mode	40 MHz; 13,5 Mbit/s MCS0	100.0%	5230.0	16.6	45.71	0.9107	0.0262	20	PASS
WLAN ac-Mode	80 MHz; 433 Mbit/s MCS0	100.0%	5210.0	9.7	9.33	0.9083	0.0054	20	PASS

3.2 RF Exposure Evaluation for multiple transmitters in co-location

Standards
OET Bulletin 65 Edition 97-01 August 1997
FCC 47 CFR §1.1307
FCC 47 CFR §1.1310
RSS-102 Issue 5 – March 2015

3.2.1 Co-Location Considerations

The calculation below is used to consider situations in which simultaneous exposure to fields of different frequencies occur. The calculation is performed by the sum of each relative exposure for each equipment according to the following criteria.

$$\sum_{1}^{N} \frac{S_{eqn}}{S_{Limn}} = \frac{S_{eq1}}{S_{Lim1}} + \frac{S_{eq2}}{S_{Lim2}} + \dots + \frac{S_{eqN}}{S_{LimN}} \leq 1$$

Where:

S_{eq} is the power density of the electromagnetic field at a given distance by a specific transmitter and a defined frequency.

S_{lin} is the MPE limit for the frequency being evaluated.

3.2.2 Assumptions

1. Primary transmitter does not support power reduction for multiple time slots on the uplink.
2. Antenna separation from module to human body is ≥ 20 cm.
3. Separation distance between co-located transmitting antennas is 0cm.
4. Hypothetical Bluetooth radio is assumed to have an output power of 9.5dBm and an antenna gain of 4dBi.
5. Hypothetical WLAN radio is assumed to have an output power of 19dBm and an antenna gain of 5dBi.

3.2.3 Test Protocol

Below are the relative exposure values for the primary, secondary and combined primary + secondary transmitters for both FCC and Industry Canada limits.

Relative exposure for Primary Transmitter for FCC							
OP-Mode	Mode	Output Power	Frequency (MHZ)	Seq	Slin (mW/cm ²)	Seq ----- Slin	Verdict
WLAN b-Mode; 20 MHz	DSSS, 11 Mbps	63.0957	2437.0	0.0297	1.0000	0.02969823	Pass
WLAN g-Mode; 20 MHz	OFDM, 36 Mbps	39.8107	2437.0	0.0187	1.0000	0.01873831	Pass
WLAN n-Mode; 20 MHz	OFDM, MCS3	39.8107	2437.0	0.0187	1.0000	0.01873831	Pass
WLAN n-Mode; 40 MHz	OFDM, MCS4	25.1189	2437.0	0.0118	1.0000	0.01182308	Pass
Bluetooth	GFSK 1-DH1	3.6308	2441.0	0.0017	1.0000	0.00170895	Pass
WLAN a-Mode; 20 MHz	6 Mbit/s	50.1187	5260.0	0.0288	1.0000	0.02875613	Pass
WLAN n-Mode; 20 MHz	6,5 Mbit/s MCS0	43.6516	5220.0	0.0250	1.0000	0.02504555	Pass
WLAN n-Mode; 40 MHz	13,5 Mbit/s MCS0	43.6516	5230.0	0.0250	1.0000	0.02504555	Pass
WLAN ac-Mode	20 MHz; 6,5 Mbit/s MCS0	43.6516	5220.0	0.0250	1.0000	0.02504555	Pass
WLAN ac-Mode	40 MHz; 13,5 Mbit/s MCS0	43.6516	5230.0	0.0250	1.0000	0.02504555	Pass
WLAN ac-Mode	80 MHz; 433 Mbit/s MCS0	9.5499	5210.0	0.0055	1.0000	0.00547937	Pass

Relative exposure for Primary Transmitter for Industry Canada							
OP-Mode	Mode	Output Power	Frequency (MHZ)	Seq	Slin (mW/cm ²)	Seq ----- Slin	Verdict
WLAN b-Mode; 20 MHz	DSSS, 11 Mbps	63.0957	2437.0	0.0297	0.5404	0.054956358	Pass
WLAN g-Mode; 20 MHz	OFDM, 36 Mbps	39.8107	2437.0	0.0187	0.5404	0.034675118	Pass
WLAN n-Mode; 20 MHz	OFDM, MCS3	39.8107	2437.0	0.0187	0.5404	0.034675118	Pass
WLAN n-Mode; 40 MHz	OFDM, MCS4	25.1189	2437.0	0.0118	0.5404	0.02187852	Pass
Bluetooth	GFSK 1-DH1	3.6308	2441.0	0.0017	0.5410	0.003158866	Pass
WLAN a-Mode; 20 MHz	6 Mbit/s	50.1187	5260.0	0.0288	0.9142	0.031453817	Pass
WLAN n-Mode; 20 MHz	6,5 Mbit/s MCS0	43.6516	5220.0	0.0250	0.9095	0.027538418	Pass
WLAN n-Mode; 40 MHz	13,5 Mbit/s MCS0	43.6516	5230.0	0.0250	0.9107	0.027502423	Pass
WLAN ac-Mode	20 MHz; 6,5 Mbit/s MCS0	43.6516	5220.0	0.0250	0.9095	0.027538418	Pass
WLAN ac-Mode	40 MHz; 13,5 Mbit/s MCS0	43.6516	5230.0	0.0250	0.9107	0.027502423	Pass
WLAN ac-Mode	80 MHz; 433 Mbit/s MCS0	9.5499	5210.0	0.0055	0.9083	0.00603265	Pass

Simultaneous exposure for FCC					
Band	Mode	Frequency (MHZ)	Maximum S_{eq} / S_{Lin}	Maximum $S_{pri} / S_{lim_pri} + S_{sec} / S_{lin_Sec}$	Compliance Maximum $(S_{pri} / S_{lim_pri}) + (S_{sec} / S_{lin_Sec}) < 1$
Bluetooth	GFSK 1-DH1	2441	0.0025	0.1899	Compliant
WLAN b-Mode; 20 MHz	DSSS, 11 Mbps	2437	0.1874		
Bluetooth	GFSK 1-DH1	2441	0.0025	0.0288	Compliant
WLAN a-Mode; 20 MHz	6 Mbit/s	5260	0.0288		

Simultaneous exposure for Industry Canada					
Band	Mode	Frequency (MHZ)	Maximum S_{eq} / S_{Lin}	Maximum $S_{pri} / S_{lim_pri} + S_{sec} / S_{lin_Sec}$	Compliance Maximum $(S_{pri} / S_{lim_pri}) + (S_{sec} / S_{lin_Sec}) < 1$
Bluetooth	GFSK 1-DH1	2441	0.0047	0.3514	Compliant
WLAN b-Mode; 20 MHz	DSSS, 11 Mbps	2437	0.3468		
Bluetooth	GFSK 1-DH1	2441	0.0047	0.0327	Compliant
WLAN a-Mode; 20 MHz	6 Mbit/s	5260	0.0315		

Conclusion

The calculations above demonstrate that the highest calculated power density for the 2.4GHz Wi-Fi and 5 GHz Wi-Fi in combination with the highest calculated Bluetooth Power density are under the limit of allowed exposure. Thus, it can be concluded that all other modes, data rates and channel combinations supported by this device are also under the limits for RF exposure.