THIS MUST BE SIGNED BY THE APPLICANT/AGENT AND SHOULD BE PLACED ON APPROPRIATE LETTERHEAD

Request for Modular/Limited Modular Approval

Date: October 11, 2024					
Subject: Manufacturer's Declaration for ⊠ - Modular Approval □ - Split Modul □ - Limited Modular Approval □ - Limited Spl		approval			
Confidentiality Request for: XPYMAYAW160					
8 Basic Requirements – FCC Part 15.212(a)(1) For Itama Marked "NO(*)" the Limited Module Description Must be Filled Out on the F	llowing Dago				
For Items Marked "NO(*)", the Limited Module Description Must be Filled Out on the Fo Modular Approval Requirement		ment Met			
1. The modular transmitter must have its own RF shielding. This is intended to ensure that the module does not have to rely upon the shielding provided by the device into which it is installed in order for all modular transmitter emissions to comply with FCC limits. It is also intended to prevent coupling between the RF circuitry of the module and any wires or circuits in the device into which the module is installed. Such coupling may result in non-compliant operation. The physical crystal and tuning capacitors may be located external to the shielded radio elements. 15.212(a)(1)(i)	⊠ - YES	□ - NO(*)			
Details: <example a="" all="" and="" antenna="" board="" circuitry.="" components="" connector="" contains="" covers="" is="" located="" metal="" module="" next="" of="" on="" rf="" shield="" the="" to="" top="" which="" –=""></example>					
2. The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with FCC requirements under conditions of excessive data rates or over-modulation. 15.212(a)(1)(ii)	⊠ - YES	□ - NO(*)			
Details: <example as="" buffered="" circuit="" data="" described="" descripapplication="" in="" is="" modulation="" operational="" the="" to="" –=""></example>	otion provided	with the			
3. The modular transmitter must have its own power supply regulation on the module. This is intended to ensure that the module will comply with FCC requirements regardless of the design of the power supplying circuitry in the device into which the module is installed. 15.212(a)(1)(iii)	⊠ - YES	□ - NO(*)			
Details: <example application="" contains="" filed="" its="" module="" own="" please="" power="" refer="" regulation.="" schematic="" supply="" the="" this="" to="" with="" –=""></example>					
4. The modular transmitter must comply with the antenna and transmission system requirements of §§ 15.203, 15.204(b), 15.204(c), 15.212(a), and 2.929(b). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of § 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph 15.212(b). 15.212(a)(1)(iv)	⊠ - YES	□ - NO(*)			
Details: <example a="" an="" and="" antenna="" antennas="" approved="" be="" connector="" connector.="" connects="" considere="" device="" found="" in="" is="" its="" list="" manual="" may="" module="" of="" proved.<="" td="" tested="" the="" this="" to="" ufl="" users="" using="" which="" with="" –=""><td></td><td></td></example>					
5. The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified or commercially available (see Section 15.31(i)). 15.212(a)(1)(v)	⊠ - YES	□ - NO(*)			
Details: <example as="" filed="" in="" module="" photographs="" setup="" shown="" stand-alone="" td="" test="" tested="" the="" was="" with<="" –=""><td>this application</td><td>on></td></example>	this application	on>			

THIS MUST BE SIGNED BY THE APPLICANT/AGENT AND SHOULD BE PLACED ON APPROPRIATE LETTERHEAD

	Modular Approval Requirement	Require	ment Met
6.	The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748). If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization. If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization. 15.212(a)(1)(vi)	⊠ - YES	□ - NO(*)
	Details: <example a="" applabeling="" application.="" are="" as="" exhibit="" filed="" in="" installation="" instructions="" is="" label="" labeling="" manual="" module="" on="" shown="" the="" there="" this="" with="" –=""></example>	olication. Hos	t specific
7.	The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii)	⊠ - YES	□ - NO(*)
	Details: <example 15c="" application.="" complies="" fcc="" filed="" installation="" instructions="" manual="" module="" oem="" part="" requirements.="" the="" this="" to="" with="" –=""></example>	I installer are	provided in
8.	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii)	⊠ - YES	□ - NO(*)
	Details: <example application.="" as="" exclusion="" exposure="" filed="" in="" information="" levels="" meets="" module="" portable="" rf="" shown="" the="" this="" with="" –=""></example>		th this

THIS MUST BE SIGNED BY THE APPLICANT/AGENT AND SHOULD BE PLACED ON APPROPRIATE LETTERHEAD

Limited Module Description – When Applicable

* If a module does NOT meet one or more of the above 8 requirements, the applicant may request Limited Modular Approval (LMA). This Limited Modular Approval (LMA) is applied with the understanding that the applicant will demonstrate and will retain control over the final installation of the device, such that compliance of the end product is always assured. The operating condition(s) for the LMA; the module is only approved for use when installed in devices produced by grantee. A description regarding how control of the end product, into which the module will be installed, will be maintained by the applicant/manufacturer, such that full compliance of the end product is always ensured should be provided here.

Details: <example - N/A>

Software Considerations – KDB 594280 / KDB 442812 (One of the following 2 items must be applied)			
Requirement		Requirement Met	
1.	For <u>non-Software Defined Radio</u> transmitter modules where software is used to ensure compliance of the device, technical description must be provided about how such control is implemented to ensure prevention of third-party modification; see KDB Publication 594280.	☐ - Provided in Separate Cover Letter	⊠ - N/A
	Details: <example adjusted="" application.="" be="" by="" can="" device="" filed="" firmware="" letter="" modified="" not="" of="" or="" the="" this="" with="" –=""></example>	e end user as described in a se	parate cover
2.	For <u>Software Defined Radio (SDR)</u> devices, transmitter module applications must provide a software security description; see KDB Publication 442812.	☐ - Provided in Separate Cover Letter	⊠ - N/A
	Details: <example -n="" a=""></example>		

1. For split modular transmitters, specific descriptions for secure communications between front-end and control sections, including authentication and restrictions on		
third-party modifications; also, instructions to third-party integrators on how control is maintained.	- Provided in Separate Cover Letter	⊠ - N/A

THIS MUST BE SIGNED BY THE APPLICANT/AGENT AND SHOULD BE PLACED ON APPROPRIATE LETTERHEAD

	071/1			
OEM Integration Manual Guidance – KDB 996369 D03 Section 2				
Clas	Clear and Specific Instructions Describing the Conditions, Limitations, and Procedures			
for third-parties to use and/or integrate the module into a host device.				
	for third parties to use	and of integrate the mount into a nost device	•	
Requirement				
		□ - N	lo.	
		If No, and LMA applies, the applic		
		make the following detailed info pu		
Is this module intende	d for	to be basic integration instruction		
sale to third parties?	⊠ - YE	S information below must still be	included in the operational	
l sure to thin a parties.		description. If the applicant wishe		
		this will require a separate statem		
		module is not for sale to third		
	Itams required to be i	instructions are internal contraction are internal contractions are internal contraction and instructions are internal contraction.		
As of May 1 2010 the		the manual – See KDB 990309 D03, Section 2 lowing information to be in the installation ma		
		ctions for all these items indicating clearly who		
		indicate "Not Applicable". Also if a module is		
		the user instructions may not need to be detailed		
		ption, but this should include a cover letter as		
	Crules. KDB 996369 D03, S			
	st rules related to the transmi			
		KDB 996369 D03, Section 2.3		
		as, cable loss, reduction of power for point to poin	nt	
	s, professional installation in			
	edures. KDB 996369 D03, Se			
	g conditions	grantee uses to verify the host meets the necessar		
		cessary, state how control will be maintained such	✓ - All Items shown to	
	inpliance is ensured, such as		the left are provided in	
	. KDB 996369 D03, Section		the Modular Integration	
		tenna, connectors, isolation requirements, tests fo	r Guide (or UM) for Full Modular Approval (MA)	
		est procedures for ensuring compliance. If	or I MA	
		p confidential must be identified and information	of Bivin i.	
	ed in the operational descript		☐ - An LMA applies	
	ations. KDB 996369 D03, Se	ction 2.6 as that allow host manufacturers to use the modul	1.1	
		ary: first to the host manufacturer to define	for use by the grantee in	
		n from body) and second additional text needed to		
	ed to the end user in the host		not intended for sale to	
6. Antennas. KDB 99636	69 D03, Section 2.7		3 rd parties as provided in	
		ication and all applicable professional installer	a separate cover letter.	
		ntenna list shall also identify the antenna types	Therefore the information shown to the	
		that "omni-directional" is not considered a type)	left is found in the	
	information. KDB 996369 I		theory of operation.	
	to nost integrators that they ins FCC ID: " with their finish	need to provide a physical or e-label stating		
		quirements. KDB 996369 D03, Section 2.9		
		consideration by host integrators including		
	clarifications necessary for stand-alone and simultaneous configurations.			
		igure test modes for evaluation		
9. Additional testing, Par	t 15 Subpart B disclaimer. K	DB 996369 D03, Section 2.10		
Sin a analy				
Sincerely,	Duniant Manager	Detrial I may		
By:	Project Manager	Patrick Lmax		
	(Signature/Title ¹)	(Print name)		

Must be signed by applicant contact given for applicant on the FCC site, or by the authorized agent if an appropriate authorized agent letter has been provided. Letters should be placed on appropriate letterhead.