



<b>RF-EXPOSURE REPORT</b> <b>FCC 47 CFR Part 2.1091</b> <b>Maximum permissible exposure</b>	
<b>Report Reference No</b>	G0M-2302-1881-TFC091-W271-MP-V05
<b>Testing Laboratory</b>	Eurofins Product Service GmbH
<b>Address</b>	Storkower Str. 38c 15526 Reichenwalde Germany
<b>Accreditation</b>	 <p>A2LA Accredited Testing Laboratory, Certificate No.: 1983.01 FCC Test Firm Designation Number: DE0008 ISED Testing Laboratory site: 3470A</p>
<b>Applicant</b>	u-blox AG
<b>Address</b>	Zürcherstrasse 68 8800 Thalwil Switzerland
<b>Test Specification</b>	According to FCC rules
<b>Standard</b>	FCC 47 CFR 2.1091
<b>Non-Standard Test Method</b>	None
<b>Equipment under Test (EUT):</b>	
<b>Product Description</b>	MAYA-W2 host-based multiradio modules
<b>Model(s)</b>	MAYA-W271-00B
<b>Additional Model(s)</b>	None
<b>Brand Name(s)</b>	u-blox
<b>Hardware Version(s)</b>	02, 03
<b>Software Version(s)</b>	1.0.0.39.1-18.80.1.p154.38
<b>FCC-ID</b>	XPYMAYAW2A
<b>Test Result</b>	<b>PASSED</b>

<b>Possible test case verdicts:</b>		
required by standard but not tested	N/T	
not required by standard	N/R	
test object does meet the requirement	P(PASS)	
test object does not meet the requirement	F(FAIL)	
<b>Testing:</b>		
Test Lab Temperature	20 °C - 30 °C	
Test Lab Humidity	25 % - 55 %	
Date of performance	2024-04-23	
Date of receipt of test item	2023-03-02	
<b>Report:</b>		
Compiled by	Burkhard Pudell	
Created by (+ signature) (Responsible)	Burkhard Pudell	
Approved by (+ signature) (Test Lab Engineer)	Radwan Jaafar	
Date of Issue	2024-04-25	
Total number of pages	20	
<b>General Remarks:</b>		
<p><b>The test results presented in this report relate only to the object tested.</b></p> <p><b>The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.</b></p> <p>This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.</p>		
<b>Additional Comments:</b>		
None		

**ADDITIONAL VARIANTS**

Additional Variants (not tested and not evaluated variants)		
Not-tested Variant	Description	
1	Product Type Description	Host-based multiradio module
	Model name	MAYA-W261-00B
	Brand name	u-blox
	Hardware Version	3
	Software Version	1.0.0.39.1-18.80.1.p154.38
	FCC-ID	XPYMAYAW2A
2	Product Type Description	Host-based multiradio module
	Model name	MAYA-W260-00B
	Brand name	u-blox
	Hardware Version	3
	Software Version	1.0.0.39.1-18.80.1.p154.38
	FCC-ID	XPYMAYAW2A
Comment: Those named additional variants above have not been tested. Those additional variants of the series have been declared by the manufacturer. The test report explicitly states that those variants were neither tested nor assessed nor evaluated.		

**VERSION HISTORY**

Version History			
Version	Issue Date	Remarks	Revised By
01	2023-11-23	Initial Release	--
02	2023-11-30	Replaced document: G0M-2302-1881-TFC091-W271-MP-V01 Replaced by: G0M-2302-1881-TFC091-W271-MP-V02  Reason: Test reports USRC239070001 and USRC239070003 have been added to the reference documents.	R. Jaafar
03	2024-01-12	Replaced document: G0M-2302-1881-TFC091-W271-MP-V02 Replaced by: G0M-2302-1881-TFC091-W271-MP-V03  Reason: Change of Eurofins Product Service GmbH Test Reports as Reference Documents	R. Jaafar
04	2024-02-01	Replaced document: G0M-2302-1881-TFC091-W271-MP-V03 Replaced by: G0M-2302-1881-TFC091-W271-MP-V04  Reason: Add HW Version and new evaluation of results	St. Liebich
05	2024-04-25	Replaced document: G0M-2302-1881-TFC091-W271-MP-V04 Replaced by: G0M-2302-1881-TFC091-W271-MP-V05  Reason: New evaluation and calculation of exposure under consideration of IEEE 802.11 (U-NII-4) Additional Variants added	B. Pudell

**ABBREVIATIONS AND ACRONYMS**

Acronyms	
Acronym	Description
EIRP	Equivalent Isotropic Radiated Power
EUT	Equipment Under Test
MPE	Maximum Permissible Exposure

**REPORT INDEX**

<b>1</b>	<b>Equipment (Test Item) Under Test.....</b>	<b>7</b>
1.1	Reference Documents.....	8
1.2	Power density radiation sources.....	9
1.3	Field strength radiation sources .....	9
1.4	Concurrent Sources .....	9
<b>2</b>	<b>Result Summary.....</b>	<b>10</b>
<b>3</b>	<b>RF-Exposure classification .....</b>	<b>12</b>
<b>4</b>	<b>RF-Exposure limits .....</b>	<b>13</b>
<b>5</b>	<b>RF-Exposure Evaluation .....</b>	<b>14</b>
<b>6</b>	<b>Single Source Evaluation Results - FCC .....</b>	<b>15</b>
<b>7</b>	<b>Concurrent Evaluation Results - FCC.....</b>	<b>18</b>

## 1 Equipment (Test Item) Under Test

Description	MAYA-W2 host-based multiradio modules		
Model	MAYA-W271-00B		
Additional Model(s)	None		
Brand Name(s)	u-blox		
Sample Identification	EUT #	Sample-ID	Serial Number
	EUT 1	see Ref-Doc	see Ref-Doc
Hardware Version(s)	02, 03		
Software Version(s)	1.0.0.39.1-18.80.1.p154.38		
FCC ID	XPYMAYAW2A		
Equipment type	Radio module		
Environment	General public		

## 1.1 Reference Documents

Document Type	Document No.	Issued by	Date
Test-Report	G0M-2302-1881-TFC407WF-W271-V03	Eurofins Product Service GmbH	2024-01-11
Test-Report	G0M-2302-1881-TFC247WF-W271-V03	Eurofins Product Service GmbH	2024-01-11
Test-Report	G0M-2302-1881-TFC247ZB-W271-V03	Eurofins Product Service GmbH	2024-01-11
Test-Report	G0M-2302-1881-TFC247BT-W271-V03	Eurofins Product Service GmbH	2024-01-11
Test-Report	G0M-2302-1881-TFC247BL-W271-V03	Eurofins Product Service GmbH	2024-01-11
Test-Report	USRC239070001	Eurofins E&E Wireless Taiwan Co., Ltd.	2023-11-27
Test-Report	USRC239070003	Eurofins E&E Wireless Taiwan Co., Ltd.	2023-11-24
Test-Report	USRC23N389001	Eurofins E&E Wireless Taiwan Co., Ltd.	2023-12-22



## 1.2 Power density radiation sources

Mode	Operating Frequency [MHz]	Maximum conducted power [dBm]	Maximum radiated power [dBm EIRP]	Maximum duty cycle [%]	Maximum antenna gain [dBi]	Maximum antenna diameter [cm]
IEEE 802.11 (U-NII-1)	5240	19.5	24.6	100	5.1	N/A
IEEE 802.11 (U-NII-4)	5835	17.58	22.68	100	5.1	N/A
IEEE 802.11 (2.4 GHz)	2437	19.1	23.2	100	4.1	N/A
IEEE 802.15.4 (2.4 GHz)	2440	21.4	25.5	26	4.1	N/A
Bluetooth	2402	17.9	22.0	77	4.1	N/A
Bluetooth LE	2402	19.7	23.8	86	4.1	N/A
Comment: --						

## 1.3 Field strength radiation sources

None

## 1.4 Concurrent Sources

Concurrent operating conditions
IEEE 802.11 (U-NII-1) + IEEE 802.15.4 (2.4 GHz)
IEEE 802.11 (U-NII-1) + Bluetooth
IEEE 802.11 (U-NII-1) + Bluetooth LE
IEEE 802.11 (U-NII-4) + IEEE 802.15.4 (2.4 GHz)
IEEE 802.11 (U-NII-4) + Bluetooth
IEEE 802.11 (U-NII-4) + Bluetooth LE
IEEE 802.11 (2.4 GHz) + IEEE 802.15.4 (2.4 GHz)
IEEE 802.11 (2.4 GHz) + Bluetooth
IEEE 802.11 (2.4 GHz) + Bluetooth LE
Comment: --

## 2 Result Summary

FCC MPE Evaluation - Single radiation sources					
Product Standard Reference	Requirement	Reference Method	Mode	Distance [m]	Verdict
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	IEEE 802.11 (U-NII-1)	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	IEEE 802.11 (U-NII-4)	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	IEEE 802.11 (2.4 GHz)	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	IEEE 802.15.4 (2.4 GHz)	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	Bluetooth	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	Bluetooth LE	0.20	PASS
Comment: --					

FCC MPE Evaluation - Multi-transmitter sources					
Product Standard Reference	Requirement	Reference Method	Mode	Distance [m]	Verdict
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	IEEE 802.11 (U-NII-1) + IEEE 802.15.4 (2.4 GHz)	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	IEEE 802.11 (U-NII-1) + Bluetooth	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	IEEE 802.11 (U-NII-1) + Bluetooth LE	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	IEEE 802.11 (U-NII-4) + IEEE 802.15.4 (2.4 GHz)	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	IEEE 802.11 (U-NII-4) + Bluetooth	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	IEEE 802.11 (U-NII-4) + Bluetooth LE	0.20	PASS

47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	IEEE 802.11 (2.4 GHz) + IEEE 802.15.4 (2.4 GHz)	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	IEEE 802.11 (2.4 GHz) + Bluetooth	0.20	PASS
47 CFR 2.1091	Maximum permissible exposure	FCC KDB 447498	IEEE 802.11 (2.4 GHz) + Bluetooth LE	0.20	PASS
Comment: --					

### 3 RF-Exposure classification

RF-Exposure Categories	
Fixed	A fixed device is defined as a device physically secured at one fixed location and cannot be easily re-located.
Mobile	A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.
Portable	A portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

RF-Exposure Categories	
Occupational / Controlled	Limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.
General population / Uncontrolled	Exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

#### 4 RF-Exposure limits

FCC Limits – General Population / Uncontrolled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m <sup>2</sup> ]	Averaging time [min]
0.3 – 1.34	614	1.63	1000	30
1.34 – 30	824/f	2.19/f	1800/f <sup>2</sup>	30
30 – 300	27.5	0.073	2	30
300 – 1500	-	-	f/150	30
1500 – 100000	-	-	10.0	30

FCC Limits – Occupational / Controlled Exposure				
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [W/m <sup>2</sup> ]	Averaging time [min]
0.3 – 3.0	614	1.63	1000	6
3.0 – 30	1842/f	4.89/f	9000/f <sup>2</sup>	6
30 – 300	61.4	0.163	10.0	6
300 – 1500	-	-	f/30	6
1500 – 100000	-	-	50	6

## 5 RF-Exposure Evaluation

Evaluation Relations
$\lambda[m] = \frac{c \left[ \frac{m}{s} \right]}{f[Hz]} ; R_{FF}[m] \geq \frac{2 \cdot D[m]^2}{\lambda[m]}$
$S[W/m^2] = \frac{P_{E.I.R.P.}[W]}{4\pi R[m]^2} ; R[m] = \sqrt{\frac{P_{E.I.R.P.}[W]}{4\pi S[W/m^2]}}$
$DCC [dB] = 10 \cdot \text{Log}_{10} \left( \frac{DC[\%]}{100} \right)$
$\sum_{i=1}^N \frac{S_i \left[ \frac{W}{m^2} \right]}{S_{Li} \left[ \frac{W}{m^2} \right]} + \sum_{j=1}^M \left( \frac{E_j \left[ \frac{V}{m} \right]}{E_{Lj} \left[ \frac{V}{m} \right]} \right)^2 + \sum_{k=1}^o \left( \frac{H_k \left[ \frac{A}{m} \right]}{H_{Lk} \left[ \frac{A}{m} \right]} \right)^2 < 1$

Evaluation Procedure
<p><u>Standalone operation evaluation:</u></p> <p>For each radio and frequency band the worst case transmission mode with the highest peak conducted or radiated power is evaluated at the frequency that results in the most restrictive rf-exposure limit. From the peak power values, antenna gains and duty cycles taken from the reference documents, the source average radiated power values are calculated. From the average radiated power the power densities at antenna far-field distance is calculated. The distance from the radiation source for compliance power density is calculated. If the separation distance is lower than the far-field distance, the far-field distance is given as compliance separation distance because the plane wave power density assessment is only valid in the far-field of the radiation source.</p> <p>For radiation sources for which the average electric and magnetic fields are measured using field probes, the measured field strength values are compared to the reference limits. For those sources no calculations are performed. Compliance with the reference values is determined with the near field measurements.</p> <p><u>Concurrent operation evaluation:</u></p> <p>First the evaluation distance is set to an appropriate value. For all radiation sources for which power densities are calculated, the power densities at the evaluation distance are calculated and for all other sources the electric or magnetic field strengths are measured using field probes. Finally the ratios of the power densities and/or field strength values and the corresponding limits are calculated and summed and the sum is compared to the maximum of 1.</p>

## 6 Single Source Evaluation Results - FCC

IEEE 802.11 (U-NII-1)	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	5240
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	24.6
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	24.60
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	10.000
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	0.574
Power density ratio @ 0.20 m	0.06
Distance for compliance power density (S=SL) [m]	0.048
<b>Compliance</b>	
Verdict	PASS
Comment: --	

IEEE 802.11 (U-NII-4)	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	5835
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	22.68
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	22.68
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	10.000
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	0.369
Power density ratio @ 0.20 m	0.04
Distance for compliance power density (S=SL) [m]	0.038
<b>Compliance</b>	
Verdict	PASS
Comment: --	

IEEE 802.11 (2.4 GHz)	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	2437
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	23.2
Maximum transmission duty cycle (DC)	1.00
Duty cycle correction (DCC) [dB]	0.00
Average radiated power (PRAVG) [dBm EIRP]	23.20
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	10.000
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	0.416
Power density ratio @ 0.20 m	0.04
Distance for compliance power density (S=SL) [m]	0.041
<b>Compliance</b>	
Verdict	PASS
Comment: --	

IEEE 802.15.4 (2.4 GHz)	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	2440
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	25.5
Maximum transmission duty cycle (DC)	0.26
Duty cycle correction (DCC) [dB]	-5.85
Average radiated power (PRAVG) [dBm EIRP]	19.65
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	10.000
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	0.184
Power density ratio @ 0.20 m	0.02
Distance for compliance power density (S=SL) [m]	0.027
<b>Compliance</b>	
Verdict	PASS
Comment: --	



Bluetooth	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	2402
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	22.0
Maximum transmission duty cycle (DC)	0.77
Duty cycle correction (DCC) [dB]	-1.14
Average radiated power (PRAVG) [dBm EIRP]	20.86
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	10.000
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	0.243
Power density ratio @ 0.20 m	0.02
Distance for compliance power density (S=SL) [m]	0.031
<b>Compliance</b>	
Verdict	PASS
Comment: --	

Bluetooth LE	
<b>Transmission Mode</b>	
Transmission Frequency (f) [MHz]	2402
<b>Antenna far-field distance</b>	
Maximum antenna diameter (D) [m]	N/A
Transmission wavelength ( $\lambda$ ) [m]	N/A
Antenna far-field distance ( $R_{FF}$ ) [m]	N/A
<b>Source average power</b>	
Peak radiated power (PR) [dBm EIRP]	23.8
Maximum transmission duty cycle (DC)	0.86
Duty cycle correction (DCC) [dB]	-0.66
Average radiated power (PRAVG) [dBm EIRP]	23.14
<b>Power density</b>	
Compliance power density limit [W/m <sup>2</sup> ]	10.000
Power density (S) @ Antenna far-field distance [W/m <sup>2</sup> ]	N/A
Power density (S) @ 0.20 m [W/m <sup>2</sup> ]	0.410
Power density ratio @ 0.20 m	0.04
Distance for compliance power density (S=SL) [m]	0.041
<b>Compliance</b>	
Verdict	PASS
Comment: --	

## 7 Concurrent Evaluation Results - FCC

IEEE 802.11 (U-NII-1) + IEEE 802.15.4 (2.4 GHz)	
<b>Information</b>	
Number of concurrent modes	2
Evaluation distance [m]	0.20
<b>Maximum MPE Ratios</b>	
IEEE 802.11 (U-NII-1)	0.06
IEEE 802.15.4 (2.4 GHz)	0.02
<b>Sum of MPE Ratios</b>	
Sum	0.08
<b>Compliance</b>	
Verdict	PASS

IEEE 802.11 (U-NII-1) + Bluetooth	
<b>Information</b>	
Number of concurrent modes	2
Evaluation distance [m]	0.20
<b>Maximum MPE Ratios</b>	
IEEE 802.11 (U-NII-1)	0.06
Bluetooth	0.02
<b>Sum of MPE Ratios</b>	
Sum	0.08
<b>Compliance</b>	
Verdict	PASS

IEEE 802.11 (U-NII-1) + Bluetooth LE	
<b>Information</b>	
Number of concurrent modes	2
Evaluation distance [m]	0.20
<b>Maximum MPE Ratios</b>	
IEEE 802.11 (U-NII-1)	0.06
Bluetooth LE	0.04
<b>Sum of MPE Ratios</b>	
Sum	0.10
<b>Compliance</b>	
Verdict	PASS

IEEE 802.11 (U-NII-4) + IEEE 802.15.4 (2.4 GHz)	
<b>Information</b>	
Number of concurrent modes	2
Evaluation distance [m]	0.20
<b>Maximum MPE Ratios</b>	
IEEE 802.11 (U-NII-4)	0.04
IEEE 802.15.4 (2.4 GHz)	0.02
<b>Sum of MPE Ratios</b>	
Sum	0.06
<b>Compliance</b>	
Verdict	PASS

IEEE 802.11 (U-NII-4) + Bluetooth	
<b>Information</b>	
Number of concurrent modes	2
Evaluation distance [m]	0.20
<b>Maximum MPE Ratios</b>	
IEEE 802.11 (U-NII-4)	0.04
Bluetooth	0.02
<b>Sum of MPE Ratios</b>	
Sum	0.06
<b>Compliance</b>	
Verdict	PASS

IEEE 802.11 (U-NII-4) + Bluetooth LE	
<b>Information</b>	
Number of concurrent modes	2
Evaluation distance [m]	0.20
<b>Maximum MPE Ratios</b>	
IEEE 802.11 (U-NII-4)	0.04
Bluetooth LE	0.04
<b>Sum of MPE Ratios</b>	
Sum	0.08
<b>Compliance</b>	
Verdict	PASS

IEEE 802.11 (2.4 GHz) + IEEE 802.15.4 (2.4 GHz)	
<b>Information</b>	
Number of concurrent modes	2
Evaluation distance [m]	0.20
<b>Maximum MPE Ratios</b>	
IEEE 802.11 (2.4 GHz)	0.04
IEEE 802.15.4 (2.4 GHz)	0.02
<b>Sum of MPE Ratios</b>	
Sum	0.06
<b>Compliance</b>	
Verdict	PASS

IEEE 802.11 (2.4 GHz) + Bluetooth	
<b>Information</b>	
Number of concurrent modes	2
Evaluation distance [m]	0.20
<b>Maximum MPE Ratios</b>	
IEEE 802.11 (2.4 GHz)	0.04
Bluetooth	0.02
<b>Sum of MPE Ratios</b>	
Sum	0.06
<b>Compliance</b>	
Verdict	PASS

<b>IEEE 802.11 (2.4 GHz) + Bluetooth LE</b>	
<b>Information</b>	
Number of concurrent modes	2
Evaluation distance [m]	0.20
<b>Maximum MPE Ratios</b>	
IEEE 802.11 (2.4 GHz)	0.04
Bluetooth LE	0.04
<b>Sum of MPE Ratios</b>	
Sum	0.08
<b>Compliance</b>	
Verdict	PASS

=== END OF TEST REPORT ===