



11.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the coefficient of stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter pathorization of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Report No.: AGC09881200801FE05

Page 52 of 81

11.3. LIMITS AND MEASUREMENT RESULT

15.209(a) Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested For restricted band radiated emission, the test records reported below are the worst result compared to other modes.

11.4. TEST RESULT


RADIATED EMISSION BELOW 30MHZ

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.



RADIATED EMISSION BELOW 1GHZ

EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHZ	Antenna	Horizontal




No.	Mi	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		151.2500	9.69	17.02	26.71	43.50	-16.79	peak
2		299.9832	3.15	21.47	24.62	46.00	-21.38	peak
3		400.2167	7.07	20.99	28.06	46.00	-17.94	peak
4		479.4332	6.98	24.17	31.15	46.00	-14.85	peak
5		500.4499	9.02	25.00	34.02	46.00	-11.98	peak
6	*	720.3166	10.19	28.61	38.80	46.00	-7.20	peak

RESULT: PASS



EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHZ	Antenna	Vertical




No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		114.0666	10.68	15.90	26.58	43.50	-16.92	peak
2		138.3165	11.98	14.54	26.52	43.50	-16.98	peak
3		400.2167	7.32	20.99	28.31	46.00	-17.69	peak
4		479.4331	9.21	24.17	33.38	46.00	-12.62	peak
5		500.4499	8.84	25.00	33.84	46.00	-12.16	peak
6	*	720.3165	11.19	28.61	39.80	46.00	-6.20	peak

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

- 2. The "Factor" value can be calculated automatically by software of measurement system.
- 3. All test modes had been pre-tested. The 802.11b at low channel is the worst case and recorded in the report.






RADIATED EMISSION ABOVE 1GHZ

EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHZ	Antenna	Horizontal

uV) (dB)	(dBµV/m)	(dD11)//m)	(ID)	Value Type
	(45,47,)	(dBµV/m)	(dB)	(8)
42 0.08	57.5	74	-16.5	peak
18 0.08	46.26	54	-7.74	AVG
47 2.21	54.68	74	-19.32	peak
68 2.21	43.89	54	-10.11	AVG
	8			1
	18 0.08 47 2.21 68 2.21	18 0.08 46.26 47 2.21 54.68	18 0.08 46.26 54 47 2.21 54.68 74 68 2.21 43.89 54	18 0.08 46.26 54 -7.74 47 2.21 54.68 74 -19.32 68 2.21 43.89 54 -10.11

EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2412MHZ	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4824.000	55.63	0.08	55.71	74	-18.29	peak
4824.000	45.17	0.08	45.25	54	-8.75	AVG
7236.000	51.27	2.21	53.48	74	-20.52	peak
7236.000	40.49	2.21	42.7	54	_{-11.3}	AVG
						(8)
		®				
Remark:		- G	8			
actor = Ante	enna Factor + Ca	ble Loss –	Pre-amplifier.			






EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2437MHZ	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4874.000	57.64	0.14	57.78	74	-16.22	peak
4874.000	46.35	0.14	46.49	54	-7.51	AVG
7311.000	52.91	2.36	55.27	74	-18.73	peak
7311.000	41.08	2.36	43.44	54	-10.56	AVG
emark:			10	- GC	8	

EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2437MHZ	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4874.000	57.16	0.14	57.3	74	-16.7	peak
4874.000	45.37	0.14	45.51	54	-8.49	AVG
7311.000	52.97	2.36	55.33	74	-18.67	peak
7311.000	41.22	2.36	43.58	54	-10.42	AVG
(6)					©	
						®
emark:		®				
actor = Ante	enna Factor + Ca	ble Loss – F	Pre-amplifier.			





EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2462MHZ	Antenna	Horizontal

Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
56.34	0.22	56.56	74	-17.44	peak
45.18	0.22	45.4	54	-8.6	AVG
51.37	2.64	54.01	74	-19.99	peak
43.19	2.64	45.83	54	-8.17	AVG
	(dBµV) 56.34 45.18 51.37 43.19	(dBµV) (dB) 56.34 0.22 45.18 0.22 51.37 2.64 43.19 2.64	(dBμV) (dB) (dBμV/m) 56.34 0.22 56.56 45.18 0.22 45.4 51.37 2.64 54.01	(dBμV) (dB) (dBμV/m) (dBμV/m) 56.34 0.22 56.56 74 45.18 0.22 45.4 54 51.37 2.64 54.01 74 43.19 2.64 45.83 54	(dBμV) (dB) (dBμV/m) (dBμV/m) (dB) 56.34 0.22 56.56 74 -17.44 45.18 0.22 45.4 54 -8.6 51.37 2.64 54.01 74 -19.99 43.19 2.64 45.83 54 -8.17

EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with date rate 1 2462MHZ	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4924.000	57.34	0.22	57.56	74	-16.44	peak
4924.000	46.19	0.22	46.41	54	-7.59	AVG
7386.000	52.18	2.64	54.82	74	-19.18	peak
7386.000	42.24	2.64	44.88	54	-9.12	AVG
			*	(e)		
emark:	©		10	C		
actor = Ante	enna Factor + Ca	ble Loss – I	Pre-amplifier.			

RESULT: PASS

Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

All test modes had been pre-tested. The 802.11b mode is the worst case and recorded in the report.



Report No.: AGC09881200801FE05

Page 58 of 81

12. BAND EDGE EMISSION

12.1. MEASUREMENT PROCEDURE

Radiated restricted band edge measurements

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting

12.2. TEST SET-UP

same as 11.2

Note:


- 1. Factor=Antenna Factor + Cable loss Amplifier gain. Field Strength=Factor + Reading level
- 2. The factor had been edited in the "Input Correction" of the Spectrum Analyzer.




12.3. TEST RESULT

EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHZ	Antenna	Horizontal

PK



ΑV




RESULT: PASS




EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHZ	Antenna	Vertical

PΚ



ΑV




RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated restriction. Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter pathorization of AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2462MHZ	Antenna	Horizontal

PΚ



ΑV




RESULT: PASS




EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2462MHZ	Antenna	Vertical


PΚ



ΑV



RESULT: PASS






EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2412MHZ	Antenna	Horizontal


PΚ



ΑV



RESULT: PASS






EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2412MHZ	Antenna	Vertical

PΚ




ΑV



RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Steamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuence of Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.





EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2462MHZ	Antenna	Horizontal

PΚ



ΑV



RESULT: PASS




EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2462MHZ	Antenna	Vertical

PΚ




ΑV



RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the stedicated restroy is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.






EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 20 with data rate 6.5 2412MHZ	Antenna	Horizontal

PΚ



ΑV



RESULT: PASS




EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 20 with data rate 6.5 2412MHZ	Antenna	Vertical

PΚ



ΑV



RESULT: PASS




EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 20 with data rate 6.5 2462MHZ	Antenna	Horizontal

PΚ



ΑV



RESULT: PASS




EUT	NINA-W1	Model Name	NINA-W106
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 20 with data rate 6.5 2462MHZ	Antenna	Vertical

PΚ



ΑV



RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the stedicated restriction is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




EUT	Tablet	Model Name	GS61016
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 40 with data rate 13.5 2422MHZ	Antenna	Horizontal

PΚ



ΑV



RESULT: PASS




EUT	Tablet	Model Name	GS61016
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 40 with data rate 13.5 2422MHZ	Antenna	Vertical


PΚ



ΑV



RESULT: PASS






EUT	Tablet	Model Name	GS61016
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 40with data rate 13.5 2452MHZ	Antenna	Horizontal


PΚ



ΑV



RESULT: PASS






EUT	Tablet	Model Name	GS61016
Temperature	21.8° C	Relative Humidity	58%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 40 with data rate 13.5 2452MHZ	Antenna	Vertical

PΚ



ΑV



RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the stedicated feature. Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



13. FCC LINE CONDUCTED EMISSION TEST


13.1. LIMITS OF LINE CONDUCTED EMISSION TEST


F	Maximum RF Line Voltage		
Frequency	Q.P.(dBuV)	Average(dBuV)	
150kHz~500kHz	66-56	56-46	
500kHz~5MHz	56	46	
5MHz~30MHz	60	50	

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

13.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST







13.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipments received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 3.3V power from control board which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


13.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.



13.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

Line Conducted Emission Test Line 1-L



MEASUREMENT RESULT: "agc_fin"


20	020/8/31 19:	52					
	Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
	0.514000	41.80	9.3	56	14.2	QP	L1
	0.534000	44.80	9.3	56	11.2	QP	L1
	0.554000	45.30	9.3	56	10.7	QP	L1
	1.210000	33.80	9.3	56	22.2	QP	L1
	2.122000	33.60	9.3	56	22.4	QP	L1
	2.986000	32.90	9.4	56	23.1	QP	L1

MEASUREMENT RESULT: "agc fin2"

2020/8/31	19:52					
Frequenc MH	-	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.51400	0 33.20	9.3	46	12.8	AV	L1
0.53400	0 37.10	9.3	46	8.9	AV	L1
0.55400	0 38.10	9.3	46	7.9	AV	L1
1.19800	0 26.10	9.3	46	19.9	AV	L1
2.11800	0 24.10	9.3	46	21.9	AV	L1
2.97800	0 24.40	9.4	46	21.6	AV	L1



Line Conducted Emission Test Line 2-N



MEASUREMENT RESULT: "agc_fin"

2020/8/31 19:24											
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line					
0.510000	40.80	9.3	56	15.2	QP	N					
0.534000	43.00	9.3	56	13.0	QP	N					
0.550000	41.90	9.3	56	14.1	QP	N					
1.086000	34.20	9.3	56	21.8	QP	N					
2.150000	31.80	9.3	56	24.2	QP	N					
3.006000	31.20	9.4	56	24.8	QP	N					

MEASUREMENT RESULT: "agc fin2"

2020/8/31	19:24						
Frequen M	-	evel Tra NBµV		nit Mar βμV	rgin I dB	etector :	Line
0.5100	00 32	2.00	9.3	46 1	14.0 A	7A	N
0.5340	00 37	7.60	9.3	46	8.4 A	.V	N
0.5540	00 36	5.80	9.3	46	9.2 A	.V	N
1.0860	00 27	7.00	9.3	46 1	19.0 A	AV.	N
2.1380	00 23	3.30	9.3	46 2	22.7 A	.V	N
3.0220	00 23	3.40	9.4	46 2	22.6 A	V.	N

RESULT: PASS

Note: All the test modes had been tested, the mode 1 was the worst case. Only the data of the worst case would be record in this test report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Dedicated Pesthod/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC where the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC RADIATED EMISSION TEST SETUP BELOW 1GHZ




FCC RADIATED EMISSION TEST SETUP ABOVE 1GHZ




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the specificated resting/inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter pathorization of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




CONDUCTED EMISSION TEST SETUP



CONDUCTED TEST SETUP



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the specificated resting/inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter pathorization of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.





APPENDIX B: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC09881200801AP03

----END OF REPORT----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3.The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. The non-CMA report issued by AGC is only permitted to be used by the client as internal reference use and shall not be used for public demonstration purpose.
- 5. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 6. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 7. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 8. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 9. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 10. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.

he test report.