

**FCC PART 15, SUBPART B and C; FCC 15.231; and RSS-210 & RSS GEN
 TEST REPORT**

for

FLOOD FREEZE SENSOR

Model: CS-612

Prepared for

ECOLINK INTELLIGENT TECHNOLOGY, INC.
 2055 CORTE DEL NOGAL
 CARLSBAD, CALIFORNIA 92011

Prepared by: _____

KYLE FUJIMOTO

Approved by: _____

JAMES ROSS

COMPATIBLE ELECTRONICS INC.
 114 OLINDA DRIVE
 BREA, CALIFORNIA 92823
 (714) 579-0500

DATE: JANUARY 28, 2021

	REPORT BODY	APPENDICES					TOTAL
		A	B	C	D	E	
PAGES	22	2	2	2	10	25	63

This report shall not be reproduced except in full, without the written approval of Compatible Electronics.





TABLE OF CONTENTS

Section / Title	PAGE
GENERAL REPORT SUMMARY	4
SUMMARY OF TEST RESULTS	5
1. PURPOSE	6
1.1 Decision Rule & Risk	6
2. ADMINISTRATIVE DATA	7
2.1 Location of Testing	7
2.2 Traceability Statement	7
2.3 Cognizant Personnel	7
2.4 Date Test Sample was Received	7
2.5 Disposition of the Test Sample	7
2.6 Abbreviations and Acronyms	7
3. APPLICABLE DOCUMENTS	8
4. DESCRIPTION OF TEST CONFIGURATION	9
4.1 Description of Test Configuration – Emissions	9
4.1.1 Cable Construction and Termination	9
5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT	10
5.1 EUT and Accessory List	10
5.2 Emissions Test Equipment	11
6. TEST SITE DESCRIPTION	12
6.1 Test Facility Description	12
6.2 EUT Mounting, Bonding and Grounding	12
6.3 Measurement Uncertainty	12
7. TEST PROCEDURES	13
7.1 RF Emissions	13
7.1.1 Conducted Emissions Test	13
7.1.2 Radiated Emissions Test	14
7.1.3 RF Emissions Test Results	16
7.1.4 Sample Calculations	17
7.1.5 Duty Cycle Calculation	19
7.1.6 99% Bandwidth	20
7.1.7 -20 dB Bandwidth	20
7.1.8 Transmission Time	21
8. CONCLUSIONS	22

LIST OF APPENDICES

APPENDIX	TITLE
A	Laboratory Accreditations and Recognitions
B	Modifications to the EUT
C	Models Covered Under This Report
D	Diagrams, Charts, and Photos <ul style="list-style-type: none">• Test Setup Diagrams• Antenna and Effective Gain Factors• Radiated Emissions Photos
E	Data Sheets

LIST OF FIGURES

FIGURE	TITLE
1	Layout of the Semi-Anechoic Test Chamber

LIST OF TABLES

TABLE	TITLE
1	Radiated Emission Results

GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Compatible Electronics Inc., which is an independent testing and consulting firm. The test report is based on testing performed by Compatible Electronics personnel according to the measurement procedures described in the test specifications given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced without the written permission of Compatible Electronics, unless done so in full.

This report must not be used by the client to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the United States government.

Device Tested: Flood Freeze Sensor
Model: CS-612
S/N: N/A

Product Description: The equipment under test is a battery powered Flood Freeze Sensor manufactured by Ecolink Intelligent Technology. The transmit frequency is 345 MHz. The clock frequencies are 4 MHz and 10.78125 MHz. Dimensions: 6.0 cm (L) x 2.5 cm (W) x 0.7 cm (H).

Modifications: The EUT was not modified to meet the specifications.

Customer: Ecolink Intelligent Technology, Inc.
2055 Corte Del Nogal
Carlsbad, California 92011

Test Dates: November 5, 2020 and December 14, 2020

Test Specifications covered by accreditation:

Test Specifications: Emissions requirements
CFR Title 47, Part 15, Subpart B;
CFR Title 47, Part 15, Subpart C, sections 15.205, 15.209, and 15.231; RSS-210 and RSS-Gen



Test Procedures: ANSI C63.4 and ANSI C63.10

Test Deviations: The test procedure was not deviated from during the testing.

Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Newbury Park Division
1050 Lawrence Drive
Newbury Park, CA 91320
(805) 480-4044

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

SUMMARY OF TEST RESULTS

TEST	DESCRIPTION	RESULTS
1	Spurious Radiated RF Emissions, 9 kHz – 3.45 GHz (Transmitter and Digital portion)	Complies with the Class B limits of CFR Title 47, Part 15 Subpart B; the limits of CFR Title 47, Part 15 Subpart C, sections 15.205, 15.209, and 15.231; and the limits of RSS-210 and RSS-Gen <small>Highest reading in relation to spec limit 75.20 dBuV/m (AVG) @ 345 MHz (*U = 3.19 dB)</small>
2	-20 dB Bandwidth	Complies with limits of CFR Title 47, Part 15 Subpart C, section 15.231 (c); and the limits of RSS-210
3	Transmission Time	Complies with limits of CFR Title 47, Part 15 Subpart C, section 15.231 (a)(1) and (a)(2); and the limits of RSS-210

*U = Expanded Uncertainty with a coverage factor of k=2

1. PURPOSE

This document is a qualification test report based on the emissions tests performed on the Flood Freeze Sensor, Model: CS-612. The emissions measurements were performed according to the measurement procedure described in ANSI C63.4 and ANSI C63.10. The tests were performed to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT hereafter, are within the Class B specification limits defined by CFR Title 47, Part 15 Subpart B section, 15.109; the specification limits defined by CFR Title 47, Part 15 Subpart C sections 15.205, 15.209 and 15.231; and the specifications limits defined by RSS-210 and RSS-Gen.

1.1 Decision Rule & Risk

If a measured value exceeds a specification limit it implies non-compliance. If the value is below a specification limit it implies compliance. Measurement uncertainty of the laboratory is reported with all measurement results but generally not taken into consideration unless a standard, rule or law requires it to be considered.

Qualification test reports are only produced for products that are in compliance with the test requirements, therefore results are always in conformity. Otherwise, an engineering report or just the data is provided to the customer.

When performing a measurement and making a statement of conformity, in or out-of-specification to manufacturer's specifications or Pass/Fail against a requirement, there are two possible outcomes:

- The result is reported as conforming with the specification
- The result is reported as not conforming with the specification

The decision rule is defined below.

When the test result is found to be below the limit but within our measurement uncertainty of the limit, it is our policy that the final acceptance decision is left to the customer, after discussing the implications and potential risks of the decision.

When the test result is found to be exactly on the specification, it is our policy, in the case of unwanted emissions measurements to consider the result non-compliant, however, the final decision is left to the customer, after discussing the implications and potential risks of the decision.

When the test result is found to be over the specification limit under any condition, it is our policy to consider the result non-compliant.

In terms of uncertainty of measurement, the laboratory is a calibrated and tightly controlled environment and generally exceptionally stable, the measurement uncertainties are evaluated without the considering of the test sample. When it comes to the test sample however, as most testing is performed on a single sample rather than a sample population, and that sample is often a pre-production representation of the final product, that test sample represents a significantly higher source of measurement uncertainty. We advise our customers of this and that when in doubt (small test to limit margins), they may wish to perform statistical sampling on a population to gain a higher confidence in the results. All lab reported results are that of a single sample in any event.



2. ADMINISTRATIVE DATA

2.1 Location of Testing

The emissions tests described herein were performed at the test facility of Compatible Electronics, 114 Olinda Drive, Brea, California 92823.

2.2 Traceability Statement

The calibration certificates of all test equipment used during the test are on file at the location of the test. The calibration is traceable to the National Institute of Standards and Technology (NIST).

2.3 Cognizant Personnel

Ecolink Intelligent Technology, Inc.

David Shepard	Engineer
Jay Stone	Director of Engineering

Compatible Electronics Inc.

Kyle Fujimoto	Test Engineer
James Ross	Test Engineer

2.4 Date Test Sample was Received

The test sample was received prior to the date of this report.

2.5 Disposition of the Test Sample

The test sample has not been returned to Ecolink Intelligent Technology, Inc. as of the date of this test report.

2.6 Abbreviations and Acronyms

The following abbreviations and acronyms may be used in this document.

EMI	Electromagnetic Interference
EUT	Equipment Under Test
P/N	Part Number
S/N	Serial Number
FCC	Federal Communications Commission
DoC	Declaration of Conformity
N/A	Not Applicable
Tx	Transmit
Rx	Receive
Inc.	Incorporated
RF	Radio Frequency
BLE	Bluetooth Low Energy
CFR	Code of Federal Regulations
N/A	Not Applicable
DC	Direct Current

3. APPLICABLE DOCUMENTS

The following documents are referenced or used in the preparation of this emission Test Report.

SPEC	TITLE
FCC Title 47, Part 15 Subpart C	FCC Rules – Radio frequency devices (including digital devices) – Intentional Radiators
FCC Title 47, Part 15 Subpart B	FCC Rules – Radio frequency devices (including digital devices) –Unintentional Radiators
RSS-210 Issue 10: 2019	License-exempt Radio Apparatus: Category I Equipment
RSS-Gen Issue 5: 2019 + Amendment 1	General Requirements for Compliance of Radio Apparatus
ANSI C63.4: 2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
ANSI C63.10: 2013	American National Standard of procedure for compliance testing of unlicensed wireless devices

4. DESCRIPTION OF TEST CONFIGURATION

4.1 Description of Test Configuration – Emissions

The Flood Freeze Sensor, Model: CS-612 (EUT) was tested as a stand alone unit. The EUT was transmitting at 345 MHz on a continuous basis.

The EUT was tested for emissions while in the X, Y and Z axis. The X orientation is when the EUT is parallel to the ground. The Y orientation is when the EUT is perpendicular to the ground mounted vertically. The Z orientation is when the EUT is perpendicular to the ground mounted horizontally.

The EUT was tested with a new battery.

The final radiated emissions data for the EUT was taken in the configuration described above. Please see Appendix E for the data sheets.

4.1.1 Cable Construction and Termination

Cable 1

This is a 50-centimeter unshielded cable connecting the EUT to a normally closed external sensor. The cable has a 2-pin jumper connector at the EUT end and is hard wired into the normally closed external sensor.



5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT

5.1 EUT and Accessory List

EQUIPMENT	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	FCC ID
FLOOD FREEZE SENSOR (EUT)	ECOLINK INTELLIGENT TECHNOLOGY, INC.	CS-612	N/A	XQC-CS612 IC: 9863B-CS612
EXTERNAL SENSOR	ECOLINK INTELLIGENT TECHNOLOGY, INC.	N/A	N/A	N/A



5.2 Emissions Test Equipment

EQUIPMENT TYPE	MANU-FACTURER	MODEL NUMBER	SERIAL NUMBER	CALIBRATION DATE	CAL. CYCLE
RADIATED EMISSIONS TEST EQUIPMENT					
TDK TestLab	TDK RF Solutions, Inc.	9.22	700145	N/A	N/A
EMI Receiver, 20 Hz – 40GHz	Rohde & Schwarz	ESIB40	100172	July 15, 2020	1 Year
Loop Antenna	Com-Power	AL-130R	121090	February 5, 2019	2 Year
CombiLog Antenna	Com-Power	AC-220	061093	June 5, 2019	2 Year
Horn Antenna	Com-Power	AH-118	10050113	February 4, 2020	2 Year
Preamplifier	Com-Power	PA-118	181653	February 5, 2020	1 Year
System Controller	Sunol Sciences Corporation	SC110V	112213-1	N/A	N/A
Turntable	Sunol Sciences Corporation	2011VS	N/A	N/A	N/A
Antenna-Mast	Sunol Sciences Corporation	TWR95-4	112213-3	N/A	N/A
Computer	Hewlett Packard	p6716f	MXX1030PX0	N/A	N/A
LCD Monitor	Hewlett Packard	52031a	3CQ046N3MG	N/A	N/A



6. TEST SITE DESCRIPTION

6.1 Test Facility Description

Please refer to section 2.1 of this report for emissions test location.

6.2 EUT Mounting, Bonding and Grounding

For frequencies 1 GHz and below: The EUT was mounted on a 0.6 by 1.2 meter non-conductive table 0.8 meters above the ground plane.

For frequencies above 1 GHz: The EUT was mounted on a 0.6 by 1.2 meter non-conductive table 1.5 meters above the ground plane.

The EUT was not grounded.

6.3 Measurement Uncertainty

Compatible Electronics' U_{lab} value is less than U_{cispr} , thus based on this – compliance is deemed to occur if no measured disturbance exceeds the disturbance limit

$$u_c(y) = \sqrt{\sum_i c_i^2 u^2(x_i)}$$

Measurement		U_{cispr}	$U_{lab} = 2 u_c(y)$
Conducted disturbance (mains port)	(150 kHz – 30 MHz)	3.4 dB	2.73 dB
Radiated disturbance (electric field strength on an open area test site or alternative test site)	(30 MHz – 1 000 MHz)	6.3 dB	3.27 dB (Vertical) 3.19 dB (Horizontal)
Radiated disturbance (electric field strength on an open area test site or alternative test site)	(1 GHz - 6 GHz)	5.2 dB	3.95 dB
Radiated disturbance (electric field strength on an open area test site or alternative test site)	(6 GHz – 18 GHz)	5.5 dB	3.95 dB
Radiated disturbance (electric field strength on an open area test site or alternative test site)	(18 GHz – 26.5 GHz)	N/A	4.69 dB
Radiated disturbance (electric field strength on an open area test site or alternative test site)	(26.5 GHz – 40 GHz)	N/A	4.55 dB



7. TEST PROCEDURES

The following sections describe the test methods and the specifications for the tests. Test results are also included in this section.

7.1 RF Emissions

7.1.1 Conducted Emissions Test

The EMI Receiver was used as a measuring meter. A quasi-peak and/or average reading was taken only where indicated in the data sheets. A 10 dB attenuator was used for the protection of the EMI Receiver input stage, and the offset was adjusted accordingly to read the actual data measured. The LISN output was measured using the EMI Receiver. The output of the second LISN was terminated by a 50-ohm termination. The effective measurement bandwidth used for this test was 9 kHz.

Please see section 6.2 of this report for mounting, bonding, and grounding of the EUT. The EUT was powered through the LISN, which was bonded to the ground plane. The LISN power was filtered and the filter was bonded to the ground plane. The EUT was set up with the minimum distances from any conductive surfaces as specified in ANSI 63:4. The excess power cord was wrapped in a figure eight pattern to form a bundle not exceeding 0.4 meters in length.

The conducted emissions from the EUT were maximized for operating mode as well as cable placement. The final data was collected under program control by computer software. The final qualification data is located in Appendix E.

Test Results:

This test was not performed because the EUT operates on battery power only and cannot be connected to the AC public mains.

7.1.2 Radiated Emissions Test

The EMI Receiver was used as the measuring meter. An internal preamplifier was used to increase the sensitivity of the instrument during emissions tests up to 1000 MHz, and an external preamplifier was used to increase the sensitivity of the instrument during emissions tests above 1 GHz. The EMI Receiver was initially used with the Analyzer mode feature activated. In this mode, the EMI receiver can then record the actual frequency to be measured. This final reading is then taken accurately in the EMI Receiver mode, which takes into account the cable loss, amplifier gain and antenna factors, so that a true reading is compared to the true limit. The effective measurement bandwidth used for the radiated emissions test was according to the frequency measured.

The frequencies below 1 GHz, except for the fundamental frequency and the 2nd harmonic of the fundamental frequency, were quasi-peaked using the quasi-peak detector of the EMI Receiver.

The harmonic frequencies above 1 GHz, the fundamental frequency, and the 2nd harmonic were averaged using the duty cycle correction calculation.

All other frequencies above 1 GHz were averaged using the average detector of the EMI Receiver.

The EMI test chamber of Compatible Electronics, Inc. was used for radiated emissions testing. This test site is in full compliance with ANSI C63.4. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees in order to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. At each reading, the EUT was rotated 360 degrees and the antenna height was varied from 1 to 4 meters (for E field radiated field strength). The gunsight method was used when measuring with the horn antenna to ensure accurate results.

The EUT was tested at a 3-meter test distance. The six highest emissions are listed in Table 1.



Radiated Emissions Test (Continued)

The measurement bandwidths and transducers used for the radiated emissions test were:

FREQUENCY RANGE	EFFECTIVE MEASUREMENT BANDWIDTH	TRANSDUCER
9 kHz to 150 kHz	200 Hz	Loop Antenna
150 kHz to 30 MHz	9 kHz	Loop Antenna
30 MHz to 1 GHz	120 kHz	CombiLog Antenna
1 GHz to 3.45 GHz	1 MHz	Horn Antenna

Test Results:

The EUT complies with the **Class B** limits of CFR Title 47, Part 15, Subpart B; the limits of CFR Title 47, Part 15, Subpart C sections 15.205, 15.209 and 15.231; and the limits of RSS-210 and RSS-Gen for radiated emissions.

7.1.3 RF Emissions Test Results

Table 1 RADIATED EMISSION RESULTS
Flood Freeze Sensor
Model: CS-612

Frequency (MHz)	EMI Reading (dBuV/m)	Specification Limit (dBuV/m)	Delta (Cor. Reading – Spec. Limit) (dB)
345.00 (H) (X-Axis)	75.20 (AVG)	77.26	-2.07
345.00 (V) (Y-Axis)	71.76 (AVG)	77.26	-5.50
345.00 (H) (Z-Axis)	71.59 (AVG)	77.26	-5.67
345.00 (H) (Y-Axis)	69.87 (AVG)	77.26	-7.39
690.00 (V) (Y-Axis)	48.38 (AVG)	57.26	-8.88
2760.00 (V) (Y-Axis)	44.76 (AVG)	53.97	-9.21

Notes:

- * The complete emissions data is given in Appendix E of this report.
- (V) Vertical Polarization
- (H) Horizontal Polarization
- (AVG) Average Reading



7.1.4 Sample Calculations

A correction factor for the antenna, cable, and a distance factor (if any) must be applied to the meter reading before a true field strength reading can be obtained. This Corrected Meter Reading is then compared to the specification limit in order to determine compliance with the limits.

Conversion to logarithmic terms: Specification limit ($\mu\text{V}/\text{m}$) $\log \times 20 =$ Specification Limit in $\text{dB}\mu\text{V}/\text{m}$

To correct for distance when measuring at a distance other than the specification

For measurements below 30 MHz: (Specification distance / test distance) $\log \times 40 =$ distance factor

For measurements above 30 MHz: (Specification distance / test distance) $\log \times 20 =$ distance factor

Note: When using an Active Antenna, the Antenna factor shall be subtracted due to the combination of the internal amplification and antenna loss.

Corrected Meter Reading = meter reading + F – A + C

where: F = antenna factor
A = amplifier gain
C = cable loss

The correction factors for the antenna and the amplifier gain are attached in Appendix D of this report. The data sheets are attached in Appendix E.

The distance factor D is 0 when the test is performed at the required specification distance.

When the limit is in terms of magnetic field, the following equation applies:

$$H[\text{dB}(\mu\text{A}/\text{m})] = V[\text{dB}(\mu\text{V})] + L_C [\text{dB}] - G_{PA} [\text{dB}] + AF^H [\text{dB}(\text{S}/\text{m})]$$

where: H is the magnetic field strength (to be compared with the limit),
 V is the voltage level measured by the receiver or spectrum analyzer,
 L_C is the cable loss,
 G_{PA} is the gain of the preamplifier (if used), and
 AF^H is the magnetic antenna factor.

The G_{PA} term is only included in the equation when an external preamplifier is used in the measurement chain, in front of the receiver or spectrum analyzer. An external preamplifier is not usually necessary (or even advisable, due to risk of saturating the input mixer of the receiver) when an active loop antenna is used. In that case, the antenna factor of the loop already includes the gain of its built-in preamplifier.



Sample Calculations (Continued)

If the “electrical” antenna factor is used instead, the above equation becomes:

$$H[\text{dB}(\mu\text{A}/\text{m})] = V[\text{dB}(\mu\text{V})] + L_C[\text{dB}] - G_{PA}[\text{dB}] + AF^E[\text{dB}(\text{m}^{-1})] - 51.5[\text{dB}\Omega]$$

where: AF^E is the “electric” antenna factor, as provided by the antenna calibration laboratory.

When the limit is in terms of electric field, the following equation applies:

$$E[\text{dB}(\mu\text{V}/\text{m})] = V[\text{dB}(\mu\text{V})] + L_C[\text{dB}] - G_{PA}[\text{dB}] + AF^E[\text{dB}(\text{m}^{-1})]$$

or, if the magnetic antenna factor is used:

$$E[\text{dB}(\mu\text{V}/\text{m})] = V[\text{dB}(\mu\text{V})] + L_C[\text{dB}] - G_{PA}[\text{dB}] + AF^H[\text{dB}(\text{S}/\text{m})] + 51.5[\text{dB}\Omega]$$

The display of the receiver (or spectrum analyzer) **shall not** be configured in units of current, e.g. μA or $\text{dB}(\mu\text{A})$. That conversion is calculated inside the receiver (or spectrum analyzer) using its input impedance, which is $50\ \Omega$, while the magnetic field calculation is based on the free-space impedance of $377\ \Omega$.



7.1.5 Duty Cycle Calculation

The fundamental and harmonics were measured at a 3-meter test distance. The EMI Receiver was used to obtain the final test data. The final qualification data sheets are located in Appendix E.

Where

$$\delta(\text{dB}) = 20 \log \left[\sum (nt_1 + mt_2 + \dots + \xi t_x) / T \right]$$

n is the number of pulses of duration t_1

m is the number of pulses of duration t_2

ξ is the number of pulses of duration t_x

T is the period of the pulse train or 100 ms if the pulse train length is greater than 100 ms

Duty Cycle Correction Factor = -19.12 dB

Time of One Small Pulse = 140.280561 us

Time of One Large Pulse = 270.541082 us

Number of Small Pulses = 48

Number of Large Pulses = 16

Total On Time = 11062.12424 us = 11.06212424 ms

The time between pulses is greater than 100 ms

Duty Cycle = 11.06212424 ms / 100 ms = 11.06212424%

7.1.6 99% Bandwidth

The 99% bandwidth was measured using an EMI Receiver.

The following steps were performed for measuring the 99% bandwidth per RSS-GEN, Issue 5, clause 6.7:

1. Set RBW to 1 % to 5 % of the actual occupied bandwidth.
2. Set VBW to greater than 3 times the RBW.
3. Set the EMI Receiver to the occupied bandwidth Function set at 99%
4. Set the peak detector to max hold.
5. Set the sweep time to auto
6. Allow the trace to stabilize.

Please note that this was only used to determine the emission bandwidth and that there are no limits or pass/fail criteria for this test. Please see the data sheets located in Appendix E.

7.1.7 -20 dB Bandwidth

The -20 dB bandwidth was measured using an EMI Receiver.

The following steps were performed for measuring the -20 dB bandwidth:

1. Set RBW to at least 1% of the maximum occupied bandwidth allowed.
2. Set VBW to greater than 3 times the RBW.
3. Set the peak detector to max hold.
4. Set the sweep time to auto
5. Allow the trace to stabilize.
6. Set the markers to -20 dB of the peak fundamental emission

Test Results:

The EUT complies with limits of CFR Title 47, Part 15, Subpart C section 15.231 (c); and the limits of RSS-210.

7.1.8 Transmission Time

The transmission time was measured using an EMI Receiver.

The following steps were performed for measuring transmission time:

1. Set RBW = 120 kHz.
2. Set VBW = 500 kHz
3. Span = 0 Hz
4. Set the sweep time to 10 seconds
5. Push a button on the EUT, which automatically activated the transmitter.
6. Allow the trace to stabilize.
7. Set the 1st marker to start of the transmission
8. Set the 2nd marker for 5 seconds after the start of the transmission
9. Verify the transmission does not go beyond the 2nd marker.
10. Verify that the total number of transmissions is less than 2 seconds when the EUT is polling.

Test Results:

The EUT complies with limits of CFR Title 47, Part 15, Subpart C section 15.231 (a)(1) and (a)(2); and the limits of RSS-210.

8. CONCLUSIONS

The Flood Freeze Sensor, Model: CS-612 (EUT), as tested, meets all of the specification limits defined in RSS-210, RSS-Gen, the **Class B** specification limits defined in CFR Title 47, Part 15, Subpart B; and the specification limits defined in CFR Title 47, Part, 15, Subpart C, sections 15.205, 15.209 and 15.231.





APPENDIX A

LABORATORY ACCREDITATIONS AND RECOGNITIONS

LABORATORY ACCREDITATIONS AND RECOGNITIONS



For US, Canada, Australia/New Zealand, Japan, Taiwan, Korea, and the European Union, Compatible Electronics is currently accredited by NVLAP to ISO/IEC 17025. **For the most up-to-date version of our scopes and certificates please visit <http://celectronics.com/quality/scope/>**

Quote from ISO-ILAC-IAF Communiqué on 17025:

"A laboratory's fulfilment of the requirements of ISO/IEC 17025:2005 means the laboratory meets both the technical competence requirements and management system requirements that are necessary for it to consistently deliver technically valid test results and calibrations. The management system requirements in ISO/IEC 17025:2005 (Section 4) are written in language relevant to laboratory operations and meet the principles of ISO 9001:2008 Quality Management Systems — Requirements."

Innovation, Science and Economic Development Canada
Lab Code 2154A



APPENDIX B

MODIFICATIONS TO THE EUT

MODIFICATIONS TO THE EUT

The modifications listed below were made to the EUT to pass FCC Subpart B, FCC 15.231, RSS-210, and RSS-Gen specifications.

All the rework described below was implemented during the test in a method that could be reproduced in all the units by the manufacturer.

No modifications were made to the EUT during the testing.





APPENDIX C

MODELS COVERED UNDER THIS REPORT

MODELS COVERED UNDER THIS REPORT

USED FOR THE PRIMARY TEST

Flood Freeze Sensor

Model: CS-612

S/N: N/A

There are no additional models or part numbers covered under this report.






APPENDIX D

DIAGRAMS, CHARTS, AND PHOTOS

**FIGURE 1: LAYOUT OF THE
SEMI-ANECHOIC TEST CHAMBER**



COM-POWER AL-130R**LOOP ANTENNA**

S/N: 121090

CALIBRATION DATE: FEBRUARY 5, 2019

FREQUENCY (MHz)	MAGNETIC (dB/m)	ELECTRIC (dB/m)
0.009	16.1	-35.4
0.01	15.6	-35.9
0.02	14.8	-36.7
0.03	15.6	-35.9
0.04	15.1	-36.4
0.05	14.4	-37.0
0.06	14.6	-36.9
0.07	14.4	-37.1
0.08	14.3	-37.1
0.09	14.5	-36.9
0.10	14.1	-37.3
0.20	14.1	-37.3
0.30	14.0	-37.4
0.40	14.0	-37.4
0.50	14.2	-37.2
0.60	14.2	-37.2
0.70	14.2	-37.2
0.80	14.2	-37.3
0.90	14.3	-37.2
1.00	14.5	-37.0
2.00	14.5	-36.9
3.00	14.5	-36.9
4.00	14.7	-36.8
5.00	14.6	-36.9
6.00	14.6	-36.9
7.00	14.6	-36.9
8.00	14.6	-36.9
9.00	14.6	-36.9
10.00	14.8	-36.6
11.00	14.9	-36.6
12.00	14.8	-36.6
13.00	14.8	-36.7
14.00	14.6	-36.8
15.00	14.5	-36.9
16.00	14.5	-37.0
17.00	14.6	-36.9
18.00	14.7	-36.7
19.00	14.8	-36.6
20.00	14.9	-36.6
21.00	14.6	-36.8
22.00	14.2	-37.2
23.00	13.7	-37.7
24.00	13.3	-38.2
25.00	13.0	-38.5
26.00	12.9	-38.6
27.00	13.0	-38.5
28.00	13.1	-38.4
29.00	13.1	-38.4
30.00	12.9	-38.5

COM-POWER AC-220**COMBILOG ANTENNA****S/N: 61093****CALIBRATION DATE: JUNE 5, 2019**

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
30	22.10	200	15.30
35	20.90	250	16.80
40	20.10	300	19.00
45	19.40	350	19.60
50	18.40	400	21.70
60	15.10	450	21.60
70	12.00	500	22.20
80	11.60	550	22.70
90	13.50	600	24.20
100	14.70	650	24.40
120	15.90	700	24.50
125	15.90	750	25.40
140	14.80	800	26.30
150	15.50	850	26.70
160	19.80	900	27.50
175	15.20	950	27.80
180	14.90	1000	27.90

COM POWER AH-118**HORN ANTENNA**

S/N: 10050113

CALIBRATION DATE: FEBRUARY 4, 2020


FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
1.0	24.343	10.0	38.826
1.5	25.419	10.5	39.102
2.0	28.838	11.0	38.259
2.5	28.971	11.5	39.920
3.0	29.919	12.0	40.149
3.5	30.674	12.5	40.576
4.0	31.670	13.0	40.264
4.5	32.437	13.5	40.364
5.0	33.414	14.0	40.424
5.5	34.003	14.5	41.677
6.0	34.799	15.0	43.010
6.5	35.381	15.5	39.799
7.0	37.024	16.0	40.187
7.5	37.403	16.5	40.155
8.0	37.445	17.0	40.507
8.5	37.390	17.5	41.963
9.0	38.076	18.0	43.196
9.5	38.809		

COM-POWER PA-118**PREAMPLIFIER**

S/N: 181653

CALIBRATION DATE: FEBRUARY 5, 2020

FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
1.0	40.10	6.0	40.60
1.1	40.10	6.5	39.50
1.2	40.00	7.0	39.40
1.3	39.70	7.5	39.30
1.4	39.60	8.0	39.20
1.5	39.90	8.5	40.50
1.6	40.00	9.0	39.60
1.7	39.70	9.5	39.50
1.8	39.50	10.0	38.80
1.9	39.60	11.0	38.70
2.0	39.90	12.0	42.20
2.5	40.10	13.0	40.00
3.0	40.80	14.0	40.30
3.5	40.60	15.0	40.20
4.0	40.50	16.0	41.00
4.5	41.60	17.0	39.70
5.0	39.20	18.0	40.90
5.5	40.00		




FRONT VIEW

ECOLINK INTELLIGENT TECHNOLOGY, INC.
FLOOD FREEZE SENSOR
MODEL: CS-612

FCC SUBPART B AND C; RSS-210 AND RSS-GEN – RADIATED EMISSIONS – BELOW 1 GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**




REAR VIEW

ECOLINK INTELLIGENT TECHNOLOGY, INC.
FLOOD FREEZE SENSOR
MODEL: CS-612

FCC SUBPART B AND C; RSS-210 AND RSS-GEN – RADIATED EMISSIONS – BELOW 1 GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



FRONT VIEW


1ECOLINK INTELLIGENT TECHNOLOGY, INC.
ECOLINK INTELLIGENT TECHNOLOGY, INC.

FLOOD FREEZE SENSOR

MODEL: CS-612

FCC SUBPART B AND C; RSS-210 AND RSS-GEN – RADIATED EMISSIONS – ABOVE 1 GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**

**REAR VIEW**

ECOLINK INTELLIGENT TECHNOLOGY, INC.

FLOOD FREEZE SENSOR

MODEL: CS-612

FCC SUBPART B AND C; RSS-210 AND RSS-GEN – RADIATED EMISSIONS – ABOVE 1 GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONs**

APPENDIX E

DATA SHEETS

RADIATED EMISSIONS


DATA SHEETS

Title: Pre-Scan - FCC Class B
 File: 1 - LF - Pre-Scan - Flood Sensor - NO Read Switch - X-Axis - FCC Class B - 12-14-2020.st
 Operator: Kyle Fujimoto
 EUT Type: Flood Sensor
 EUT Condition: The EUT is continuously transmitting at 345 MHz
 Company: Ecolink Intelligent Technology, Inc.
 M/N: CS-612
 S/N: N/A
 X-Axis
 Note: The Frequency at 345 MHz is from the intentional radiator and is subject to the limits of FCC 15.231 instead.

12/14/2020 1:39:35 PM
 Sequence: Preliminary Scan

FCC Class B

Electric Field Strength (dB μ V/m)



Title: Radiated Final - FCC Class B
 File: 1 - LF - Final Scan - Flood Sensor - NO Read Switch - X-Axis - FCC Class B - 12-14-2020.set
 Operator: Kyle Fujimoto
 EUT Type: Flood Sensor
 EUT Condition: The EUT is continuously transmitting at 345 MHz
 Comments: Company: Ecolink Intelligent Technology, Inc.
 M/N: CS-612
 S/N: N/A
 X-Axis (Worst Case)

12/14/2020 1:49:27 PM
 Sequence: Final Measurements

FCC Class B										
Freq (MHz)	Pol	(PEAK) EMI (dB μ V/m)	(QP) EMI (dB μ V/m)	(PEAK) Margin (dB)	(QP) Margin (dB)	Limit (dB μ V/m)	Transducer (dB)	Cable (dB)	Ttbl Aql (dea)	Twr Ht (cm)
161.50	V	34.82	22.94	-8.68	-20.56	43.50	22.06	0.88	275.50	238.80
162.00	H	35.59	22.56	-7.91	-20.94	43.50	21.68	0.88	353.75	319.22
866.00	H	42.25	29.04	-3.75	-16.96	46.00	26.70	2.34	13.25	285.67
895.80	H	43.16	29.83	-2.84	-16.17	46.00	27.40	2.43	329.25	158.92
917.60	H	44.76	30.51	-1.24	-15.49	46.00	28.00	2.51	54.75	287.22
920.10	H	43.95	30.55	-2.05	-15.45	46.00	28.02	2.53	294.00	334.98
921.40	H	44.49	30.61	-1.51	-15.39	46.00	28.08	2.53	1.50	387.76
928.60	H	43.82	30.41	-2.18	-15.59	46.00	27.85	2.56	179.00	351.52
929.00	H	44.51	30.36	-1.49	-15.64	46.00	27.80	2.56	352.75	222.98
953.90	H	44.70	30.45	-1.30	-15.55	46.00	27.80	2.65	169.00	174.86





FUNDAMENTAL AND HARMONICS

DATA SHEETS



FCC 15.231

Ecolink Intelligent Technology, Inc.
 Flood Freeze Sensor
 Model: CS-612

Date: 12/14/2020
 Lab: D
 Tested By: Kyle Fujimoto

Fundamental

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
345.00	85.02	V	97.26	-12.25	Peak	349.75	116.89	X-Axis
345.00	65.90	V	77.26	-11.37	Avg	349.75	116.89	Vertical Polarization
345.00	90.88	V	97.26	-6.38	Peak	273.00	167.76	Y-Axis
345.00	71.76	V	77.26	-5.50	Avg	273.00	167.76	Vertical Polarization
345.00	90.71	V	97.26	-6.55	Peak	58.75	195.88	Z-Axis
345.00	71.59	V	77.26	-5.67	Avg	58.75	195.88	Vertical Polarization
345.00	94.32	H	97.26	-2.95	Peak	3.75	101.00	X-Axis
345.00	75.20	H	77.26	-2.07	Avg	3.75	101.00	Horizontal Polarization
345.00	88.99	H	97.26	-8.27	Peak	207.50	100.28	Y-Axis
345.00	69.87	H	77.26	-7.39	Avg	207.50	100.28	Horizontal Polarization
345.00	86.76	H	97.26	-10.50	Peak	176.00	201.31	Z-Axis
345.00	67.64	H	77.26	-9.62	Avg	176.00	201.31	Horizontal Polarization

**FCC 15.231**

Ecolink Intelligent Technology, Inc.
 Flood Freeze Sensor
 Model: CS-612

Date: 12/14/2020
 Lab: D
 Tested By: Kyle Fujimoto

Harmonics**Transmit Mode - X-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
690.00	43.00	V	77.26	-34.26	Peak	201.50	104.65	
690.00	23.88	V	57.26	-33.38	Avg	201.50	104.65	
1035.00	40.74	V	73.97	-33.23	Peak	229.00	185.07	
1035.00	21.62	V	53.97	-32.35	Avg	229.00	158.07	
1380.00	43.40	V	73.97	-30.57	Peak	265.50	152.23	
1380.00	24.28	V	53.97	-29.69	Avg	265.50	152.23	
1725.00	44.04	V	77.26	-33.22	Peak	195.75	153.73	
1725.00	24.92	V	57.26	-32.34	Avg	195.75	153.73	
2070.00	48.35	V	77.26	-28.91	Peak	192.00	157.43	
2070.00	29.23	V	57.26	-28.03	Avg	192.00	157.43	
2415.00	53.37	V	77.26	-23.89	Peak	108.75	211.04	
2415.00	34.25	V	57.26	-23.01	Avg	108.75	21.04	
2760.00	55.94	V	73.97	-18.03	Peak	56.00	188.11	
2760.00	36.82	V	53.97	-17.15	Avg	56.00	188.11	
3105.00	57.04	V	77.26	-20.22	Peak	304.00	136.65	
3105.00	37.92	V	57.26	-19.34	Avg	304.00	136.65	
3450.00	53.38	V	77.26	-23.88	Peak	259.75	118.20	
3450.00	34.26	V	57.26	-23.00	Avg	259.75	118.20	

**FCC 15.231**

Ecolink Intelligent Technology, Inc.
Flood Freeze Sensor
Model: CS-612

Date: 12/14/2020

Lab: D

Tested By: Kyle Fujimoto

Harmonics**Transmit Mode - Y-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
690.00	67.50	V	77.26	-9.76	Peak	67.50	111.40	
690.00	48.38	V	57.26	-8.88	Avg	67.50	111.40	
1035.00	45.31	V	73.97	-28.66	Peak	258.00	125.13	
1035.00	26.19	V	53.97	-27.78	Avg	258.00	125.13	
1380.00	46.17	V	73.97	-27.80	Peak	0.50	114.38	
1380.00	27.05	V	53.97	-26.92	Avg	0.50	114.38	
1725.00	51.48	V	77.26	-25.78	Peak	159.25	111.10	
1725.00	32.36	V	57.26	-24.90	Avg	159.25	111.10	
2070.00	57.58	V	77.26	-19.68	Peak	189.25	164.77	
2070.00	38.46	V	57.26	-18.80	Avg	189.25	164.77	
2415.00	55.72	V	77.26	-21.55	Peak	279.75	176.17	
2415.00	36.60	V	57.26	-20.67	Avg	279.75	176.17	
2760.00	63.88	V	73.97	-10.09	Peak	240.50	159.94	
2760.00	44.76	V	53.97	-9.21	Avg	240.50	159.94	
3105.00	61.94	V	77.26	-15.33	Peak	265.25	159.94	
3105.00	42.82	V	57.26	-14.45	Avg	265.25	159.94	
3450.00	58.51	V	77.26	-18.76	Peak	191.75	161.43	
3450.00	39.39	V	57.26	-17.88	Avg	191.75	161.43	

**FCC 15.231**

Ecolink Intelligent Technology, Inc.
 Flood Freeze Sensor
 Model: CS-612

Date: 12/14/2020
 Lab: D
 Tested By: Kyle Fujimoto

Harmonics**Transmit Mode - Z-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
690.00	41.26	V	77.26	-36.00	Peak	110.00	111.68	
690.00	22.14	V	57.26	-35.12	Avg	110.00	111.68	
1035.00	44.93	V	73.97	-29.04	Peak	350.00	100.25	
1035.00	25.81	V	53.97	-28.16	Avg	350.00	100.25	
1380.00	44.94	V	73.97	-29.03	Peak	139.00	174.62	
1380.00	25.82	V	53.97	-28.15	Avg	139.00	174.62	
1725.00	49.69	V	77.26	-27.57	Peak	271.00	129.67	
1725.00	30.57	V	57.26	-26.69	Avg	271.00	129.67	
2070.00	51.88	V	77.26	-25.38	Peak	284.50	136.65	
2070.00	32.76	V	57.26	-24.50	Avg	284.50	136.65	
2415.00	59.29	V	77.26	-17.97	Peak	155.00	130.74	
2415.00	40.17	V	57.26	-17.09	Avg	155.00	130.74	
2760.00	60.49	V	73.97	-13.48	Peak	358.25	130.74	
2760.00	41.37	V	53.97	-12.60	Avg	358.25	130.74	
3105.00	61.01	V	77.26	-16.26	Peak	352.00	114.98	
3105.00	41.89	V	57.26	-15.38	Avg	352.00	114.98	
3450.00	60.86	V	77.26	-16.40	Peak	261.50	194.92	
3450.00	41.74	V	57.26	-15.52	Avg	261.50	194.92	

**FCC 15.231**

Ecolink Intelligent Technology, Inc.

Flood Freeze Sensor

Model: CS-612

Date: 12/14/2020

Lab: D

Tested By: Kyle Fujimoto

Harmonics**Transmit Mode - X-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
690.00	43.50	H	77.26	-33.76	Peak	309.25	110.86	
690.00	24.38	H	57.26	-32.88	Avg	309.25	110.86	
1035.00	45.04	H	73.97	-28.93	Peak	325.25	161.79	
1035.00	25.92	H	53.97	-28.05	Avg	325.25	161.79	
1380.00	46.64	H	73.97	-27.33	Peak	350.00	164.47	
1380.00	27.52	H	53.97	-26.45	Avg	350.00	164.47	
1725.00	53.61	H	77.26	-23.65	Peak	180.75	203.46	
1725.00	34.49	H	57.26	-22.77	Avg	108.75	203.46	
2070.00	57.30	H	77.26	-19.96	Peak	224.50	159.16	
2070.00	38.18	H	57.26	-19.08	Avg	224.50	159.16	
2415.00	59.39	H	77.26	-17.87	Peak	296.75	203.52	
2415.00	40.27	H	57.26	-16.99	Avg	296.75	203.52	
2760.00	63.81	H	73.97	-10.16	Peak	167.75	122.08	
2760.00	44.69	H	53.97	-9.28	Avg	167.75	122.08	
3105.00	61.19	H	77.26	-16.07	Peak	226.25	133.91	
3105.00	42.07	H	57.26	-15.19	Avg	226.25	133.91	
3450.00	57.80	H	77.26	-19.46	Peak	357.25	173.37	
3450.00	38.68	H	57.26	-18.58	Avg	357.25	173.37	

**FCC 15.231**

Ecolink Intelligent Technology, Inc.

Flood Freeze Sensor

Model: CS-612

Date: 12/14/2020

Lab: D

Tested By: Kyle Fujimoto

Harmonics**Transmit Mode - Y-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
690.00	44.13	H	77.26	-33.13	Peak	228.50	115.22	
690.00	25.01	H	57.26	-32.25	Avg	228.50	115.22	
1035.00	38.06	H	73.97	-35.91	Peak	283.50	113.97	
1035.00	18.94	H	53.97	-35.03	Avg	283.50	113.97	
1380.00	43.76	H	73.97	-30.21	Peak	173.75	180.47	
1380.00	24.64	H	53.97	-29.33	Avg	173.75	180.47	
1725.00	50.24	H	77.26	-27.02	Peak	168.50	176.23	
1725.00	31.12	H	57.26	-26.14	Avg	168.50	176.23	
2070.00	57.95	H	77.26	-19.31	Peak	345.50	180.83	
2070.00	38.83	H	57.26	-18.43	Avg	345.50	180.83	
2415.00	60.05	H	77.26	-17.21	Peak	350.00	143.40	
2415.00	40.93	H	57.26	-16.33	Avg	350.00	143.40	
2760.00	60.44	H	73.97	-13.53	Peak	317.00	131.10	
2760.00	41.32	H	53.97	-12.65	Avg	317.00	131.10	
3105.00	62.91	H	77.26	-14.35	Peak	137.00	121.01	
3105.00	43.79	H	57.26	-13.47	Avg	137.00	121.01	
3450.00	55.87	H	77.26	-21.40	Peak	175.25	134.38	
3450.00	36.75	H	57.26	-20.52	Avg	175.25	134.38	

**FCC 15.231**

Ecolink Intelligent Technology, Inc.
Flood Freeze Sensor
Model: CS-612

Date: 12/14/2020

Lab: D

Tested By: Kyle Fujimoto

Harmonics**Transmit Mode - Z-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
690.00	41.24	H	77.26	-36.02	Peak	26.75	101.00	
690.00	22.12	H	57.26	-35.14	Avg	26.75	101.00	
1035.00	42.29	H	73.97	-31.68	Peak	352.00	136.05	
1035.00	23.17	H	53.97	-30.80	Avg	352.00	136.05	
1380.00	43.18	H	73.97	-30.79	Peak	125.75	190.02	
1380.00	24.06	H	53.97	-29.91	Avg	125.75	190.02	
1725.00	53.40	H	77.26	-23.86	Peak	142.00	192.89	
1725.00	34.28	H	57.26	-22.98	Avg	142.00	192.89	
2070.00	59.33	H	77.26	-17.93	Peak	350.00	205.37	
2070.00	40.21	H	57.26	-17.05	Avg	350.00	205.37	
2415.00	56.30	H	77.26	-20.96	Peak	10.00	158.56	
2415.00	37.18	H	57.26	-20.08	Avg	10.00	158.56	
2760.00	60.58	H	73.97	-13.40	Peak	108.25	150.98	
2760.00	41.46	H	53.97	-12.52	Avg	180.25	150.98	
3105.00	60.83	H	77.26	-16.43	Peak	158.25	161.55	
3105.00	41.71	H	57.26	-15.55	Avg	158.25	161.55	
3450.00	57.68	H	77.26	-19.58	Peak	151.00	149.61	
3450.00	38.56	H	57.26	-18.70	Avg	51.00	149.61	



FCC Class B and FCC 15.231

Ecolink Intelligent Technology, Inc.
Flood Freeze Sensor
Model: CS-612

Date: 12/14/2020
Lab: D
Tested By: Kyle Fujimoto

Non Harmonic Emissions from the Tx and Digital Portion - 9 kHz to 30 MHz
Non Harmonic Emissions from the Tx and Digital Portion - 1 GHz To 3.45 GHz

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
								No Emissions Detected
								from 9 kHz to 30 MHz
								for the digital portion
								of the EUT
								No Emissions Detected
								from 1 GHz to 3.45 GHz
								for the digital portion
								of the EUT
								from 9 kHz to 30 MHz
								for the Non-Harmonic Emissions
								of the Transmitter for the EUT
								No Emissions Detected
								from 1 GHz to 3.45 GHz
								for the Non-Harmonic Emissions
								of the Transmitter for the EUT
								Investigated in the X-Axis,
								Y-Axis, and Z-Axis



99 % BANDWIDTH
DATA SHEET



Marker 1 [T2]

RBW 1 kHz RF Att 10 dB

Ref Lvl 92.60 dBV

VBW 3 kHz


108.4 dBV

344.99624248 MHz

SWT 1.25 s

Unit

dBV



Date: 5.NOV.2020 08:35:26

99 Percent Bandwidth Plot

Brea Division
 114 Olinda Drive
 Brea, CA 92823
 (714) 579-0500

Newbury Park Division
 1050 Lawrence Drive
 Newbury Park, CA 91320
 (805) 480-4044

Lake Forest Division
 20621 Pascal Way
 Lake Forest, CA 92630
 (949) 587-0400



-20 dB BANDWIDTH PLOT
DATA SHEET



Delta 2 [T2]

RBW 10 kHz RF Att 10 dB


Ref Lvl -0.90 dB

VBW 30 kHz

108.4 dBmV 505.01002004 kHz

SWT 100 ms Unit

dBmV



Date: 5.NOV.2020 08:27:26

-20 dB Bandwidth Plot

Brea Division
 114 Olinda Drive
 Brea, CA 92823
 (714) 579-0500

Newbury Park Division
 1050 Lawrence Drive
 Newbury Park, CA 91320
 (805) 480-4044

Lake Forest Division
 20621 Pascal Way
 Lake Forest, CA 92630
 (949) 587-0400



TRANSMISSION TIME
DATA SHEET



Delta 1 [T2]

RBW 1 MHz RF Att 10 dB


Ref Lvl 0.13 dB

VBW 3 MHz

128.4 dBmV 2.324649 s

SWT 10 s

Unit dBmV



Date: 5.NOV.2020 08:17:34

The transmit time is 2.324649 seconds

Brea Division
 114 Olinda Drive
 Brea, CA 92823
 (714) 579-0500

Newbury Park Division
 1050 Lawrence Drive
 Newbury Park, CA 91320
 (805) 480-4044

Lake Forest Division
 20621 Pascal Way
 Lake Forest, CA 92630
 (949) 587-0400



Delta 1 [T2]

RBW 1 MHz RF Att 10 dB

Ref Lvl -0.12 dB

VBW 3 MHz


128.4 dBμV

5.010020 s

SWT 10 s

Unit

dBμV



Date: 5.NOV.2020 08:17:52

The transmitter shuts off within 5 seconds of being activated

Brea Division
 114 Olinda Drive
 Brea, CA 92823
 (714) 579-0500

Newbury Park Division
 1050 Lawrence Drive
 Newbury Park, CA 91320
 (805) 480-4044

Lake Forest Division
 20621 Pascal Way
 Lake Forest, CA 92630
 (949) 587-0400

DUTY CYCLE

DATA SHEETS



Delta 1 [T2]


RBW 1 MHz RF Att 10 dB

Ref Lvl 0.27 dB

VBW 3 MHz

128.4 dBV 148.296593 ms

SWT 1 s Unit dBV



Date: 5.NOV.2020 07:53:49

The pulse train only appears once every 100 ms

Brea Division
 114 Olinda Drive
 Brea, CA 92823
 (714) 579-0500

Newbury Park Division
 1050 Lawrence Drive
 Newbury Park, CA 91320
 (805) 480-4044

Lake Forest Division
 20621 Pascal Way
 Lake Forest, CA 92630
 (949) 587-0400



Delta 1 [T2]

RBW 1 MHz RF Att 10 dB


Ref Lvl -0.66 dB

VBW 3 MHz

107.7 dBV 140.280561 us

SWT 1 ms Unit

dBV



Date: 5.NOV.2020 08:56:33

Time of Small Pulse = 140.280561 us

Brea Division
 114 Olinda Drive
 Brea, CA 92823
 (714) 579-0500

Newbury Park Division
 1050 Lawrence Drive
 Newbury Park, CA 91320
 (805) 480-4044

Lake Forest Division
 20621 Pascal Way
 Lake Forest, CA 92630
 (949) 587-0400



Delta 1 [T2]

RBW 1 MHz RF Att 10 dB


Ref Lvl 3.13 dB

VBW 3 MHz

107.7 dBV 270.541082 us

SWT 1 ms

Unit dBV



Date: 5.NOV.2020 08:56:04

Time of Large Pulse = 270.541082 us

Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Newbury Park Division
1050 Lawrence Drive
Newbury Park, CA 91320
(805) 480-4044

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400



Delta 1 [T2]

RBW 1 MHz RF Att 10 dB


Ref Lvl 0.00 dB

VBW 3 MHz

128.4 dBV 0.000000 s

SWT 25 ms

Unit dBV



Date: 5.NOV.2020 08:05:01

Number of Small Pulses = 48 = (48*140.280561 us) = 6733.466928 us

Number of Large Pulses = 16 = (16*270.541082 us) = 4328.657312 us

Total On Time = 11062.12424 us = 11.06212424 ms

Duty Cycle = 11.06212424 ms / 100 ms = 11.06212424%

The peak to average ratio is -19.12 dB

Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Newbury Park Division
1050 Lawrence Drive
Newbury Park, CA 91320
(805) 480-4044

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400