

**FCC PART 15, SUBPART B and C
TEST REPORT***for***SINGLE DECORA LIGHT SWITCH****Model: SDLS2-ZWAVE5**

Prepared for

ECOLINK INTELLIGENT TECHNOLOGY, INC.
2055 CORTE DEL NOGAL
CARLSBAD, CALIFORNIA 92011Prepared by: 

EDGAR VALENCIA

Approved by: 

KYLE FUJIMOTO

COMPATIBLE ELECTRONICS INC.
114 OLINDA DRIVE
BREA, CALIFORNIA 92823
(714) 579-0500

DATE: NOVEMBER 30, 2017

	REPORT BODY	APPENDICES					TOTAL
		A	B	C	D	E	
PAGES	17	2	2	2	11	35	69

This report shall not be reproduced except in full, without the written approval of Compatible Electronics.



TABLE OF CONTENTS

Section / Title	PAGE
GENERAL REPORT SUMMARY	4
SUMMARY OF TEST RESULTS	5
1. PURPOSE	6
2. ADMINISTRATIVE DATA	7
2.1 Location of Testing	7
2.2 Traceability Statement	7
2.3 Cognizant Personnel	7
2.4 Date Test Sample was Received	7
2.5 Disposition of the Test Sample	7
2.6 Abbreviations and Acronyms	7
3. APPLICABLE DOCUMENTS	8
4. DESCRIPTION OF TEST CONFIGURATION	9
4.1 Description of Test Configuration – Emissions	9
4.1.1 Cable Construction and Termination	9
5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT	10
5.1 EUT and Accessory List	10
6. TEST SITE DESCRIPTION	12
6.1 Test Facility Description	12
6.2 EUT Mounting, Bonding and Grounding	12
6.3 Measurement Uncertainty	12
7. TEST PROCEDURES	13
7.1 RF Emissions	13
7.1.1 Conducted Emissions Test	13
7.1.2 Radiated Emissions Test	14
7.1.3 RF Emissions Test Results	15
7.1.4 Duty Cycle Calculation	16
8. CONCLUSIONS	17

LIST OF APPENDICES

APPENDIX	TITLE
A	Laboratory Accreditations and Recognitions
B	Modifications to the EUT
C	Additional Model Covered Under This Report
D	Diagrams and Charts <ul style="list-style-type: none">• Test Setup Diagrams• Antenna and Effective Gain Factors
E	Data Sheets

LIST OF FIGURES

FIGURE	TITLE
1	Conducted Emissions Test Setup
2	Layout of the Semi-Anechoic Test Chamber

LIST OF TABLES

TABLE	TITLE
1.0	Radiated Emission Results

GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Compatible Electronics Inc., which is an independent testing and consulting firm. The test report is based on testing performed by Compatible Electronics personnel according to the measurement procedures described in the test specifications given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced without the written permission of Compatible Electronics, unless done so in full.

This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the federal government.

Device Tested: Single Decora Light Switch
Model: SDLS2-ZWAVE5
S/N: N/A

Product Description: The EUT is a battery-powered device for home automation applications.

Modifications: The EUT was not modified in order to meet the specifications.

Customer: Ecolink Intelligent Technology, Inc.
2055 Corte Del Nogal
Carlsbad, California 92011

Test Dates: November 20, 21, 27, and 28, 2017; and December 12, 2017

Test Specifications covered by accreditation:

CFR Title 47, Part 15, Subpart B; and Subpart C sections 15.205, 15.209, and 15.249



Test Procedures: ANSI C63.4: 2014 and ANSI C63.10: 2013

SUMMARY OF TEST RESULTS

<i>TEST</i>	DESCRIPTION	RESULTS
1	Spurious Radiated RF Emissions, 9 kHz – 9300 MHz (Transmitter and Digital portion)	Complies with the Class B limits of CFR Title 47, Part 15 Subpart B; and the limits of CFR Title 47, Part 15 Subpart C, section 15.205, 15.209 and 15.249 <small>Highest reading in relation to spec limit 93.32 dBuV/m @ 908.42 MHz (*U = 4.54 dB)</small>
2	Conducted RF Emissions, 150 kHz to 30 MHz	This test was not performed because the EUT does not connect to the AC mains

1. PURPOSE

This document is a qualification test report based on the emissions tests performed on the Single Decora Light Switch, Model: SDLS2-ZWAVE5. The emissions measurements were performed according to the measurement procedure described in ANSI C63.4 and ANSI C63.10. The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT hereafter, are within the Class B specification limits defined by CFR Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.209, and 15.249.



2. ADMINISTRATIVE DATA

2.1 Location of Testing

The emissions tests described herein were performed at the test facility of Compatible Electronics, 114 Olinda Drive, Brea, California 92823.

2.2 Traceability Statement

The calibration certificates of all test equipment used during the test are on file at the location of the test. The calibration is traceable to the National Institute of Standards and Technology (NIST).

2.3 Cognizant Personnel

Ecolink Intelligent Technology, Inc.

Keyoor Gosalia Principal RF Engineer

Compatible Electronics Inc.

Kyle Haag Test Technician
Edgar Valencia Test Technician
Kyle Fujimoto Test Engineer

2.4 Date Test Sample was Received

The test sample was received on prior to the initial date of testing.

2.5 Disposition of the Test Sample

The test sample has not been returned to Ecolink Intelligent Technology, Inc. as of the date of this test report.

2.6 Abbreviations and Acronyms

The following abbreviations and acronyms may be used in this document.

RF	Radio Frequency
EMI	Electromagnetic Interference
EUT	Equipment Under Test
P/N	Part Number
S/N	Serial Number
ASK	Amplitude Shift Key
ITE	Information Technology Equipment
LISN	Line Impedance Stabilization Network
N/A	Not Applicable
Tx	Transmit
Rx	Receive
PIR	Pyroelectric ("Passive") Infrared
Inc.	Incorporated

3. APPLICABLE DOCUMENTS

The following documents are referenced or used in the preparation of this emissions Test Report.

SPEC	TITLE
FCC Title 47, Part 15 Subpart C	FCC Rules – Radio frequency devices (including digital devices) – Intentional Radiators
FCC Title 47, Part 15 Subpart B	FCC Rules – Radio frequency devices (including digital devices) – Unintentional Radiators
ANSI C63.4 2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
ANSI C63.10 2013	American National Standard of procedure for compliance testing of unlicensed wireless devices

4. DESCRIPTION OF TEST CONFIGURATION

4.1 Description of Test Configuration – Emissions

The Single Decora Light Switch, Model: SDLS2-ZWAVE5 (EUT) was setup in a stand-alone configuration. The EUT was investigated in all three orthogonal axis. During the testing, the EUT was continuously transmitting or receiving at the low channel of 908.42 MHz and high channel of 916 MHz.

The X orientation is when the EUT is parallel to the ground. The Y orientation is when the EUT is perpendicular to the ground mounted vertically. The Z orientation is when the EUT is perpendicular to the ground mounted horizontally.

The EUT was programmed to be able to continuously transmit or receive at the low and high channels. Fresh batteries were installed inside the EUT prior to the testing. The EUT was preset via internal firmware to continuously transmit or receive at the low or high, respectively.

The firmware is stored in one of the network drives in the company's server.

The final radiated data for the EUT was taken in the mode described above. Please see Appendix E for the data sheets.

4.1.1 Cable Construction and Termination

The EUT had no external cables.

5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT**5.1 EUT and Accessory List**

EQUIPMENT	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	FCC ID
SINGLE DECORA LIGHT SWITCH (EUT)	ECOLINK INTELLIGENT TECHNOLOGY, INC.	SDLS2-ZWAVE5	N/A	XQC-SDLS2ZWAVE5
FIRMWARE FOR EUT*	ECOLINK INTELLIGENT TECHNOLOGY, INC.	1.0	N/A	N/A

*Located inside the EUT to allow the EUT to transmit on a continuous basis.

5.2 Emissions Test Equipment

EQUIPMENT TYPE	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	CALIBRATION DATE	CAL. CYCLE
GENERAL TEST EQUIPMENT USED IN LAB D					
TDK TestLab	TDK RF Solutions, Inc.	9.22	700145	N/A	N/A
Computer	Hewlett Packard	p6716f	MXX1030PX0	N/A	N/A
LCD Monitor	Hewlett Packard	52031a	3CQ046N3MG	N/A	N/A
EMI Receiver, 20 Hz – 26.5 GHz	Keysight	N9038A	MY5120150	December 6, 2017	1 Year
EMI Receiver, 20 Hz – 40 GHz	Rohde & Schwarz	ESIB40	100194	September 26, 2017	1 Year
RF RADIATED EMISSIONS TEST EQUIPMENT					
CombiLog Antenna	Com-Power	AC-220	61060	July 27, 2017	1 Year
Preamplifier	Com-Power	PAM-118A	551024	May 12, 2016	2 Year
Loop Antenna	Com-Power	AL-130R	121090	February 9, 2017	2 Year
Horn Antenna	Com-Power	AH-118	071175	February 26, 2016	2 Year
Antenna Mast	Com Power	AM-100	N/A	N/A	N/A
System Controller	Sunol Sciences Corporation	SC110V	112213-1	N/A	N/A
Turntable	Sunol Sciences Corporation	2011VS	N/A	N/A	N/A
Antenna-Mast	Sunol Sciences Corporation	TWR95-4	112213-3	N/A	N/A

6. TEST SITE DESCRIPTION

6.1 Test Facility Description

Please refer to section 2.1 and 7.1 of this report for emissions test location.

6.2 EUT Mounting, Bonding and Grounding

For frequencies 1 GHz and below: The EUT was mounted on a 1.0 by 1.5 meter non-conductive table 0.8 meters above the ground plane.

For frequencies above 1 GHz: The EUT was mounted on a 1.0 by 1.5 meter non-conductive table 1.5 meters above the ground plane.

The EUT was not grounded.

6.3 Measurement Uncertainty

The uncertainty values are in the table below.

The uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level, using a coverage factor of $k=2$

MEASUREMENT TYPE	PARTICULAR CONFIGURATION	UNCERTAINTY VALUES
RADIATED EMISSIONS	3-METER CHAMBER, COMBILOG ANTENNA	4.54 dB
RADIATED EMISSIONS	3-METER CHAMBER, HORN ANTENNA	3.70 dB
AC LINE CONDUCTED EMISSIONS	3-METER CHAMBER, COM-POWER LISN	2.88 dB

7. TEST PROCEDURES

The following sections describe the test methods and the specifications for the tests. Test results are also included in this section.

7.1 RF Emissions

7.1.1 Conducted Emissions Test

The EMI Receiver was used as a measuring meter. A quasi-peak and/or average reading was taken only where indicated in the data sheets. A transient limiter was used for the protection of the EMI Receiver input stage, and the offset was adjusted accordingly to read the actual data measured. The LISN output was measured using the EMI Receiver. The output of the second LISN was terminated by a 50-ohm termination. The effective measurement bandwidth used for this test was 9 kHz.

Please see section 6.2 of this report for mounting, bonding, and grounding of the EUT. The EUT was powered through the LISN, which was bonded to the ground plane. The LISN power was filtered and the filter was bonded to the ground plane. The EUT was set up with the minimum distances from any conductive surfaces as specified in ANSI 63:4. The excess power cord was wrapped in a figure eight pattern to form a bundle not exceeding 0.4 meters in length.

The conducted emissions from the EUT were maximized for operating mode as well as cable placement. The final data was collected under program control by computer software. The final qualification data is located in Appendix E.

Test Results:

This device is battery powered and does not connect to the AC public mains, thus this test was not performed.

7.1.2 Radiated Emissions Test

The EMI Receiver was used as the measuring meter. A built-in, internal preamplifier was used to increase the sensitivity of the instrument. The EMI Receiver was initially used with the Analyzer mode feature activated. In this mode, the EMI receiver can then record the actual frequency to be measured. This final reading is then taken accurately in the EMI Receiver mode, which takes into account the cable loss, amplifier gain and antenna factors, so that a true reading is compared to the true limit. The effective measurement bandwidth used for the radiated emissions test was according to the frequency measured (200 Hz for 9 kHz to 150 kHz, 9 kHz for 150 kHz to 30 MHz, 120 kHz for 30 MHz to 1 GHz and 1 MHz for 1 GHz to 9.3 GHz).

The frequencies above 1 GHz were averaged using a duty cycle correction factor as explained in section 7.1.4 of this test report.

The EMI test chamber of Compatible Electronics, Inc. was used for radiated emissions testing. This test site is in full compliance with ANSI C63.4. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees in order to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. At each reading, the EUT was rotated 360 degrees and the antenna height was varied from 1 to 4 meters (for E field radiated field strength). The gunsight method was used when measuring with the horn antenna in order to ensure accurate results.

The EUT was tested at a 3-meter test distance. The six highest emissions are listed in Table 1.0.

The measurement bandwidths and transducers used for the radiated emissions test were:

FREQUENCY RANGE	EFFECTIVE MEASUREMENT BANDWIDTH	TRANSDUCER
9 kHz to 150 kHz	200 Hz	Loop Antenna
150 kHz to 30 MHz	9 kHz	Loop Antenna
30 MHz to 1 GHz	120 kHz	CombiLog Antenna
1 GHz to 9.3 GHz	1 MHz	Horn Antenna

Test Results:

The EUT complies with the **Class B** limits of **CFR** Title 47, Part 15, Subpart B; and Subpart C sections 15.205, 15.209 and 15.249 for radiated emissions.

7.1.3 RF Emissions Test Results

Table 1.0 RADIATED EMISSION RESULTS
Single Decora Light Switch
Model: SDLS2-ZWAVE5

Frequency MHz	Quasi-Peak EMI Reading (dBuV/m)	Quasi-Peak Specification Limit (dBuV/m)	Delta (Cor. Reading – Spec. Limit) dB
908.42 (H) (X-Axis)	93.32	93.97	-0.65
916.00 (H) (X-Axis)	92.41	93.97	-1.56
908.42 (V) (Y-Axis)	90.47	93.97	-3.50
928.00 (H) (X-Axis)	42.16	46.00	-3.84
916.00 (V) (Z-Axis)	89.91	93.97	-4.06
902.00 (H) (X-Axis)	41.57	46.00	-4.43

Notes:

- * The complete emissions data is given in Appendix E of this report.
- (V) Vertical
- (H) Horizontal

7.1.4 Duty Cycle Calculation

The fundamental and harmonics were measured at a 3-meter test distance. The EMI Receiver was used to obtain the final test data. The final qualification data sheets are located in Appendix E.

Where

$$\delta(\text{dB}) = 20 \log \left[\sum (nt_1 + mt_2 + \dots + \xi t_x) / T \right]$$

n is the number of pulses of duration t_1

m is the number of pulses of duration t_2

ξ is the number of pulses of duration t_x

T is the period of the pulse train or 100 ms if the pulse train length is greater than 100 ms

The worst case was when the EUT was attempting to communicate just after inserting the battery:

Duty Cycle Correction Factor = -16.23 dB

Pulse = 5.8 ms

Worst Case Between Pulses = 37.6 ms

5.8 ms / 37.6 ms = 0.1543

20 log (0.1543) = -10.88 dB correction factor

8. CONCLUSIONS

The Single Decora Light Switch, Model: SDLS2-ZWAVE5, as tested, meets all of the **Class B** specification limits defined in FCC Title 47, Part 15, Subpart B; and Subpart C, sections 15.205, 15.209 and 15.249.



APPENDIX A

LABORATORY ACCREDITATIONS AND RECOGNITIONS

Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Newbury Park Division
1050 Lawrence Drive
Newbury Park, CA 91320
(805) 480-4044

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

LABORATORY ACCREDITATIONS AND RECOGNITIONS




NVLAP LAB CODE 200528-0

Quote from ISO-ILAC-IAF Communiqué on 17025:

"A laboratory's fulfilment of the requirements of ISO/IEC 17025:2005 means the laboratory meets both the technical competence requirements and management system requirements that are necessary for it to consistently deliver technically valid test results and calibrations. The management system requirements in ISO/IEC 17025:2005 (Section 4) are written in language relevant to laboratory operations and meet the principles of ISO 9001:2008 Quality Management Systems — Requirements."

Test Site Number for Innovation, Science and Economic Development Canada: 2154A-3



APPENDIX B

MODIFICATIONS TO THE EUT

MODIFICATIONS TO THE EUT

The modifications listed below were made to the EUT to pass FCC Subpart B and FCC 15.249 specifications.

All the rework described below was implemented during the test in a method that could be reproduced in all the units by the manufacturer.

No modifications were made to the EUT during the testing.



APPENDIX C

***ADDITIONAL MODEL COVERED
UNDER THIS REPORT***

ADDITIONAL MODEL COVERED UNDER THIS REPORT

USED FOR THE PRIMARY TEST

Single Decora Light Switch
Model: SDLS2-ZWAVE5
S/N: N/A

There are no additional Models covered under this report.





APPENDIX D

DIAGRAMS AND CHARTS

FIGURE 1: CONDUCTED EMISSIONS TEST SETUP





FIGURE 2: LAYOUT OF THE SEMI -ANECHOIC TEST CHAMBER



COM-POWER AL-130**LOOP ANTENNA**

S/N: 121090

CALIBRATION DATE: FEBRUARY 9, 2017

FREQUENCY (MHz)	MAGNETIC (dB/m)	ELECTRIC (dB/m)
0.009	-36.17	15.33
0.01	-35.86	15.64
0.02	-37.30	14.20
0.03	-36.58	14.92
0.04	-36.99	14.51
0.05	-37.66	13.84
0.06	-37.53	13.97
0.07	-37.64	13.86
0.08	-37.52	13.98
0.09	-37.62	13.88
0.1	-37.59	13.91
0.2	-37.79	13.71
0.3	-37.80	13.70
0.4	-37.70	13.80
0.5	-37.79	13.71
0.6	-37.79	13.71
0.7	-37.69	13.81
0.8	-37.49	14.01
0.9	-37.39	14.11
1	-37.39	14.11
2	-37.09	14.41
3	-37.09	14.41
4	-37.19	14.31
5	-36.98	14.52
6	-37.17	14.33
7	-37.05	14.45
8	-36.85	14.65
9	-36.84	14.66
10	-36.75	14.75
15	-37.16	14.34
20	-36.44	15.06
25	-37.88	13.62
30	-39.14	12.36

COM-POWER AC-220**COMBILOG ANTENNA****S/N: 61060****CALIBRATION DATE: JULY 27, 2017**

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
30	23.80	200	14.10
35	24.00	250	15.30
40	24.70	300	17.70
45	22.90	350	17.70
50	22.10	400	19.00
60	17.60	450	21.30
70	12.70	500	21.00
80	11.20	550	22.30
90	13.10	600	23.40
100	14.40	650	22.90
120	15.30	700	24.60
125	15.00	750	24.50
140	12.80	800	25.40
150	16.50	850	26.40
160	12.90	900	27.20
175	14.30	950	27.80
180	14.50	1000	26.80

COM POWER AH-118**HORN ANTENNA**

S/N: 071175

CALIBRATION DATE: FEBRUARY 26, 2016


FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
1.0	23.93	10.0	39.33
1.5	25.54	10.5	39.64
2.0	28.09	11.0	41.04
2.5	30.21	11.5	44.29
3.0	30.15	12.0	41.22
3.5	30.17	12.5	41.50
4.0	31.90	13.0	41.62
4.5	33.51	13.5	40.63
5.0	33.87	14.0	39.94
5.5	35.08	14.5	41.84
6.0	34.81	15.0	42.69
6.5	34.26	15.5	39.03
7.0	36.33	16.0	39.07
7.5	37.03	16.5	41.40
8.0	37.56	17.0	43.18
8.5	40.07	17.5	47.01
9.0	38.92	18.0	46.48
9.5	38.21		

COM-POWER PAM-118A**PREAMPLIFIER**

S/N: 551024

CALIBRATION DATE: MAY 12, 2016


FREQUENCY (GHz)	FACTOR (dB)	FREQUENCY (GHz)	FACTOR (dB)
1.0	39.84	6.0	39.05
1.1	39.40	6.5	38.94
1.2	39.58	7.0	39.25
1.3	39.68	7.5	39.09
1.4	39.91	8.0	39.01
1.5	39.78	8.5	38.60
1.6	39.50	9.0	38.64
1.7	39.81	9.5	39.67
1.8	39.89	10.0	39.30
1.9	39.94	11.0	39.15
2.0	39.57	12.0	39.24
2.5	40.39	13.0	39.49
3.0	40.63	14.0	39.44
3.5	40.80	15.0	39.94
4.0	40.86	16.0	40.09
4.5	39.94	17.0	40.06
5.0	34.47	18.0	39.76
5.5	39.32		



FRONT VIEW

ECOLINK INTELLIGENT TECHNOLOGY, INC.
SINGLE DECORA LIGHT SWITCH
MODEL: SDLS2-ZWAVE5
FCC SUBPART B AND C – RADIATED EMISSIONS – BELOW 1 GHz


**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



REAR VIEW

ECOLINK INTELLIGENT TECHNOLOGY, INC.
SINGLE DECORA LIGHT SWITCH
MODEL: SDLS2-ZWAVE5
FCC SUBPART B AND C – RADIATED EMISSIONS – BELOW 1 GHz


**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



FRONT VIEW

ECOLINK INTELLIGENT TECHNOLOGY, INC.
SINGLE DECORA LIGHT SWITCH
MODEL: SDLS2-ZWAVE5
FCC SUBPART B AND C – RADIATED EMISSIONS – ABOVE 1 GHz


**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



REAR VIEW

ECOLINK INTELLIGENT TECHNOLOGY, INC.
SINGLE DECORA LIGHT SWITCH
MODEL: SDLS2-ZWAVE5
FCC SUBPART B AND C – RADIATED EMISSIONS – ABOVE 1 GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**






***RADIATED EMISSIONS
DATA SHEETS***

Title: Pre-Scan - FCC Class B
File: Rohde & Schwarz - Pre-Scan - FCC Class B - 30 MHz to 1000 MHz SR4_SRS Y-Axis.set
Operator: Kyle Haag
EUT Type: Single Decora Light Switch
EUT Condition: The EUT was receiving at 908.42 MHz - Y-Axis Worst Case
Company: Ecolink Intelligent Technology, Inc
Model: SDLS2-ZWAVES
S/N: N/A
Note: The frequency at 908.42 MHz is from an accessory unit (and not the EUT) that was transmitting at 908.42 MHz inside the chamber so that the EUT could receive at 908.42 MHz.

11/27/2017 4:38:31 PM
Sequence: Preliminary Scan



Note: A manual scan was taken from 1 GHz to 5 GHz. No emissions were detected.

Title: Radiated Final - FCC Class B
 File: Rohde & Schwarz - Final Scan - FCC Class B - 30 MHz to 1000 MHz SR4_SRS Y-Axis.set
 Operator: Kyle Haag
 EUT Type: Single Decora Light Switch
 EUT Condition: The EUT was receiving at 908.42 MHz - Y-Axis Worst Case
 Company: Ecolink Intelligent Technology, Inc
 Model: SDLS2-ZWAVES
 S/N: N/A

11/28/2017 8:06:41 AM
 Sequence: Final Measurements


FCC Class B										
Freq (MHz)	Pol	(PEAK) EMI (dBuV/m)	(QP) EMI (dBuV/m)	(PEAK) Margin (dB)	(QP) Margin (dB)	Limit (dBuV/m)	Transducer (dB)	Cable (dB)	Ttbl Aql (deg)	Twr Ht (cm)
37.30	H	28.45	23.16	-11.55	-16.84	40.00	24.33	0.48	45.25	111.34
38.00	H	28.64	23.23	-11.36	-16.77	40.00	24.45	0.48	47.00	357.19
38.50	H	28.25	23.25	-11.75	-16.75	40.00	24.53	0.48	62.00	390.26
38.80	H	27.81	23.21	-12.19	-16.79	40.00	24.54	0.48	95.25	226.26
39.60	V	27.64	23.21	-12.36	-16.79	40.00	24.65	0.49	47.25	390.26
40.40	H	28.51	23.25	-11.49	-16.75	40.00	24.63	0.49	47.00	176.71

Note: A manual scan was taken from 1 GHz to 5 GHz. No emissions were detected.



Title: Pre-Scan - FCC Class B
File: Rohde & Schwarz - Pre-Scan - FCC Class B - 30 MHz to 1000 MHz SR4_SR6 Y-Axis_1.set Operator: Kyle Haag
EUT Type: Single Decora Light Switch
EUT Condition: The EUT was receiving at 916 MHz - Y-Axis Worst Case
Company: Ecolink Intelligent Technology, Inc
Model: SDLS2-ZWAVE5
S/N: N/A
Note: The frequency at 916 MHz is from an accessory unit (and not the EUT) that was transmitting at 916 MHz inside the chamber so that the EUT could receive at 916 MHz.

11/27/2017 3:53:35 PM
Sequence: Preliminary Scan



Note: A manual scan was taken from 1 GHz to 5 GHz. No emissions were detected.

Title: Radiated Final - FCC Class B
 File: Rohde & Schwarz - Final Scan - FCC Class B - 30 MHz to 1000 MHz SR\$_SR6 Y-Axis.set
 Operator: Kyle Haag
 EUT Type: Single Decora Light Switch
 EUT Condition: The EUT was receiving at 916 MHz - Y-Axis Worst Case
 Company: Ecolink Intelligent Technology, Inc
 Model: SDLS2-ZWAVE5
 S/N: N/A

11/27/2017 4:18:50 PM
 Sequence: Final Measurements


FCC Class B										
Freq (MHz)	Pol	(PEAK) EMI (dBµV/m)	(QP) EMI (dBµV/m)	(PEAK) Margin (dB)	(QP) Margin (dB)	Limit (dBµV/m)	Transducer (dB)	Cable (dB)	Ttbl Aql (dec)	Twr Ht (cm)
33.10	H	27.16	21.85	-12.84	-18.15	40.00	23.92	0.45	271.75	176.89
36.20	V	27.17	22.34	-12.83	-17.66	40.00	24.21	0.47	21.50	176.95
37.50	H	27.92	22.48	-12.08	-17.52	40.00	24.34	0.48	153.75	209.85
39.40	V	27.88	22.88	-12.12	-17.12	40.00	24.61	0.49	72.00	209.79
40.30	V	27.28	22.80	-12.72	-17.20	40.00	24.59	0.49	162.00	176.95
40.80	H	28.17	22.61	-11.83	-17.39	40.00	24.39	0.50	199.50	144.11

Note: A manual scan was taken from 1 GHz to 5 GHz. No emissions were detected.



Title: Pre-Scan - FCC Class B
File: Rohde & Schwarz - Pre-Scan - FCC Class B - 30 MHz to 1000 MHz SR5 Y-Axis.set
Operator: Kyle Haag
EUT Type: Single Decora Light Switch
EUT Condition: The SR5 was transmitting at 908.42 MHz - Y-Axis Worst Case
Company: Ecolink Intelligent Technology, Inc
Model: SDLS2-ZWAVE5
S/N: N/A

11/27/2017 1:54:09 PM
Sequence: Preliminary Scar



Note: The frequency at 908.42 MHz is from the intentional radiator of the EUT and is subject to the limits of FCC 15.249 instead.

Title: Radiated Final - FCC Class B
 File: Rohde & Schwarz - Final Scan - FCC Class B - 30 MHz to 1000 MHz SRS Y-Axis.set
 Operator: Kyle Haag
 EUT Type: Single Decora Light Switch
 EUT Condition: The SRS was Transmitting at 908.42 MHz Y-Axis Worst Case
 Comments: Company: Ecolink Intelligent Technology, Inc
 Model: SDLS2-ZWAVE5
 S/N: N/A


11/27/2017 2:19:15 PM
 Sequence: Final Measurements

FCC Class B										
Freq (MHz)	Pol	(PEAK) EMI (dBµV/m)	(QP) EMI (dBµV/m)	(PEAK) Margin (dB)	(QP) Margin (dB)	Limit (dBµV/m)	Transducer (dB)	Cable (dB)	Ttbi Aql (deca)	Twr Ht (cm)
37.10	H	28.03	22.41	-11.97	-17.59	40.00	24.34	0.48	183.25	292.00
38.20	H	27.68	22.62	-12.32	-17.38	40.00	24.48	0.48	6.50	308.05
38.90	V	27.68	22.68	-12.32	-17.32	40.00	24.53	0.48	266.00	144.17
39.20	H	28.04	22.75	-11.96	-17.25	40.00	24.61	0.49	249.75	127.82
39.50	H	28.60	22.82	-11.40	-17.18	40.00	24.66	0.49	311.25	275.46
39.70	V	28.23	22.88	-11.77	-17.12	40.00	24.67	0.49	31.25	341.19



Title: Pre-Scan - FCC Class B
File: Rohde & Schwarz - Pre-Scan - FCC Class B - 30 MHz to 1000 MHz SR6 Y-Axis.set
Operator: Kyle Haag
EUT Type: Single Decora Light Switch
EUT Condition: The SR6 was transmitting at 916 MHz Y-Axis Worst Case
Comments: Company: Ecolink Intelligent Technology, Inc
Model: SDLS2-ZWAVE5
S/N: N/A

11/27/2017 2:41:01 PM
Sequence: Preliminary Scan



Note: The frequency at 916 MHz is from the intentional radiator of the EUT and is subject to the limits of FCC 15.249 instead.

Title: Radiated Final - FCC Class B
 File: Rohde & Schwarz - Final Scan - FCC Class B - 30 MHz to 1000 MHz SR6 Y-Axis.set
 Operator: Kyle Haaq
 EUT Type: Single Decora Light Switch
 EUT Condition: The SR6 was transmitting at 916 MHz Y-Axis Worst Case
 Comments: Company: Ecolink Intelligent Technology, Inc
 Model: SDLS2-ZWAVE5
 S/N: N/A

11/27/2017 3:04:56 PM
 Sequence: Final Measurements

FCC Class B										
Freq (MHz)	Pol	(PEAK) EMI (dB μ V/m)	(QP) EMI (dB μ V/m)	(PEAK) Margin (dB)	(QP) Margin (dB)	Limit (dB μ V/m)	Transducer (dB)	Cable (dB)	Ttbl Aql (dea)	Twr Ht (cm)
896.10	V	42.31	39.72	-3.69	-6.28	46.00	27.14	2.64	288.00	176.65
904.00	V	40.26	35.79	-5.74	-10.21	46.00	27.25	2.65	253.50	111.52
904.10	V	37.16	31.94	-8.84	-14.06	46.00	27.25	2.65	282.25	160.47
908.00	V	38.07	34.41	-7.93	-11.59	46.00	27.30	2.65	311.00	111.34
928.00	V	35.87	29.80	-10.13	-16.20	46.00	27.54	2.67	255.75	144.05
928.10	V	36.79	31.49	-9.21	-14.51	46.00	27.54	2.67	288.25	160.35



FCC 15.249

Ecolink Intelligent Technology, Inc.
 Single Decora Light Switch
 Model: SDLS2-ZWAVE5

Date: 11/20/2017
 Lab: D
 Tested By: Kyle Haag

**Harmonics - Low Channel
 Transmit Mode - X-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
1816.84	34.53	V	73.97	-39.44	Peak	94.50	101.21	
1816.84	18.30	V	53.97	-35.67	Avg	94.50	101.21	
2725.26	46.95	V	73.97	-27.02	Peak	346.50	161.85	
2725.26	30.72	V	53.97	-23.25	Avg	346.50	161.85	
3633.68	47.83	V	73.97	-26.14	Peak	114.25	224.89	
3633.68	31.60	V	53.97	-22.37	Avg	114.25	224.89	
4542.10	46.60	V	73.97	-27.37	Peak	137.25	178.86	
4542.10	30.37	V	53.97	-23.60	Avg	137.25	178.86	
5450.52	43.64	V	73.97	-30.33	Peak	35.00	185.58	
5450.52	27.41	V	53.97	-26.56	Avg	35.00	185.58	
6358.94	45.52	V	73.97	-28.45	Peak	184.50	137.07	
6358.94	29.29	V	53.97	-24.68	Avg	184.50	137.07	
7267.36	45.18	V	73.97	-28.79	Peak	355.55	158.58	
7267.36	28.95	V	53.97	-25.02	Avg	355.55	158.58	
8175.78	49.47	V	73.97	-24.50	Peak	271.50	122.02	
8175.78	33.24	V	53.97	-20.73	Avg	271.50	122.02	
9084.20	49.42	V	73.97	-24.55	Peak	119.50	125.58	
9084.20	33.19	V	53.97	-20.78	Avg	199.50	125.58	

FCC 15.249

Ecolink Intelligent Technology, Inc.
 Single Decora Light Switch
 Model: SDLS2-ZWAVE5

Date: 11/20/2017
 Lab: D
 Tested By: Kyle Haag

**Harmonics - Low Channel
 Transmit Mode - Y-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
1816.84	36.47	V	73.97	-37.50	Peak	10.25	202.34	
1816.84	20.24	V	53.97	-33.73	Avg	10.25	202.34	
2725.26	51.08	V	73.97	-22.89	Peak	359.50	199.34	
2725.26	34.85	V	53.97	-19.12	Avg	359.50	199.34	
3633.68	51.71	V	73.97	-22.26	Peak	12.00	202.98	
3633.68	35.48	V	53.97	-18.49	Avg	12.00	202.98	
4542.10	47.42	V	73.97	-26.55	Peak	18.00	157.31	
4542.10	31.19	V	53.97	-22.78	Avg	18.00	157.31	
5450.52	44.18	V	73.97	-29.79	Peak	262.00	158.58	
5450.52	27.95	V	53.97	-26.02	Avg	262.00	158.58	
6358.94	47.57	V	73.97	-26.40	Peak	52.50	130.56	
6358.94	31.34	V	53.97	-22.63	Avg	52.50	130.56	
7267.36	47.60	V	73.97	-26.37	Peak	330.25	129.85	
7267.36	31.37	V	53.97	-22.60	Avg	330.25	129.85	
8175.78	50.85	V	73.97	-23.12	Peak	350.00	151.82	
8175.78	34.62	V	53.97	-19.35	Avg	350.00	151.82	
9084.20	49.97	V	73.97	-24.00	Peak	217.25	125.31	
9084.20	33.74	V	53.97	-20.23	Avg	217.25	125.31	

FCC 15.249

Ecolink Intelligent Technology, Inc.
 Single Decora Light Switch
 Model: SDLS2-ZWAVE5

Date: 11/20/2017
 Lab: D
 Tested By: Kyle Haag

**Harmonics - Low Channel
 Transmit Mode - Z-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
1816.84	38.26	V	73.97	-35.71	Peak	347.75	202.25	
1816.84	22.03	V	53.97	-31.94	Avg	347.75	202.25	
2725.26	41.26	V	73.97	-32.71	Peak	44.75	218.44	
2725.26	25.03	V	53.97	-28.94	Avg	44.75	218.44	
3633.68	45.29	V	73.97	-28.68	Peak	10.00	221.55	
3633.68	29.06	V	53.97	-24.91	Avg	10.00	221.55	
4542.10	44.06	V	73.97	-29.91	Peak	277.75	249.25	
4542.10	27.83	V	53.97	-26.14	Avg	277.75	249.25	
5450.52	45.28	V	73.97	-28.69	Peak	87.75	210.25	
5450.52	29.05	V	53.97	-24.92	Avg	87.75	210.25	
6358.94	46.24	V	73.97	-27.73	Peak	156.75	249.36	
6358.94	30.01	V	53.97	-23.96	Avg	156.75	249.36	
7267.36	46.29	V	73.97	-27.68	Peak	86.50	241.25	
7267.36	30.06	V	53.97	-23.91	Avg	86.50	241.25	
8175.78	48.25	V	73.97	-25.72	Peak	266.50	145.26	
8175.78	32.02	V	53.97	-21.95	Avg	266.50	145.26	
9084.20	48.25	V	73.97	-25.72	Peak	350.00	245.25	
9084.20	32.02	V	53.97	-21.95	Avg	350.00	245.25	

FCC 15.249

Ecolink Intelligent Technology, Inc.
 Single Decora Light Switch
 Model: SDLS2-ZWAVE5

Date: 11/20/2017
 Lab: D
 Tested By: Kyle Haag

**Harmonics - Low Channel
 Transmit Mode - X-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
1816.84	33.67	H	73.97	-40.30	Peak	113.50	122.02	
1816.84	17.44	H	53.97	-36.53	Avg	113.50	122.02	
2725.26	47.72	H	73.97	-26.25	Peak	215.75	138.32	
2725.26	31.49	H	53.97	-22.48	Avg	215.75	138.32	
3633.68	43.32	H	73.97	-30.65	Peak	10.25	158.58	
3633.68	27.09	H	53.97	-26.88	Avg	10.25	158.58	
4542.10	46.66	H	73.97	-27.31	Peak	211.25	135.25	
4542.10	30.43	H	53.97	-23.54	Avg	211.25	135.25	
5450.52	43.68	H	73.97	-30.29	Peak	81.75	138.38	
5450.52	27.45	H	53.97	-26.52	Avg	81.75	138.38	
6358.94	46.74	H	73.97	-27.23	Peak	116.25	140.25	
6358.94	30.51	H	53.97	-23.46	Avg	116.25	140.25	
7267.36	45.45	H	73.97	-28.52	Peak	150.00	129.01	
7267.36	29.22	H	53.97	-24.75	Avg	150.00	129.01	
8175.78	51.05	H	73.97	-22.92	Peak	250.25	135.25	
8175.78	34.82	H	53.97	-19.15	Avg	250.25	135.25	
9084.20	47.83	H	73.97	-26.14	Peak	222.50	120.11	
9084.20	31.60	H	53.97	-22.37	Avg	222.50	120.11	

FCC 15.249

Ecolink Intelligent Technology, Inc.
 Single Decora Light Switch
 Model: SDLS2-ZWAVE5

Date: 11/20/2017
 Lab: D
 Tested By: Kyle Haag

**Harmonics - Low Channel
 Transmit Mode - Y-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
1816.84	36.97	H	73.97	-37.00	Peak	356.00	130.98	
1816.84	20.74	H	53.97	-33.23	Avg	356.00	130.98	
2725.26	43.50	H	73.97	-30.47	Peak	75.25	155.55	
2725.26	27.27	H	53.97	-26.70	Avg	75.25	155.55	
3633.68	48.67	H	73.97	-25.30	Peak	71.25	144.05	
3633.68	32.44	H	53.97	-21.53	Avg	71.25	144.05	
4542.10	42.61	H	73.97	-31.36	Peak	250.75	165.05	
4542.10	26.38	H	53.97	-27.59	Avg	250.75	165.05	
5450.52	44.32	H	73.97	-29.65	Peak	56.50	146.52	
5450.52	28.09	H	53.97	-25.88	Avg	56.50	146.52	
6358.94	44.41	H	73.97	-29.56	Peak	33.00	185.85	
6358.94	28.18	H	53.97	-25.79	Avg	33.00	185.85	
7267.36	45.21	H	73.97	-28.76	Peak	247.75	198.25	
7267.36	28.98	H	53.97	-24.99	Avg	247.75	198.25	
8175.78	49.68	H	73.97	-24.29	Peak	25.00	175.25	
8175.78	33.45	H	53.97	-20.52	Avg	25.00	175.25	
9084.20	46.36	H	73.97	-27.61	Peak	330.00	126.25	
9084.20	30.13	H	53.97	-23.84	Avg	330.00	126.25	

FCC 15.249

Ecolink Intelligent Technology, Inc.
 Single Decora Light Switch
 Model: SDLS2-ZWAVE5

Date: 11/20/2017
 Lab: D
 Tested By: Kyle Haag

**Harmonics - Low Channel
 Transmit Mode - Z-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
1816.84	37.54	H	73.97	-36.43	Peak	345.50	121.79	
1816.84	21.31	H	53.97	-32.66	Avg	345.50	121.79	
2725.26	48.26	H	73.97	-25.71	Peak	4.50	161.67	
2725.26	32.03	H	53.97	-21.94	Avg	4.50	161.67	
3633.68	45.29	H	73.97	-28.68	Peak	304.50	200.47	
3633.68	29.06	H	53.97	-24.91	Avg	304.50	200.47	
4542.10	42.57	H	73.97	-31.40	Peak	350.00	172.25	
4542.10	26.34	H	53.97	-27.63	Avg	350.00	172.25	
5450.52	44.59	H	73.97	-29.38	Peak	229.25	173.25	
5450.52	28.36	H	53.97	-25.61	Avg	229.25	173.25	
6358.94	46.29	H	73.97	-27.68	Peak	277.00	149.37	
6358.94	30.06	H	53.97	-23.91	Avg	277.00	149.37	
7267.36	46.58	H	73.97	-27.39	Peak	350.25	150.25	
7267.36	30.35	H	53.97	-23.62	Avg	350.25	150.25	
8175.78	52.58	H	73.97	-21.39	Peak	337.25	127.64	
8175.78	36.35	H	53.97	-17.62	Avg	337.25	127.64	
9084.20	48.29	H	73.97	-25.68	Peak	159.50	122.44	
9084.20	32.06	H	53.97	-21.91	Avg	159.50	122.44	

FCC 15.249

Ecolink Intelligent Technology, Inc.
 Single Decora Light Switch
 Model: SDLS2-ZWAVE5

Date: 11/20/2017
 Lab: D
 Tested By: Kyle Haag

**Harmonics - High Channel
 Transmit Mode - X-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
1832.00	34.31	V	73.97	-39.66	Peak	350.00	134.92	
1832.00	18.08	V	53.97	-35.89	Avg	350.00	134.92	
2748.00	48.44	V	73.97	-25.53	Peak	236.75	169.49	
2748.00	32.21	V	53.97	-21.76	Avg	236.75	169.49	
3664.00	41.08	V	73.97	-32.89	Peak	12.50	192.83	
3664.00	24.85	V	53.97	-29.12	Avg	12.50	192.83	
4580.00	45.52	V	73.97	-28.45	Peak	232.75	140.71	
4580.00	29.29	V	53.97	-24.68	Avg	232.75	140.71	
5496.00	44.59	V	73.97	-29.38	Peak	13.25	145.25	
5496.00	28.36	V	53.97	-25.61	Avg	13.25	145.25	
6412.00	44.99	V	73.97	-28.98	Peak	109.00	156.11	
6412.00	28.76	V	53.97	-25.21	Avg	109.00	156.11	
7328.00	47.21	V	73.97	-26.76	Peak	340.00	155.55	
7328.00	30.98	V	53.97	-22.99	Avg	340.00	155.55	
8244.00	47.78	V	73.97	-26.19	Peak	43.75	152.41	
8244.00	31.55	V	53.97	-22.42	Avg	43.75	152.41	
9160.00	48.74	V	73.97	-25.23	Peak	152.41	268.00	
9160.00	32.51	V	53.97	-21.46	Avg	152.41	268.00	

FCC 15.249

Ecolink Intelligent Technology, Inc.
 Single Decora Light Switch
 Model: SDLS2-ZWAVE5

Date: 11/20/2017
 Lab: D
 Tested By: Kyle Haag

**Harmonics - High Channel
 Transmit Mode - Y-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
1832.00	45.98	V	73.97	-27.99	Peak	74.75	102.22	
1832.00	29.75	V	53.97	-24.22	Avg	74.75	102.22	
2748.00	43.38	V	73.97	-30.59	Peak	300.75	116.89	
2748.00	27.15	V	53.97	-26.82	Avg	300.75	116.89	
3664.00	42.14	V	73.97	-31.83	Peak	124.53	101.75	
3664.00	25.91	V	53.97	-28.06	Avg	124.53	101.75	
4580.00	42.70	V	73.97	-31.27	Peak	9.00	124.53	
4580.00	26.47	V	53.97	-27.50	Avg	9.00	124.53	
5496.00	44.06	V	73.97	-29.91	Peak	178.00	135.25	
5496.00	27.83	V	53.97	-26.14	Avg	178.00	135.25	
6412.00	43.69	V	73.97	-30.28	Peak	10.25	124.53	
6412.00	27.46	V	53.97	-26.51	Avg	10.25	124.53	
7328.00	46.97	V	73.97	-27.00	Peak	261.25	134.92	
7328.00	30.74	V	53.97	-23.23	Avg	261.25	134.92	
8244.00	48.49	V	73.97	-25.48	Peak	351.25	134.58	
8244.00	32.26	V	53.97	-21.71	Avg	351.25	134.58	
9160.00	49.59	V	73.97	-24.38	Peak	304.00	121.25	
9160.00	33.36	V	53.97	-20.61	Avg	304.00	121.25	

FCC 15.249

Ecolink Intelligent Technology, Inc.
 Single Decora Light Switch
 Model: SDLS2-ZWAVE5

Date: 11/20/2017
 Lab: D
 Tested By: Kyle Haag

**Harmonics - High Channel
 Transmit Mode - Z-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
1832.00	34.09	V	73.97	-39.88	Peak	138.00	129.25	
1832.00	17.86	V	53.97	-36.11	Avg	138.00	129.25	
2748.00	48.65	V	73.97	-25.32	Peak	146.25	175.34	
2748.00	32.42	V	53.97	-21.55	Avg	146.25	175.34	
3664.00	42.60	V	73.97	-31.37	Peak	130.25	144.23	
3664.00	26.37	V	53.97	-27.60	Avg	130.25	144.23	
4580.00	45.73	V	73.97	-28.24	Peak	152.50	176.47	
4580.00	29.50	V	53.97	-24.47	Avg	152.50	176.47	
5496.00	44.99	V	73.97	-28.98	Peak	10.00	176.53	
5496.00	28.76	V	53.97	-25.21	Avg	10.00	176.53	
6412.00	45.15	V	73.97	-28.82	Peak	216.25	145.25	
6412.00	28.92	V	53.97	-25.05	Avg	216.25	145.25	
7328.00	45.90	V	73.97	-28.07	Peak	18.50	161.25	
7328.00	29.67	V	53.97	-24.30	Avg	18.50	161.25	
8244.00	50.25	V	73.97	-23.72	Peak	10.00	162.50	
8244.00	34.02	V	53.97	-19.95	Avg	10.00	162.50	
9160.00	48.45	V	73.97	-25.52	Peak	11.25	168.25	
9160.00	32.22	V	53.97	-21.75	Avg	11.25	168.25	

FCC 15.249

Ecolink Intelligent Technology, Inc.
 Single Decora Light Switch
 Model: SDLS2-ZWAVE5

Date: 11/20/2017
 Lab: D
 Tested By: Kyle Haag

**Harmonics - High Channel
 Transmit Mode - X-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
1832.00	39.67	H	73.97	-34.30	Peak	72.50	128.41	
1832.00	23.44	H	53.97	-30.53	Avg	72.50	128.41	
2748.00	48.65	H	73.97	-25.32	Peak	138.25	117.97	
2748.00	32.42	H	53.97	-21.55	Avg	138.25	117.97	
3664.00	43.23	H	73.97	-30.74	Peak	35.25	134.92	
3664.00	27.00	H	53.97	-26.97	Avg	35.25	134.92	
4580.00	45.53	H	73.97	-28.44	Peak	329.00	134.92	
4580.00	29.30	H	53.97	-24.67	Avg	329.00	134.92	
5496.00	44.19	H	73.97	-29.78	Peak	171.50	135.25	
5496.00	27.96	H	53.97	-26.01	Avg	171.50	135.25	
6412.00	44.60	H	73.97	-29.37	Peak	346.50	134.92	
6412.00	28.37	H	53.97	-25.60	Avg	346.75	134.92	
7328.00	47.41	H	73.97	-26.56	Peak	168.00	120.47	
7328.00	31.18	H	53.97	-22.79	Avg	168.00	120.47	
8244.00	48.07	H	73.97	-25.90	Peak	125.25	120.59	
8244.00	31.84	H	53.97	-22.13	Avg	125.25	120.59	
9160.00	47.51	H	73.97	-26.46	Peak	270.00	120.88	
9160.00	31.28	H	53.97	-22.69	Avg	270.00	120.88	

FCC 15.249

Ecolink Intelligent Technology, Inc.
 Single Decora Light Switch
 Model: SDLS2-ZWAVE5

Date: 11/20/2017
 Lab: D
 Tested By: Kyle Haag

**Harmonics - High Channel
 Transmit Mode - Y-Axis**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
1832.00	37.12	H	73.97	-36.85	Peak	10.00	184.32	
1832.00	20.89	H	53.97	-33.08	Avg	10.00	184.32	
2748.00	51.36	H	73.97	-22.61	Peak	351.00	194.32	
2748.00	35.13	H	53.97	-18.84	Avg	351.00	194.32	
3664.00	44.16	H	73.97	-29.81	Peak	51.00	158.58	
3664.00	27.93	H	53.97	-26.04	Avg	51.00	168.58	
4580.00	45.89	H	73.97	-28.08	Peak	262.25	167.94	
4580.00	29.66	H	53.97	-24.31	Avg	262.25	167.94	
5496.00	44.34	H	73.97	-29.63	Peak	84.75	191.25	
5496.00	28.11	H	53.97	-25.86	Avg	84.75	191.25	
6412.00	47.25	H	73.97	-26.72	Peak	355.00	190.92	
6412.00	31.02	H	53.97	-22.95	Avg	355.00	190.92	
7328.00	46.55	H	73.97	-27.42	Peak	225.25	175.46	
7328.00	30.32	H	53.97	-23.65	Avg	225.25	175.46	
8244.00	49.45	H	73.97	-24.52	Peak	233.75	163.64	
8244.00	33.22	H	53.97	-20.75	Avg	233.75	163.64	
9160.00	48.36	H	73.97	-25.61	Peak	108.00	151.46	
9160.00	32.13	H	53.97	-21.84	Avg	108.00	151.46	

FCC 15.249

Ecolink Intelligent Technology, Inc.
 Single Decora Light Switch
 Model: SDLS2-ZWAVE5

Date: 11/20/2017
 Lab: D
 Tested By: Kyle Haag

**Harmonics - High Channel
 Transmit Mode - Z-Axis**


Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table Angle (deg)	Ant. Height (cm)	Comments
1832.00	39.19	H	73.97	-34.78	Peak	156.50	130.56	
1832.00	22.96	H	53.97	-31.01	Avg	156.50	130.56	
2748.00	49.44	H	73.97	-24.53	Peak	217.00	178.50	
2748.00	33.21	H	53.97	-20.76	Avg	217.00	178.50	
3664.00	44.21	H	73.97	-29.76	Peak	89.50	178.50	
3664.00	27.98	H	53.97	-25.99	Avg	89.50	178.50	
4580.00	45.62	H	73.97	-28.35	Peak	222.00	179.52	
4580.00	29.39	H	53.97	-24.58	Avg	222.00	179.52	
5496.00	41.16	H	73.97	-32.81	Peak	33.75	158.38	
5496.00	24.93	H	53.97	-29.04	Avg	33.75	158.38	
6412.00	44.56	H	73.97	-29.41	Peak	44.00	159.58	
6412.00	28.33	H	53.97	-25.64	Avg	44.00	159.58	
7328.00	47.58	H	73.97	-26.39	Peak	35.50	158.38	
7328.00	31.35	H	53.97	-22.62	Avg	35.50	158.38	
8244.00	46.98	H	73.97	-26.99	Peak	209.25	158.38	
8244.00	30.75	H	53.97	-23.22	Avg	209.25	158.38	
9160.00	47.41	H	73.97	-26.56	Peak	200.00	145.58	
9160.00	31.18	H	53.97	-22.79	Avg	200.00	145.58	



***BAND EDGES
DATA SHEETS***




Att 40 dB Marker 4 [T2] Det MA/QP Trd LAB_A_LF
 INPUT 1 902.00000000 MHz ResBW 120 kHz
 Meas T 100 ms Unit dBV



Date: 21.NOV.2017 14:47:49

Band Edge - 908.42 MHz - Horizontal - X-Axis - Worst Case




Date: 21.NOV.2017 12:48:24

Band Edge - 908.42 MHz - Vertical - Y-Axis - Worst Case




Att 40 dB Marker 4 [T2] Det MA/QP Trd LAB_A_LF
 INPUT 1 928.00000000 MHz ResBW 120 kHz
 Meas T 100 ms Unit dBV




Date: 21.NOV.2017 15:42:05


Band Edge - 916 MHz - Horizontal - X-Axis - Worst Case




Date: 21.NOV.2017 11:29:46

Band Edge - 916 MHz - Vertical - Z-Axis - Worst Case





Pulse = 5.8 ms



Plot Showing that the pulses repeats at a worst case of 37.60 ms

Total Duty Cycle = 5.8 ms / 37.60 ms = 15.43% Duty Cycle

The Peak to Average Ratio is -16.23 dB