

*FCC PART 15, SUBPART B and C; FCC 15.231; and RSS-210 & RSS GEN
TEST REPORT*

for

MOTION DETECTOR

Model: WST-740

Prepared for

**ECOLINK INTELLIGENT TECHNOLOGY, INC.
2055 CORTE DEL NOGAL
CARLSBAD, CALIFORNIA 92011**

Prepared by: _____

KYLE FUJIMOTO

Approved by: _____

JAMES ROSS

**COMPATIBLE ELECTRONICS INC.
114 OLINDA DRIVE
BREA, CALIFORNIA 92823
(714) 579-0500**

DATE: MAY 16, 2022

| | REPORT BODY | APPENDICES | | | | | TOTAL |
|-------|----------------|------------|---|---|----|----|-------|
| | | A | B | C | D | E | |
| PAGES | 22 | 2 | 2 | 2 | 11 | 26 | 65 |

This report shall not be reproduced except in full, without the written approval of Compatible Electronics.



TABLE OF CONTENTS

| Section / Title | PAGE |
|--|-----------|
| GENERAL REPORT SUMMARY | 4 |
| SUMMARY OF TEST RESULTS | 5 |
| 1. PURPOSE | 6 |
| 1.1 Decision Rule & Risk | 7 |
| 2. ADMINISTRATIVE DATA | 8 |
| 2.1 Location of Testing | 8 |
| 2.2 Traceability Statement | 8 |
| 2.3 Cognizant Personnel | 8 |
| 2.4 Date Test Sample was Received | 8 |
| 2.5 Disposition of the Test Sample | 8 |
| 2.6 Abbreviations and Acronyms | 8 |
| 3. APPLICABLE DOCUMENTS | 9 |
| 4. DESCRIPTION OF TEST CONFIGURATION | 10 |
| 4.1 Description of Test Configuration – Emissions | 10 |
| 4.1.1 Cable Construction and Termination | 10 |
| 5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT | 11 |
| 5.1 EUT and Accessory List | 11 |
| 5.2 Emissions Test Equipment | 12 |
| 6. TEST SITE DESCRIPTION | 13 |
| 6.1 Test Facility Description | 13 |
| 6.2 EUT Mounting, Bonding and Grounding | 13 |
| 6.3 Measurement Uncertainty | 13 |
| 7. TEST PROCEDURES | 14 |
| 7.1 RF Emissions | 14 |
| 7.1.1 Conducted Emissions Test | 14 |
| 7.1.2 Radiated Emissions Test | 15 |
| 7.1.3 RF Emissions Test Results | 17 |
| 7.1.4 Sample Calculations | 18 |
| 7.1.5 Duty Cycle Calculation | 19 |
| 7.1.6 99 % Bandwidth | 20 |
| 7.1.7 -20 dB Bandwidth | 20 |
| 7.1.8 Transmission Time | 21 |
| 7.1.9 Variation of the Input Power | 21 |
| 8. CONCLUSIONS | 22 |

LIST OF APPENDICES

| APPENDIX | TITLE |
|-----------------|---|
| A | Laboratory Accreditations and Recognitions |
| B | Modifications to the EUT |
| C | Models Covered Under This Report |
| D | Diagrams, Charts, and Photos <ul style="list-style-type: none">• Test Setup Diagrams• Antenna and Effective Gain Factors• Radiated and Conducted Emissions Photos |
| E | Data Sheets |

LIST OF FIGURES

| FIGURE | TITLE |
|---------------|--|
| 1 | Conducted Emissions Test Setup |
| 2 | Layout of the Semi-Anechoic Test Chamber |

LIST OF TABLES

| TABLE | TITLE |
|--------------|---------------------------|
| 1 | Radiated Emission Results |

GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Compatible Electronics Inc., which is an independent testing and consulting firm. The test report is based on testing performed by Compatible Electronics personnel according to the measurement procedures described in the test specifications given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced without the written permission of Compatible Electronics, unless done so in full.

This report must not be used by the client to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the United States government.

Device Tested: Motion Detector
Model: WST-740
S/N: N/A

Product Description: The equipment under test is a Motion Detector that uses RF technology. The transmit frequency is 433.92 MHz.
The clock oscillator is 13.56 MHz.
Dimensions: 2.3 cm (L) x 9.2 cm (W) x 13.7 cm (H).

Modifications: The EUT was not modified to meet the specifications.

Customer: Ecolink Intelligent Technology, Inc.
2055 Corte Del Nogal
Carlsbad, California 92011

Test Dates: May 4, 2022

Test Specifications covered by accreditation:

Test Specifications: Emissions requirements
CFR Title 47, Part 15, Subpart B;
CFR Title 47, Part 15, Subpart C, sections 15.205, 15.207, 15.209, and 15.231;
RSS-210 and RSS-Gen



Test Procedures: ANSI C63.4 and ANSI C63.10

Test Deviations: The test procedure was not deviated from during the testing.


SUMMARY OF TEST RESULTS

| TEST | DESCRIPTION | RESULTS |
|------|--|--|
| 1 | Conducted RF Emissions, 150 kHz – 30 MHz | This test was not performed because the EUT operates on battery power only and cannot be plugged into the AC public mains. |
| 2 | Spurious Radiated RF Emissions, 9 kHz – 4.34 GHz (Transmitter and Digital portion) | Complies with the Class B limits of CFR Title 47, Part 15 Subpart B; the limits of CFR Title 47, Part 15 Subpart C, sections 15.205, 15.209, and 15.231; and the limits of RSS-210 and RSS-Gen Highest reading in relation to spec limit 77.57 dBuV/m (AVG) @ 433.92 MHz (*U = 3.30 dB) |
| 3 | -20 dB Bandwidth | Complies with limits of CFR Title 47, Part 15 Subpart C, section 15.231 (c); and the limits of RSS-210 |
| 4 | Transmission Time | Complies with limits of CFR Title 47, Part 15 Subpart C, section 15.231 (a)(1) and (a)(2); and the limits of RSS-210 |

*U = Expanded Uncertainty with a coverage factor of k=2

1. PURPOSE

This document is a qualification test report based on the emissions tests performed on the Motion Detector, Model: WST-740. The emissions measurements were performed according to the measurement procedure described in ANSI C63.4 and ANSI C63.10. The tests were performed to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT hereafter, are within the **Class B** specification limits defined by CFR Title 47, Part 15 Subpart B section, 15.109; the specification limits defined by CFR Title 47, Part 15 Subpart C sections 15.205, 15.209 and 15.231; and the specifications limits defined by RSS-210 and RSS-Gen.





1.1 Decision Rule & Risk

If a measured value exceeds a specification limit it implies non-compliance. If the value is below a specification limit it implies compliance. Measurement uncertainty of the laboratory is reported with all measurement results but generally not taken into consideration unless a standard, rule or law requires it to be considered.

Qualification test reports are only produced for products that are in compliance with the test requirements, therefore results are always in conformity. Otherwise, an engineering report or just the data is provided to the customer.

When performing a measurement and making a statement of conformity, in or out-of-specification to manufacturer's specifications or Pass/Fail against a requirement, there are two possible outcomes:

- The result is reported as conforming with the specification
- The result is reported as not conforming with the specification

The decision rule is defined below.

When the test result is found to be below the limit but within our measurement uncertainty of the limit, it is our policy that the final acceptance decision is left to the customer, after discussing the implications and potential risks of the decision.

When the test result is found to be exactly on the specification, it is our policy, in the case of unwanted emissions measurements to consider the result non-compliant, however, the final decision is left to the customer, after discussing the implications and potential risks of the decision.

When the test result is found to be over the specification limit under any condition, it is our policy to consider the result non-compliant.

In terms of uncertainty of measurement, the laboratory is a calibrated and tightly controlled environment and generally exceptionally stable, the measurement uncertainties are evaluated without the considering of the test sample. When it comes to the test sample however, as most testing is performed on a single sample rather than a sample population, and that sample is often a pre-production representation of the final product, that test sample represents a significantly higher source of measurement uncertainty. We advise our customers of this and that when in doubt (small test to limit margins), they may wish to perform statistical sampling on a population to gain a higher confidence in the results. All lab reported results are that of a single sample in any event.

2. ADMINISTRATIVE DATA

2.1 Location of Testing

The emissions tests described herein were performed at the test facility of Compatible Electronics, 114 Olinda Drive, Brea, California 92823.

2.2 Traceability Statement

The calibration certificates of all test equipment used during the test are on file at the location of the test. The calibration is traceable to the National Institute of Standards and Technology (NIST).

2.3 Cognizant Personnel

Ecolink Intelligent Technology, Inc.

| | |
|---------------|----------------------------------|
| David Shepard | Product Compliance/QA Specialist |
| Jay Stone | Director of Engineering |

Compatible Electronics Inc.

| | |
|---------------|----------------------|
| Kyle Fujimoto | Senior Test Engineer |
| James Ross | Senior Test Engineer |

2.4 Date Test Sample was Received

The test sample was received prior to the date of this report.

2.5 Disposition of the Test Sample

The test sample has not been returned to Ecolink Intelligent Technology, Inc. as of the date of this report.

2.6 Abbreviations and Acronyms

The following abbreviations and acronyms may be used in this document.

| | |
|------|-----------------------------------|
| EMI | Electromagnetic Interference |
| EUT | Equipment Under Test |
| P/N | Part Number |
| S/N | Serial Number |
| FCC | Federal Communications Commission |
| DoC | Declaration of Conformity |
| N/A | Not Applicable |
| Tx | Transmit |
| Rx | Receive |
| Inc. | Incorporated |
| RSS | Radio Standards Specification |
| RF | Radio Frequency |
| BLE | Bluetooth Low Energy |
| CFR | Code of Federal Regulations |
| PCB | Printed Circuit Board |
| DC | Direct Current |
| LED | Light Emitting Diode |



3. APPLICABLE DOCUMENTS

The following documents are referenced or used in the preparation of this emission Test Report.

| SPEC | TITLE |
|---|---|
| FCC Title 47, Part 15 Subpart B | FCC Rules – Radio frequency devices (including digital devices) – Unintentional Radiators |
| FCC Title 47, Part 15 Subpart C | FCC Rules – Radio frequency devices (including digital devices) – Intentional Radiators |
| RSS-210 Issue 10: 2019 + Amendment (April 2020) | License-exempt Radio Apparatus: Category I Equipment |
| RSS-Gen Issue 5: 2018 + Amendment 1: 2019 + Amendment 2: 2021 | General Requirements for Compliance of Radio Apparatus |
| ANSI C63.4: 2014 | American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz |
| ANSI C63.10: 2013 | American National Standard of procedure for compliance testing of unlicensed wireless devices |



4. DESCRIPTION OF TEST CONFIGURATION

4.1 Description of Test Configuration – Emissions

The Motion Detector, Model: WST-740 (EUT) tested as a stand alone unit and placed in the middle of the turntable. The EUT was transmitting at 433.92 MHz on a continuous basis.

The EUT was tested for emissions while in the X, Y and Z axis. The X orientation is when the EUT is parallel to the ground. The Y orientation is when the EUT is perpendicular to the ground mounted vertically. The Z orientation is when the EUT is perpendicular to the ground mounted horizontally.

The EUT had fresh batteries installed prior to the testing.

The firmware inside the EUT allowed the EUT to continuously transmit at 433.92 MHz.

The firmware is stored on the company's servers.

The final radiated emissions data for the EUT was taken in the configuration described above. Please see Appendix E for the data sheets.

4.1.1 Cable Construction and Termination

There were no external cables connected to the EUT.

**5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT****5.1 EUT and Accessory List**

| EQUIPMENT | MANUFACTURER | MODEL NUMBER | SERIAL NUMBER | FCC ID |
|-----------------------|--------------------------------------|---------------------|----------------------|--------------------------------|
| MOTION DETECTOR (EUT) | ECOLINK INTELLIGENT TECHNOLOGY, INC. | WST-740 | N/A | XQC-WST740 IC: 9863B-WST740 |
| FIRMWARE | ECOLINK INTELLIGENT TECHNOLOGY, INC. | 1.0 | N/A | N/A |

5.2 Emissions Test Equipment

| EQUIPMENT TYPE | MANU-FACTURER | MODEL NUMBER | SERIAL NUMBER | CAL. DATE | CAL. CYCLE |
|---|-----------------------------|--------------|---------------|--------------------|------------|
| RF RADIATED AND CONDUCTED EMISSIONS TEST EQUIPMENT | | | | | |
| TDK TestLab | TDK RF Solutions, Inc. | 9.22 | 700145 | N/A | N/A |
| MXE EMI Receiver, 20 Hz – 26.5 GHz | Keysight Technologies, Inc. | N9038A | MY51210150 | September 17, 2021 | 2 Year |
| System Controller | Sunol Sciences Corporation | SC110V | 112213-1 | N/A | N/A |
| Turntable | Sunol Sciences Corporation | 2011VS | N/A | N/A | N/A |
| Antenna-Mast | Sunol Sciences Corporation | TWR95-4 | 112213-3 | N/A | N/A |
| Loop Antenna | Com-Power | AL-130R | 121090 | February 10 2022 | 3 Year |
| CombiLog Antenna | Com-Power | AC-220 | 61093 | December 14, 2021 | 2 Year |
| Horn Antenna | Com-Power | AH-118 | 10050113 | December 16, 2021 | 2 Year |
| Preamplifier | Com-Power | PAM-118 | 181653 | March 7, 2022 | 1 Year |
| Computer | Hewlett Packard | p6716f | MXX1030PX0 | N/A | N/A |
| LCD Monitor | Hewlett Packard | 52031a | 3CQ046N3MG | N/A | N/A |

6. TEST SITE DESCRIPTION

6.1 Test Facility Description

Please refer to section 2.1 of this report for emissions test location.

6.2 EUT Mounting, Bonding and Grounding

For frequencies 1 GHz and below: The EUT was mounted on a 0.6 by 1.2 meter non-conductive table 0.8 meters above the ground plane.

For frequencies above 1 GHz: The EUT was mounted on a 0.6 by 1.2 meter non-conductive table 1.5 meters above the ground plane.

The EUT was not grounded.

6.3 Measurement Uncertainty

Compatible Electronics' U_{lab} value is less than U_{cispr} , thus based on this – compliance is deemed to occur if no measured disturbance exceeds the disturbance limit

$$u_c(y) = \sqrt{\sum_i c_i^2 u^2(x_i)}$$

| Measurement | | U_{cispr} | $U_{lab} = 2 u_c(y)$ |
|---|----------------------|-------------|--|
| Conducted disturbance (mains port) | (150 kHz – 30 MHz) | 3.4 dB | 2.72 dB |
| Radiated disturbance (electric field strength on an open area test site or alternative test site) | (30 MHz – 1 000 MHz) | 6.3 dB | 3.32 dB (Vertical) 3.30 dB (Horizontal) |
| Radiated disturbance (electric field strength on an open area test site or alternative test site) | (1 GHz - 6 GHz) | 5.2 dB | 4.06 dB |
| Radiated disturbance (electric field strength on an open area test site or alternative test site) | (6 GHz – 18 GHz) | 5.5 dB | 4.06 dB |
| Radiated disturbance (electric field strength on an open area test site or alternative test site) | (18 GHz – 26.5 GHz) | N/A | 4.43 dB |
| Radiated disturbance (electric field strength on an open area test site or alternative test site) | (26.5 GHz – 40 GHz) | N/A | 4.57 dB |



7. TEST PROCEDURES

The following sections describe the test methods and the specifications for the tests. Test results are also included in this section.

7.1 RF Emissions

7.1.1 Conducted Emissions Test

The EMI Receiver was used as a measuring meter. A quasi-peak and/or average reading was taken only where indicated in the data sheets. A 10 dB attenuator was used for the protection of the EMI Receiver input stage, and the offset was adjusted accordingly to read the actual data measured. The LISN output was measured using the EMI Receiver. The output of the second LISN was terminated by a 50-ohm termination. The effective measurement bandwidth used for this test was 9 kHz.

Please see section 6.2 of this report for mounting, bonding, and grounding of the EUT. The EUT was powered through the LISN, which was bonded to the ground plane. The LISN power was filtered and the filter was bonded to the ground plane. The EUT was set up with the minimum distances from any conductive surfaces as specified in ANSI 63:4. The excess power cord was wrapped in a figure eight pattern to form a bundle not exceeding 0.4 meters in length.

The conducted emissions from the EUT were maximized for operating mode as well as cable placement. The final data was collected under program control by computer software. The final qualification data is located in Appendix E.

Test Results:

This test was not performed because the EUT operates on battery power only and cannot be plugged into the AC public mains.

7.1.2 Radiated Emissions Test

The EMI Receiver was used as the measuring meter. An internal preamplifier was used to increase the sensitivity of the instrument during emissions tests up to 1000 MHz, and an external preamplifier was used to increase the sensitivity of the instrument during emissions tests above 1 GHz. The EMI Receiver was initially used with the Analyzer mode feature activated. In this mode, the EMI receiver can then record the actual frequency to be measured. This final reading is then taken accurately in the EMI Receiver mode, which considers the cable loss, amplifier gain and antenna factors, so that a true reading is compared to the true limit. The effective measurement bandwidth used for the radiated emissions test was according to the frequency measured.

The frequencies below 1 GHz, except for the fundamental frequency and the 2nd harmonic of the fundamental frequency, were quasi-peaked using the quasi-peak detector of the EMI Receiver.

The harmonic frequencies above 1 GHz, the fundamental frequency, and the 2nd harmonic were averaged using the duty cycle correction calculation.

All other frequencies above 1 GHz were averaged using the average detector of the EMI Receiver.

The EMI test chamber of Compatible Electronics, Inc. was used for radiated emissions testing. This test site is in full compliance with ANSI C63.4. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. At each reading, the EUT was rotated 360 degrees and the antenna height was varied from 1 to 4 meters (for E field radiated field strength). The gunsight method was used when measuring with the horn antenna to ensure accurate results.

The EUT was tested at a 3-meter test distance. The six highest emissions are listed in Table 1.

**Radiated Emissions Test (Continued)**

The measurement bandwidths and transducers used for the radiated emissions test were:

| FREQUENCY RANGE | EFFECTIVE MEASUREMENT BANDWIDTH | TRANSDUCER |
|------------------------|--|-------------------|
| 9 kHz to 150 kHz | 200 Hz | Loop Antenna |
| 150 kHz to 30 MHz | 9 kHz | Loop Antenna |
| 30 MHz to 1 GHz | 120 kHz | CombiLog Antenna |
| 1 GHz to 4.34 GHz | 1 MHz | Horn Antenna |

Test Results:

The EUT complies with the **Class B** limits of CFR Title 47, Part 15, Subpart B; the limits of CFR Title 47, Part 15, Subpart C sections 15.205, 15.209 and 15.231; and the limits of RSS-210 and RSS-Gen for radiated emissions.



7.1.3 RF Emissions Test Results

Table 1 RADIATED EMISSION RESULTS
Motion Detector, Model: WST-740

| Frequency MHz | Corrected Reading* dB μ V/m | Specification Limit dB μ V/m | Delta (Cor. Reading – Spec. Limit) dB |
|----------------------|------------------------------------|-------------------------------------|---|
| 433.92 (H) (X-Axis) | 77.57 (AV) | 80.82 | -3.25 |
| 433.92 (H) (Z-Axis) | 76.47 (AV) | 80.82 | -4.35 |
| 433.92 (V) (Y-Axis) | 75.65 (AV) | 80.82 | -5.17 |
| 1301.76 (V) (Z-Axis) | 47.83 (AV) | 53.97 | -6.14 |
| 433.92 (V) (Z-Axis) | 74.58 (AV) | 80.82 | -6.24 |
| 433.92 (H) (Y-Axis) | 71.56 (AV) | 80.82 | -9.27 |

Notes:

- * The complete emissions data is given in Appendix E of this report.
- (V) Vertical
- (H) Horizontal
- (AV) Average

7.1.4 Sample Calculations

A correction factor for the antenna, cable and a distance factor (if any) must be applied to the meter reading before a true field strength reading can be obtained. This Corrected Meter Reading is then compared to the specification limit in order to determine compliance with the limits.

Conversion to logarithmic terms: Specification limit ($\mu\text{V}/\text{m}$) $\log \times 20 =$ Specification Limit in $\text{dB}\mu\text{V}/\text{m}$

To correct for distance when measuring at a distance other than the specification

For measurements below 30 MHz: (Specification distance / test distance) $\log \times 40 =$ distance factor

For measurements above 30 MHz: (Specification distance / test distance) $\log \times 20 =$ distance factor

Note: When using an Active Antenna, the Antenna factor shall be subtracted due to the combination of the internal amplification and antenna loss.

Corrected Meter Reading = meter reading + F – A + C

where: F = antenna factor
A = amplifier gain
C = cable loss

The correction factors for the antenna and the amplifier gain are attached in Appendix D of this report. The data sheets are attached in Appendix E.

The distance factor D is 0 when the test is performed at the required specification distance.

When the limit is in terms of magnetic field, the following equation applies:

$$H[\text{dB}(\mu\text{A}/\text{m})] = V[\text{dB}(\mu\text{V})] + L_C [\text{dB}] - G_{PA} [\text{dB}] + AF^H [\text{dB}(\text{S}/\text{m})]$$

where: H is the magnetic field strength (to be compared with the limit),
 V is the voltage level measured by the receiver or spectrum analyzer,
 L_C is the cable loss,
 G_{PA} is the gain of the preamplifier (if used), and
 AF^H is the magnetic antenna factor.

The G_{PA} term is only included in the equation when an external preamplifier is used in the measurement chain, in front of the receiver or spectrum analyzer. An external preamplifier is not usually necessary (or even advisable, due to risk of saturating the input mixer of the receiver) when an active loop antenna is used. In that case, the antenna factor of the loop already includes the gain of its built-in preamplifier.

If the “electrical” antenna factor is used instead, the above equation becomes:

$$H[\text{dB}(\mu\text{A}/\text{m})] = V[\text{dB}(\mu\text{V})] + L_C [\text{dB}] - G_{PA}[\text{dB}] + AF^E [\text{dB}(\text{m}^{-1})] - 51.5 [\text{dB}\Omega]$$

where: AF^E is the “electric” antenna factor, as provided by the antenna calibration laboratory.

When the limit is in terms of electric field, the following equation applies:

$$E[\text{dB}(\mu\text{V}/\text{m})] = V[\text{dB}(\mu\text{V})] + L_C[\text{dB}] - G_{PA}[\text{dB}] + AF^E [\text{dB}(\text{m}^{-1})]$$

or, if the magnetic antenna factor is used:

$$E[\text{dB}(\mu\text{V}/\text{m})] = V[\text{dB}(\mu\text{V})] + L_C[\text{dB}] - G_{PA}[\text{dB}] + AF^H [\text{dB}(\text{S}/\text{m})] + 51.5[\text{dB}\Omega]$$

The display of the receiver (or spectrum analyzer) **shall not** be configured in units of current, e.g. μA or $\text{dB}(\mu\text{A})$. That conversion is calculated inside the receiver (or spectrum analyzer) using its input impedance, which is 50Ω , while the magnetic field calculation is based on the free-space impedance of 377Ω .



7.1.5 Duty Cycle Calculation

The fundamental and harmonics were measured at a 3-meter test distance. The EMI Receiver was used to obtain the final test data. The final qualification data sheets are in Appendix E.

Where

$$\delta(\text{dB}) = 20 \log \left[\frac{\sum (nt_1 + mt_2 + \dots + \xi t_x)}{T} \right]$$

n is the number of pulses of duration t_1

m is the number of pulses of duration t_2

ξ is the number of pulses of duration t_x

T is the period of the pulse train or 100 ms if the pulse train length is greater than 100 ms

Duty Cycle Correction Factor = -19.84 dB

Time of One Small Pulse = 275 μs

Time of One Large Pulse = 2750 μs

Number of Small Pulses = 27

Number of Large Pulses = 1

Total On Time = 10175 μs = 10.175 ms

The time between pulses is greater than 100 ms

Duty Cycle = 10.175 ms / 100 ms = 10.175 %



7.1.6 99 % Bandwidth

The 99 % bandwidth was measured using an EMI Receiver.

The following steps were performed for measuring the 99 % bandwidth per RSS-GEN, Issue 5, clause 6.7:

1. Set RBW to 1% to 5% of the actual occupied bandwidth.
2. Set VBW to greater than 3 times the RBW.
3. Set the EMI Receiver to the occupied bandwidth Function set at 99 %
4. Set the peak detector to max hold.
5. Set the sweep time to auto
6. Allow the trace to stabilize.

Please note that this was only used to determine the emission bandwidth and that there are no limits or pass/fail criteria for this test. Please see the data sheets located in Appendix E.

7.1.7 -20 dB Bandwidth

The -20 dB bandwidth was measured using an EMI Receiver.

The following steps were performed for measuring the -20 dB bandwidth:

1. Set RBW from 1% to 5% of the Occupied Bandwidth.
2. Set the span to 100 kHz.
3. Set VBW to greater than 3 times the RBW.
4. Set the peak detector to max hold.
5. Set the sweep time to auto
6. Allow the trace to stabilize.
7. Set the markers to -20 dB of the peak fundamental emission

Test Results:

The EUT complies with limits of CFR Title 47, Part 15, Subpart C section 15.231 (c); and the limits of RSS-210.



7.1.8 Transmission Time

The transmission time was measured using an EMI Receiver.

The following steps were performed for measuring transmission time:

1. Set RBW = 120 kHz
2. Set VBW = 510 kHz
3. Span = 0 Hz
4. Set the sweep time to 7 seconds
5. Push a button on the EUT, which automatically activated the transmitter.
6. Allow the trace to stabilize.
7. Set the 1st marker to start of the transmission
8. Set the 2nd marker for 5 seconds after the start of the transmission
9. Verify the transmission does not go beyond the 2nd marker.

Test Results:

The EUT complies with limits of CFR Title 47, Part 15, Subpart C section 15.231 (a)(1) and (a)(2); and the limits of RSS-210.

7.1.9 Variation of the Input Power

The variation of the input power test was performed using the EMI Receiver. The EUT input power was varied between 85% and 115% of the nominal rated supply voltage. The carrier frequency was monitored for any change in amplitude.

Test Results:

This test was not performed because the EUT is battery power only.



8. CONCLUSIONS

The Motion Detector, Model: WST-740 (EUT), as tested, meets all the specification limits defined in RSS-210, RSS-Gen, the **Class B** specification limits defined in CFR Title 47, Part 15, Subpart B; and the specification limits defined in CFR Title 47, Part, 15, Subpart C, sections 15.205, 15.207, 15.209 and 15.231.





APPENDIX A

LABORATORY ACCREDITATIONS AND RECOGNITIONS

Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Newbury Park Division
1050 Lawrence Drive
Newbury Park, CA 91320
(805) 480-4044

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400



LABORATORY ACCREDITATIONS AND RECOGNITIONS



For US, Canada, Australia/New Zealand, Japan, Taiwan, Korea, and the European Union, Compatible Electronics is currently accredited by NVLAP to ISO/IEC 17025.

For the most up-to-date version of our scopes and certificates please visit
<http://celectronics.com/quality/scope/>

Quote from ISO-ILAC-IAF Communiqué on the Management Systems Requirements of ISO/IEC 17025, General Requirements for the competence of testing and calibration laboratories:

"A laboratory's fulfilment of the requirements of ISO/IEC 17025 means the laboratory meets both the technical competence requirements and management system requirements that are necessary for it to consistently deliver technically valid test results and calibrations. The management system requirements in ISO/IEC 17025 are written in language relevant to laboratory operations and operate generally in accordance with the principles of ISO 9001"

Innovation, Science and Economic Development Canada
Lab Code 2154A

Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Newbury Park Division
1050 Lawrence Drive
Newbury Park, CA 91320
(805) 480-4044

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400



APPENDIX B

MODIFICATIONS TO THE EUT

MODIFICATIONS TO THE EUT

The modifications listed below were made to the EUT to pass FCC Subpart B, FCC 15.231, RSS-210, and RSS-Gen specifications.

All the rework described below was implemented during the test in a method that could be reproduced in all the units by the manufacturer.

No modifications were made to the EUT during the testing.





APPENDIX C

MODELS COVERED UNDER THIS REPORT

MODELS COVERED UNDER THIS REPORT

USED FOR THE PRIMARY TEST

Motion Detector
Model: WST-740
S/N: N/A

There are no additional models or part numbers covered under this report.





APPENDIX D

DIAGRAMS, CHARTS, AND PHOTOS

FIGURE 1: CONDUCTED EMISSIONS TEST SETUP





FIGURE 2: LAYOUT OF THE SEMI-ANECHOIC TEST CHAMBER





COM-POWER AL-130R

LOOP ANTENNA

S/N: 121090

CALIBRATION DATE: FEBRUARY 10, 2022

| FREQUENCY (MHz) | MAGNETIC (dB/m) | ELECTRIC (dB/m) |
|--------------------|--------------------|--------------------|
| 0.009 | 15.6 | -35.8 |
| 0.01 | 15.8 | -35.6 |
| 0.02 | 14.8 | -36.6 |
| 0.03 | 15.6 | -35.9 |
| 0.04 | 15.0 | -36.5 |
| 0.05 | 14.4 | -37.1 |
| 0.06 | 14.6 | -36.9 |
| 0.07 | 14.3 | -37.2 |
| 0.08 | 14.3 | -37.2 |
| 0.09 | 14.4 | -37.0 |
| 0.10 | 14.1 | -37.4 |
| 0.20 | 14.1 | -37.4 |
| 0.30 | 14.0 | -37.5 |
| 0.40 | 13.9 | -37.6 |
| 0.50 | 14.1 | -37.3 |
| 0.60 | 14.1 | -37.3 |
| 0.70 | 14.2 | -37.3 |
| 0.80 | 14.2 | -37.3 |
| 0.90 | 14.2 | -37.2 |
| 1.00 | 14.4 | -37.0 |
| 2.00 | 14.6 | -36.9 |
| 3.00 | 14.6 | -36.8 |
| 4.00 | 14.9 | -36.6 |
| 5.00 | 14.9 | -36.7 |
| 6.00 | 14.8 | -36.7 |
| 7.00 | 14.6 | -36.8 |
| 8.00 | 14.5 | -37.0 |
| 9.00 | 14.3 | -37.2 |
| 10.00 | 14.5 | -37.0 |
| 11.00 | 14.6 | -36.9 |
| 12.00 | 14.7 | -36.7 |
| 13.00 | 14.9 | -36.6 |
| 14.00 | 15.0 | -36.5 |
| 15.00 | 14.9 | -36.6 |
| 16.00 | 14.9 | -36.6 |
| 17.00 | 14.6 | -36.8 |
| 18.00 | 14.4 | -37.1 |
| 19.00 | 14.5 | -37.0 |
| 20.00 | 14.5 | -37.0 |
| 21.00 | 14.2 | -37.3 |
| 22.00 | 13.9 | -37.5 |
| 23.00 | 13.9 | -37.5 |
| 24.00 | 13.8 | -37.7 |
| 25.00 | 13.4 | -38.0 |
| 26.00 | 13.2 | -38.2 |
| 27.00 | 13.2 | -38.3 |
| 28.00 | 12.7 | -38.7 |
| 29.00 | 12.7 | -38.8 |
| 30.00 | 12.4 | -39.0 |

Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Newbury Park Division
1050 Lawrence Drive
Newbury Park, CA 91320
(805) 480-4044

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400



COM-POWER AC-220

COMBILOG ANTENNA

S/N: 61093

CALIBRATION DATE: DECEMBER 14, 2021


| FREQUENCY (MHz) | FACTOR (dB) | FREQUENCY (MHz) | FACTOR (dB) |
|--------------------|----------------|--------------------|----------------|
| 30 | 22.50 | 200 | 16.00 |
| 35 | 21.40 | 250 | 17.40 |
| 40 | 21.00 | 300 | 19.70 |
| 45 | 20.60 | 350 | 20.00 |
| 50 | 19.70 | 400 | 22.20 |
| 60 | 16.10 | 450 | 22.40 |
| 70 | 12.80 | 500 | 23.10 |
| 80 | 12.50 | 550 | 23.40 |
| 90 | 14.20 | 600 | 24.90 |
| 100 | 15.40 | 650 | 25.30 |
| 120 | 16.50 | 700 | 25.40 |
| 125 | 16.80 | 750 | 26.40 |
| 140 | 15.90 | 800 | 26.70 |
| 150 | 16.60 | 850 | 27.10 |
| 160 | 18.50 | 900 | 27.90 |
| 175 | 15.90 | 950 | 28.00 |
| 180 | 15.50 | 1000 | 28.00 |

COM POWER AH-118**HORN ANTENNA****S/N: 10050113****CALIBRATION DATE: DECEMBER 16, 2021**

| FREQUENCY (GHz) | FACTOR (dB) | FREQUENCY (GHz) | FACTOR (dB) |
|----------------------------|------------------------|----------------------------|------------------------|
| 1.0 | 23.86 | 10.0 | 38.91 |
| 1.5 | 25.67 | 10.5 | 39.94 |
| 2.0 | 28.25 | 11.0 | 39.10 |
| 2.5 | 29.17 | 11.5 | 39.70 |
| 3.0 | 29.78 | 12.0 | 40.29 |
| 3.5 | 30.88 | 12.5 | 41.93 |
| 4.0 | 31.21 | 13.0 | 41.34 |
| 4.5 | 32.96 | 13.5 | 40.57 |
| 5.0 | 33.30 | 14.0 | 40.23 |
| 5.5 | 34.24 | 14.5 | 42.25 |
| 6.0 | 34.57 | 15.0 | 43.63 |
| 6.5 | 35.61 | 15.5 | 39.96 |
| 7.0 | 36.60 | 16.0 | 40.38 |
| 7.5 | 37.49 | 16.5 | 40.56 |
| 8.0 | 37.44 | 17.0 | 40.93 |
| 8.5 | 37.98 | 17.5 | 42.27 |
| 9.0 | 38.01 | 18.0 | 43.77 |
| 9.5 | 38.53 | | |

COM-POWER PAM-118**PREAMPLIFIER****S/N: 181653****CALIBRATION DATE: MARCH 7, 2022**

| FREQUENCY (GHz) | FACTOR (dB) | FREQUENCY (GHz) | FACTOR (dB) |
|----------------------------|------------------------|----------------------------|------------------------|
| 1.0 | 40.02 | 6.0 | 38.84 |
| 1.1 | 39.72 | 6.5 | 39.20 |
| 1.2 | 39.93 | 7.0 | 39.46 |
| 1.3 | 39.98 | 7.5 | 39.67 |
| 1.4 | 39.99 | 8.0 | 39.28 |
| 1.5 | 40.20 | 8.5 | 38.63 |
| 1.6 | 40.05 | 9.0 | 38.96 |
| 1.7 | 40.15 | 9.5 | 39.33 |
| 1.8 | 40.20 | 10.0 | 39.58 |
| 1.9 | 40.33 | 11.0 | 38.25 |
| 2.0 | 40.33 | 12.0 | 40.03 |
| 2.5 | 40.60 | 13.0 | 40.55 |
| 3.0 | 40.76 | 14.0 | 40.36 |
| 3.5 | 40.87 | 15.0 | 39.34 |
| 4.0 | 40.39 | 16.0 | 37.34 |
| 4.5 | 39.55 | 17.0 | 42.14 |
| 5.0 | 40.34 | 18.0 | 42.54 |
| 5.5 | 39.45 | | |



FRONT VIEW

ECOLINK INTELLIGENT TECHNOLOGY, INC.

MOTION DETECTOR

MODEL: WST-740

FCC SUBPART B AND C; RSS-210 AND RSS-GEN – RADIATED EMISSIONS – BELOW 1 GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**

**Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500**

**Newbury Park Division
1050 Lawrence Drive
Newbury Park, CA 91320
(805) 480-4044**

**Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400**

**REAR VIEW**


ECOLINK INTELLIGENT TECHNOLOGY, INC.

MOTION DETECTOR

MODEL: WST-740

FCC SUBPART B AND C; RSS-210 AND RSS-GEN – RADIATED EMISSIONS – BELOW 1 GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



FRONT VIEW


ECOLINK INTELLIGENT TECHNOLOGY, INC.

MOTION DETECTOR

MODEL: WST-740

FCC SUBPART B AND C; RSS-210 AND RSS-GEN – RADIATED EMISSIONS – ABOVE 1 GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



REAR VIEW

**ECOLINK INTELLIGENT TECHNOLOGY, INC.
MOTION DETECTOR
MODEL: WST-740**

FCC SUBPART B AND C; RSS-210 AND RSS-GEN – RADIATED EMISSIONS – ABOVE 1 GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



APPENDIX E

DATA SHEETS



RADIATED EMISSIONS


DATA SHEETS

Title: Pre-Scan - FCC Class B
 File: 1 - LF - Pre-Scan - FCC Class B - 05-04-2022.set
 Operator: Kyle Fujimoto
 EUT Type: Motion Detector
 EUT Condition: The EUT is continuously transmitting at 433.92 MHz
 Company: Ecolink Intelligent Technologies, Inc.
 Model: WST-740
 S/N: N/A
 Note: The frequencies at 433.92 MHz and 867.84 MHz are subject to the limits of FCC 15.231 (a) instead.
 X-Axis Worst Case

5/4/2022 10:49:02 AM
 Sequence: Preliminary Scan

FCC Class B

Electric Field Strength (dBμV/m)



Title: Radiated Final - FCC Class B
 File: 1 - LF - Final Scan - FCC Class B - 05-04-2022.set
 Operator: Kyle Fujimoto
 EUT Type: Motion Detector
 EUT Condition: The EUT is continuously transmitting at 433.92 MHz
 Company: Ecolink Intelligent Technologies, Inc.
 Model: WST-740
 S/N: N/A

5/4/2022 10:59:42 AM
 Sequence: Final Measurements

FCC Class B

| Freq (MHz) | Pol | (PEAK) EMI (dBμV/m) | (QP) EMI (dBμV/m) | (PEAK) Margin (dB) | (QP) Margin (dB) | Limit (dBμV/m) | Transducer (dB) | Cable (dB) | Ttbl Aql (deg) | Twr Ht (cm) |
|------------|-----|---------------------|-------------------|--------------------|------------------|----------------|-----------------|------------|----------------|-------------|
| 161.90 | H | 31.31 | 25.98 | -12.19 | -17.52 | 43.50 | 22.52 | 1.07 | 275.00 | 111.52 |
| 162.80 | H | 31.39 | 26.03 | -12.11 | -17.47 | 43.50 | 22.57 | 1.07 | 157.50 | 174.92 |
| 382.50 | H | 33.33 | 27.92 | -12.67 | -18.08 | 46.00 | 22.83 | 1.67 | 359.75 | 302.56 |
| 385.80 | H | 33.58 | 28.05 | -12.42 | -17.95 | 46.00 | 22.97 | 1.68 | 178.00 | 366.20 |
| 390.90 | H | 35.23 | 28.48 | -10.77 | -17.52 | 46.00 | 23.39 | 1.69 | 147.75 | 382.02 |
| 485.80 | H | 34.25 | 28.68 | -11.75 | -17.32 | 46.00 | 23.62 | 1.82 | 77.75 | 397.73 |





FUNDAMENTAL AND HARMONICS

DATA SHEETS

**FCC 15.231**

Ecolink Intelligent Technology, Inc.
Motion Detector
Model: WST-740

Date: 05/04/2022
Lab: D
Tested By: Kyle Fujimoto

Harmonics**Transmit Mode - X-Axis**

| Freq. (MHz) | Level (dBuV/m) | Pol (v/h) | Limit | Margin | Peak / QP / Avg | Table Angle (deg) | Ant. Height (cm) | Comments |
|-------------|----------------|-----------|-------|--------|-----------------|-------------------|------------------|----------|
| 867.84 | 49.74 | V | 80.82 | -31.08 | Peak | 172.50 | 191.10 | |
| 867.84 | 29.90 | V | 60.82 | -30.92 | Avg | 172.50 | 191.10 | |
| 1301.76 | 52.23 | V | 73.97 | -21.74 | Peak | 134.75 | 222.92 | |
| 1301.76 | 32.39 | V | 53.97 | -21.58 | Avg | 134.75 | 222.92 | |
| 1735.68 | 60.91 | V | 80.82 | -19.91 | Peak | 134.50 | 207.10 | |
| 1735.68 | 41.07 | V | 60.82 | -19.75 | Avg | 134.50 | 207.10 | |
| 2169.60 | 60.84 | V | 80.82 | -19.98 | Peak | 103.50 | 143.82 | |
| 2169.60 | 41.00 | V | 60.82 | -19.82 | Avg | 103.50 | 143.82 | |
| 2603.52 | 57.97 | V | 80.82 | -22.85 | Peak | 290.25 | 143.22 | |
| 2603.52 | 38.13 | V | 60.82 | -22.69 | Avg | 290.25 | 143.22 | |
| 3037.44 | 59.45 | V | 80.82 | -21.37 | Peak | 296.25 | 143.70 | |
| 3037.44 | 39.61 | V | 60.82 | -21.21 | Avg | 296.25 | 143.70 | |
| 3471.36 | 61.46 | V | 80.82 | -19.36 | Peak | 148.50 | 158.86 | |
| 3471.36 | 41.62 | V | 60.82 | -19.20 | Avg | 148.50 | 158.86 | |
| 3905.28 | 47.25 | V | 73.97 | -26.72 | Peak | 228.25 | 126.68 | |
| 3905.28 | 27.41 | V | 53.97 | -26.56 | Avg | 228.25 | 126.68 | |
| 4339.20 | 49.20 | V | 73.97 | -24.77 | Peak | 74.50 | 190.86 | |
| 4339.20 | 29.36 | V | 53.97 | -24.61 | Avg | 74.50 | 190.86 | |

**FCC 15.231**

Ecolink Intelligent Technology, Inc.
 Motion Detector
 Model: WST-740

Date: 05/04/2022

Lab: D

Tested By: Kyle Fujimoto

Harmonics**Transmit Mode - Y-Axis**

| Freq. (MHz) | Level (dBuV/m) | Pol (v/h) | Limit | Margin | Peak / QP / Avg | Table Angle (deg) | Ant. Height (cm) | Comments |
|-------------|----------------|-----------|-------|--------|-----------------|-------------------|------------------|----------|
| 867.84 | 57.13 | V | 80.82 | -23.70 | Peak | 290.50 | 130.80 | |
| 867.84 | 37.29 | V | 60.82 | -23.54 | Avg | 290.50 | 130.80 | |
| 1301.76 | 52.09 | V | 73.97 | -21.88 | Peak | 195.50 | 175.16 | |
| 1301.76 | 32.25 | V | 53.97 | -21.72 | Avg | 195.50 | 175.16 | |
| 1735.68 | 60.23 | V | 80.82 | -20.59 | Peak | 65.75 | 127.52 | |
| 1735.68 | 40.39 | V | 60.82 | -20.43 | Avg | 65.75 | 127.52 | |
| 2169.60 | 65.98 | V | 80.82 | -14.84 | Peak | 115.00 | 127.46 | |
| 2169.60 | 46.14 | V | 60.82 | -14.68 | Avg | 115.00 | 127.46 | |
| 2603.52 | 59.18 | V | 80.82 | -21.64 | Peak | 253.50 | 127.34 | |
| 2603.52 | 39.34 | V | 60.82 | -21.48 | Avg | 253.50 | 127.34 | |
| 3037.44 | 59.67 | V | 80.82 | -21.15 | Peak | 238.00 | 223.10 | |
| 3037.44 | 39.83 | V | 60.82 | -20.99 | Avg | 238.00 | 223.10 | |
| 3471.36 | 61.63 | V | 80.82 | -19.19 | Peak | 120.50 | 143.04 | |
| 3471.36 | 41.79 | V | 60.82 | -19.03 | Avg | 120.50 | 143.04 | |
| 3905.28 | 52.14 | V | 73.97 | -21.83 | Peak | 75.00 | 127.40 | |
| 3905.28 | 32.30 | V | 53.97 | -21.67 | Avg | 75.00 | 127.40 | |
| 4339.20 | 51.90 | V | 73.97 | -22.07 | Peak | 95.75 | 143.28 | |
| 4339.20 | 32.06 | V | 53.97 | -21.91 | Avg | 95.75 | 143.28 | |

**FCC 15.231**

Ecolink Intelligent Technology, Inc.
 Motion Detector
 Model: WST-740

Date: 05/04/2022
 Lab: D
 Tested By: Kyle Fujimoto

Harmonics**Transmit Mode - Z-Axis**

| Freq. (MHz) | Level (dBuV/m) | Pol (v/h) | Limit | Margin | Peak / QP / Avg | Table Angle (deg) | Ant. Height (cm) | Comments |
|-------------|----------------|-----------|-------|--------|-----------------|-------------------|------------------|----------|
| 867.84 | 51.65 | V | 80.82 | -29.17 | Peak | 178.50 | 182.44 | |
| 867.84 | 31.81 | V | 60.82 | -29.01 | Avg | 178.50 | 182.44 | |
| 1301.76 | 67.67 | V | 73.97 | -6.30 | Peak | 201.75 | 127.34 | |
| 1301.76 | 47.83 | V | 53.97 | -6.14 | Avg | 201.75 | 127.34 | |
| 1735.68 | 67.67 | V | 80.82 | -13.15 | Peak | 201.75 | 127.34 | |
| 1735.68 | 47.83 | V | 60.82 | -12.99 | Avg | 201.75 | 127.34 | |
| 2169.60 | 68.19 | V | 80.82 | -12.63 | Peak | 114.00 | 127.40 | |
| 2169.60 | 48.35 | V | 60.82 | -12.47 | Avg | 114.00 | 127.40 | |
| 2603.52 | 61.32 | V | 80.82 | -19.50 | Peak | 229.75 | 127.46 | |
| 2603.52 | 41.48 | V | 60.82 | -19.34 | Avg | 229.75 | 127.46 | |
| 3037.44 | 67.57 | V | 80.82 | -13.25 | Peak | 332.25 | 127.76 | |
| 3037.44 | 47.73 | V | 60.82 | -13.09 | Avg | 332.25 | 127.76 | |
| 3471.36 | 67.97 | V | 80.82 | -12.85 | Peak | 163.50 | 111.34 | |
| 3471.36 | 48.13 | V | 60.82 | -12.69 | Avg | 163.50 | 111.34 | |
| 3905.28 | 55.00 | V | 73.97 | -18.97 | Peak | 299.75 | 127.34 | |
| 3905.28 | 35.16 | V | 53.97 | -18.81 | Avg | 299.75 | 127.34 | |
| 4339.20 | 51.77 | V | 73.97 | -22.20 | Peak | 310.75 | 206.92 | |
| 4339.20 | 31.93 | V | 53.97 | -22.04 | Avg | 310.75 | 206.92 | |

**FCC 15.231**

Ecolink Intelligent Technology, Inc.
 Motion Detector
 Model: WST-740

Date: 05/04/2022
 Lab: D
 Tested By: Kyle Fujimoto

Harmonics**Transmit Mode - X-Axis**

| Freq. (MHz) | Level (dBuV/m) | Pol (v/h) | Limit | Margin | Peak / QP / Avg | Table Angle (deg) | Ant. Height (cm) | Comments |
|-------------|----------------|-----------|-------|--------|-----------------|-------------------|------------------|----------|
| 867.84 | 59.09 | H | 80.82 | -21.73 | Peak | 262.75 | 101.85 | |
| 867.84 | 39.25 | H | 60.82 | -21.57 | Avg | 262.75 | 101.85 | |
| 1301.76 | 58.01 | H | 73.97 | -15.96 | Peak | 181.00 | 161.13 | |
| 1301.76 | 38.17 | H | 53.97 | -15.80 | Avg | 181.00 | 161.13 | |
| 1735.68 | 69.65 | H | 80.82 | -11.17 | Peak | 175.75 | 111.22 | |
| 1735.68 | 49.81 | H | 60.82 | -11.01 | Avg | 175.75 | 111.22 | |
| 2169.60 | 66.59 | H | 80.82 | -14.23 | Peak | 36.00 | 143.34 | |
| 2169.60 | 46.75 | H | 60.82 | -14.07 | Avg | 36.00 | 143.34 | |
| 2603.52 | 56.43 | H | 80.82 | -24.39 | Peak | 219.75 | 143.16 | |
| 2603.52 | 36.59 | H | 60.82 | -24.23 | Avg | 219.75 | 143.16 | |
| 3037.44 | 66.45 | H | 80.82 | -14.37 | Peak | 342.50 | 143.34 | |
| 3037.44 | 46.61 | H | 60.82 | -14.21 | Avg | 342.50 | 143.34 | |
| 3471.36 | 68.63 | H | 80.82 | -12.19 | Peak | 151.25 | 111.46 | |
| 3471.36 | 48.79 | H | 60.82 | -12.03 | Avg | 151.25 | 111.46 | |
| 3905.28 | 49.90 | H | 73.97 | -24.07 | Peak | 79.50 | 175.28 | |
| 3905.28 | 30.06 | H | 53.97 | -23.91 | Avg | 79.50 | 175.28 | |
| 4339.20 | 47.47 | H | 73.97 | -26.50 | Peak | 83.25 | 158.86 | |
| 4339.20 | 27.63 | H | 53.97 | -26.34 | Avg | 83.25 | 158.86 | |

**FCC 15.231**

Ecolink Intelligent Technology, Inc.
Motion Detector
Model: WST-740

Date: 05/04/2022

Lab: D

Tested By: Kyle Fujimoto

Harmonics**Transmit Mode - Y-Axis**

| Freq. (MHz) | Level (dBuV/m) | Pol (v/h) | Limit | Margin | Peak / QP / Avg | Table Angle (deg) | Ant. Height (cm) | Comments |
|-------------|----------------|-----------|-------|--------|-----------------|-------------------|------------------|----------|
| 867.84 | 48.83 | H | 80.82 | -32.00 | Peak | 10.00 | 158.32 | |
| 867.84 | 28.99 | H | 60.82 | -31.84 | Avg | 10.00 | 158.32 | |
| 1301.76 | 55.23 | H | 73.97 | -18.74 | Peak | 348.25 | 144.11 | |
| 1301.76 | 35.39 | H | 53.97 | -18.58 | Avg | 348.25 | 144.11 | |
| 1735.68 | 56.22 | H | 80.82 | -24.60 | Peak | 30.00 | 177.61 | |
| 1735.68 | 36.38 | H | 60.82 | -24.44 | Avg | 30.00 | 177.61 | |
| 2169.60 | 64.48 | H | 80.82 | -16.34 | Peak | 0.00 | 175.40 | |
| 2169.60 | 44.64 | H | 60.82 | -16.18 | Avg | 0.00 | 175.40 | |
| 2603.52 | 62.58 | H | 80.82 | -18.24 | Peak | 185.50 | 111.40 | |
| 2603.52 | 42.74 | H | 60.82 | -18.08 | Avg | 185.50 | 111.40 | |
| 3037.44 | 55.34 | H | 80.82 | -25.48 | Peak | 306.00 | 111.46 | |
| 3037.44 | 35.50 | H | 60.82 | -25.32 | Avg | 306.00 | 111.46 | |
| 3471.36 | 66.24 | H | 80.82 | -14.58 | Peak | 192.50 | 111.28 | |
| 3471.36 | 46.40 | H | 60.82 | -14.42 | Avg | 192.50 | 111.28 | |
| 3905.28 | 53.31 | H | 73.97 | -20.66 | Peak | 109.75 | 143.28 | |
| 3905.28 | 33.47 | H | 53.97 | -20.50 | Avg | 109.75 | 143.28 | |
| 4339.20 | 54.12 | H | 73.97 | -19.85 | Peak | 107.00 | 159.22 | |
| 4339.20 | 34.28 | H | 53.97 | -19.69 | Avg | 107.00 | 159.22 | |

**FCC 15.231**

Ecolink Intelligent Technology, Inc.
 Motion Detector
 Model: WST-740

Date: 05/04/2022
 Lab: D
 Tested By: Kyle Fujimoto


Harmonics**Transmit Mode - Z-Axis**

| Freq. (MHz) | Level (dBuV/m) | Pol (v/h) | Limit | Margin | Peak / QP / Avg | Table Angle (deg) | Ant. Height (cm) | Comments |
|-------------|----------------|-----------|-------|--------|-----------------|-------------------|------------------|----------|
| 867.84 | 57.78 | H | 80.82 | -23.04 | Peak | 70.75 | 165.79 | |
| 867.84 | 37.94 | H | 60.82 | -22.88 | Avg | 70.75 | 165.79 | |
| 1301.76 | 48.79 | H | 73.97 | -25.18 | Peak | 118.50 | 143.34 | |
| 1301.76 | 28.95 | H | 53.97 | -25.02 | Avg | 118.50 | 143.34 | |
| 1735.68 | 63.83 | H | 80.82 | -16.99 | Peak | 118.75 | 143.22 | |
| 1735.68 | 43.99 | H | 60.82 | -16.83 | Avg | 118.75 | 143.22 | |
| 2169.60 | 70.85 | H | 80.82 | -9.97 | Peak | 275.50 | 111.46 | |
| 2169.60 | 51.01 | H | 60.82 | -9.81 | Avg | 275.50 | 111.46 | |
| 2603.52 | 59.36 | H | 80.82 | -21.46 | Peak | 111.52 | 76.50 | |
| 2603.52 | 39.52 | H | 60.82 | -21.30 | Avg | 111.52 | 76.50 | |
| 3037.44 | 63.80 | H | 80.82 | -17.02 | Peak | 66.75 | 111.28 | |
| 3037.44 | 43.96 | H | 60.82 | -16.86 | Avg | 66.75 | 111.28 | |
| 3471.36 | 67.52 | H | 80.82 | -13.30 | Peak | 207.00 | 110.68 | |
| 3471.36 | 47.68 | H | 60.82 | -13.14 | Avg | 207.00 | 110.68 | |
| 3905.28 | 47.38 | H | 73.97 | -26.59 | Peak | 181.00 | 174.08 | |
| 3905.28 | 27.54 | H | 53.97 | -26.43 | Avg | 181.00 | 174.08 | |
| 4339.20 | 50.31 | H | 73.97 | -23.66 | Peak | 182.25 | 111.28 | |
| 4339.20 | 30.47 | H | 53.97 | -23.50 | Avg | 182.25 | 111.28 | |



-20 dB BANDWIDTH PLOT


DATA SHEET



-20 dB Bandwidth Plot



***TRANSMISSION TIME
DATA SHEET***




The total on time of the transmission is 1.953 seconds.

Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Newbury Park Division
1050 Lawrence Drive
Newbury Park, CA 91320
(805) 480-4044

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400



Plot showing the transmission time is less than 5 seconds

Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Newbury Park Division
1050 Lawrence Drive
Newbury Park, CA 91320
(805) 480-4044

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400



99% BANDWIDTH

DATA SHEET




99% Bandwidth Plot




DUTY CYCLE

DATA SHEETS



The pulse train only repeats at an interval that is greater than 100 ms




Plot showing the Pulse Train – 27 Small Pulses and 1 Large Pulse



**COMPATIBLE
ELECTRONICS**

*Motion Detector
Model: WST-740*




Time of Small Pulse = 275 us

Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Newbury Park Division
1050 Lawrence Drive
Newbury Park, CA 91320
(805) 480-4044

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400




Time of Large Pulse = 2.750 ms

Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Newbury Park Division
1050 Lawrence Drive
Newbury Park, CA 91320
(805) 480-4044

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400



Number of Small Pulses = 27 = (27*275 us) = 7425 us
Number of Large Pulses = 1 = (1*2750 us) = 2750 us

Total On Time = 10175 us = 10.175 ms

Duty Cycle = 10.175 ms / 100 ms = 10.175%

The peak to average ratio is -19.84 dB