

RF EXPOSURE REPORT

FOR

| | | |
|-----------------------------|---|---|
| Applicant | : | Fender Musical Instruments |
| Address | : | 17600 North Perimeter Drive, Suite 100, Scottsdale, AZ 85255 USA |
| Equipment under Test | : | Guitar Headphone amplifier (w/ QCC 3024) |
| Model No. | : | Mustang Micro |
| HVIN | : | TYPE PR:5833 |
| Trade Mark | : | <i>Fender</i> |
| FCC ID | : | XQW-MUM2PR5833 |
| Manufacturer | : | Fender Musical Instruments |
| Address | : | 17600 North Perimeter Drive, Suite 100, Scottsdale, AZ 85255 USA |

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,
Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

| | | |
|------|-------------------------------------|---|
| | Test report declares..... | 3 |
| 1. | General Information | 5 |
| 1.1. | Description of equipment | 5 |
| 1.2. | Assess laboratory..... | 5 |
| 2. | RF Exposure evaluation for FCC..... | 6 |

Test Report Declare

| | | |
|-----------------------------|---|---|
| Applicant | : | Fender Musical Instruments |
| Address | : | 17600 North Perimeter Drive, Suite 100, Scottsdale, AZ 85255 USA |
| Equipment under Test | : | Guitar Headphone amplifier (w/ QCC 3024) |
| Model No. | : | Mustang Micro |
| HVIN | : | TYPE PR:5833 |
| Trade mark | : | <i>Fender</i> |
| Manufacturer | : | Fender Musical Instruments |
| Address | : | 17600 North Perimeter Drive, Suite 100, Scottsdale, AZ 85255 USA |

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

| | | | |
|-------------------------|--------------------|----------------------|-------------------------------|
| Report No: | DDT-R21121004-2E08 | | |
| Date of Receipt: | Dec. 13, 2021 | Date of Test: | Dec. 13, 2021 ~ Jan. 27, 2022 |

Prepared By:

Sam Li

Sam Li/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

| Rev. | Revisions | Issue Date | Revised By |
|------|---------------|---------------|------------|
| --- | Initial issue | Jan. 28, 2022 | |
| | | | |

1. General Information

1.1. Description of equipment

| | |
|--------------------------|--|
| EUT* Name | : Guitar Headphone amplifier (w/ QCC 3024) |
| Model Number | : Mustang Micro |
| HVIN | : TYPE PR:5833 |
| EUT function description | : Please reference user manual of this device |
| Power Supply | : Powered by DC 5V external adapter or 3.7V built-in lithium battery |
| Radio Specification | : Bluetooth V5.1 |
| Operation Frequency | : 2402 MHz - 2480 MHz |
| Modulation | : GFSK, $\pi/4$ -DQPSK, 8DPSK |
| Data Rate | : 1 Mbps, 2 Mbps, 3 Mbps |
| Antenna Type | : Ceramic antenna, maximum PK gain: -3.03 dBi |
| Sample Type | : Series production |
| Serial Number | : N/A |

Note: EUT is the abbreviation of equipment under test.

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Addr.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,
Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, G-20118

2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

BT Manufacturing Tolerance

| GFSK (Peak) | | | |
|----------------------|-----------|------------|------------|
| Channel | Channel 0 | Channel 39 | Channel 78 |
| Target (dBm) | 2 | 3 | 3 |
| Tolerance \pm (dB) | 1 | 1 | 1 |
| $\pi/4$ DQPSK (Peak) | | | |
| Channel | Channel 0 | Channel 39 | Channel 78 |
| Target (dBm) | 4 | 5 | 5 |
| Tolerance \pm (dB) | 1 | 1 | 1 |
| 8DPSK (Peak) | | | |
| Channel | Channel 0 | Channel 39 | Channel 78 |
| Target (dBm) | 4 | 5 | 5 |
| Tolerance \pm (dB) | 1 | 1 | 1 |

BLE Manufacturing Tolerance

| BLE_1M (Peak) | | | |
|----------------------|-----------|------------|------------|
| Channel | Channel 0 | Channel 19 | Channel 39 |
| Target (dBm) | 0 | 0 | -3 |
| Tolerance \pm (dB) | 1 | 1 | 1 |
| BLE_2M (Peak) | | | |
| Channel | Channel 0 | Channel 19 | Channel 39 |
| Target (dBm) | 0 | 0 | -3 |
| Tolerance \pm (dB) | 1 | 1 | 1 |

Estimation Result

Worse case is as below: [2480 MHz, 6 dBm, 3.98 mW] output power]

$(3.98/5) \cdot [\sqrt{2.480(\text{GHz})}] = 1.25 < 3.0$ for 1-g SAR

Then SAR evaluation is not required

END OF REPORT