

# RF EXPOSURE REPORT

## FOR

<b>Applicant</b>	:	Fender Musical Instruments
<b>Address</b>	:	17600 N. Perimeter Dr., Suite 100, Scottsdale, AZ 85255 USA
<b>Equipment under Test</b>	:	Portable Audio Amplifier System (W/BK32881)
<b>Model No.</b>	:	PASSPORT CONFERENCE SERIES 2
<b>Type No.</b>	:	PR 844
<b>Trade Mark</b>	:	FENDER
<b>FCC ID</b>	:	XQWPC2PR844BK
<b>IC</b>	:	8690A-PC2PR844BK
<b>Manufacturer</b>	:	Fender Musical Instruments
<b>Address</b>	:	17600 N. Perimeter Dr., Suite 100, Scottsdale, AZ 85255 USA

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan  
City, Guangdong Province, China, 523808

**Tel:** +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

# REPORT

## Table of Contents

	Test report declares.....	3
1.	General information.....	5
1.1.	Description of Equipment.....	5
1.2.	Assess laboratory.....	5
2.	RF Exposure evaluation.....	6

## Test Report Declare

<b>Applicant</b>	:	Fender Musical Instruments
<b>Address</b>	:	17600 N. Perimeter Dr., Suite 100, Scottsdale, AZ 85255 USA
<b>Equipment under Test</b>	:	Portable Audio Amplifier System (W/BK32881)
<b>Model No.</b>	:	PASSPORT CONFERENCE SERIES 2
<b>Type No.</b>	:	PR 844
<b>Trade mark</b>	:	FENDER
<b>Manufacturer</b>	:	Fender Musical Instruments
<b>Address</b>	:	17600 N. Perimeter Dr., Suite 100, Scottsdale, AZ 85255 USA

**Standard Used:** KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

**After evaluation, our opinion is that the equipment In Accordance with above standard.**

<b>Report No.:</b>	DDT-R22102518-2E03		
<b>Date of Receipt:</b>	Nov. 03, 2022	<b>Date of Test:</b>	Nov. 03, 2022 ~ Dec. 10, 2022

**Prepared By:**

*Jacky Huang*

**Jacky Huang/Engineer**

**Approved By:**



**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

### Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Dec. 12, 2022	

## 1. General information

### 1.1. Description of Equipment

EUT* Name	: Portable Audio Amplifier System (W/BK32881)
Model Number	: PASSPORT CONFERENCE SERIES 2
EUT function description	: Please reference user manual of this device
Power supply	: AC 100-120V, 50/60Hz
Radio Specification	: Bluetooth V5.2
Operation frequency	: 2402MHz-2480MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK
Data Rate	: 1 Mbps, 2 Mbps, 3 Mbps
Antenna Type	: FPC antenna, maximum PK gain: -4.49 dBi
Sample Number	: S22102518-06

### 1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,  
Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com).

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

## 2. RF Exposure evaluation

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

### Manufacturing Tolerance

#### BT

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-13.5	-13.5	-13.5
Tolerance $\pm$ (dB)	1.5	1.5	1.5
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-13.5	-13.5	-13.5
Tolerance $\pm$ (dB)	1.5	1.5	1.5
8DPSK (Peak)			
Channel	Channel	Channel	Channel
Target (dBm)	-13.5	-13.5	-13.5
Tolerance $\pm$ (dB)	1.5	1.5	1.5

#### BLE

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-13.5	-13.5	-13.5
Tolerance $\pm$ (dB)	1.5	1.5	1.5

### Evaluation Result

Worse case is as below: [2480 MHz, -12 dBm, (0.063mW) output power]

$(0.063/5) \cdot [\sqrt{2.480(\text{GHz})}] = 0.020 < 3.0$  for 1-g SAR

Then SAR evaluation is not required.

**END OF REPORT**