




Fender®

PASSPORT® VENUE SERIES 2

100-120V~ 50/60Hz 220-240V~ 50/60Hz



FUSE
T10A H
250V



**INPUT POWER
750W**

CAUTION:
TO REDUCE THE RISK OF
FIRE, REPLACE FUSE WITH
SAME TYPE AND RATING

ATTENTION:
UTILISER UN FUSIBLE DE
RECHANGE DE MEME
TYPE ET CALIBRE

Laite on liitettävä suojakoskettimilla varustettuun pistorasiaan
Apparatets stikprop skal tilsluttes en stikkontakt
med jord, som giver forbindelse til stikproppens jord.
Apparatet må tilkoples jordet stikkontakt
Apparaten skall anslutas till jordat uttag


WARNING: MAINTAIN 6" CLEARANCE FOR VENTILATION.

TYPE: PR 846
SERIAL NUMBER



Use only with supplied
4 ohm speakers

SPEAKER OUTPUTS



LEFT

600W total
4Ω MIN 300W



RIGHT

THIS DEVICE COMPLIES WITH
PART 15 OF FCC RULES.
OPERATION IS SUBJECT TO THE
FOLLOWING TWO CONDITIONS:
(1) THIS DEVICE MAY NOT CAUSE
HARMFUL INTERFERENCE, AND
(2) THIS DEVICE MUST ACCEPT
ANY INTERFERENCE RECEIVED,
INCLUDING INTERFERENCE THAT
MAY CAUSE UNDESIRABLE OPERATION.

WARNING:
FENDER AMPLIFIER SYSTEMS
ARE CAPABLE OF PRODUCING
VERY HIGH SOUND PRESSURE
LEVELS WHICH MAY CAUSE
TEMPORARY OR PERMANENT
HEARING DAMAGE. USE CARE
WHEN SETTING AND ADJUSTING
VOLUME LEVELS DURING USE.



CAUTION:
CHASSIS SURFACE HOT
WARNING:
TO REDUCE THE RISK OF FIRE
OR ELECTRIC SHOCK, DO NOT
EXPOSE THIS EQUIPMENT TO
RAIN OR MOISTURE

ATTENTION:
RISQUE DE CHOC ELECTRIQUE
- NE PAS OUVRIIR

ATTENTION:
SUPERFICIE DE CHASSIS CHAUDE



PRODUCED BY:
**FENDER MUSICAL INSTRUMENTS CORP.,
CORONA, CA, U.S.A.
MADE IN CHINA
DESIGNED AND ENGINEERED IN U.S.A.**

**UK
CA**

Homologación IFT:
RCPFEPA20-2429-A2

Model:
PASSPORT® VENUE SERIES 2
FCC ID: XQWPV2PR846BK
IC: 8690A-PV2PR846BK

Venue 2 rear panel
P/N: 1407-1619+3
Scale: 100%
Color:

TEXT AND GRAPHICS TO BE: WHITE.
BACKGROUND TO BE: PANTONE PROCESS BLACK.

V01-20221208