

RF EXPOSURE REPORT

FOR

Applicant	:	Fender Musical Instruments
Address	:	17600 N. Perimeter Dr., Suite 100, Scottsdale, AZ 85255 USA
Equipment under Test	:	Portable Audio Amplifier System (W/BK32881)
Model No.	:	PASSPORT VENUE SERIES 2
Type No.	:	PR 846
Trade Mark	:	FENDER
FCC ID	:	XQWPV2PR846BK
IC	:	8690A-PV2PR846BK
Manufacturer	:	Fender Musical Instruments
Address	:	17600 N. Perimeter Dr., Suite 100, Scottsdale, AZ 85255 USA

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan
City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

Test report declares.....	3
1. General information.....	5
1.1. Description of Equipment.....	5
1.2. Assess laboratory.....	5
2. RF Exposure evaluation.....	6

Test Report Declare

Applicant	:	Fender Musical Instruments
Address	:	17600 N. Perimeter Dr., Suite 100, Scottsdale, AZ 85255 USA
Equipment under Test	:	Portable Audio Amplifier System (W/BK32881)
Model No.	:	PASSPORT VENUE SERIES 2
Type No.	:	PR 846
Trade mark	:	FENDER
Manufacturer	:	Fender Musical Instruments
Address	:	17600 N. Perimeter Dr., Suite 100, Scottsdale, AZ 85255 USA

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No.:	DDT-R22102518-6E03		
Date of Receipt:	Nov. 03, 2022	Date of Test:	Nov. 03, 2022 ~ Dec. 07, 2022

Prepared By:

Jacky Huang
Jacky Huang/Engineer

Approved By:


Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Dec. 09, 2022	

1. General information

1.1. Description of Equipment

EUT* Name	: Portable Audio Amplifier System (W/BK32881)
Model Number	: PASSPORT VENUE SERIES 2
EUT function description	: Please reference user manual of this device
Power supply	: AC 100-120V, 50/60Hz
Radio Specification	: Bluetooth V5.2
Operation frequency	: 2402MHz-2480MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK
Data Rate	: 1 Mbps, 2 Mbps, 3 Mbps
Antenna Type	: PCB antenna, maximum PK gain: -1.07 dBi
Sample Number	: S22102518-10

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,
Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2. RF Exposure evaluation

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Manufacturing Tolerance

BT

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-1.0	-1.0	-1.0
Tolerance \pm (dB)	1.5	1.5	1.5
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-1.0	-1.0	-1.0
Tolerance \pm (dB)	1.5	1.5	1.5
8DPSK (Peak)			
Channel	Channel	Channel	Channel
Target (dBm)	-1.0	-1.0	-1.0
Tolerance \pm (dB)	1.5	1.5	1.5

BLE

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-1.0	-1.0	-1.0
Tolerance \pm (dB)	1.5	1.5	1.5

Evaluation Result

Worse case is as below: [2480 MHz, 0.5 dBm, (1.12mW) output power]

$(1.12/5) \cdot [\sqrt{2.480(\text{GHz})}] = 0.35 < 3.0$ for 1-g SAR

Then SAR evaluation is not required.

END OF REPORT