

Compliance Testing

Previously Flom Test Lab

RF, EMC & Safety Testing Experts Since 1963

toll-free: (866)311-3268 fax: (480)926-3598 http://www.ComplanceTesting.com

info@ComplianceTesting.com

Date: December 24, 2009

Applicant: Fender Musical Instruments Corp.

8860 E. Chaparral Road, Suite 100

Scottsdale, AZ 85250-2618

Attention of: Larry Clauss, Sr. Project Engineer - Compliance

(480) 367-5203; FAX (480) 948-9155

Iclauss@fenderusa.com

Equipment: UHF WRLS HH FCC ID: XQWUHFHHPR601

FCC Rules: Radio Frequency Radiation Exposure Limits 47 CFR 1.1307

RF Exposure Statement

1. Standard Applicable

According to 1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a portable device.

2. Measurement Result:

This is a portable device and the max peak conducted output power is 15.0 dBm (31.6 mW) with a 100% duty cycle.

Using the formula $60/f_{GHz} = mW$ to determine the SAR threshold a limit of 96.5 mW was determined.

Calculation 60 / 0.62185 = 96.5 mW

A SAR measurement is not necessary.