



Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

TEST REPORT

FCC PART 15 SUBPART E 15.407

Report Reference No.....: GTS20211120011-1-2

FCC ID.....: XR3-MAXLUMI2

Compiled by
(position+printed name+signature)..: File administrators Jimmy Wang

Supervised by
(position+printed name+signature)..: Test Engineer Aaron Tan



Approved by
(position+printed name+signature)..: Manager Jason Hu

Date of issue.....: Nov. 20, 2021

Representative Laboratory Name .: Shenzhen Global Test Service Co.,Ltd.

Address.....: No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong, China

Applicant's name.....: ONYX INTERNATIONAL INC.

Address: Room 301-6, 10 Honglou Street, Liwan District, Guangzhou City, Guangdong Province, China

Test specification

Standard.....: **FCC Part 15 Subpart E 15.407**

TRF Originator.....: Shenzhen Global Test Service Co.,Ltd.

Master TRF.....: Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description E Ink Tablet, Smart E Ink Tablet, ePaper Tablet, E-bag Tablet, E-book Tablet, E-reader Tablet, Eyes protection E Ink Tablet, E-paper Tablet, Color E Ink Tablet, Color ePaper Tablet

Trade Mark.....: BOOX

Manufacturer.....: ONYX INTERNATIONAL INC.

Model/Type reference.....: Max lumi2

Listed Models.....: Max Lumi2 Lite, Max Lumi2 Pro, Max Lumi2 Plus, Max Lumi2 Color

Ratings.....: DC 3.85V from battery; Charging input: 5V---3A

Modulation.....: OFDM

Hardware version.....: BOOX_M4_MAX5_V03

Software version.....: V1.0

Frequency.....: From 5180MHz-5240MHz, 5745MHz-5825MHz

Result.....: **PASS**

TEST REPORT

| | | |
|--------------------------|---------------------------|---------------|
| Test Report No. : | GTS20211120011-1-2 | Nov. 20, 2021 |
| | | Date of issue |

Equipment under Test : E Ink Tablet, Smart E Ink Tablet, ePaper Tablet, E-bag Tablet, E-book Tablet, E-reader Tablet, Eyes protection E Ink Tablet, E-paper Tablet, Color E Ink Tablet, Color ePaper Tablet

Model /Type : Max lumi2

Listed Models : Max Lumi2 Lite, Max Lumi2 Pro, Max Lumi2 Plus, Max Lumi2 Color

Applicant : **ONYX INTERNATIONAL INC.**

Address : Room 301-6, 10 Honglou Street, Liwan District, Guangzhou City, Guangdong Province, China

Manufacturer : **ONYX INTERNATIONAL INC.**

Address : Building 4, 202 Shiyu Road, Dongchong Town, Nansha District, Guangzhou City, Guangdong Province, China

| | |
|---------------------|-------------|
| Test Result: | PASS |
|---------------------|-------------|

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

| | | |
|-----------------|---|------------------|
| <u>1</u> | <u>TEST STANDARDS</u> | <u>4</u> |
| <u>2</u> | <u>SUMMARY</u> | <u>5</u> |
| 2.1 | General Remarks | 5 |
| 2.2 | Product Description | 5 |
| 2.3 | Test Sample | 5 |
| 2.4 | Equipment Under Test | 5 |
| 2.5 | Short description of the Equipment under Test (EUT) | 5 |
| 2.6 | EUT operation mode | 6 |
| 2.7 | Block Diagram of Test Setup | 6 |
| 2.8 | Special Accessories | 6 |
| 2.9 | Related Submittal(s) / Grant (s) | 6 |
| 2.10 | Modifications | 6 |
| <u>3</u> | <u>TEST ENVIRONMENT</u> | <u>7</u> |
| 3.1 | Address of the test laboratory | 7 |
| 3.2 | Test Facility | 7 |
| 3.3 | Environmental conditions | 7 |
| 3.4 | Test Description | 8 |
| 3.5 | Statement of the measurement uncertainty | 8 |
| 3.6 | Equipments Used during the Test | 9 |
| <u>4</u> | <u>TEST CONDITIONS AND RESULTS.....</u> | <u>10</u> |
| 4.1 | AC Power Conducted Emission | 10 |
| 4.2 | Radiated Emissions | 13 |
| 4.3 | Maximum Conducted Average Output Power | 20 |
| 4.4 | Power Spectral Density | 22 |
| 4.5 | Emission Bandwidth (26dBm Bandwidth) | 29 |
| 4.6 | Minimum Emission Bandwidth (6dBm Bandwidth) | 33 |
| 4.7 | Frequency Stability | 37 |
| <u>5</u> | <u>TEST SETUP PHOTOS OF THE EUT</u> | <u>39</u> |
| <u>6</u> | <u>PHOTOS OF THE EUT</u> | <u>40</u> |

1 TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15 Subpart E](#)—Unlicensed National Information Infrastructure Devices

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB789033 D02](#): General UNII Test Procedures New Rules v01r02

2 SUMMARY

2.1 General Remarks

| | | |
|--------------------------------|---|---------------|
| Date of receipt of test sample | : | Sep. 25, 2021 |
| | | |
| Testing commenced on | : | Sep. 26, 2021 |
| | | |
| Testing concluded on | : | Oct. 25, 2021 |

2.2 Product Description

| | | | | |
|----------------------|--|------------------------------------|--------------------|---------------|
| Product Description: | E Ink Tablet, Smart E Ink Tablet, ePaper Tablet, E-bag Tablet, E-book Tablet, E-reader Tablet, Eyes protection E Ink Tablet, E-paper Tablet, Color E Ink Tablet, Color ePaper Tablet | | | |
| Model: | Max lumi2 | | | |
| Power supply: | DC 3.85V from battery | | | |
| Sample ID: | GTS20211120011-1-1#/ GTS20211120011-1-2# | | | |
| WIFI | | | | |
| | 20MHz system | 40MHz system | 80MHz system | 160MHz system |
| Supported type: | 802.11a 802.11n 802.11ac | 802.11n 802.11ac | 802.11ac | N/A |
| Operation frequency: | 5180MHz-5240MHz 5745MHz-5825MHz | 5190MHz-5230MHz 5755MHz-5795MHz | 5210MHz 5775MHz | N/A |
| Modulation: | OFDM | OFDM | OFDM | N/A |
| Channel number: | 9 | 4 | 2 | N/A |
| Channel separation: | 20MHz | 40MHz | 80MHz | N/A |
| Antenna type: | FPC Antenna | | | |
| Antenna gain: | 1.00dBi | | | |

2.3 Test Sample

The application provides 2 samples to meet requirement.

| | |
|---------------------|---------------------------------------|
| Sample Number | Description |
| GTS20211120011-1-1# | Engineer sample – continuous transmit |
| GTS20211120011-1-2# | Normal sample – Intermittent transmit |

2.4 Equipment Under Test

Power supply system utilised

| | | | |
|----------------------|---|---|-----------------------------------|
| Power supply voltage | : | <input type="radio"/> 230V / 50 Hz | <input type="radio"/> 120V / 60Hz |
| | | <input type="radio"/> 12 V DC | <input type="radio"/> 24 V DC |
| | | <input checked="" type="radio"/> Other (specified in blank below) | |

DC 3.85V from battery

2.5 Short description of the Equipment under Test (EUT)

This is a Smart E Ink Tablet.

For more details, refer to the user's manual of the EUT.

2.6 EUT operation mode


The Applicant provides communication tools software (QRCT4) to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing. All test performed at the low, middle and high of operational frequency range of each mode.

Operation Frequency List WIFI on 5G Band:

| Operating band | 20MHz | | 40MHz | | 80MHz | |
|------------------------------|---------|-----------------|---------|-----------------|---------|-----------------|
| | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| U-NII 1 (5150MHz-5250MHz) | 36 | 5180 | 38 | 5190 | 42 | 5210 |
| | 40 | 5200 | | | | |
| | 44 | 5220 | 46 | 5230 | | |
| | 48 | 5240 | | | | |
| U-NII 3 (5725MHz-5850MHz) | 149 | 5745 | 151 | 5755 | 155 | 5775 |
| | 153 | 5765 | | | | |
| | 157 | 5785 | 159 | 5795 | | |
| | 161 | 5805 | | | | |
| | 165 | 5825 | | | | |

Note: The line display in grey is those Channels/Frequencies select to test in this report for each operation mode.

2.7 Block Diagram of Test Setup



2.8 Special Accessories

Follow auxiliary equipment(s) test with EUT that provided by the manufacturer or laboratory is listed as follow:

| Description | Manufacturer | Model | Technical Parameters | Certificate | Provided by |
|---------------|--------------|------------|---|-------------|-------------|
| AC-DC Adapter | MOSO | EP-TA20CBC | Input:AC100-240V-50/60Hz, 0.5A Output:DC 5V,3A | FCC | Laboratory |
| / | / | / | / | / | / |
| / | / | / | / | / | / |
| / | / | / | / | / | / |

2.9 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

2.10 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 165725 Designation Number: CN1234

Shenzhen Global Test Service Co.,Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

A2LA-Lab Cert. No.: 4758.01

Shenzhen Global Test Service Co.,Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

CNAS-Lab Code: L8169

Shenzhen Global Test Service Co.,Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories. Date of Registration: Dec. 11, 2015. Valid time is until Dec. 10, 2024.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

| | |
|-----------------------|--------------|
| Temperature: | 15-35 ° C |
| Humidity: | 30-60 % |
| Atmospheric pressure: | 950-1050mbar |

3.4 Test Description

| FCC Requirement | | |
|----------------------------------|--|-----------------------|
| FCC Part 15.207 | AC Power Conducted Emission | PASS |
| FCC Part 15.407(a) | Emission Bandwidth(26dBm Bandwidth) | PASS ^{Note1} |
| FCC Part 15.407(e) | Minimum Emission Bandwidth(6dBm Bandwidth) | PASS ^{Note2} |
| FCC Part 15.407(a) | Maximum Conducted Output Power | PASS |
| FCC Part 15.407(a) | Peak Power Spectral Density | PASS |
| FCC Part 15.407(g) | Frequency Stability | PASS |
| FCC Part 15.407(b) | Undesirable emission | PASS |
| FCC Part 15.407(b)/15.205/15.209 | Radiated Emissions | PASS |
| FCC Part 15.407(h) | Dynamic Frequency Selection | N/A ^{Note 3} |
| FCC Part 15.203/15.247(b) | Antenna Requirement | PASS |

Note 1: Apply to U-NII 1, U-NII 2A, and U-NII 2C band.

Note 2: Apply to U-NII 3 band only.

Note 3: This device not work in DFS band.

Data Rate Used:

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

| Test Items | Mode | Data Rate |
|--|-----------------------------|-----------|
| Maximum Conducted Output Power Power Spectral Density Emission Bandwidth(26dBm Bandwidth) Minimum Emission Bandwidth(6dBm Bandwidth) Undesirable emission Frequency Stability | 11a/OFDM | 6 Mbps |
| | 11n(20MHz),11ac(20MHz)/OFDM | 7.2 Mbps |
| | 11n(40MHz),11ac(40MHz)/OFDM | 15.0Mbps |
| | 11ac(80MHz)/OFDM | 65.0Mbps |

3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

| Test | Range | Measurement Uncertainty | Notes |
|-----------------------|------------|-------------------------|-------|
| Radiated Emission | 30~1000MHz | 4.10 dB | (1) |
| Radiated Emission | 1~18GHz | 4.32 dB | (1) |
| Radiated Emission | 18-40GHz | 5.54 dB | (1) |
| Conducted Disturbance | 0.15~30MHz | 3.12 dB | (1) |

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6 Equipments Used during the Test


| Test Equipment | Manufacturer | Model No. | Serial No. | Calibration Date | Calibration Due Date |
|----------------------------|-----------------------------------|-----------------------|-----------------|------------------|----------------------|
| LISN | CYBERTEK | EM5040A | E1850400105 | 2021/07/23 | 2022/07/22 |
| LISN | R&S | ESH2-Z5 | 893606/008 | 2021/07/23 | 2022/07/22 |
| EMI Test Receiver | R&S | ESPI3 | 101841-cd | 2021/07/23 | 2022/07/22 |
| EMI Test Receiver | R&S | ESCI7 | 101102 | 2021/09/19 | 2022/09/18 |
| Spectrum Analyzer | Agilent | N9020A | MY48010425 | 2021/09/19 | 2022/09/18 |
| Spectrum Analyzer | R&S | FSV40 | 100019 | 2021/07/23 | 2022/07/22 |
| Vector Signal generator | Agilent | N5181A | MY49060502 | 2021/07/23 | 2022/07/22 |
| Spectrum Analyzer | Agilent | E4421B | 3610AO1069 | 2021/09/19 | 2022/09/18 |
| Climate Chamber | ESPEC | EL-10KA | A20120523 | 2021/09/19 | 2022/09/18 |
| Controller | EM Electronics | Controller EM 1000 | N/A | N/A | N/A |
| Horn Antenna | Schwarzbeck | BBHA 9120D | 01622 | 2020/11/08 | 2021/11/07 |
| Active Loop Antenna | Beijing Da Ze Technology Co.,Ltd. | ZN30900C | 15006 | 2021/10/10 | 2022/10/09 |
| Bilog Antenna | Schwarzbeck | VULB9163 | 000976 | 2021/07/23 | 2022/07/22 |
| Broadband Horn Antenna | SCHWARZBECK | BBHA 9170 | 791 | 2020/11/08 | 2021/11/07 |
| Amplifier | Schwarzbeck | BBV 9743 | #202 | 2021/07/23 | 2022/07/22 |
| Amplifier | Schwarzbeck | BBV9179 | 9719-025 | 2021/07/23 | 2022/07/22 |
| Amplifier | EMCI | EMC051845B | 980355 | 2021/07/23 | 2022/07/22 |
| Temperature/Humidity Meter | Gangxing | CTH-608 | 02 | 2021/07/23 | 2022/07/22 |
| High-Pass Filter | K&L | 9SH10-2700/X12750-O/O | KL142031 | 2021/07/23 | 2022/07/22 |
| High-Pass Filter | K&L | 41H10-1375/U12750-O/O | KL142032 | 2021/07/23 | 2022/07/22 |
| RF Cable(below 1GHz) | HUBER+SUHNER | RG214 | RE01 | 2021/07/23 | 2022/07/22 |
| RF Cable(above 1GHz) | HUBER+SUHNER | RG214 | RE02 | 2021/07/23 | 2022/07/22 |
| Data acquisition card | Agilent | U2531A | TW53323507 | 2021/07/23 | 2022/07/22 |
| Power Sensor | Agilent | U2021XA | MY5365004 | 2021/07/23 | 2022/07/22 |
| Test Control Unit | Tonscend | JS0806-1 | 178060067 | 2021/07/23 | 2022/07/22 |
| Automated filter bank | Tonscend | JS0806-F | 19F8060177 | 2021/07/23 | 2022/07/22 |
| EMI Test Software | Tonscend | JS1120-1 | Ver 2.6.8.0518 | / | / |
| EMI Test Software | Tonscend | JS1120-3 | Ver 2.5.77.0418 | / | / |
| EMI Test Software | Tonscend | JS32-CE | Ver 2.5 | / | / |
| EMI Test Software | Tonscend | JS32-RE | Ver 2.5.1.8 | / | / |

Note: The Cal.Interval was one year.

4 TEST CONDITIONS AND RESULTS

4.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC 12V power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

| Frequency range (MHz) | Limit (dBuV) | |
|-----------------------|--------------|-----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

* Decreases with the logarithm of the frequency.

TEST RESULTS


| | | | |
|---------------|----------|----------------|---------|
| Temperature | 22.8°C | Humidity | 56% |
| Test Engineer | Moon Tan | Configurations | WLAN 5G |

Remark:

- All modes of 802.11a/n were tested at Low, Middle, and High channel; only the worst result of 802.11a CH36 was reported as below:
- Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:

| | | | |
|---------------|-----------------------|--------------|---|
| Power supply: | AC 120V/60Hz(adapter) | Polarization | L |
|---------------|-----------------------|--------------|---|

Test Graph



| Suspected List | | | | | | | | | |
|----------------|-------------|----------------|--------------|-------------|--------------|-------------|----------|------|---------|
| NO. | Freq. [MHz] | Reading [dBµV] | Level [dBµV] | Factor [dB] | Limit [dBµV] | Margin [dB] | Detector | Type | Verdict |
| 1 | 0.186 | 38.07 | 48.57 | 10.50 | 64.21 | 15.64 | PK | L1 | PASS |
| 2 | 0.195 | 22.88 | 33.38 | 10.50 | 53.82 | 20.44 | AV | L1 | PASS |
| 3 | 0.4605 | 34.24 | 44.74 | 10.50 | 56.68 | 11.94 | PK | L1 | PASS |
| 4 | 0.4875 | 21.50 | 32.00 | 10.50 | 46.21 | 14.21 | AV | L1 | PASS |
| 5 | 0.645 | 36.53 | 47.03 | 10.50 | 56.00 | 8.97 | PK | L1 | PASS |
| 6 | 0.6495 | 23.30 | 33.80 | 10.50 | 46.00 | 12.20 | AV | L1 | PASS |
| 7 | 1.194 | 35.34 | 45.84 | 10.50 | 56.00 | 10.16 | PK | L1 | PASS |
| 8 | 1.2075 | 20.18 | 30.68 | 10.50 | 46.00 | 15.32 | AV | L1 | PASS |
| 9 | 2.229 | 18.53 | 29.03 | 10.50 | 46.00 | 16.97 | AV | L1 | PASS |
| 10 | 2.265 | 33.26 | 43.76 | 10.50 | 56.00 | 12.24 | PK | L1 | PASS |
| 11 | 22.209 | 25.28 | 35.78 | 10.50 | 50.00 | 14.22 | AV | L1 | PASS |
| 12 | 22.6815 | 39.58 | 50.08 | 10.50 | 60.00 | 9.92 | PK | L1 | PASS |

- Note: 1). Level (dBµV) = Reading (dBµV) + Factor (dB)
 2). Factor (dB) = insertion loss of LISN (dB) + Cable loss (dB)
 3). Margin (dB) = Limit (dBµV) - Level (dBµV)


Power supply:

AC 120V/60Hz(adapter)

Polarization

N

Test Graph



| Suspected List | | | | | | | | | |
|----------------|-------------|----------------|--------------|-------------|--------------|-------------|----------|------|---------|
| NO. | Freq. [MHz] | Reading [dBµV] | Level [dBµV] | Factor [dB] | Limit [dBµV] | Margin [dB] | Detector | Type | Verdict |
| 1 | 0.1905 | 35.71 | 46.21 | 10.50 | 64.01 | 17.80 | PK | N | PASS |
| 2 | 0.1905 | 21.62 | 32.12 | 10.50 | 54.01 | 21.89 | AV | N | PASS |
| 3 | 0.2895 | 18.39 | 28.89 | 10.50 | 50.54 | 21.65 | AV | N | PASS |
| 4 | 0.312 | 35.45 | 45.95 | 10.50 | 59.92 | 13.97 | PK | N | PASS |
| 5 | 0.384 | 17.72 | 28.22 | 10.50 | 48.19 | 19.97 | AV | N | PASS |
| 6 | 0.411 | 34.88 | 45.38 | 10.50 | 57.63 | 12.25 | PK | N | PASS |
| 7 | 0.5235 | 32.44 | 42.94 | 10.50 | 56.00 | 13.06 | PK | N | PASS |
| 8 | 0.573 | 16.82 | 27.32 | 10.50 | 46.00 | 18.68 | AV | N | PASS |
| 9 | 1.41 | 30.26 | 40.76 | 10.50 | 56.00 | 15.24 | PK | N | PASS |
| 10 | 1.473 | 16.55 | 27.05 | 10.50 | 46.00 | 18.95 | AV | N | PASS |
| 11 | 21.939 | 39.73 | 50.23 | 10.50 | 60.00 | 9.77 | PK | N | PASS |
| 12 | 23.1315 | 24.85 | 35.35 | 10.50 | 50.00 | 14.65 | AV | N | PASS |

Note:1).Level (dBµV)= Reading (dBµV)+ Factor (dB)

2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)

3). Margin(dB) = Limit (dBµV) - Level (dBµV)

4.2 Radiated Emissions

Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Undesirable emission limits

| Requirement | Limit(EIRP) | Limit (Field strength at 3m) <small>Note1</small> |
|--------------|-----------------|---|
| 15.407(b)(1) | PK:-27(dBm/MHz) | PK:68.2(dBµV/m) |
| 15.407(b)(2) | | |
| 15.407(b)(3) | | |
| 15.407(b)(4) | | |

Note1: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$


- (5) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209
- (6) In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


| Frequency (MHz) | Distance (Meters) | Radiated (dBµV/m) | Radiated (µV/m) |
|-----------------|-------------------|----------------------------------|-----------------|
| 0.009-0.49 | 3 | 20log(2400/F(KHz))+40log(300/3) | 2400/F(KHz) |
| 0.49-1.705 | 3 | 20log(24000/F(KHz))+ 40log(30/3) | 24000/F(KHz) |
| 1.705-30 | 3 | 20log(30)+ 40log(30/3) | 30 |
| 30-88 | 3 | 40.0 | 100 |
| 88-216 | 3 | 43.5 | 150 |
| 216-960 | 3 | 46.0 | 200 |
| Above 960 | 3 | 54.0 | 500 |

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



Test Procedure

1. Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 40GHz.
6. The distance between test antenna and EUT as following table states:

| Test Frequency range | Test Antenna Type | Test Distance |
|----------------------|---------------------|---------------|
| 9KHz-30MHz | Active Loop Antenna | 3 |
| 30MHz-1GHz | Bilog Antenna | 3 |
| 1GHz-18GHz | Horn Antenna | 3 |
| 18GHz-25GHz | Horn Antenna | 1 |

7. Setting test receiver/spectrum as following table states:

| Test Frequency range | Test Receiver/Spectrum Setting | Detector |
|----------------------|---|----------|
| 9KHz-150KHz | RBW=200Hz/VBW=3KHz, Sweep time=Auto | QP |
| 150KHz-30MHz | RBW=9KHz/VBW=100KHz, Sweep time=Auto | QP |
| 30MHz-1GHz | RBW=120KHz/VBW=1000KHz, Sweep time=Auto | QP |
| 1GHz-40GHz | Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto | Peak |

TEST RESULTS

| | | | |
|---------------|----------|----------------|---------|
| Temperature | 22.8°C | Humidity | 56% |
| Test Engineer | Moon Tan | Configurations | WLAN 5G |


Remark:

1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
1. All 802.11a / 802.11n (HT20) / 802.11n (HT40) modes have been tested for below 1GHz test, only the worst case 802.11a low channel of U-NII 1 band was recorded.
2. All 802.11a / 802.11n (HT20) / 802.11n (HT40) modes have been tested for above 1GHz test, only the worst case 802.11a was recorded.
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

For 30MHz-1GHz


Horizontal

Test Graph



| Suspected Data List | | | | | | | | | |
|---------------------|-------------|------------------|----------------|-------------|----------------|-------------|-------------|-----------|------------|
| NO. | Freq. [MHz] | Reading [dBµV/m] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
| 1 | 50.37 | 40.08 | 23.94 | -16.14 | 40.00 | 16.06 | 100 | 126 | Horizontal |
| 2 | 151.128 | 48.60 | 26.86 | -21.74 | 43.50 | 16.64 | 100 | 126 | Horizontal |
| 3 | 251.887 | 60.12 | 42.18 | -17.94 | 46.00 | 3.82 | 100 | 126 | Horizontal |
| 4 | 302.327 | 55.94 | 38.63 | -17.31 | 46.00 | 7.37 | 100 | 126 | Horizontal |
| 5 | 453.526 | 51.85 | 36.80 | -15.05 | 46.00 | 9.20 | 100 | 126 | Horizontal |
| 6 | 554.406 | 46.33 | 32.81 | -13.52 | 46.00 | 13.19 | 100 | 126 | Horizontal |

- Note: 1). Level (dBµV/m) = Reading (dBµV/m) + Factor (dB/m)
 2). Factor (dB/m) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)
 3). Margin (dB) = Limit (dBµV/m) - Level (dBµV/m)



| Tested Channel | Frequency (MHz) | Emission Level (dBuV/m) | Detector Mode | ANT Pol | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre amplifier (dB) | Correction Factor (dB/m) |
|------------------|-----------------|-------------------------|---------------|---------|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| 149 (5745MHz) | 5720.00 | 64.08 | PK | H | 110.80 | 46.72 | 76.13 | 34.22 | 7.05 | 53.32 | -12.05 |
| | 5725.00 | 75.23 | PK | H | 122.20 | 46.97 | 87.27 | 34.22 | 7.06 | 53.32 | -12.04 |
| | 11490.00 | 58.10 | PK | H | 68.20 | 10.10 | 58.78 | 39.69 | 12.90 | 53.27 | -0.68 |
| | 11490.00 | 50.07 | AV | H | 54.00 | 3.93 | 50.75 | 39.69 | 12.90 | 53.27 | -0.68 |
| | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |
| 157 (5785MHz) | 11570.00 | 57.78 | PK | H | 68.20 | 10.42 | 58.21 | 39.71 | 13.05 | 53.19 | -0.43 |
| | 11570.00 | 46.57 | AV | H | 54.00 | 7.43 | 47.00 | 39.71 | 13.05 | 53.19 | -0.43 |
| | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |
| 165 (5825MHz) | 5850.00 | 71.76 | PK | H | 122.50 | 50.74 | 83.37 | 34.51 | 7.21 | 53.33 | -11.61 |
| | 5855.00 | 62.15 | PK | H | 110.80 | 48.65 | 73.75 | 34.51 | 7.22 | 53.33 | -11.60 |
| | 11650.00 | 56.67 | PK | H | 68.20 | 11.53 | 56.85 | 39.73 | 13.19 | 53.10 | -0.18 |
| | 11650.00 | 46.18 | AV | H | 54.00 | 7.82 | 46.36 | 39.73 | 13.19 | 53.10 | -0.18 |
| | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- | -- |

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the other emission levels were very low against the limit.
5. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.
6. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11ac VHT20 ,IEEE 802.11ac VHT40 and IEEE 802.11ac VHT80;

4.3 Maximum Conducted Average Output Power

Limit

For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.


For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

Test Configuration



Test Results

| | | | |
|---------------|----------|----------------|---------|
| Temperature | 22.8°C | Humidity | 56% |
| Test Engineer | Moon Tan | Configurations | WLAN 5G |

U-NII 1

| Type | Channel | Output power (dBm) | Limit (dBm) | Result |
|----------------|---------|--------------------|-------------|--------|
| 802.11a | 36 | 7.35 | 23.98 | Pass |
| | 40 | 6.93 | | |
| | 48 | 6.93 | | |
| 802.11n(HT20) | 36 | 7.29 | 23.98 | Pass |
| | 40 | 6.85 | | |
| | 48 | 6.87 | | |
| 802.11n(HT40) | 38 | 6.95 | 23.98 | Pass |
| | 46 | 6.46 | | |
| 802.11ac(HT20) | 36 | 7.33 | 23.98 | Pass |
| | 40 | 6.95 | | |
| | 48 | 6.89 | | |
| 802.11ac(HT40) | 38 | 6.84 | 23.98 | Pass |
| | 46 | 6.52 | | |
| 802.11ac(HT80) | 42 | 7.47 | 23.98 | Pass |

U-NII 3

| Type | Channel | Output power (dBm) | Limit (dBm) | Result |
|----------------|---------|--------------------|-------------|--------|
| 802.11a | 149 | 7.11 | 30.00 | Pass |
| | 157 | 6.34 | | |
| | 165 | 6.62 | | |
| 802.11n(HT20) | 149 | 7.02 | 30.00 | Pass |
| | 157 | 6.27 | | |
| | 165 | 6.51 | | |
| 802.11n(HT40) | 151 | 6.52 | 30.00 | Pass |
| | 159 | 5.87 | | |
| 802.11ac(HT20) | 149 | 7.05 | 30.00 | Pass |
| | 157 | 6.24 | | |
| | 165 | 6.48 | | |
| 802.11ac(HT40) | 151 | 6.62 | 30.00 | Pass |
| | 159 | 5.84 | | |
| 802.11ac(HT80) | 155 | 7.49 | 30.00 | Pass |

4.4 Power Spectral Density

Limit

(1) For the band 5.15 - 5.25 GHz.

(i) For an outdoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band. ^{note1}

(ii) For an indoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band. ^{note1}

(iii) For fixed point-to-point access points operating in the band 5.15 - 5.25 GHz, transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi.

(iv) For mobile and portable client devices in the 5.15 - 5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 MHz band. ^{note1}

(2) For the 5.25 - 5.35 GHz and 5.47 - 5.725 GHz bands, the peak power spectral density shall not exceed 11 dBm in any 1 MHz band. ^{note1}

(3) For the band 5.725 - 5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band. ^{note1, note2}


Note1: If transmitting antennas of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note2: Fixed point - to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW = 1MHz for U-NII 1, U-NII 2A, U-NII C band and 510KHz for U-NII 3 band.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to encompass the entire EBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.

Test Configuration



Test Results

| | | | |
|---------------|----------|----------------|---------|
| Temperature | 22.8°C | Humidity | 56% |
| Test Engineer | Moon Tan | Configurations | WLAN 5G |

| Type | Bands | Channel | Power Spectral Density (dBm/MHz) | Limit (dBm/MHz) | Result |
|-----------------|---------|---------|----------------------------------|-----------------|--------|
| 802.11a | U-NII 1 | 36 | -2.506 | 11 | Pass |
| | | 40 | -3.178 | | |
| | | 48 | -2.882 | | |
| 802.11n (HT20) | U-NII 1 | 36 | -3.016 | | |
| | | 40 | -3.520 | | |
| | | 48 | -3.302 | | |
| 802.11n (HT40) | U-NII 1 | 38 | -6.200 | | |
| | | 46 | -6.525 | | |
| 802.11ac (HT20) | U-NII 1 | 36 | -2.872 | | |
| | | 40 | -3.392 | | |
| | | 48 | -3.403 | | |
| 802.11ac (HT40) | U-NII 1 | 38 | -6.465 | | |
| | | 46 | -6.640 | | |
| 802.11ac (HT80) | U-NII 1 | 42 | -9.160 | | |

| Type | Bands | Channel | Power Spectral Density (dBm/500KHz) | Limit (dBm/500KHz) | Result |
|-----------------|---------|---------|-------------------------------------|--------------------|--------|
| 802.11a | U-NII 3 | 149 | -4.773 | 30 | Pass |
| | | 157 | -5.947 | | |
| | | 165 | -5.545 | | |
| 802.11n (HT20) | U-NII 3 | 149 | -5.575 | | |
| | | 157 | -6.353 | | |
| | | 165 | -5.800 | | |
| 802.11n (HT40) | U-NII 3 | 151 | -8.639 | | |
| | | 159 | -9.495 | | |
| 802.11ac (HT20) | U-NII 3 | 149 | -5.272 | | |
| | | 157 | -6.385 | | |
| | | 165 | -5.968 | | |
| 802.11ac (HT40) | U-NII 3 | 151 | -9.217 | | |
| | | 159 | -9.934 | | |
| 802.11ac (HT80) | U-NII 3 | 155 | -11.480 | | |

Note:

1. $P.S.D(dBm/500KHz) = P.S.D(dBm/300KHz) + 10 \log(500 \text{ kHz}/300KHz)$.
2. RBW Factor is compensated in the graph.
3. Measured output power at difference data rate for each mode and recorded worst case for each mode.
4. Test results including cable loss;
5. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11ac VHT20, IEEE 802.11ac VHT40 and IEEE 802.11ac VHT80;

Test plot as follows:

802.11a

U-NII 1



U-NII 3



CH36



CH149



CH40



CH157



CH48

CH165

802.11n(HT20)

U-NII 1



U-NII 3



CH36



CH149




CH40




CH157



CH48



CH165



802.11n(HT40)


U-NII 1



U-NII 3



CH38



CH151



CH46

CH159

802.11ac(HT20)

U-NII 1



U-NII 3



CH36



CH149



CH40



CH157



CH48

CH165

802.11ac(HT40)

U-NII 1



U-NII 3



CH38

CH151



CH46

CH159

802.11ac(HT80)

U-NII 1



U-NII 3



CH42

CH155

4.5 Emission Bandwidth (26dBm Bandwidth)


Limit

N/A

Test Procedure

1. Set resolution bandwidth (RBW) = approximately 1 % of the EBW.
2. Set the video bandwidth (VBW) > RBW.
3. Detector = Peak.
4. Trace mode = Max hold.
5. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW / EBW ratio is approximately 1 %.

Test Configuration









Test Results

| | | | |
|---------------|----------|----------------|---------|
| Temperature | 22.8°C | Humidity | 56% |
| Test Engineer | Moon Tan | Configurations | WLAN 5G |







| Type | Bands | Channel | 26dB Bandwidth (MHz) | Limit (MHz) | Result |
|----------------|---------|---------|----------------------|-------------|--------|
| 802.11a | U-NII 1 | 36 | 23.00 | N/A | Pass |
| | | 40 | 23.40 | | |
| | | 48 | 23.40 | | |
| 802.11n(HT20) | U-NII 1 | 36 | 23.24 | | |
| | | 40 | 23.20 | | |
| | | 48 | 24.04 | | |
| 802.11n(HT40) | U-NII 1 | 38 | 41.28 | | |
| | | 46 | 41.36 | | |
| 802.11ac(HT20) | U-NII 1 | 36 | 23.68 | | |
| | | 40 | 23.08 | | |
| | | 48 | 23.12 | | |
| 802.11ac(HT40) | U-NII 1 | 38 | 41.20 | | |
| | | 46 | 41.20 | | |
| 802.11ac(HT80) | U-NII 1 | 42 | 82.56 | | |

Test plot as follows:



CH48

CH48



CH46

CH40

CH46

CH48


802.11ac(HT40)




802.11ac(HT80)




CH38



CH42



CH46



4.6 Minimum Emission Bandwidth (6dBm Bandwidth)


Limit

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure

1. Set resolution bandwidth (RBW) = 100 kHz
2. Set the video bandwidth 3 x RBW.
3. Detector = Peak.
4. Trace mode = Max hold.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Configuration









Test Results

| | | | |
|---------------|----------|----------------|---------|
| Temperature | 22.8°C | Humidity | 56% |
| Test Engineer | Moon Tan | Configurations | WLAN 5G |







| Type | Bands | Channel | 6dB Bandwidth (MHz) | Limit (KHz) | Result |
|----------------|---------|---------|---------------------|-------------|--------|
| 802.11a | U-NII 3 | 149 | 15.760 | ≥500KHz | Pass |
| | | 157 | 15.840 | | |
| | | 165 | 15.520 | | |
| 802.11n(HT20) | U-NII 3 | 149 | 16.560 | | |
| | | 157 | 15.160 | | |
| | | 165 | 15.400 | | |
| 802.11n(HT40) | U-NII 3 | 151 | 36.000 | | |
| | | 159 | 35.440 | | |
| 802.11ac(HT20) | U-NII 3 | 149 | 17.000 | | |
| | | 157 | 15.760 | | |
| | | 165 | 17.400 | | |
| 802.11ac(HT40) | U-NII 3 | 151 | 36.080 | | |
| | | 159 | 36.080 | | |
| 802.11ac(HT80) | U-NII 3 | 155 | 75.520 | | |

Test plot as follows:




CH165

CH165




CH165


802.11ac(HT40)




802.11ac(HT80)



CH151



CH155




CH159

4.7 Frequency Stability

LIMIT

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

TEST CONFIGURATION



TEST PROCEDURE

Frequency Stability under Temperature Variations:

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

Frequency Stability under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

TEST RESULTS




| | | | |
|---------------|----------|----------------|---------|
| Temperature | 22.8°C | Humidity | 56% |
| Test Engineer | Moon Tan | Configurations | WLAN 5G |

Record worst case as below:

| Reference Frequency: 802.11ac channel=36 frequency=5180MHz | | | | | |
|--|------------------|-----------------|-------|------------------------------|--------|
| Voltage (V) | Temperature (°C) | Frequency error | | Limit (ppm) | Result |
| | | Hz | ppm | | |
| 3.85 | -30 | 38.57 | 0.007 | Within the band of operation | Pass |
| | -20 | 51.27 | 0.010 | | |
| | -10 | 41.85 | 0.008 | | |
| | 0 | 76.76 | 0.015 | | |
| | 10 | 58.33 | 0.011 | | |
| | 20 | 82.58 | 0.016 | | |
| | 30 | 65.80 | 0.013 | | |
| | 40 | 41.31 | 0.008 | | |
| 4.43 | 25 | 90.00 | 0.017 | | |
| 3.27 | 25 | 48.78 | 0.009 | | |

| Reference Frequency: 802.11ac channel=149 frequency=5745MHz | | | | | |
|---|------------------|-----------------|-------|------------------------------|--------|
| Voltage (V) | Temperature (°C) | Frequency error | | Limit (ppm) | Result |
| | | Hz | ppm | | |
| 3.85 | -30 | 77.00 | 0.013 | Within the band of operation | Pass |
| | -20 | 46.45 | 0.008 | | |
| | -10 | 40.18 | 0.007 | | |
| | 0 | 96.10 | 0.017 | | |
| | 10 | 91.29 | 0.016 | | |
| | 20 | 97.53 | 0.017 | | |
| | 30 | 31.17 | 0.005 | | |
| | 40 | 71.20 | 0.012 | | |
| 4.43 | 25 | 75.58 | 0.013 | | |
| 3.27 | 25 | 65.01 | 0.011 | | |

5 Test Setup Photos of the EUT



6 Photos of the EUT

Reference to the test report No. GTS20211120011-1-1

***** End of Report *****