




Band-edge Measurements for RF Conducted Emissions:









Report No.: GTS20191021009-1-9-11 Page 36 of 42

4.7 Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited


FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1) (I):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Test Result:

The maximum gain of antenna was 1.20dBi for 2.4GHz WIFI.

5 Test Setup Photos of the EUT







Report No.: GTS20191021009-1-9-11 Page 38 of 42


6 Photos of the EUT














Internal Photos









Report No.: GTS20191021009-1-9-11 Page 41 of 42







Report No.: GTS20191021009-1-9-11

