


# RF Exposure Evaluation Report

**APPLICANT** : Fitbit, Inc.  
**EQUIPMENT** : Wireless Fitness Headphone  
**BRAND NAME** : Fitbit  
**MODEL NAME** : FB205  
**FCC ID** : XRAFB205  
**STANDARD** : 47 CFR Part 2.1093  
FCC KDB 447498 D01 v06

We, SPORTON INTERNATIONAL INC., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1093, and pass the limit. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Manager



Approved by: Jones Tsai / Manager



## **SPORTON INTERNATIONAL INC.**

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

- 1. Administration Data ..... 3
- 2. General Information ..... 4
- 2.1 Description of Device Under Test (DUT) ..... 4
- 3. Maximum RF output power among production units ..... 4
- 4. RF Exposure Evaluation ..... 5

## Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA741718	Rev. 01	Initial issue of report	Jul. 20, 2017



**1. Administration Data**

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978

Applicant	
Company Name	Fitbit, Inc.
Address	405 Howard Street Suite 550, San Francisco, California, United States, 94105

Manufacturer	
Company Name	Fitbit, Inc.
Address	405 Howard Street Suite 550, San Francisco, California, United States, 94105



## 2. General Information

### 2.1 Description of Device Under Test (DUT)

Product Feature & Specification	
DUT Type	Wireless Fitness Headphone
Brand Name	Fitbit
Model Name	FB205
FCC ID	XRAFB205
Wireless Technology and Frequency Range	Bluetooth: 2402 MHz ~ 2480 MHz
Mode	Bluetooth BR/EDR
Antenna Type	Stamping Antenna
Antenna Gain	-0.01dBi
HW Version	DVT2.0
SW Version	DVT_V09
DUT Stage	Identical Prototype

**Remark:** The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 3. Maximum RF output power among production units

Mode / Band	Average Power (dBm)
	Bluetooth
	BR / EDR
2.4GHz Bluetooth	9.5



#### 4. RF Exposure Evaluation

Bluetooth Max Power (dBm)	mW	Separation Distance (mm)	Frequency (GHz)	Exclusion Thresholds
9.5	8.91	5	2.48	2.83

**Note:**

1. Per KDB 447498 D01v06 the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for}$$

1-g SAR and ≤ 7.5 for 10-g extremity SAR

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

**Conclusion:** Per KDB 447498 D01v06, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 2.83 which is ≤ 3, SAR testing is not required.