

A-601-GP SILVER

Gloss Silver Vinyl Permanent Specification

A high quality calendered metallic PVC films coated with a pressure sensitive acrylic adhesive for use in on roll labelling on a wide variety of clean dry surfaces.

Typical Properties

Face Film Type:	Calendered, plasticised monomeric PVC
Face Film Thickness:	90 Micron +/- 10 Micron
Substance:	125gsm +/- 10%
Adhesive Type:	Acrylic emulsion pressure sensitive
Initial Type:	900 g/25mm
48 Hour Adhesion:	1800 + g/25mm
Siliconised Release Liner:	Glassine 67gsm white
Temperature Range in Application:	+10 deg C to + 60 deg C
Intermittent Service in Dry Conditions:	-30 deg C to +120 deg C
Shelf Life (at 20 deg C and 50.5 RH):	½ years

We reserve the right to supply comparable materials against any product without prior notice.

All statements, technical data, and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, express or implied.

Seller's and manufacturers only obligation shall be to replace such quantity of the product is proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use or the inability to use the product. Before using, users shall determine the suitability of the product for their initial use, and users assume all risk and liability whatsoever in connection with them.

No statement or recommendation not contained herein shall have any force or effect unless embodied in a written agreement signed by authorised officers of seller and manufacturer.