



Product Service

**Choose certainty.
Add value.**

Report On

RF Exposure Assessment of the
Domo Tactical Communications Ltd
SOL8SDR 2x2W-P-234091
SOFTWARE DEFINED RADIO (SDR-P) PLAIN

FCC ID: XRFSOL8SDRP234091



Product Service

TÜV SÜD Product Service, Octagon House, Concorde Way, Segensworth North,
Fareham, Hampshire, United Kingdom, PO15 5RL
Tel: +44 (0) 1489 558100. Website: www.tuv-sud.co.uk

REPORT ON

RF Exposure Assessment of the
Domo Tactical Communications Ltd
SOL8SDR 2x2W-P-234091 SOFTWARE DEFINED RADIO (SDR-P)
PLAIN

Document 75942063 Report 07 Issue 2

December 2018

PREPARED FOR

Domo Tactical Communications Ltd
The Cobham Centre - Solent, Fusion 2
1100 Parkway
Solent Business Park
Whiteley, Fareham
Hants
PO15 7AB
United Kingdom

PREPARED BY

Peter Dorey
Principal Consultant

APPROVED BY

Simon Bennett
Authorised Signatory

DATED

14 December 2018

This report has been up-issued to Issue 2 to amend the FCC ID.



Product Service

CONTENTS

Section	Page No
1	REPORT SUMMARY 3
1.1	Introduction 4
1.2	Regional Requirements 5
1.3	Product Information 6
1.3.1	Technical Description 6
1.3.2	Supported Features 6
1.3.3	Antennas 6
2	TEST DETAILS 8
2.1	Rationale for Assessment of the RF Exposure 9
2.2	Test Result Details 10
3	DISCLAIMERS AND COPYRIGHT 12
3.1	Disclaimers and Copyright 13



Product Service

SECTION 1

REPORT SUMMARY

RF Exposure Assessment of the
Domo Tactical Communications Ltd
SOL8SDR 2x2W-P-234091 SOFTWARE DEFINED RADIO (SDR-P) PLAIN



Product Service

1.1 INTRODUCTION

The information contained in this report is intended to show verification of the RF Exposure Assessment of the Domo Tactical Communications Ltd SOL8SDR 2x2W-P-234091 SOFTWARE DEFINED RADIO (SDR-P) PLAIN to the requirements of the applied test specifications.

Objective	To perform RF Exposure Assessment to determine the Equipment Under Test's (EUT's) compliance of the applied rules.
Applicant	Domo Tactical Communications Ltd
Manufacturer	Domo Tactical Communications Ltd
Manufacturing Description	SOFTWARE DEFINED RADIO (SDR-P) PLAIN
Model Number(s)	SOL8SDR 2x2W-P-234091
Test Specification/Issue/Date	CFR 47 Pt 2 Subpart J 2.1091 (Radiofrequency radiation exposure evaluation: mobile devices) CFR 47 Pt 1 Subpart I 1.1310 (Radiofrequency radiation exposure limits)



Product Service

1.2 REGIONAL REQUIREMENTS

The table below shows the regional requirements that are referenced in this test report. A full list of the requirements is shown in Annex A.

Report Reference	Regional Requirement
FCC	CFR 47 Pt 2 Subpart J 2.1091



Product Service

1.3 PRODUCT INFORMATION

1.3.1 Technical Description

The Equipment under test was a Domo Tactical Communications Ltd SOL8SDR 2x2W-P-234091 SOFTWARE DEFINED RADIO (SDR-P) PLAIN. A full technical description can be found in the manufacturer's documentation.

All reported calculations were carried out on the relevant information supplied for the SOL8SDR 2x2W-P-234091 SOFTWARE DEFINED RADIO (SDR-P) PLAIN to demonstrate compliance with the applied test specification(s). The sample assessed was found to comply with the requirements of the applied rules.

1.3.2 Supported Features

The following radio access technologies and frequency bands are supported by the equipment under test.

Radio Access Technology	COFDM
	COFDM

Frequency Band	2400
	2400

The unit is capable of transmitting on two antenna ports 2 x 2W. They can be transmitted independently and or at the same time to form a MIMO radio. Hence if used in MIMO mode the unit will transmit from 2 ports at the same time, one port being Horizontally orientated the other Vertically polarised. The two ports are coupled to the two antennas.

1.3.3 Antennas

The following antennas are supported by the equipment under test.

No.	Model	Gain(dB)
1	1	2
2	2	2



1.4 BRIEF SUMMARY OF RESULTS

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields for both General Public and Occupational. The calculations shown in this report were made in accordance with the procedures specified in the applied test specification(s).

Required Compliance Boundary (m)	
Occupational	General Population
0.2	0.2

Table 1 – Compliance Boundary Results

Regional Requirement	Calculated RF exposure level at compliance boundary of 0.2 m					
	S Field (mW/cm ²)		E Field (V/m)		H Field (A/m)	
	Result (proportion of limit)	Limit	Result	Limit	Result	Limit
FCC*	0.0830	5.0000	N/A	N/A	N/A	N/A

* Requirement in mW/cm²

Table 2 – Occupational Results

The calculations show that the EUT complies with the occupational exposure levels described in CFR 47 Pt 2 Subpart J 2.1091 at the point of investigation, 0.2 m.

Regional Requirement	Calculated RF exposure level at compliance boundary of 0.2 m					
	S Field (mW/cm ²)		E Field (V/m)		H Field (A/m)	
	Result (proportion of limit)	Limit	Result	Limit	Result	Limit
FCC*	0.4152	1.0000	N/A	N/A	N/A	N/A

* Requirement in mW/cm²

Table 3 – General Population Results

The calculations show that the EUT complies with the occupational exposure levels described in CFR 47 Pt 2 Subpart J 2.1091 at the point of investigation, 0.2 m.



Product Service

SECTION 2

TEST DETAILS



Product Service

2.1 RATIONALE FOR ASSESSMENT OF THE RF EXPOSURE

The aim of the assessment report is to evaluate the compliance boundary for a set of given input power(s) according to the basic restrictions (directly or indirectly via compliance with reference levels) related to human exposure to radio frequency electromagnetic fields.

The chosen assessment method to establish the compliance boundary in the far-field region is the reference method as defined in the relevant specifications.

The RF exposure assessment is based upon the following criteria:

The SOL8SDR 2x2W-P-234091 SOFTWARE DEFINED RADIO (SDR-P) PLAIN operates with the following transmitters active on the antenna ports shown in Section 1.3.3. For each transmitter, the Radio Access Technology (RAT), EIRP inclusive of antenna gain and duty cycle, gain of the antenna and lowest frequency of operation are shown as they contribute to the calculation of S Field, E field and H field values according to the following formulas.

The power flux (S Field):

$$S = \frac{PG_{(\theta, \phi)}}{4\pi r^2}$$

The electric field strength (E Field):

$$E = \frac{\sqrt{30PG_{(\theta, \phi)}}}{r}$$

The magnetic field strength (H Field):

$$H = \frac{E}{\eta_0}$$

Where:

S = Power Flux Density (W/m²) (Note 1 W/m² = 0.1 mW/cm²)

E = Electric Field Strength (V/m)

H = Magnetic Field Strength (A/m)

P = Average Power (W)

G = Antenna Gain (dBi)

r = Distance (cm) or (m)

$\eta_0 = 377$



Product Service

2.2 TEST RESULT DETAILS

The frequencies shown in the tables below have been chosen based on the lowest possible frequency that the EUT can transmit.

Antenna Port	Tx No.	Ant No.	RAT	EIRP (W)	Duty Cycle (%)	Gain (dBi)	Frequency (MHz)	RF Exposure Level at compliance boundary of 0.2 m		
								S Field (mW/cm ²)	E Field (V/m)	H Field (A/m)
1	1	1	COFDM	1.044	33	2	2450	0.20761	27.9761	0.0742
2	1	2	COFDM	1.044	33	2	2450	0.20761	27.9761	0.0742

Table 4 – Occupational Transmitter Summary

Antenna Port	Tx No.	Ant No.	RAT	EIRP (W)	Duty Cycle (%)	Gain (dBi)	Frequency (MHz)	RF Exposure Level at compliance boundary of 0.2 m		
								S Field (mW/cm ²)	E Field (V/m)	H Field (A/m)
1	1	1	COFDM	1.044	33	2	2450	0.20761	27.9761	0.0742
2	1	2	COFDM	1.044	33	2	2450	0.20761	27.9761	0.0742

Table 5 – General Population Transmitter Summary



Product Service

The following tables show a summary of each antenna port and the summation of the RF exposure results and limit for each region.

Antenna Port	EIRP (W)	Regional Requirement	Calculated RF exposure level at compliance boundary of 0.2 m					
			S Field		E Field		H Field	
			Result (proportion of limit)	Limit	Result	Limit	Result	Limit
1	1.044	FCC*	0.0415	5.0000	N/A	N/A	N/A	N/A
2	1.044	FCC*	0.0415	5.0000	N/A	N/A	N/A	N/A
Summation		FCC*	0.0830	5.0000	N/A	N/A	N/A	N/A

* Requirement in mW/cm²

Table 6 – Occupational Antenna Port Summary

Antenna Port	EIRP (W)	Regional Requirement	Calculated RF exposure level at compliance boundary of 0.2 m					
			S Field		E Field		H Field	
			Result (proportion of limit)	Limit	Result	Limit	Result	Limit
1	1.044	FCC*	0.2076	1.0000	N/A	N/A	N/A	N/A
2	1.044	FCC*	0.2076	1.0000	N/A	N/A	N/A	N/A
Summation		FCC*	0.4152	1.0000	N/A	N/A	N/A	N/A

* Requirement in mW/cm²

Table 7 – General Population Antenna Port Summary



Product Service

SECTION 3

DISCLAIMERS AND COPYRIGHT



Product Service

3.1 DISCLAIMERS AND COPYRIGHT

This report relates only to the actual item/items tested.

This report must not be reproduced, except in its entirety, without the written permission of
TÜV SÜD Product Service

© 2018 TÜV SÜD Product Service



Product Service

ANNEX A

REGIONAL REQUIREMENTS



Product Service

Frequency Range (MHz)	Power Density (mW/cm ²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0 - 0.3	-	-	-
0.3 - 3	100	614	1.63
3 - 30	900/f ²	1842/f	4.89/f
30 - 300	1	61.4	0.163
300 - 1500	f/300	-	-
1500 - 100000	5	-	-

Table A.1 – CFR 47 Pt1 Subpart I 1.1310 Occupational Limits

Frequency Range (MHz)	Power Density (mW/cm ²)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)
0 - 0.3	-	-	-
0.3 - 3	100	614	1.63
3 - 30	180/f ²	824/f	2.19/f
30 - 300	0.2	27.5	0.073
300 - 1500	f/1500	-	-
1500 - 100000	1	-	-

Table A.2 – CFR 47 Pt1 Subpart I 1.1310 General Population Limits