

INCH 0 .25 .50 .75 1 2 3 4 5 6


Manufacturing Capabilities Approved Materials Surface Finishes

- Layer Count 2-36
- Line Widths and Spaces .003"
- Sequential Lamination (3x)
- Panel Sizes 12x18, 18x24, 21x24
- Min. Panel Thickness .018"
- Max. Panel Thickness .250"
- Isola FR406, FR408(HR), 370HR
- Getek, Polyimide, IS410
- Vantec VT-47, VT-48
- Nelco 4000-6, 4000-29, 4000-13(ep)
- Rogers 4000, 3000 and 3200 Series
- Max. Panel Thickness .250"
- Immersion Tin, Gold, Silver, Hard Gold
- Entek 106A Organic
- SMOBC/HASL
- Tin Lead

INCH 0 1 2 3 4 5 6

www.apc.com

when reliability and p



APC





WASP MAIN REV. G_2

94V-0

WASP003
REV. G NPE

AX2832

GAINSPAN
GS_MODULE-MI
REV. 1.2

003"
21x24
• Isola FR406, FR408(HK), 370HR
Getek, Polyimide, IS410
• Ventec VT-47, VT-48
• Nelco 4000-6, 4000-29, 4000-13(ep)
• Rogers 4000, 3000 and 3200 Series
• Max. Panel Thickness .250"

• Immersion Plating, Gold,
Silver, Hard Gold
• Entek 106A Organic
• SMOBC/HASL
• Tin Lead

when reliab
W

