

FCC ID: XRN-MAX600

Operational Description

Before installing Pepwave MAX Mobile Router, please prepare the following:

- At least one Internet/WAN access account.
- For WAN connection(s), one 10/100BaseT UTP cable with RJ45 connector for Ethernet port, or one 3G USB modem for the USB port, or one Wi-Fi antenna for the Wi-Fi WAN connector, or one PC Card/ExpressCard for the corresponding card slot.
- A computer with TCP/IP network protocol and a web browser installed. Supported browsers include Microsoft Internet Explorer 6.0 or above, Mozilla Firefox 2.0 or above, Apple Safari 3.1.1 or above, and Google Chrome 2.0 or above.

At the high level, construct the network according to the following steps:

1. With a network cable, connect a computer to one of the LAN ports on the Pepwave MAX. Repeat with different cables for up to 4 computers to be connected.
2. With another network cable, connect the WAN/broadband modem to one of the WAN ports on the Pepwave MAX. Repeat using different cables for other WAN/broadband connections, or connect 3G USB modem to the USB port.
3. Connect to one of the WAN ports on the Pepwave MAX using one of the following:
 - A network cable (connect to the Ethernet WAN port)
 - PC Card
 - ExpressCard
 - USB modem (connect to the USB ports)
 - Wi-Fi antenna (connect to the Wi-Fi WAN port)
4. Connect the provided power adapter to the power connector on the Pepwave MAX, and then plug the power adapter into a power outlet.

After Configured the Pepwave MAX Mobile Router,computers and wan,we can through it sent and receive wifi signal 2.4G to working.