

## RF Exposure Info / MPE Sample Calculation

### **ION-B Series Booster for 800/850 MHz Commercial Band**

**Model: ION-M 80-85HP/19P**

**FCC ID: XS5-ION-M19PEU**

The ION-M 80-85HP/19P is a fibre optic based RF repeater for wireless applications. A RF signal is converted to an optical signal by directly modulating a laser. There is no frequency conversion in this system.

The optical signal is converted back to RF at the ION-B remote unit, amplified and broadcast from an antenna or into a passive RF distribution system, such as radiating cable.

This specific device generally will be **professionally** installed.

Hereby the gain of the finally installed antenna(s), cable attenuation and antenna height will be defined site specific at the time of licensing with the appropriate FCC Bureau(s).

The maximum permissible exposure limit is defined in 47 CFR 1.1310 (B) Limits for General Population / Uncontrolled Exposures)

Frequency Range (MHz)	Power Density (mW/cm <sup>2</sup> )
>1500	1mW/ cm <sup>2</sup>

The Repeater operates in the frequency range of 1930 - 1995 MHz, so that the Power Density Limit is 1mW/cm<sup>2</sup>

**The max measured conducted output power is:**

**- max composite output power based on one carrier (rated) per path: 20W (43.0 dBm)**

The maximum permitted level is to be calculated using the general equation:

$$S = P \cdot G / 4\pi R^2$$

P = 20W; G = antenna-cable attenuation to be defined (numeric gain);  $\pi = 3,1416$

The min separation distance between the antenna and any human body is to be calculated (solving for R in cm) with the final actual antenna gain/cable attenuation where the limit of 1 mW/cm<sup>2</sup> is kept.

**The antenna(s) used with this device must be fixed-mounted on outdoor permanent structures with a sufficient distance to any human body to comply with the RF Exposure limit.**