

RF Exposure Info / MPE Sample Calculation

ION-M Series

Model: ION-M85P/19HP 1900er

FCC ID: XS5-ION-M85P19HP

The ION-M 85P/19HP is a fibre optic based RF repeater for wireless applications. A RF signal is converted to an optical signal by directly modulating a laser. There is no frequency conversion in this system.

The optical signal is converted back to RF at the ION-M remote unit, amplified and broadcast from an antenna or into a passive RF distribution system, such as radiating cable.

This specific device generally will be **professionally** installed.

Hereby the gain of the finally installed antenna(s), cable attenuation and antenna height will be defined site specific at the time of licensing with the appropriate FCC Bureau(s).

The maximum permissible exposure limit is defined in 47 CFR 1.1310 (B) Limits for General Population / Uncontrolled Exposures)

Frequency Range
1500-100,000 MHz

Power Density
1 mW/cm²

The Repeater operates in the frequency range of 1930-1995 MHz, so that the Power Density Limit is 1 mW/cm².

The max measured conducted output power is:

- max composite output power based on one carrier (rated) per path: 40.7 W (46.1 dBm)

The maximum permitted level is to be calculated using the general equation:

$$S = P \cdot G / 4\pi R^2$$

P = 40700 mW; G = antenna-cable attenuation to be defined (numeric gain); $\pi = 3,1416$

The min separation distance between the antenna and any human body is to be calculated (solving for R in cm) with the final actual antenna gain/cable attenuation where the limit of 1 mW/cm² is kept.

The antenna(s) used with this device must be fixed-mounted on outdoor permanent structures with a sufficient distance to any human body to comply with the RF Exposure limit.