

**PRODUCT
SPECIFICATION**



ION-M7P/17EP/19P

Multi-band, Multi-operator Remote Optical System *Support of AWS-3 Spectrum*

ION® is the unified platform for all conceivable optical distribution scenarios.

The ION optical distribution system leads the industry in flexibility while minimizing overall deployment cost.

CommScope's ION-M7P/17EP/19P is a multi-band, multi-operator remote unit configuration used in conjunction with a master unit in the ION optical distribution system. By supporting the entire AWS-3 spectrum, faster and more reliable wireless service is ensured and network quality can be improved.

This system transports up to four frequency bands simultaneously (700 MHz, 1700/2100 MHz, 1900 MHz), providing a cost-effective solution for distributing capacity from one or more base stations.

The ION system transports signals on the RF layer in a very cost-effective manner enabling

multiple operators to use multiple technologies and move their signals simultaneously from a cluster of base station to a number of remote locations over the same fiber.

The ION-M optical distribution system is a cost-effective coverage solution for dense urban areas, tunnels, subways, airports, convention centers, high-rise buildings and other locations where physical structures increase path loss.

The combination of these units gives maximum flexibility while providing a scalable solution. The system is optimized for GSM, LTE, CDMA and WCDMA signals in the 700 MHz, 1900 MHz and 1700/2100 MHz bands. Furthermore it is provisioned for future modulation schemes and frequency bands.

The ION can be easily set-up and supervised from a graphical user interface (GUI). Remote units are commissioned through the use of built-in test equipment. An auto leveling function compensates for the optical link loss making installation easy and quick.

The entire system as well as complete network of systems can be managed remotely most efficiently by CommScope's A.I.M.O.S., which includes alarm monitoring, task automation, statistics, inventory management and

many more features. Should a sophisticated interface not be required, the master unit can be directly connected to the alarm interface of a base station via its contact relay.

- Reduced visual impact form factor
- Optimized power consumption
- Efficient, high power amplifier
- Multi-operator support
- Complete operations and management system for configuration and alarming
- OMC with SNMP according to X.733 standard
- With reference to 3GPP TS25.143/ TS25.106/ 36.143/TS36.106 and 3GPP2C.S0051-0
- Single fiber for multiple bands and multiple remotes
- Easy installation and commissioning

ION-M7P/17EP/19P - Product Specification

Electrical

Mains power, Vac	nominal	100 to 240
	operating	85 to 264
Mains power, Vdc	nominal	48 to 60
	operating	36 to 72
Power consumption, Watts		850

Optical

Optical Link Connectors	E2000/APC 8°
Optical return loss, dB	45
Fibre type	Single mode E9/125 µm
Optical link budget, dB	0 to 10
Composite input power @ OTRx master side, dBm	
700 MHz	3.0 nominal
AWS1700/2100	3.0 / 2.5 nominal
PCS1900	3.0 / 2.5 nominal

Interface

BTS Side (SMA)	
Number of connectors . . . Standard	
700 MHz	4
AWS1700/2100	4
PCS1900	4
System optimized for BTS power, dBm	
	33
	46
Antenna port	
Connector	4.3-10
RF output power	see band specification
Return loss, dB	15

Commercial 700 MHz

Frequency range, MHz	
Uplink	698 to 716
	776 to 787
Downlink	728 to 757

RF output power per carrier, dBm***

Number of Carriers	1	2	4	8
LTE	43	40*	37	34

DL output tolerance over frequency, dB	±1
DL output tolerance over temperature, dB	±0.5

Spurious emission <-13 dBm / 1 MHz

Input ICP3, dBm**	
ICP3 optimized	-11 min.
Noise figure optimized	-18 min.

Noise figure, dB**	
ICP3 optimized	+10 max.
Noise figure optimized	+6 max.
	4.5

AWS1700/2100

Frequency range, MHz	
Uplink	1710 to 1780
Downlink	2110 to 2180

RF output power per carrier, dBm***

Number of Carriers	1	2	4	8
CDMA	42.5	39.5	36.5	33.5
LTE	43	40*	37	34
UMTS	42.5	39.5	36.5	33.5

DL output tolerance over frequency, dB	±1.1
DL output tolerance over temperature, dB	±0.5

Spurious emission <-13 dBm / 1 MHz

Input ICP3, dBm**	
ICP3 optimized	-12 min.
Noise figure optimized	-18 min.

Noise figure, dB**	
ICP3 optimized	+11 max.
Noise figure optimized	+6 max.
	4.5

* 2 dB reduction of Pout @ carrier bandwidth < 5 MHz
 ** from Reference point B to A
 *** PAR 7.5 dB @ 0.1 %

All figures are typical values unless otherwise stated

ION-M7P/17EP/19P - Product Specification

PCS1900

Frequency range, MHz
 Uplink 1850 to 1915
 Downlink 1930 to 1995

RF output power per carrier, dBm***

Number of Carriers	1	2	4	8
GSM	43	40	37	34
CDMA	42.5	39.5	36.5	33.5
LTE	43	40*	37	34
UMTS	42.5	39.5	36.5	33.5

DL output tolerance over frequency, dB ±1.1
 DL output tolerance over temperature, dB ±0.5

Spectrum emission mask <-13 dBm / 1 MHz

Input ICP3, dBm**
 ICP3 optimized -12 min.
 Noise figure optimized -18 min.

Noise figure, dB**
 ICP3 optimized +11 max.
 Noise figure optimized +6 max.
 4.5

System Supervision and Control

Commands RF on/off
 4 external control ports

Alarms Summary
 Power Supply
 Optical UL and DL failure
 RF UL and DL failure
 Temperature
 4 external alarm inputs

Supervision Composite output power

Mechanical****

Height, width, depth, mm (in) 824 x 176 x 220
 (32.4 x 6.9 x 8.7)

Weight, kg (lb) 27 (59.4)

Environmental

Operating temperature range, °C -33 to +50

Ingress protection
 RF part IP67
 Fan part IP55

Minimum SW Requirements for Basic Support

ION-M SW V7.0.1

Ordering Information

ION-M7P/17EP/19P 7714179****
 Depending on the selected options and the configuration the ordering material number contains an identifying suffix.

Extension Unit Options

No connection to extension unit possible.


Corresponding Master Unit OTRx

OTRx 70-85/90/17-21 MU-G 7604304-XX


* 2 dB reduction of Pout @ carrier bandwidth < 5 MHz
 ** from Reference point B to A
 *** PAR 7.5 dB @ 0.1 %
 **** Spacing required 50 mm (1.97 in) around unit
 ***** Subpopulations possible

All figures are typical values, unless otherwise stated.

ION-M7P/17EP/19P - Product Specification



ION-M7P/17EP/19P Remote Unit Design Principle - Combined Antenna Port



Design Principle ION System

WARNING:
 This is NOT a CONSUMER device. It is designed for installation by FCC LICENSEES and QUALIFIED INSTALLERS.
 You MUST have an FCC LICENSE or express consent of an FCC LICENSE to operate this device.
 Unauthorized use may result in significant forfeiture penalties, including penalties in excess of \$ 100,000 for each continuing violation.



www.commscope.com

Visit our Web site or contact your local Commscope representative for more information.

© 2016 Commscope, Inc. All rights reserved.

All trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of Commscope, Inc. This document is for planning purposes only and is not intended to modify or supplement any specifications or warranties relating to Commscope products or services.

Commscope reserves the right to change all hardware and software characteristics without notice.

Bulletin PA-110265-EN.GB (05/16)