

Manufacturer: Andrew Wireless Systems

Name: Oscar Frau

Product: UAP 2 17E/19/25T/37T

Title: Project Handler

FCC ID: XS5-UAP217192537

Signature:



MPE limits (§1.1310)

Mode	Frequency MHz	Duty Cycle %	Power ⁴ dBm	Tolerance dB	Antenna		EIRP ^{1,5} dBm	EIRP mW	Distance cm	PD ² mW/cm ²	PD Limit ³ mW/cm ²	Margin dB	PD/PD Limit	Worst PD/PD values to be considered
					Peak Gain ⁶ dBi									
LTE B66	2112,5	100	24,0	1	5,7	33,7 (+3dB)	2342	30	0,20712	1,000	6,84	0,20712	0,20712	
LTE B25	1932,5	100	24,6	1	5,9	34,5 (+3dB)	2814	30	0,24885	1,000	6,04	0,24885	0,24885	
LTE B41	2498,5	100	24,4	1	4,9	33,3 (+3dB)	2135	30	0,18875	1,000	7,24	0,18875	0,18875	
C-BAND	3700,0	100	23,0	1	4,3	31,3 (+3dB)	1352	30	0,11956	1,000	9,22	0,11956	0,11956	
FCC Co-Location =			0,76428	< 1										

¹EIRP = (Power dBm + Antenna Gain dBi) + 10 x Log (Duty Cycle % / 100)

²PD = EIRP / (4πD²)

³CFR 47 Part 1, §1.1310(e), table 1

⁴See the following documents:

FCC ID: XS5-RML2B12-13-14

FCC ID: XS5-RML2B66

FCC ID: XS5-RML2B25

FCC ID: XS5-CAPL2CBAND

⁵+3dB considering MIMO mode

⁶See Operational Description