

RADIO TEST REPORT

No. 902530-1

EQUIPMENT UNDER TEST

Equipment: Remote Controller
 Type / model: 3LR S01 US
 Manufacturer: Velux A/S
 Tested by request of: Velux A/S

SUMMARY

The equipment complies with the requirements of the following standards:

47 CFR, Part 15, Subpart B (2008) and Subpart C (2008);

RSS-GEN, Issue 2 (June 2007)

RSS-210, Issue 7 (June 2007)

Industry Canada listed test facility No. IC 2042G-1

Date of issue: October 26, 2009

Tested by:


 Stefan Andersson

Approved by:


 Niklas Larsson

This report may not be reproduced other than in full, except with the prior written approval by SEMKO.

Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address



CONTENTS

	Page
1. Client information	3
2. Equipment under test (EUT).....	3
2.1 Identification of the EUT according to the manufacturer/client declaration.....	3
3. Test specifications	4
3.1 Standards.....	4
3.2 Additions, deviations and exclusions from standards.....	4
3.3 Test set-up	4
3.4 Operating environment.....	4
4. Test summary	5
5. Peak output power	6
5.1 Test protocol.....	6
6.6 dB Bandwidth	9
6.1 Test protocol.....	9
7. Spectral power density	11
7.1 Test protocol.....	11
8. Band edge compliance.....	13
8.1 Test protocol.....	13
9. Radiated spurious emissions	15
9.1 Operating environment.....	15
9.2 Measurement uncertainty	15
9.3 Test equipment.....	15
9.4 Measurement set-up.....	16
9.5 Test protocol.....	18
10. Out of band spurious emissions, Conducted at antenna port.....	28
11. 99% Bandwidth	35
11.1 Test protocol.....	35
Appendix – Photos of the EUT	38



Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

1. CLIENT INFORMATION

The EUT has been tested by request of

Company: Velux A/S
Aadaljsvej 99
DK-2970 Hörsholm
Denmark

Name of contact: Jens Philipsen

2. EQUIPMENT UNDER TEST (EUT)**2.1 Identification of the EUT according to the manufacturer/client declaration**

Equipment: Remote Controller

Type/Model: 3LR S01 US

Brand name: Velux

Serial number: No visible serial number on EUT

Manufacturer: Velux A/S

Rating/Supplying voltage: 3x 1.5V AA batteries

Rating RF output power: 0 dBm

Antenna gain: 0 dBi

External antenna connector: NO

Operating temperature range: -10 to +55 °C

Frequency range: 2425 – 2475 MHz

Number of channels: 3

Channel spacing: 25 MHz

Modulation characteristics: DSSS 802.15.4

Stand by mode supported: Yes



Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
Registered in Sweden: No SE556024059901, Registered office: As address

3. TEST SPECIFICATIONS

3.1 Standards

FCC 47 CFR part 15 (2008) Subpart B – Unintentional radiators

FCC 47 CFR part 15 (2008) Subpart C – Intentional Radiators; §15.247 Operation within the bands 902-928 MHz, 2400 – 2483.5 MHz and 5725 – 5850 MHz.

Measurements methods according to ANSI C63.4-2003 - Methods of Measurements of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

RSS-Gen, Issue 2 (june 2007): General Requirements and Information for the Certification of Radiocommunication Equipment

RSS-210, Issue 7 (June 2007): Low Power Licence-Exempt Radio communication Devices (All Frequency Bands): Category I Equipment.

3.2 Additions, deviations and exclusions from standards

No additions, deviations or exclusions have been made from standards.

3.3 Test set-up

Measurement set-ups for the test of out-of-band spurious emissions test are described in corresponding sections. During other tests the EUT was connected to the spectrum analyzer by cable.

3.4 Operating environment

If not additionally specified, the tests were performed under the following environmental conditions:

Air temperature: 20-25 °C
Relative humidity: 25-65 %



Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
Registered in Sweden: No SE556024059901, Registered office: As address

4. TEST SUMMARY

The results in this report apply only to the sample tested.

FCC reference	IC reference	Test	Result	Note
15.247(b)	RSS-210 A8.4 (1)	Peak output power	PASS	
15.247(a)	RSS-210 A8.1 (c)	6 dB Bandwidth	PASS	
15.247(a)	RSS-210 A8.1 (b)	Spectral power density	PASS	
15.247(d)	RSS-210 A8.5	Band edge compliance	PASS	
15.247(d)	RSS-210 A8.5	Out of band spurious emissions, radiated	PASS	1
15.247(d)	RSS-210 A8.5	Out of band spurious emissions, conducted	PASS	
15B	RSS-Gen Table 1	Out of band spurious emissions, radiated	PASS	1
15B	RSS-Gen Table 2	Conducted emission at AC port	N/A	
	RSS-GEN 4.6.1	Occupied Bandwidth	PASS	

1) The measured result is below the limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95 % level of confidence. However, the result indicates that compliance is more probable than non-compliance with the specification limit.



Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

5. PEAK OUTPUT POWER

5.1 Test protocol

Date of test: 2009-07-21

EUT mode of operation: continuous TX. Modulation on

Spectrum analyzer settings:

Span: 5 MHz
 RBW: 5 MHz
 VBW: 5 MHz
 Sweep time: Auto
 Detector: Peak
 Trace: Max Hold

Channel (MHz)	Peak Output Power (dBm)	Plot	Limit value (dBm)
2425	-0,12	plot P5.1	30
2450	-0,18	plot P5.2	
2475	0,24	plot P5.3	

Measurement results are corrected for attenuation in the set-up configuration and antenna gain declared by the manufacturer.

Example calculation:


Peak output power [dBm] = Analyser reading [dBm] + cable loss [dB] + EUT antenna gain [dBi]




Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address


Plot P5.1


	Marker 1 [T1]	RBW	5 MHz	RF Att	40 dB
Ref Lvl	0.24 dBm	VBW	5 MHz		
6.7 dBm	2.47435546 GHz	SWT	5 ms	Unit	dBm



Date: 21.JUL.2009 17:03:12

Plot P5.2

	Marker 1 [T1]	RBW	5 MHz	RF Att	40 dB
Ref Lvl	-0.12 dBm	VBW	5 MHz		
5 dBm	2.42578081 GHz	SWT	5 ms	Unit	dBm




Date: 21.JUL.2009 17:15:30




Intertek Semko AB

Torshamngatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

Plot P5.3

	Marker 1 [T1]	RBW	5 MHz	RF Att	40 dB
Ref Lvl	-0.18 dBm	VBW	5 MHz		
5 dBm	2.44957841 GHz	SWT	5 ms	Unit	dBm



Date: 21.JUL.2009 17:16:42



Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

6. 6 dB BANDWIDTH

6.1 Test protocol

Date of test: 2009-07-21

EUT mode of operation: continuous TX. Modulation on

Spectrum analyzer settings:

Span: 6.25 MHz
 RBW: 100 kHz
 VBW: 100 kHz
 Sweep time: 5 ms
 Detector: Peak
 Trace: Max Hold


Channel (MHz)	6 dB Bandwidth (MHz)	Plot	Limit value (MHz)
2425	1,623	plot P6.1	> 0.5
2450	1,609	plot P6.2	
2475	1,728	plot P6.3	




Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address


Plot P6.1



Plot P6.2



Plot P6.3



Intertek Semko AB

Torshamngsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

7. SPECTRAL POWER DENSITY

7.1 Test protocol

Date of test: 2009-07-21

EUT mode of operation: continuous TX. Modulation on

Spectrum analyzer settings:

Span: 3 MHz
 RBW: 3 kHz
 VBW: 10 kHz
 Sweep time: 1000 s
 Detector: Peak
 Trace: Max Hold


Channel	Power spectral density (dBm)	Plot	Limit value (dBm)
Low	-14,9	plot P7.1	8
Mid	-14,7	plot P7.2	8
High	-14,9	plot P7.3	8




Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address


PlotP7.1



Plot P7.2



Plot P7.3



Intertek Semko AB

Torshamngatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

8. BAND EDGE COMPLIANCE

8.1 Test protocol

Date of test: 2009-07-21

EUT mode of operation: continuous TX. Modulation on

Spectrum analyzer settings:

Span: 80 MHz
RBW: 100 kHz
VBW: 100 kHz
Sweep time: Auto
Detector: Peak
Trace: Max Hold


Channel	Plot	Results	Limit value (dBc)
Low	plot P8.1	PASS	20
High	plot P8.2	PASS	20



Intertek Semko AB


Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
Registered in Sweden: No SE556024059901, Registered office: As address

Plot P8.1



Date: 21.JUL.2009 17:20:19

Plot P8.2



Date: 21.JUL.2009 17:23:48



Intertek Semko AB

Torshammsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

9. RADIATED SPURIOUS EMISSIONS

9.1 Operating environment

Temperature: 20-25 °C (10 – 40 °C)
 Relative Humidity: 25-45 % (10 - 90 %)

9.2 Measurement uncertainty

Radiated disturbance electric field intensity, 30 – 1000 MHz: ± 4,6 dB
 Radiated disturbance electric field intensity, 1000 – 13000 MHz: ± 6,0 dB

The measurement uncertainty describes the overall uncertainty of the given measured value during operation of the EUT.

Measurement uncertainty is calculated in accordance with EA-4/02-1997. The measurement uncertainty is given with a confidence of 95%.

9.3 Test equipment

Equipment	Manufacturer	Type	SEMKO No.
<i>Test site: Semi-anechoic shielded chamber, 5,7 x 8,7 x 5,4 m (W x L x H)</i>			
Software:	Rohde & Schwarz	EMC32	
Measurement receiver:	Rohde & Schwarz	ESCI	12798
Integrated Measurement System:	Rohde & Schwarz	IMS	12800
Antenna: Ultra Broadband	Rohde & Schwarz	HL562	30711
<i>Test site: Radio anechoic shielded chamber, 3,7 x 7,0 x 2,4 m (W x L x H)</i>			
Software:	Rohde & Schwarz	ES-K1, V1.70	
Signal analyser:	Rohde & Schwarz	FSIQ 40	12793
Preamplifier:	MITEQ	AFS6/AFS44	12335
Antenna: Double Ridge Guide Horn (1-13GHz)	EMCO	3115	4936
Transformer	Tufvassons	AFM-1500	30317



9.4 Measurement set-up

Test site: Semi-anechoic shielded chamber (30 – 1000 MHz)

The radiated disturbance electric field intensity was measured in a semi-anechoic chamber at a distance of 3 m and the EUT was placed on a non-metallic table, 0,8 m above the reference ground plane. The specified test mode was enabled. Test set-up photo is given below.

An overview sweep with peak detection of the electric field intensity was performed with the measurement receiver in max-hold and with the antenna placed 1,5 m, 2,5 m and 3,5 m above the floor. The polarisation was horizontal and vertical. The measurements were repeated with the EUT rotated in 90-degree steps.

At the frequencies where high disturbance levels were found a search for max disturbance level was performed. With the EUT and antenna in the worst-case configuration new measurements were carried out.

Test set-up photo:



Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
Registered in Sweden: No SE556024059901, Registered office: As address


Test site: Radio anechoic shielded chamber (1 – 26 GHz)

In the Radio anechoic chamber the EUT was placed on a non-metallic table, 1,4 m above the floor. The radiated disturbance electric field intensity was measured at a distance of 3 m. The specified test mode was enabled.

An overview sweep with peak detection of the electric field intensity was performed with the spectrum analyser in max-hold and with the antenna placed 1,4 m above the floor. The polarisation was horizontal and vertical. The measurements were repeated with the EUT rotated in 90-degree steps.

At the frequencies where high disturbance levels were found a search for max disturbance level was performed. With the EUT and antenna in the worst-case configuration new measurements were carried out.

Test set-up photo:



Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
Registered in Sweden: No SE556024059901, Registered office: As address


9.5 Test protocol

Semi-anechoic shielded chamber

Date of test: 2009-07-14


30 – 1000 MHz, max peak at a distance of 3 m on the lower TX channel

FCC 30 - 1000 MHz FCC class B 3m



30 – 1000 MHz, max peak at a distance of 3 m on the middle TX channel

FCC 30 - 1000 MHz FCC class B 3m




Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address


30 – 1000 MHz, max peak at a distance of 3 m on the upper TX channel

FCC 30 - 1000 MHz FCC class B 3m



30 – 1000 MHz, max peak at a distance of 3 m in the stand by mode

FCC 30 - 1000 MHz FCC class B 3m




Intertek Semko AB

Torshammsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address


Radio anechoic shielded chamber

Date of test: 2009-07-15

1000 – 4000 MHz, max peak at a distance of 3 m on the lower TX channel




4000 – 13000 MHz, max peak at a distance of 3 m on the lower TX channel




Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

13000 – 18000 MHz, max peak at a distance of 3 m on the lower TX channel




18000 – 26000 MHz, max peak at a distance of 3 m on the lower TX channel




Intertek Semko AB

Torshammsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

1000 – 4000 MHz, max peak at a distance of 3 m on the middle TX channel




4000 – 13000 MHz, max peak at a distance of 3 m on the middle TX channel




Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

13000 – 18000 MHz, max peak at a distance of 3 m on the middle TX channel




18000 – 26000 MHz, max peak at a distance of 3 m on the middle TX channel




Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

1000 – 4000 MHz, max peak at a distance of 3 m on the upper TX channel




4000 – 13000 MHz, max peak at a distance of 3 m on the upper TX channel




Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

13000 – 18000 MHz, max peak at a distance of 3 m on the upper TX channel




18000 – 26000 MHz, max peak at a distance of 3 m on the upper TX channel




Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address


1000 – 13000 MHz, max peak at a distance of 3 m in the stand by mode



13000 – 18000 MHz, max peak at a distance of 3 m in the stand by mode



18000 – 26000 MHz, max peak at a distance of 3 m in the stand by mode



Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

Data summary

Field strength of spurious emissions low channel						
Frequency [MHz]	RBW [kHz]	Measured level		Limit		Note
		Peak [dB(μV/m)]	AV [dB(μV/m)]	Peak [dB(μV/m)]	AV [dB(μV/m)]	
4851.0	1000	62.9	53.9	74	54	1
7276.4	1000	58.1	49.1	74	54	1

Field strength of spurious emissions middle channel						
Frequency [MHz]	RBW [kHz]	Measured level		Limit		Note
		Peak [dB(μV/m)]	AV [dB(μV/m)]	Peak [dB(μV/m)]	AV [dB(μV/m)]	
4901,0	1000	62.1	53.1	74	54	1
7351.5	1000	59.0	50.0	74	54	1

Field strength of spurious emissions high channel						
Frequency [MHz]	RBW [kHz]	Measured level		Limit		Note
		Peak [dB(μV/m)]	AV [dB(μV/m)]	Peak [dB(μV/m)]	AV [dB(μV/m)]	
4951.0	1000	62.2	53.2	74	54	1
7426.5	1000	60.4	51.4	74	54	1

Field strength of spurious emissions standby						
Frequency [MHz]	RBW [kHz]	Measured level		Limit		Note
		Peak [dB(μV/m)]	AV [dB(μV/m)]	Peak [dB(μV/m)]	AV [dB(μV/m)]	
N/A						No significant peaks above the noise floor

1) The measured result is below the limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95 % level of confidence. However, the result indicates that compliance is more probable than non-compliance with the specification limit.

Example calculation:

Measured level [dBμV/m] = Analyser reading [dBμV] + cable loss [dB] – preamplifier gain [dB] + antenna factor [1/m]



10. OUT OF BAND SPURIOUS EMISSIONS, CONDUCTED AT ANTENNA PORT

Date of test: 2009-07-22

EUT mode of operation: continuous TX.

Spectrum analyzer settings:

RBW: 100 kHz
 VBW: 100 kHz
 Sweep time: Auto
 Detector: Peak
 Trace: Max Hold

Channel	Plot	Results	Limit value (dBc)
Low	10.1 – 10.4	PASS	20
Middle	10.5 – 10.8	PASS	20
High	10.9 – 10.12	PASS	20


Limit: In any 100 kHz bandwidth outside the operating frequency band (2400 – 2483.5 MHz), the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.



Intertek Semko AB


Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

Plot P10.1



Date: 22.JUL.2009 08:54:03

Plot P10.2




Date: 22.JUL.2009 08:54:52



Intertek Semko AB


Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

Plot P10.3



Date: 22.JUL.2009 08:55:41

Plot P10.4




Date: 22.JUL.2009 08:57:53



Intertek Semko AB


Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

Plot P10.5



Date: 22.JUL.2009 08:58:59

Plot P10.6




Date: 22.JUL.2009 08:59:48



Intertek Semko AB


Torshamngatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

Plot P10.7



Date: 22.JUL.2009 09:01:45

Plot P10.8




Date: 22.JUL.2009 09:02:29



Intertek Semko AB


Torshamngatan 43, Box 1103, SE-164 22 Kista, Sweden
Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
Registered in Sweden: No SE556024059901, Registered office: As address

Plot P10.9



Date: 22.JUL.2009 09:10:16

Plot P10.10




Date: 22.JUL.2009 09:11:23



Intertek Semko AB


Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

Plot P10.11



Date: 22.JUL.2009 09:11:58

Plot P10.12



Date: 22.JUL.2009 09:13:06



Intertek Semko AB

Torshamngatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

11. 99% BANDWIDTH

11.1 Test protocol

Date of test: 2009-10-07

EUT mode of operation: continuous TX. Modulation on

Spectrum analyzer settings:

Span: 10 MHz
 RBW: 100 kHz
 VBW: 300 kHz
 Sweep time: Auto
 Detector: Sample
 Trace: Max Hold


Channel	Plot	Measured value MHz	Limit value MHz
Low	plot P11.1	2.44	-
Middle	plot P11.2	2.46	-
High	plot P11.3	2.48	-




Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

Plot P11.1




Plot P11.2



Intertek Semko AB

Torshammsgatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

Plot P11.3



Intertek Semko AB

Torshamngatan 43, Box 1103, SE-164 22 Kista, Sweden
 Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
 Registered in Sweden: No SE556024059901, Registered office: As address

APPENDIX – PHOTOS OF THE EUT



Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
Registered in Sweden: No SE556024059901, Registered office: As address



Intertek Semko AB

Torshamnsgatan 43, Box 1103, SE-164 22 Kista, Sweden
Telephone +46 8 750 00 00, Fax +46 8 750 60 30, www.sweden.intertek-etlsemko.com
Registered in Sweden: No SE556024059901, Registered office: As address