

Humanware QT40 Tune up Value for SAR

WIFI settings

Maximum RMS output power		
Rate	Mod.	Power limit (dBm)
1 MBps	b	18.50
2 MBps	b	18.50
5.5 Mbps	b	18.50
11 Mbps	b	18.50
6 Mbps	g	23.50
9 Mbps	g	23.50
12 Mbps	g	23.50
18Mbps	g	20.83
24 Mbps	g	20.83
36 Mbps	g	18.17
48 Mbps	g	18.17
54 Mbps	g	15.50
6.5Mbps	n (20Mhz)	23.50
13 Mbps	n (20Mhz)	21.25
19.5 Mbps	n (20Mhz)	21.25
26Mbps	n (20Mhz)	19.00
39 Mbps	n (20Mhz)	19.00
52 Mbps	n (20Mhz)	16.75
58.5 Mbps	n (20Mhz)	16.75
65 Mbps	n (20Mhz)	14.50
13.5 Mbps	n (40Mhz)	21.50
27 Mbps	n (40Mhz)	19.75
40,5 Mbps	n (40Mhz)	19.75
54 Mbps	n (40Mhz)	18.00
81 Mbps	n (40Mhz)	18.00
108 Mbps	n (40Mhz)	16.25
121.5 Mbps	n (40Mhz)	16.25
135 Mbps	n (40Mhz)	14.50

Bluetooth average output power (dBm)				
Frequency (MHz)	Channel	BDR	ERD	BLE
2402	0	6.00	9.00	6.00
2440	39	6.00	9.00	6.00
2480	98	6.00	9.00	6.00

Note: EDR3 not available