



**TEST REPORT**  
**FCC ID: XT5PGI400 IC :8670A-PGI400**  
For  
Technologies Humanware Inc.  
Prodigi Connect 12

Model No. : PGI-400

Trade Name : N/A

Prepared for : Technologies Humanware Inc.  
Address : 1800, Rue Michaud, Drumondville, Quebec, J2C 7G7, Canada

Prepared by : Shenzhen Alpha Product Testing Co., Ltd.  
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, Shenzhen,  
: Guangdong, China

Report No. : T1870080 04

Date of Receipt : January 13, 2017

Date of Test : January 13, 2017 – June 06, 2017

Date of Report : June 06, 2017

Version Number : REV0

## TABLE OF CONTENT

Description	Page
<b>1 General Information -----</b>	<b>5</b>
1.1 Description of Device (EUT) -----	5
1.2 Description of Test Facility -----	5
<b>2 EMC Equipment List -----</b>	<b>6</b>
<b>3 Test Procedure -----</b>	<b>7</b>
<b>4 Summary of Measurement -----</b>	<b>8</b>
4.1 Summary of test result -----	8
4.2 Test connection -----	8
4.3 Assistant equipment used for test -----	9
4.4 Test mode -----	9
4.5 Channel list -----	9
4.6 Test Conditions -----	9
4.7 Measurement Uncertainty (95% confidence levels, k=2) -----	10
<b>5 Spurious Emission -----</b>	<b>11</b>
5.1 Radiation Emission -----	11
5.1.1 Radiation Emission Limits(15.209) -----	11
5.1.2 Test Setup -----	11
5.1.3 Test Procedure -----	13
5.1.4 Test Equipment Setting For emission test Result -----	14
5.1.5 Test Condition -----	14
5.1.6 Test Result -----	14
<b>6 POWER LINE CONDUCTED EMISSION -----</b>	<b>26</b>
6.1 Conducted Emission Limits(15.207) -----	26
6.2 Test Setup -----	26
6.3 Test Procedure -----	27
6.4 Test Results -----	27
<b>7 Conducted Maximum Output Power -----</b>	<b>30</b>
7.1 Test limit -----	30
7.2 Test Procedure -----	30
7.3 Test Setup -----	30
7.4 Test Results -----	30
<b>8 PEAK POWER SPECTRAL DENSITY -----</b>	<b>32</b>
8.1 Test limit -----	32
8.2 Method of measurement -----	32
8.3 Test Setup -----	32
8.4 Test Results -----	33
<b>9 Bandwidth -----</b>	<b>39</b>
9.1 Test limit -----	39
9.2 Method of measurement -----	39
9.3 Test Setup -----	39
9.4 Test Results -----	39
<b>10 Band Edge Check -----</b>	<b>46</b>

10.1	Test limit-----	46
10.2	Test Procedure -----	46
10.3	Test Setup-----	46
10.4	Test Result-----	46
<b>11</b>	<b>Antenna Requirement -----</b>	<b>56</b>
11.1	Standard Requirement -----	56
11.2	Antenna Connected Construction -----	56
11.3	Result-----	56
<b>12</b>	<b>Test setup photo -----</b>	<b>57</b>
12.1	Photos of Radiated emission -----	57
12.2	Photos of Conducted Emission test -----	58
<b>13</b>	<b>Photographs of EUT -----</b>	<b>59</b>

# DECLARATION

Applicant : Technologies Humanware Inc.  
 Manufacturer : Shenzhen Minghong Technology Limited.  
 Product : Prodigy Connect 12

(A) Model No. : PGI-400

(B) Trade Name : N/A

(C) Power supply : DC 7.4V from battery or DC 5V from adapter for charging


Measurement Standard Used:

**FCC Rules and Regulations Part 15 Subpart C Section 15.247: 2016,  
ANSI C63.4:2014 RSS-247 ISSUE 2**

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....: Reak Yang   
 Project Engineer

Approved by (name + signature).....: Simple Guan   
 Project Manager

Date of issue..... : June 06, 2017

# 1 General Information

## 1.1 Description of Device (EUT)

Trade Name	: N/A
EUT	: Prodigy Connect 12
Model No.	PGI-400
DIFF.	: N/A
Antenna Type	: Integrated antenna :2.81 dBi
Operation	: IEEE 802.11b/g: 2412MHz-2462MHz
Frequency	: IEEE 802.11n HT20: 2412MHz-2462MHz
Channel number	: IEEE 802.11b/g:11Channels IEEE 802.11n HT20: 11 Channels
Modulation type	: IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n :OFDM(64QAM, 16QAM, QPSK, BPSK)
Power Supply	: DC 7.4V from battery or DC 12V from adapter for charging
Hardware Version	: X1162_V1R2 20161125
Software Version	: PGI-400_20170117_V2.0
Applicant	: Technologies Humanware Inc.
Address	: 1800, Rue Michaud, Drumondville, Quebec, J2C 7G7, Canada
Manufacturer	: Shenzhen Minghong Technology Limited.
Address	: Unit 906,South Block,Resources Tech Building,No.1 Song Ping Shan Road,High-Tech Park,Shenzhen.

## 1.2 Description of Test Facility

Shenzhen Alpha Product Testing Co., Ltd  
Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, Shenzhen, Guangdong, China

August 11, 2014 File on Federal Communication Commission  
Registration Number: 203110

July 26, 2017 Certificated by IC  
Registration Number: 12135A

## 2 EMC Equipment List

Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due to day
Bilog Antenna	SCHWARZBECK	VULB 9168	9168-438	2016.09.30	2017.09.29
Test Receiver	ROHDE&SCHWARZ	ESCI	101165	2016.09.29	2017.09.28
Spectrum analyzer	Agilent	E4407B	MY49510055	2016.09.29	2017.09.28
Horn Antenna	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D(1201)	2016.09.30	2017.09.29
Filter	KANGMAI	ZLPF-LDC- 1000-1959	1209002075	2016.09.29	2017.09.28
Filter	WAINWRIGHT	WHKX2.80 /18 G- 12SS	SN1	2016.09.29	2017.09.28
RF Cable	Resenberger	Cable 4	N/A	2016.09.29	2017.09.28
CMU200	ROHDE&SCHWARZ	CMU200	116785	2016.09.29	2017.09.28
Signal Analyzer	Agilent	N9020A	MY499100060	2016.09.29	2017.09.28
vector Signal Generator	Agilent	N5182A	MY49060042	2016.09.29	2017.09.28
vector Signal Generator	Agilent	E4438C	US44271917	2016.09.29	2017.09.28
Amplifier	HP	HP8347A	2834A00455	2016.09.29	2017.09.28
Amplifier	Teseq	LNA6901	72718	2016.09.29	2017.09.28
Amplifier	Agilent	8449B	3008A02664	2016.09.29	2017.09.28
Filter	WAINWRIGHT	WHKX1.0G /15G- 10SS	SN40	2016.09.29	2017.09.28
Test Receiver	ROHDE&SCHWARZ	ESR	1316.3003K03- 102082-Wa	2016.09.29	2017.09.28
Bilog Antenna	SCHWARZBECK	VULB 9168	9168-438	2016.09.29	2017.09.28
9*6*6 anechoic chamber	CHENYU	9*6*6	N/A	2016.7.21	2019.7.20
RF Cable	Resenberger	Cable 1	N/A	2016.09.29	2017.09.28
RF Cable	Resenberger	Cable 2	N/A	2016.09.29	2017.09.28
RF Cable	Resenberger	Cable 3	N/A	2016.09.29	2017.09.28
Power Sensor	Power Radio	RPR3006W	15100041SNO91	2016.09.29	2017.09.28
Power Sensor	Power Radio	RPR3006W	15100041SNO92	2016.09.29	2017.09.28
L.I.S.N.	SCHWARZBECK	NSLK8126	8126-466	2016.09.29	2017.09.28
L.I.S.N.	ROHDE&SCHWARZ	ENV216	101043	2016.09.29	2017.09.28
20dB Attenuator	ICPROBING	IATS1	82347	2016.09.29	2017.09.28

### 3 Test Procedure

**POWER LINE CONDUCTED INTERFERENCE:** The test procedure used was ANSI Standard ANSI C63.4:2014 using a 50 u H LISN. Both Lines were observed. The bandwidth of the receiver was 10kHz with an appropriate sweep speed. The ambient temperature of the EUT was 25°C with a humidity of 58%.

**RADIATION INTERFERENCE:** The test procedure used was ANSI Standard ANSI C63.4:2014 using a ANRITSU spectrum analyzer with a pre-selector. The analyzer was calibrated in dB above a micro volt at the output of the antenna. The resolution bandwidth was 100kHz and the video bandwidth was 300 kHz up to 1 GHz and 1 MHz with a video BW of 3MHz above 1 GHz. The ambient temperature of the EUT was 25°C with a humidity of 58%.

**FORMULA OF CONVERSION FACTORS:** The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer and cable loss. The antenna correction factors and cable loss are stated in terms of dB. The gain of the Pre-selector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF + CABLE = FS

33.20 dBuV + 10.36 dB + 0.9 dB= 44.46 dBuV/m @ 3m

**ANSI STANDARD ANSI C63.4:2014 10.1.7 MEASUREMENT PROCEDURES:** The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The EUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes. The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSI Standard ANSI C63.4:2014 10.1.7 with the EUT 40 cm from the vertical ground wall.


## 4 Summary of Measurement

### 4.1 Summary of test result

Test Item	Test Requirement	Standards Paragraph	Result
Spurious Emission	FCC PART 15 : 2016 & IC RSS-247	Section 15.247&15.209 & RSS-247 Section 5.5	Compliance
Conduction Emission	FCC PART 15 : 2016 & IC RSS Gen	Section 15.207 &7.2.4	Compliance
Bandwidth Test	FCC PART 15 : 2016 & IC RSS-247	Section 15.247 & RSS-247 5.1(2)	Compliance
Peak Power	FCC PART 15 : 2016 & IC RSS-247	Section 15.247 & RSS-247 5.4(2)	Compliance
Power Density	FCC PART 15 : 2016 & IC RSS-247	Section 15.247 & Section 5.2(2) RSS-247 ISSUE 2	Compliance
Band Edge	FCC PART 15 : 2016 & IC RSS-247	Section 15.247 & Section 5.5 RSS-247 ISSUE 2	Compliance
Antenna Requirement	FCC PART 15 : 2016 & IC RSS Gen	Section 15.203 &7.1.4 RSS-247 ISSUE 2	Compliance

Note: The EUT has been tested as an independent unit. And Continual Transmitting in maximum power (The adapter be used during Test)

### 4.2 Test connection





### 4.3 Assistant equipment used for test

Description	:	Adapter
Manufacturer	:	N/A
Model No.	:	SK03T1-1200250Z

### 4.4 Test mode

Dutycycle :100%			
Keeping TX			
Mode	data rate (Mbps)(see Note)	Channel	Frequency (MHz)
IEEE 802.11b	1	Low :CH1	2412
	1	Middle: CH6	2437
	1	High: CH11	2462
IEEE 802.11g	6	Low :CH1	2412
	6	Middle: CH6	2437
	6	High: CH11	2462
IEEE 802.11 n/HT20 with 2.4G	6.5	Low :CH1	2412
	6.5	Middle: CH6	2437
	6.5	High: CH11	2462
Note: According exploratory test, EUT will have maximum output power in those data rate. so those data rate were used for all test.			

### 4.5 Channel list

For IEEE 802.11b/g and IEEE 802.11n/HT20 with 2.4G					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
CH1	2412	CH5	2432	CH9	2452
CH2	2417	CH6	2437	CH10	2457
CH3	2422	CH7	2442	CH11	2462
CH4	2427	CH8	2447		

### 4.6 Test Conditions

Temperature range	21-25°C
Humidity range	40-75%
Pressure range	86-106kPa

## 4.7 Measurement Uncertainty (95% confidence levels, k=2)

Item	MU	Remark
Uncertainty for Power point Conducted Emissions Test	2.42dB	
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	2.13 dB	Polarize: V
	2.57dB	Polarize: H
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.54dB	Polarize: V
	4.1dB	Polarize: H
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	2.08dB	Polarize: H
	2.56dB	Polarize: V
Uncertainty for radio frequency	$1 \times 10^{-9}$	
Uncertainty for conducted RF Power	0.65dB	
Uncertainty for temperature	0.2°C	
Uncertainty for humidity	1%	
Uncertainty for DC and low frequency voltages	0.06%	

## 5 Spurious Emission

### 5.1 Radiation Emission

#### 5.1.1 Radiation Emission Limits(15.209)

Frequencies (MHz)	Field Strength (micovolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Harmonic emissions limits comply with below 54 dBuV/m at 3m. Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.

**NOTE:**


- a) The tighter limit applies at the band edges.
- b) Emission Level(dB uV/m)=20log Emission Level(Uv/m)

#### 5.1.2 Test Setup


See the next page



Below 30MHz Test Setup



Above 30MHz Test Setup



Above 1GHz Test Setup

### 5.1.3 Test Procedure

- a) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1GHz, The EUT was placed on a rotating 0.8 m high above ground, The table was rotated 360 degrees to determine the position of the highest radiation
- b) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set of make measurement.
- c) The initial step in collecting conducted emission data is a spectrum analyzer Peak detector mode pre-scanning the measurement frequency range. Significant Peaks are then marked. and then Qusia Peak Detector mode premeasured
- d) If Peak value comply with QP limit Below 1GHz. The EUT deemed to comply with QP limit. But the Peak value and average value both need to comply with applicable limit above 1GHz.
- e) For the actual test configuration, please see the test setup photo.

#### 5.1.4 Test Equipment Setting For emission test Result

9KHz~150KHz	RBW 200Hz	VBW1KHz
150KHz~30MHz	RBW 9KHz	VBW 30KHz
30MHz~1GHz	RBW 120KHz	VBW 300KHz
Above 1GHz	RBW 1MHz	VBW 3MHz

#### 5.1.5 Test Condition

Continual Transmitting in maximum power.

#### 5.1.6 Test Result

We have scanned the 9KHz from 25GHz to the EUT.  
Detailed information please see the following page.

From 9KHz to 30MHz:      Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Lab on Demand, 316100, Shenzhen, Guangdong, China

Site: LAB	Polarization: <b>Horizontal</b>	Temperature: 23.9
Limit: FCC Class B Radiation	Power: AC 120V/60Hz	Humidity: 46 %
EUT:	Distance: 3m	
M/N:		
Mode: 802.11b 2412MHz		
Note:		

**Radiated Emission Measurement**




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Antenna Height cm	Table Degree degree	Comment
1	99.8777	20.31	10.60	30.91	43.50	-12.59	peak			
2	109.7960	19.31	11.49	30.80	43.50	-12.70	peak			
3	130.3789	17.52	13.26	30.78	43.50	-12.72	peak			
4	317.7010	17.34	13.81	31.15	46.00	-14.85	peak			
5 *	492.4685	17.49	17.35	34.84	46.00	-11.16	peak			
6	731.9202	9.71	21.37	31.08	46.00	-14.92	peak			

Site: LAB	Polarization: <i>Vertical</i>	Temperature: 23.9
Limit: FCC Class B Radiation	Power: AC 120V/60Hz	Humidity: 46 %
EUT:	Distance: 3m	
M/N:		
Mode: 802.11b 2412MHz		
Note:		

**Radiated Emission Measurement**

File : Prodigy Connect 12      Data #2      Date: 2017/2/7      Time: 9:59:39



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Margin dB	Antenna Height cm	Table Degree	Detector	Comment
1	39.1616	9.36	14.21	23.57	40.00	-16.43			peak	
2 *	84.7019	24.76	9.65	34.41	40.00	-5.59			peak	
3	98.8326	25.58	10.49	36.07	43.50	-7.43			peak	
4	111.3468	25.73	11.66	37.39	43.50	-6.11			peak	
5	129.4677	19.00	13.20	32.20	43.50	-11.30			peak	
6	278.0668	17.10	12.94	30.04	46.00	-15.96			peak	

Remark: All modes and channels have been tested and only worst data of 802.11b, 2412MHz is listed in this report.



From 1G-25GHz

<b>EUT</b>	Prodigi Connect 12	<b>Model Name</b>	PGI-400
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 7.4V from battery
<b>Test Mode</b>	TX Low		

IEEE 802.11b

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1103	V	42.53	---	-11.24	31.29	---	74	54	42.71	Peak
4824	V	34.91	---	0.64	35.55	---	74	54	38.45	Peak
N/A										

<b>EUT</b>	Prodigi Connect 12	<b>Model Name</b>	PGI-400
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 7.4V from battery
<b>Test Mode</b>	TX Low		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1103	H	42.05	---	-11.24	30.81	---	74	54	43.19	Peak
4824	H	34.64	---	0.64	35.28	---	74	54	38.72	Peak
N/A										

**Notes:** AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

<b>EUT</b>	Prodigi Connect 12	<b>Model Name</b>	PGI-400
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 7.4V from battery
<b>Test Mode</b>	TX Mid		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1103	V	42.31	---	-11.24	31.07	---	74	54	42.93	Peak
4874	V	37.4	---	0.76	38.16	---	74	54	35.84	Peak

<b>EUT</b>	Prodigi Connect 12	<b>Model Name</b>	PGI-400
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 7.4V from battery
<b>Test Mode</b>	TX Mid		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1103	H	41.55	---	-11.24	30.31	---	74	54	43.69	Peak
4874	H	37.82	---	0.76	38.58	---	74	54	35.42	Peak

**Notes:** AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

<b>EUT</b>	Prodigi Connect 12	<b>Model Name</b>	PGI-400
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 7.4V from battery
<b>Test Mode</b>	TX High		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1103	V	41.45	---	-11.24	30.21	---	74	54	43.79	Peak
4924	V	32.87	---	0.87	33.74	---	74	54	40.26	Peak

<b>EUT</b>	Prodigi Connect 12	<b>Model Name</b>	PGI-400
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 7.4V from battery
<b>Test Mode</b>	TX High		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1103	H	41.86	---	-11.24	30.62	---	74	54	43.38	Peak
4924	H	31.71	---	0.87	32.58	---	74	54	41.42	Peak

**Notes:** AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

IEEE 802.11 g:

<b>EUT</b>	Prodigi Connect 12	<b>Model Name</b>	PGI-400
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 7.4V from battery
<b>Test Mode</b>	TX Low		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1145	V	42.33	---	-11.24	31.09	---	74	54	42.91	Peak
2586	V	44.4	---	-7.13	37.27	---	74	54	36.73	Peak
3062	V	42.46	---	-5.74	36.72	---	74	54	37.28	Peak
4824	V	42.06	---	0.64	42.7	---	74	54	31.3	Peak
N/A										

<b>EUT</b>	Prodigi Connect 12	<b>Model Name</b>	PGI-400
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 7.4V from battery
<b>Test Mode</b>	TX Low		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1294	H	41.67	---	-10.96	30.71	---	74	54	43.29	Peak
2038	H	41.86	---	-8.58	33.28	---	74	54	40.72	Peak
3483	H	40.76	---	-4.95	35.81	---	74	54	38.19	Peak
4824	H	39.56	---	0.64	40.2	---	74	54	33.8	Peak
N/A										

**Notes:** AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

<b>EUT</b>	Prodigi Connect 12	<b>Model Name</b>	PGI-400
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 7.4V from battery
<b>Test Mode</b>	TX Mid		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1374	V	41.86	---	-10.43	31.43	---	74	54	42.57	Peak
2589	V	42.45	---	-7.13	35.32	---	74	54	38.68	Peak
3365	V	41.83	---	-5.18	36.65	---	74	54	37.35	Peak
4874	V	41.05	---	0.76	41.81	---	74	54	32.19	Peak

<b>EUT</b>	Prodigi Connect 12	<b>Model Name</b>	PGI-400
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 7.4V from battery
<b>Test Mode</b>	TX Mid		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1321	H	41.86	---	-10.84	31.02	---	74	54	42.98	Peak
2314	H	42.56	---	-7.46	35.1	---	74	54	38.9	Peak
3577	H	40.85	---	-4.76	36.09	---	74	54	37.91	Peak
4874	H	38.56	---	0.76	39.32	---	74	54	34.68	Peak

**Notes:** AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

<b>EUT</b>	Prodigi Connect 12	<b>Model Name</b>	PGI-400
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 7.4V from battery
<b>Test Mode</b>	TX High		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1302	V	41.86	---	-10.84	31.02	---	74	54	42.98	Peak
2982	V	42.4	---	-5.86	36.54	---	74	54	37.46	Peak
3831	V	41.46	---	-3.96	37.5	---	74	54	36.5	Peak
4924	V	39.86	---	0.87	40.73	---	74	54	33.27	Peak

<b>EUT</b>	Prodigi Connect 12	<b>Model Name</b>	PGI-400
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 7.4V from battery
<b>Test Mode</b>	TX High		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1446	H	42.04	---	-10.29	31.75	---	74	54	42.25	Peak
2198	H	40.86	---	-8.24	32.62	---	74	54	41.38	Peak
3905	H	41.96	---	-3.68	38.28	---	74	54	35.72	Peak
4924	H	39.44	---	0.87	40.31	---	74	54	33.69	Peak

**Notes:** AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

## IEEE 802.11n/HT20 with 2.4G

<b>EUT</b>	Prodigi Connect 12	<b>Model Name</b>	PGI-400
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 7.4V from battery
<b>Test Mode</b>	TX Low		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1492	V	42.04	---	-10.27	31.77	---	74	54	42.23	Peak
2671	V	41.63	---	-6.94	34.69	---	74	54	39.31	Peak
3948	V	41.82	---	-3.68	38.14	---	74	54	35.86	Peak
4824	V	40.57	---	0.64	41.21	---	74	54	32.79	Peak
N/A										

<b>EUT</b>	Prodigi Connect 12	<b>Model Name</b>	PGI-400
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 7.4V from battery
<b>Test Mode</b>	TX Low		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1451	H	42.07	---	-10.27	31.8	---	74	54	42.2	Peak
2839	H	42.34	---	-6.17	36.17	---	74	54	37.83	Peak
3607	H	41.91	---	-4.52	37.39	---	74	54	36.61	Peak
4824	H	40.83	---	0.64	41.47	---	74	54	32.53	Peak
N/A										

**Notes:** AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

<b>EUT</b>	Prodigi Connect 12	<b>Model Name</b>	PGI-400
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 7.4V from battery
<b>Test Mode</b>	TX Mid		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1262	V	41.76	---	-10.96	30.8	---	74	54	43.2	Peak
2013	V	42.2	---	-8.58	33.62	---	74	54	40.38	Peak
3798	V	41.44	---	-4.07	37.37	---	74	54	36.63	Peak
4874	V	40.56	---	0.76	41.32	---	74	54	32.68	Peak

<b>EUT</b>	Prodigi Connect 12	<b>Model Name</b>	PGI-400
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 7.4V from battery
<b>Test Mode</b>	TX Mid		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1511	H	41.66	---	-10.14	31.52	---	74	54	42.48	Peak
2353	H	41.82	---	-7.59	34.23	---	74	54	39.77	Peak
3266	H	42.09	---	-5.39	36.7	---	74	54	37.3	Peak
4874	H	40.83	---	0.76	41.59	---	74	54	32.41	Peak

**Notes:** AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.



<b>EUT</b>	Prodigi Connect 12	<b>Model Name</b>	PGI-400
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 7.4V from battery
<b>Test Mode</b>	TX High		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1477	V	43.09	---	-10.27	32.82	---	74	54	41.18	Peak
2703	V	41.97	---	-6.43	35.54	---	74	54	38.46	Peak
3561	V	41.86	---	-4.76	37.1	---	74	54	36.9	Peak
4924	V	40.69	---	0.87	41.56	---	74	54	32.44	Peak

<b>EUT</b>	Prodigi Connect 12	<b>Model Name</b>	PGI-400
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 7.4V from battery
<b>Test Mode</b>	TX High		

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1503	H	41.64	---	-10.14	31.5	---	74	54	42.5	Peak
3588	H	41.94	---	-4.96	36.98	---	74	54	37.02	Peak
4153	H	41.75	---	-2.48	39.27	---	74	54	34.73	Peak
4924	H	39.8	---	0.87	40.67	---	74	54	33.33	Peak

**Notes:** AV Means AV detector test data, Peak Means Peak detector test data.

Emissions attenuated more than 20 dB below the permissible value are not reported.

## 6 POWER LINE CONDUCTED EMISSION

### 6.1 Conducted Emission Limits(15.207)


Frequency MHz	Limits dB( $\mu$ V)	
	Quasi-peak Level	Average Level
0.15 -0.50	66 -56*	56 - 46*
0.50 -5.00	56	46
5.00 -30.00	60	50

Notes: 1. \*Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3.The limit decreases in line with the logarithm of the frequency in the rang of 0.15 to 0.50 MHz.

### 6.2 Test Setup



### 6.3 Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.4:2014 on Conducted Emission Measurement. The bandwidth of test receiver is set at 9 kHz.

### 6.4 Test Results


Worse case is reported only

**PASS**

Detailed information please see the following page.

Site: LAB	Phase: <b>L1</b>	Temperature: 23.3
Limit: FCC Part 15 B QP	Power: AC 120V/60Hz	Humidity: 50 %
EUT:		
M/N:		
Mode: 802.11b 2412MHz		
Note:		


**Conducted Emission Measurement**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1500	46.03	9.73	55.76	66.00	-10.24	peak	
2	*	0.1800	44.07	9.74	54.11	64.21	-10.10	peak	
3		0.2490	40.17	9.76	49.93	61.79	-11.86	peak	
4		4.5205	30.81	10.17	40.98	56.00	-15.02	peak	
5		6.1205	27.94	10.25	38.19	60.00	-21.81	peak	
6		17.0805	23.08	10.47	33.55	60.00	-26.45	peak	

Site: LAB	Phase: <b>N</b>	Temperature: 23.3
Limit: FCC Part 15 B QP	Power: AC 120V/60Hz	Humidity: 50 %
EUT:		
M/N:		
Mode: 802.11b 2412MHz		
Note:		

**Conducted Emission Measurement**



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1500	45.27	9.73	55.00	66.00	-11.00	peak	
2	*	0.1680	44.69	9.73	54.42	65.06	-10.64	peak	
3		0.2490	38.07	9.76	47.83	61.79	-13.96	peak	
4		4.3605	33.67	10.16	43.83	56.00	-12.17	peak	
5		6.1605	27.72	10.25	37.97	60.00	-22.03	peak	
6		16.6405	25.00	10.47	35.47	60.00	-24.53	peak	

Remark: All modes and channels have been tested and only worst data of 802.11b, 2412MHz is listed in this report.

## 7 Conducted Maximum Output Power

### 7.1 Test limit

Please refer section 15.247.

Regulation 15.247(b) The limit of Maximum Peak Output Power Measurement is 1W(30dBm)

### 7.2 Test Procedure

Details see the KDB558074 D01 DTS Meas Guidance v4


7.2.1 Place the EUT on the table and set it in transmitting mode.

7.2.2 Connected the EUT's antenna port to peak power meter by 20dB attenuator.

7.2.3 Measure out each mode and each bands peak output power of EUT.

Note: The cable loss and attenuator loss were offset into measure device as amplitude offset.

### 7.3 Test Setup



### 7.4 Test Results

**PASS**

Detailed information please see the following page.

EUT: Prodigy Connect 12		M/N: PGI-400		
Test date: 2017-04-21		Test site: RF site		Tested by: Eric Huang
Mode	Frequency (MHz)	PK Output power(dBm)	Limit (dBm)	Result
IEEE 802.11 b	CH1: 2412	14.89	30	Pass
	CH6: 2437	14.57	30	Pass
	CH11: 2462	15.18	30	Pass
IEEE 802.11 g	CH1: 2412	12.82	30	Pass
	CH6: 2437	12.39	30	Pass
	CH11: 2462	12.57	30	Pass
IEEE 802.11 n/HT20 with 2.4G	CH1: 2412	12.34	30	Pass
	CH6: 2437	12.41	30	Pass
	CH11: 2462	12.05	30	Pass
Conclusion: PASS				

## 8 PEAK POWER SPECTRAL DENSITY

### 8.1 Test limit

8.1.1 Please refer section 15.247.

8.1.2 For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

8.1.3 The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

### 8.2 Method of measurement

Details see the KDB558074 D01 DTS Meas Guidance v4

8.2.1 Place the EUT on the table and set it in transmitting mode.


8.2.2 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

8.2.3 Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, span=1.5\*DTS BW, detail see the test plot.

8.2.4 Record the max reading.

8.2.5 Repeat the above procedure until the measurements for all frequencies are completed.

### 8.3 Test Setup






## 8.4 Test Results

EUT: Prodigy Connect 12		M/N: PGI-400		
Test date: 2017-04-21		Test site: RF site		Tested by: Eric Huang
Mode	Frequency (MHz)	PK Output power(dBm)	Limit (dBm)	Result
IEEE 802.11 b	CH1: 2412	-5.551	8	PASS
	CH6: 2437	-5.818	8	PASS
	CH11: 2462	-6.339	8	PASS
IEEE 802.11 g	CH1: 2412	-14.318	8	PASS
	CH6: 2437	-12.113	8	PASS
	CH11: 2462	-10.521	8	PASS
IEEE 802.11 n/HT20 with 2.4G	CH1: 2412	-15.100	8	PASS
	CH6: 2437	-12.913	8	PASS
	CH11: 2462	-13.269	8	PASS
Conclusion: PASS				

IEEE 802.11b :  
CH Low :




CH Mid:




CH Hig:




IEEE 802.11g :  
CH Low




CH Mid:




CH High:




IEEE 802.11n HT20 :  
CH Low :



CH Mid:



CH Hig:



## 9 Bandwidth

### 9.1 Test limit

Please refer section 15.247


For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz.

### 9.2 Method of measurement

Details see the KDB558074 D01 DTS Meas Guidance v04

- a) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.
- b) The test receiver set RBW = 100kHz, VBW=300kHz, Peak Detector, Sweep time set auto, detail see the test plot.

### 9.3 Test Setup



### 9.4 Test Results


PASS.

Detailed information please see the following page.


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit (MHz)	Result
IEEE 802.11b:					
Low	2412	9.551	13.215	>0.5	PASS
Mid	2437	10.06	13.439	>0.5	PASS
High	2462	10.05	13.332	>0.5	PASS
IEEE 802.11g					
Low	2412	15.18	16.402	>0.5	PASS
Mid	2437	15.16	16.439	>0.5	PASS
High	2462	15.55	16.410	>0.5	PASS
IEEE 802.11n/HT20:					
Low	2412	15.17	17.560	>0.5	PASS
Mid	2437	15.13	17.598	>0.5	PASS
High	2462	17.06	17.583	>0.5	PASS




IEEE 802.11b:  
CH Low :



CH Mid :




CH High :




IEEE 802.11g:


CH Low :



CH Mid:




CH Hig:




IEEE 802.11n HT20:


CH Low :



CH Mid :



CH High :



## 10 Band Edge Check

### 10.1 Test limit

Please refer section 15.247

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz and 5725MHz to 5850MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

### 10.2 Test Procedure

12.2.1 Put the EUT on a 0.8m high table, power on the EUT. Emissions were scanned and measured rotating the EUT to 360 degrees, Find the maximum Emission

12.2.2 Check the spurious emissions out of band.

12.2.3 RBW 1MHz ,VBW 3MHz ,peak detector for peak value , RBW 1MHz ,VBW 3MHz , RMS detector for AV value.

### 10.3 Test Setup

Same as 5.2.2.

### 10.4 Test Result

PASS.

Detailed information please see the following page.

Radiated Method:  
IEEE 802.11b CH LOW

Band Edge Test result								
EUT: Prodigy Connect 12				M/N: PGI-400				
Power: DC 7.4V from battery								
Test date: 2017-04-21 Test site: 3m Chamber Tested by: Store								
Test mode: TX Low								
Antenna polarity: Vertical								
Freq (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2390	43.57	27.62	3.92	34.97	40.14	74	33.86	<b>PK</b>
2390	--	27.62	3.92	34.97	--	54	--	AV
Antenna Polarity: Horizontal								
2390	42.2	27.62	3.92	34.97	38.77	74	35.23	<b>PK</b>
2390	--	27.62	3.92	34.97	--	54	--	AV
Note:								
1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK								
2, Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: RMS								
3, Result = Read level + Antenna factor + cable loss-Amp factor								
4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.								

## IEEE 802.11b CH High

Band Edge Test result								
EUT: Prodigy Connect 12				M/N: PGI-400				
Power: DC 7.4V from battery								
Test date: 2017-04-21 Test site: 3m Chamber Tested by: Store								
Test mode: TX High								
Antenna polarity: Vertical								
Freq (MHz)	Read Level (dBUV/m)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
2483.5	43.41	27.89	4	34.97	40.33	74	33.67	<b>PK</b>
2483.5	--	27.89	4	34.97	--	54	--	<b>AV</b>
Antenna Polarity: Horizontal								
2483.5	42.61	27.89	4	34.97	39.53	74	34.47	<b>PK</b>
2483.5	--	27.89	4	34.97	--	54	--	<b>AV</b>
Note:								
1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK								
2, Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: RMS								
3, Result = Read level + Antenna factor + cable loss-Amp factor								
4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.								



## IEEE 802.11g CH LOW

Band Edge Test result								
EUT: Prodigy Connect 12				M/N: PGI-400				
Power: DC 7.4V from battery								
Test date: 2017-04-21 Test site: 3m Chamber Tested by: Store								
Test mode: TX Low								
Antenna polarity: Vertical								
Freq (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2390	42.07	27.62	3.92	34.97	38.64	74	35.36	<b>PK</b>
2390	--	27.62	3.92	34.97	--	54	--	<b>AV</b>
Antenna Polarity: Horizontal								
2390	43.02	27.62	3.92	34.97	39.59	74	34.41	<b>PK</b>
2390	--	27.62	3.92	34.97	--	54	--	<b>AV</b>
Note:								
1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK								
2, Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: RMS								
3, Result = Read level + Antenna factor + cable loss-Amp factor								
4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.								

## IEEE 802.11g CH High

Band Edge Test result								
EUT: Prodigy Connect 12				M/N: PGI-400				
Power: DC 7.4V from battery								
Test date: 2017-04-21 Test site: 3m Chamber Tested by: Store								
Test mode: TX High								
Antenna polarity: Vertical								
Freq (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2483.5	42.54	27.89	4	34.97	39.46	74	34.54	<b>PK</b>
2483.5		--	--	--	--	54	--	<b>AV</b>
Antenna Polarity: Horizontal								
2483.5	42.76	27.89	4	34.97	39.68	74	34.32	<b>PK</b>
2483.5		--	--	--	--	54	--	<b>AV</b>
Note:								
1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK								
2, Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: RMS								
3, Result = Read level + Antenna factor + cable loss-Amp factor								
4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.								


IEEE 802.11n HT20 CH Low

Band Edge Test result								
EUT: Prodigy Connect 12				M/N: PGI-400				
Power: DC 7.4V from battery								
Test date: 2017-04-21 Test site: 3m Chamber Tested by: Store								
Test mode: TX Low								
Antenna polarity: Vertical								
Freq (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2390	42.84	27.62	3.92	34.97	39.41	74	34.59	<b>PK</b>
2390	--	27.62	3.92	34.97	--	54	--	<b>AV</b>
Antenna Polarity: Horizontal								
2390	43.16	27.62	3.92	34.97	39.73	74	34.27	<b>PK</b>
2390	--	27.62	3.92	34.97	--	54	--	<b>AV</b>
Note:								
1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK								
2, Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: RMS								
3, Result = Read level + Antenna factor + cable loss-Amp factor								
4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.								


## IEEE 802.11n HT20 CH High

Band Edge Test result								
EUT: Prodigy Connect 12				M/N: PGI-400				
Power: DC 7.4V from battery								
Test date: 2017-04-21 Test site: 3m Chamber Tested by: Store								
Test mode: TX High								
Antenna polarity: Vertical								
Freq (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
2483.5	42.25	27.89	4	34.97	39.17	74	34.83	PK
2483.5		--	--	--	--	54	--	AV
Antenna Polarity: Horizontal								
2483.5	42.69	27.89	4	34.97	39.61	74	34.39	PK
2483.5		--	--	--	--	54	--	AV
Note:								
1, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK								
2, Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: RMS								
3, Result = Read level + Antenna factor + cable loss-Amp factor								
4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.								



802.11b



802.11g



802.11n HT20



## 11 Antenna Requirement

### 11.1 Standard Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 11.2 Antenna Connected Construction

The antenna connector is unique antenna and no consideration of replacement. Please see EUT photo for details.

### 11.3 Result

The EUT antenna is unique Antenna. It comply with the standard requirement.




## 12 Test setup photo


### 12.1 Photos of Radiated emission




12.2 Photos of Conducted Emission test





### 13 Photographs of EUT















-----END OF THE REPORT-----