

Test report

234511-5TRFWL

Date of issue: February 11, 2015

Applicant:

Technologies Humanware inc.

Product:

Prodigi

Model:

PGITAB

FCC ID:

XT5PGITAB

IC Registration number:


8670A-PGITAB

Specifications:

- ◆ **FCC 47 CFR Part 15 Subpart C, §15.247**
Operation in the 902–928 MHz, 2400–2483.5 MHz, 5725–5850 MHz
- ◆ **RSS-210, Issue 8, December 2010, Annex 8**
Frequency Hopping and Digital Modulation Systems Operating in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz Bands

Test location

Company name:	Nemko Canada Inc.
Address:	303 River Road
City:	Ottawa
Province:	Ontario
Postal code:	K1V 1H2
Country:	Canada
Telephone:	+1 613 737 9680
Facsimile:	+1 613 737 9691
Toll free:	+1 800 563 6336
Website:	www.nemko.com
Site number:	FCC: 176392; IC: 2040A-4 (3 m semi anechoic chamber)

Tested by:	Andrey Adelberg, Senior Wireless/EMC Specialist
Reviewed by:	Kevin Rose, Wireless/EMC Specialist
Date:	February 11, 2015
Signature:	

Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contain in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Copyright notification

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. © Nemko Canada Inc.

Table of contents

Table of contents	3
Section 1. Report summary	4
1.1 Applicant and manufacturer	4
1.2 Test specifications	4
1.3 Test methods.....	4
1.4 Statement of compliance	4
1.5 Exclusions.....	4
1.6 Test report revision history	4
Section 2. Summary of test results	5
2.1 FCC Part 15 Subpart C, general requirements test results.....	5
2.2 FCC Part 15 Subpart C, intentional radiators test results.....	5
2.3 IC RSS-GEN, Issue 4, test results	5
2.4 IC RSS-210, Issue 8, test results	6
Section 3. Equipment under test (EUT) details	7
3.1 Sample information.....	7
3.2 EUT information	7
3.3 Technical information	7
3.4 Product description and theory of operation	7
3.5 EUT exercise details.....	8
3.6 EUT sub assemblies	8
Section 4. Engineering considerations	9
4.1 Modifications incorporated in the EUT.....	9
4.2 Technical judgment.....	9
4.3 Deviations from laboratory tests procedures.....	9
Section 5. Test conditions	10
5.1 Atmospheric conditions	10
5.2 Power supply range.....	10
Section 6. Measurement uncertainty	11
6.1 Uncertainty of measurement	11
Section 7. Test equipment	12
7.1 Test equipment list.....	12
Section 8. Testing data	13
8.1 FCC 15.207(a) and RSS-Gen 8.8 AC power line conducted emissions limits	13
8.2 FCC 15.247(a)(2) and RSS-210 A8.2(a) Minimum 6 dB bandwidth for systems using digital modulation techniques	16
8.3 FCC 15.247(b) and RSS-210 A8.4 (4) Transmitter output power and e.i.r.p. requirements	18
8.4 FCC 15.247(d) and RSS-210 A8.5 Spurious (out-of-band) emissions.....	21
8.5 FCC 15.247(e) and RSS-210 A8.2(b) Power spectral density for digitally modulated devices.....	28
Section 9. Block diagrams of test set-ups	30
9.1 Radiated emissions set-up.....	30
9.2 Conducted emissions set-up	30

Section 1. Report summary

1.1 Applicant and manufacturer

Company name	Technologies Humanware inc.
Address	1800, rue Michaud
City	Drummondville
Province/State	Québec
Postal/Zip code	J2C 7G7
Country	Canada

1.2 Test specifications

FCC 47 CFR Part 15, Subpart C, Clause 15.247	Operation in the 902–928 MHz, 2400–2483.5 MHz, 5725–5850 MHz
RSS-210, Issue 8 Annex 8	Frequency Hopping and Digital Modulation Systems Operating in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz Bands

1.3 Test methods

558074 D01 DTS Meas Guidance v03r02 (June 5, 2014)	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247
ANSI C64.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

1.4 Statement of compliance

In the configuration tested, the EUT was found compliant.

Testing was completed against all relevant requirements of the test standard. Results obtained indicate that the product under test complies in full with the requirements tested. The test results relate only to the items tested.

See “Summary of test results” for full details.

1.5 Exclusions

None

1.6 Test report revision history

Revision #	Details of changes made to test report
TRF	Original report issued

Section 2. Summary of test results

2.1 FCC Part 15 Subpart C, general requirements test results

Part	Test description	Verdict
§15.207(a)	Conducted limits	Pass
§15.31(e)	Variation of power source	Pass ¹
§15.203	Antenna requirement	Pass ²

Notes: ¹ Measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, was performed with the supply voltage varied between 85 % and 115 % of the nominal rated supply voltage. No noticeable output power variation was observed

² The Antennas are located within the enclosure of EUT and not user accessible.

2.2 FCC Part 15 Subpart C, intentional radiators test results

Part	Test description	Verdict
§15.247(a)(1)(i)	Frequency hopping systems operating in the 902–928 MHz band	Not applicable
§15.247(a)(1)(ii)	Frequency hopping systems operating in the 5725–5850 MHz band	Not applicable
§15.247(a)(1)(iii)	Frequency hopping systems operating in the 2400–2483.5 MHz band	Not applicable
§15.247(a)(2)	Minimum 6 dB bandwidth for systems using digital modulation techniques	Pass
§15.247(b)(1)	Maximum peak output power of frequency hopping systems operating in the 2400–2483.5 MHz band and 5725–5850 MHz band	Not applicable
§15.247(b)(2)	Maximum peak output power of Frequency hopping systems operating in the 902–928 MHz band	Not applicable
§15.247(b)(3)	Maximum peak output power of systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands	Pass
§15.247(c)(1)	Fixed point-to-point operation with directional antenna gains greater than 6 dBi	Not applicable
§15.247(c)(2)	Transmitters operating in the 2400–2483.5 MHz band that emit multiple directional beams	Not applicable
§15.247(d)	Spurious emissions	Pass
§15.247(e)	Power spectral density for digitally modulated devices	Pass
§15.247(f)	Time of occupancy for hybrid systems	Not applicable

2.3 IC RSS-GEN, Issue 4, test results

Part	Test description	Verdict
7.1.2	Receiver radiated emission limits	Not applicable
7.1.3	Receiver conducted emission limits	Not applicable
8.8	Power Line Conducted Emissions Limits for Licence-Exempt Radio Apparatus	Pass

Notes: ¹ According to sections 5.2 and 5.3 of RSS-Gen, Issue 4 the EUT does not have a stand-alone receiver neither scanner receiver, therefore exempt from receiver requirements.

2.4 IC RSS-210, Issue 8, test results

Part	Test description	Verdict
A8.1	Frequency hopping systems	
A8.1 (a)	Bandwidth of a frequency hopping channel	Not applicable
A8.1 (b)	Minimum channel spacing for frequency hopping systems	Not applicable
A8.1 (c)	Frequency hopping systems operating in the 902–928 MHz band	Not applicable
A8.1 (d)	Frequency hopping systems operating in the 2400–2483.5 MHz band	Not applicable
A8.1 (e)	Frequency hopping systems operating in the 5725–5850 MHz band	Not applicable
A8.2	Digital modulation systems	
A8.2 (a)	Minimum 6 dB bandwidth	Pass
A8.2 (b)	Maximum power spectral density	Pass
A8.3	Hybrid systems	
A8.3 (1)	Digital modulation turned off	Not applicable
A8.3 (2)	Frequency hopping turned off	Not applicable
A8.4	Transmitter output power and e.i.r.p. requirements	
A8.4 (1)	Frequency hopping systems operating in the 902–928 MHz band	Not applicable
A8.4 (2)	Frequency hopping systems operating in the 2400–2483.5 MHz band	Not applicable
A8.4 (3)	Frequency hopping systems operating in the 5725–5850 MHz	Not applicable
A8.4 (4)	Systems employing digital modulation techniques	Pass
A8.4 (5)	Point-to-point systems in 2400–2483.5 MHz and 5725–5850 MHz band	Not applicable
A8.4 (6)	Transmitters which operate in the 2400–2483.5 MHz band with multiple directional beams	Not applicable
A8.5	Out-of-band emissions	Pass

Notes: None

Section 3. Equipment under test (EUT) details

3.1 Sample information

Receipt date	July 15, 2013
Nemko sample ID number	1 and 2

3.2 EUT information

Product name	Prodigi
Model	PGITAB
Serial number	N/A

3.3 Technical information

Applicant IC company number	8670A
IC UPN number	PGITAB
All used IC test site(s) Reg. number	2040A
RSS number and Issue number	RSS-210 Annex 8, Issue 8, December 2010
Frequency band	2400–2483.5 MHz
Frequency Min (MHz)	2402 MHz
Frequency Max (MHz)	2480 MHz
RF power Min (W), Conducted	0.0019 W (2.78 dBm)
RF power Max (W), Conducted	0.0022 W (3.36 dBm)
Field strength, Units @ distance	N/A
Measured BW (kHz) (6 dB)	693.8 kHz
Calculated BW (kHz), as per TRC-43	N/A
Type of modulation	GFSK
Emission classification (F1D, G1D, D1D)	F1D
Transmitter spurious, Units @ distance	4884 MHz: 52.67 dB μ V/m average at 3 m
Power requirements	120–240 VAC, 47–63 Hz
Hardware version	PGI-100 PCBA-2.0.19
Software version	1.0.2.2170
Antenna information	Ethertronics M310210-1K, –1.3 dBi gain antenna The EUT uses a unique antenna coupling/ non-detachable antenna to the intentional radiator.

3.4 Product description and theory of operation

The EUT is an intelligent video magnifier. It features a handheld unit with a BLE capability and a docking base station. It can be used as a mobile magnifier with a 5 inches touch screen LCD viewer running on battery.

It has lighting LEDs and a set of 2 cameras for close or far viewing.

It has text to speech capacity from any grabbed text source.

A fixed docking station provides a stable illuminated surface of viewing with no mobile part.

It is also used as for monitor support, battery charging, audio and USB connection.

The base provides a touch surface and 3 control buttons for user interface.

3.5 EUT exercise details

A software application running on a laptop PC has been provided to control directly the BT module via USB cable. 1 radiated sample and 1 conducted sample have been provided

3.6 EUT sub assemblies

Table 3.6-1: EUT sub assemblies

Description	Brand name	Model/Part number	Serial number
Prodigi docking station	Prodigi	-	-
Power supply Brick	MEGA	ATS090-P190	-
Mouse	Comfort Mouse	4500/X821912-005	-
Ear buds	-	-	-

Section 4. Engineering considerations

4.1 Modifications incorporated in the EUT

There were no modifications performed to the EUT during this assessment.

4.2 Technical judgment

None

4.3 Deviations from laboratory tests procedures

No deviations were made from laboratory procedures.

Section 5. Test conditions

5.1 Atmospheric conditions

Temperature	15–30 °C
Relative humidity	20–75 %
Air pressure	860–1060 mbar

When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.

5.2 Power supply range

The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages $\pm 5\%$, for which the equipment was designed.

Section 6. Measurement uncertainty

6.1 Uncertainty of measurement

Measurement uncertainty budgets for the tests are detailed below. Measurement uncertainty calculations assume a coverage factor of $K = 2$ with 95% certainty.

Test name	Measurement uncertainty, dB
All antenna port measurements	0.55
Conducted spurious emissions	1.13
Radiated spurious emissions	3.78
AC power line conducted emissions	3.55

Section 7. Test equipment

7.1 Test equipment list

Table 7.1-1: Equipment list

Equipment	Manufacturer	Model no.	Asset no.	Cal cycle	Next cal.
3 m EMI test chamber	TDK	SAC-3	FA002047	1 year	Mar. 18/15
Flush mount turntable	Sunol	FM2022	FA002082	—	NCR
Controller	Sunol	SC104V	FA002060	—	NCR
Antenna mast	Sunol	TLT2	FA002061	—	NCR
Power source	California Instruments	3001i	FA001021	1 year	June 27/15
Receiver/spectrum analyzer	Rohde & Schwarz	ESU 26	FA002043	1 year	Jan. 07/16
Bilog antenna (20–3000 MHz)	Sunol	JB3	FA002108	1 year	Mar. 12/15
Horn antenna (1–18 GHz)	EMCO	3115	FA000825	1 year	Mar. 10/15
Pre-amplifier (1–18 GHz)	JCA	JCA118-503	FA002091	1 year	June 23/15
Horn antenna (18–26.5 GHz)	Electro-metrics	SH-50/60-1	FA000479	—	VOU
Pre-amplifier (18–26 GHz)	Narda	BBS-1826N612	FA001550	—	VOU
LISN	Rohde & Schwarz	ENV216	FA002514	1 year	July 11/15
Spectrum analyzer	Rohde & Schwarz	FSU	FA001877	1 year	Jan. 27/15

Note: NCR - no calibration required, VOU - verify on use

Section 8. Testing data

8.1 FCC 15.207(a) and RSS-Gen 8.8 AC power line conducted emissions limits

8.1.1 Definitions and limits

FCC:

Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

IC:

A radio apparatus that is designed to be connected to the public utility (AC) power line shall ensure that the radio frequency voltage, which is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz, shall not exceed the limits in table below.

Unless the requirements applicable to a given device state otherwise, for any radio apparatus equipped to operate from the public utility AC power supply either directly or indirectly (such as with a battery charger), the radio frequency voltage of emissions conducted back onto the AC power lines in the frequency range of 0.15 MHz to 30 MHz shall not exceed the limits shown in table below. The more stringent limit applies at the frequency range boundaries.

Table 8.1-1: Conducted emissions limit

Frequency of emission, MHz	Conducted limit, dB μ V	
	Quasi-peak	Average**
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

Note: * - The level decreases linearly with the logarithm of the frequency.

** - A linear average detector is required.

8.1.2 Test summary

Test date:	January 16, 2015	Temperature:	22 °C
Test engineer:	Andrey Adelberg	Air pressure:	1003 mbar
Verdict:	Pass	Relative humidity:	32 %

8.1.3 Observations, settings and special notes

The EUT was set up as tabletop configuration.

The spectral scan has been corrected with transducer factors (i.e. cable loss, LISN factors, and attenuators) for determination of compliance.

A preview measurement was generated with the receiver in continuous scan mode. Emissions detected within 6 dB or above limit were re-measured with the appropriate detector against the correlating limit and recorded as the final measurement.

Measurement Uncertainty = 1.7 dB


Receiver settings for preview measurements:

Resolution bandwidth:	9 kHz
Video bandwidth:	30 kHz
Detector mode:	Peak and Average
Trace mode:	Max Hold
Measurement time:	1000 ms

Receiver settings for final measurements:


Resolution bandwidth:	9 kHz
Video bandwidth:	30 kHz
Detector mode:	Quasi-Peak and Average
Trace mode:	Max Hold
Measurement time:	1000 ms

8.1.4 Test data



NEX-234511 120 Vac 60 Hz Phase scan
— CISPR 22 Mains QP Class B
- - - CISPR 22 Mains AV Class B
— Preview Result 1-PK+
— Preview Result 2-AVG

Plot 8.1-1: Conducted emissions on phase line



NEX-234511 120 Vac 60 Hz Neutral scan
— CISPR 22 Mains QP Class B
- - - CISPR 22 Mains AV Class B
— Preview Result 1-PK+
— Preview Result 2-AVG

Plot 8.1-2: Conducted emissions on neutral line

Section 8 Testing data
Test name FCC 15.247(a)(2) and RSS-210 A8.2(a) Minimum 6 dB bandwidth for systems using digital modulation techniques
Specification FCC 15 Subpart C and RSS-210, Issue 8



8.2 FCC 15.247(a)(2) and RSS-210 A8.2(a) Minimum 6 dB bandwidth for systems using digital modulation techniques

8.2.1 Definitions and limits

FCC and IC:

- (a) Operation under the provisions of this Section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:
- (2) Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.2.2 Test summary

Test date:	January 16, 2015	Temperature:	23 °C
Test engineer:	Andrey Adelberg	Air pressure:	1003 mbar
Verdict:	Pass	Relative humidity:	32 %

8.2.3 Observations, settings and special notes

Spectrum analyser settings:

Resolution bandwidth:	100 kHz
Video bandwidth:	≥3 × RBW
Frequency span:	2 MHz
Detector mode:	Peak
Trace mode:	Max Hold

8.2.4 Test data

Table 8.2-1: 6 dB bandwidth results

Frequency, MHz	6 dB bandwidth, kHz	Minimum limit, kHz	Margin, kHz
2402	688.8	500.0	188.8
2442	693.8	500.0	193.8
2480	691.2	500.0	191.2

Section 8


Test name

Specification

Testing data


FCC 15.247(a)(2) and RSS-210 A8.2(a) Minimum 6 dB bandwidth for systems using digital modulation techniques

FCC 15 Subpart C and RSS-210, Issue 8




Date: 16.JAN.2015 14:30:07

Figure 8.2-1: 6 dB bandwidth on low channel



Date: 16.JAN.2015 14:13:50

Figure 8.2-2: 6 dB bandwidth on mid channel



Date: 16.JAN.2015 14:25:47

Figure 8.2-3: 6 dB bandwidth on high channel

8.3 FCC 15.247(b) and RSS-210 A8.4 (4) Transmitter output power and e.i.r.p. requirements

8.3.1 Definitions and limits

FCC:

- (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:
- (3) For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 W (30 dBm). As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
 - (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
 - (i) Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Fixed, point-to-point operation, as used in paragraphs (b)(3)(i) and (b)(3)(ii) of this section, excludes the use of point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.

- (c) Operation with directional antenna gains greater than 6 dBi.
- (2) In addition to the provisions in paragraphs (b)(1), (b)(3), (b)(4) and (c)(1)(i) of this section, transmitters operating in the 2400–2483.5 MHz band that emit multiple directional beams, simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers provided the emissions comply with the following:
 - (i) Different information must be transmitted to each receiver.
 - (ii) If the transmitter employs an antenna system that emits multiple directional beams but does not do emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device, i.e., the sum of the power supplied to all antennas, antenna elements, staves, etc. and summed across all carriers or frequency channels, shall not exceed the limit specified in paragraph (b)(1) or (b)(3) of this section, as applicable. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as follows:
 - (A) The directional gain shall be calculated as the sum of 10 log (number of array elements or staves) plus the directional gain of the element or staff having the highest gain.

IC:
A8.4 (4) Transmitter Output Power and e.i.r.p. Requirements for systems employing digital modulation techniques operating in the bands 902–928 MHz, 2400–2483.5 MHz and 5725–5850 MHz bands

For systems employing digital modulation techniques operating in the bands 902–928 MHz, 2400–2483.5 MHz and 5725–5850 MHz, the maximum peak conducted output power shall not exceed 1 W. Except as provided in Section A8.4(5), the e.i.r.p. shall not exceed 4 W. As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power (see RSS-Gen).

8.3.2 Test summary

Test date:	January 16, 2015	Temperature:	22 °C
Test engineer:	Andrey Adelberg	Air pressure:	1003 mbar
Verdict:	Pass	Relative humidity:	32 %

8.3.3 Observations, settings and special notes


The test was performed according to DTS guidelines section 9.1.1: Maximum peak conducted output power using spectrum analyzer with RBW \geq DTS bandwidth. Spectrum analyzer settings:

Resolution bandwidth:	1 MHz
Video bandwidth:	$\geq 3 \times$ RBW
Frequency span:	5 MHz
Detector mode:	Peak
Trace mode:	Max Hold

8.3.4 Test data


Table 8.3-1: Output power measurements results

Frequency, MHz	Conducted output power, dBm		Margin, dB	Antenna gain, dBi	EIRP, dBm	EIRP limit, dBm	EIRP margin, dB
	Measured	Limit					
2402	2.78	30.00	27.22	-1.30	1.48	36.00	34.52
2440	3.22	30.00	26.78	-1.30	1.92	36.00	34.08
2480	3.36	30.00	26.64	-1.30	2.06	36.00	33.94



Date: 16.JAN.2015 14:11:50

Figure 8.3-1: Peak output power on low channel




Date: 16.JAN.2015 14:13:10

Figure 8.3-2: Peak output power on mid channel

Section 8
Test name
Specification

Testing data
FCC 15.247(b) and RSS-210 A8.4 (4) Transmitter output power and e.i.r.p. requirements
FCC Part 15 Subpart C and RSS-210, Issue 8



Date: 16.JAN.2015 14:32:40

Figure 8.3-3: Peak output power on high channel

8.4 FCC 15.247(d) and RSS-210 A8.5 Spurious (out-of-band) emissions

8.4.1 Definitions and limits

FCC:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

IC:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the radio frequency power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under Section A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Tables 2 and 3 is not required.

Table 8.4-1: FCC §15.209 and RSS-Gen – Radiated emission limits

Frequency, MHz	Field strength of emissions		Measurement distance, m
	µV/m	dBµV/m	
0.009–0.490	2400/F	$67.6 - 20 \times \log_{10}(F)$	300
0.490–1.705	24000/F	$87.6 - 20 \times \log_{10}(F)$	30
1.705–30.0	30	29.5	30
30–88	100	40.0	3
88–216	150	43.5	3
216–960	200	46.0	3
above 960	500	54.0	3

Notes: In the emission table above, the tighter limit applies at the band edges.

For frequencies above 1 GHz the limit on peak RF emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test

Table 8.4-2: IC restricted frequency bands

MHz	MHz	MHz	GHz
0.090–0.110	12.51975–12.52025	399.9–410	5.35–5.46
2.1735–2.1905	12.57675–12.57725	608–614	7.25–7.75
3.020–3.026	13.36–13.41	960–1427	8.025–8.5
4.125–4.128	16.42–16.423	1435–1626.5	9.0–9.2
4.17725–4.17775	16.69475–16.69525	1645.5–1646.5	9.3–9.5
4.20725–4.20775	16.80425–16.80475	1660–1710	10.6–12.7
5.677–5.683	25.5–25.67	1718.8–1722.2	13.25–13.4
6.215–6.218	37.5–38.25	2200–2300	14.47–14.5
6.26775–6.26825	73–74.6	2310–2390	15.35–16.2
6.31175–6.31225	74.8–75.2	2655–2900	17.7–21.4
8.291–8.294	108–138	3260–3267	22.01–23.12
8.362–8.366	156.52475–156.52525	3332–3339	23.6–24.0
8.37625–8.38675	156.7–156.9	3345.8–3358	31.2–31.8
8.41425–8.41475	240–285	3500–4400	36.43–36.5
12.29–12.293	322–335.4	4500–5150	Above 38.6

Note: Certain frequency bands listed in Table 8.4-2 and above 38.6 GHz are designated for low-power licence-exempt applications. These frequency bands and the requirements that apply to the devices are set out in this Standard

Table 8.4-3: FCC restricted frequency bands

MHz	MHz	MHz	GHz
0.090–0.110	16.42–16.423	399.9–410	4.5–5.15
0.495–0.505	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225	123–138	2200–2300	14.47–14.5
8.291–8.294	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675	156.7–156.9	2690–2900	22.01–23.12
8.41425–8.41475	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025	240–285	3345.8–3358	36.43–36.5
12.57675–12.57725	322–335.4	3600–4400	Above 38.6
13.36–13.41			

8.4.2 Test summary

Test date:	January 16, 2015	Temperature:	22 °C
Test engineer:	Andrey Adelberg	Air pressure:	1003 mbar
Verdict:	Pass	Relative humidity:	32 %

8.4.3 Observations, settings and special notes

The spectrum was searched from 30 MHz to the 10th harmonic.
 Since fundamental power was tested using peak method, the outside restricted bands spurious emissions limit is –20 dBc/100 kHz.
 Radiated spurious emissions (cabinet radiation test) within restricted bands were performed with antenna port terminated with the 50 Ω load.

Spectrum analyser settings for radiated measurements within restricted bands below 1 GHz:

Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Detector mode:	Peak
Trace mode:	Max Hold

Spectrum analyser settings for peak radiated measurements within restricted bands above 1 GHz:

Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Detector mode:	Peak
Trace mode:	Max Hold

Spectrum analyser settings for average radiated measurements within restricted bands above 1 GHz:

Resolution bandwidth:	1 MHz
Video bandwidth:	10 Hz
Detector mode:	Peak
Trace mode:	Max Hold

8.4.3 Observations, settings and special notes, continued

Spectrum analyser settings for conducted spurious emissions measurements:

Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Detector mode:	Peak
Trace mode:	Max Hold

Conducted inside-restricted-bands limit calculations.

Peak limit: $74 \text{ dB}\mu\text{V/m} - 95.23 \text{ dB} - (-1.3 \text{ dBi}) = -19.93 \text{ dBm}$


Average limit: $54 \text{ dB}\mu\text{V/m} - 95.23 \text{ dB} - (-1.3 \text{ dBi}) = -39.93 \text{ dBm}$

8.4.4 Test data

Table 8.4-4: Radiated field strength measurement results


Frequency, MHz	Quasi-Peak Field strength, dB $\mu\text{V/m}$	Limit, dB $\mu\text{V/m}$	Margin, dB
101.670	35.5	40.5	5.0
106.050	38.3	40.5	2.2
297.000	44.2	47.5	3.3

Notes: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.




Date: 16.JAN.2015 14:10:57

Figure 8.4-1: Conducted spurious emissions outside restricted bands at low channel




Date: 16.JAN.2015 14:09:37

Figure 8.4-2: Conducted spurious emissions outside restricted bands at mid channel




Date: 16.JAN.2015 14:08:58

Figure 8.4-3: Conducted spurious emissions outside restricted bands at high channel




Date: 16.JAN.2015 14:36:42

Figure 8.4-4: Conducted spurious emissions within restricted bands at low channel



Date: 16.JAN.2015 11:56:28

Figure 8.4-5: Conducted spurious emissions within restricted bands at mid channel




Date: 16.JAN.2015 11:55:05

Figure 8.4-6: Conducted spurious emissions within restricted bands at high channel

The peak and average limits for restricted band emissions on the plots were calculated for 3.5 dBi gain. Actual gain of the EUT is -1.3 dBi, therefore the limits are even less stringent. The actual limits were calculated as follows:


$$\text{Peak limit: } 74 \text{ dB}\mu\text{V/m} - 95.23 \text{ dB} - (-1.3 \text{ dBi}) = -19.93 \text{ dBm}$$

$$\text{Average limit: } 54 \text{ dB}\mu\text{V/m} - 95.23 \text{ dB} - (-1.3 \text{ dBi}) = -39.93 \text{ dBm}$$




Date: 16.JAN.2015 14:33:38

Figure 8.4-7: Lower band edge emission outside restricted band at 2.4 GHz




Date: 16.JAN.2015 14:34:27

Figure 8.4-8: Lower band edge emission within restricted band at 2.39 GHz, Peak. Note: peak measurement result was below average limit; therefore no average measurement was performed in addition.



Date: 16.JAN.2015 14:06:27

Figure 8.4-9: Upper band edge emission outside restricted band limit at 2.4835 GHz




Date: 16.JAN.2015 14:05:16

Figure 8.4-10: Upper band edge emission within restricted band at 2.4835 GHz, Peak. Note: peak measurement result was below average limit; therefore no average measurement was performed in addition.

The peak and average limits for restricted band emissions on the plots were calculated for 3.5 dBi gain. Actual gain of the EUT is -1.3 dBi, therefore the limits are even less stringent. The actual limits were calculated as follows:


$$\text{Peak limit: } 74 \text{ dB}\mu\text{V/m} - 95.23 \text{ dB} - (-1.3 \text{ dBi}) = -19.93 \text{ dBm}$$

$$\text{Average limit: } 54 \text{ dB}\mu\text{V/m} - 95.23 \text{ dB} - (-1.3 \text{ dBi}) = -39.93 \text{ dBm}$$




Date: 16.JAN.2015 14:35:15

Figure 8.4-11: Second harmonic peak measurement at low channel




Date: 16.JAN.2015 14:35:35

Figure 8.4-12: Second harmonic average measurement at low channel



Date: 16.JAN.2015 11:57:22

Figure 8.4-13: Second harmonic peak measurement at mid channel




Date: 16.JAN.2015 11:57:40

Figure 8.4-14: Second harmonic average measurement at mid channel


The peak and average limits for restricted band emissions on the plots were calculated for 3.5 dBi gain. Actual gain of the EUT is -1.3 dBi, therefore the limits are even less stringent. The actual limits were calculated as follows:

$$\text{Peak limit: } 74 \text{ dB}\mu\text{V/m} - 95.23 \text{ dB} - (-1.3 \text{ dBi}) = -19.93 \text{ dBm}$$

$$\text{Average limit: } 54 \text{ dB}\mu\text{V/m} - 95.23 \text{ dB} - (-1.3 \text{ dBi}) = -39.93 \text{ dBm}$$



Date: 16.JAN.2015 11:53:35



Date: 16.JAN.2015 11:54:02

a

Figure 8.4-15: Second harmonic peak measurement at high channel

Figure 8.4-16: Second harmonic average measurement at high channel

The peak and average limits for restricted band emissions on the plots were calculated for 3.5 dBi gain. Actual gain of the EUT is -1.3 dBi, therefore the limits are even less stringent. The actual limits were calculated as follows:

Peak limit: $74 \text{ dB}\mu\text{V/m} - 95.23 \text{ dB} - (-1.3 \text{ dBi}) = -19.93 \text{ dBm}$

Average limit: $54 \text{ dB}\mu\text{V/m} - 95.23 \text{ dB} - (-1.3 \text{ dBi}) = -39.93 \text{ dBm}$

8.5 FCC 15.247(e) and RSS-210 A8.2(b) Power spectral density for digitally modulated devices

8.5.1 Definitions and limits

FCC:

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

IC:

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission or over 1.0 second if the transmission exceeds 1.0-second duration. This power spectral density shall be determined in accordance with the provisions of Section A8.4(4); (i.e. the power spectral density shall be determined using the same method for determining the conducted output power).

8.5.2 Test summary

Test date:	January 16, 2015	Temperature:	22 °C
Test engineer:	Andrey Adelberg	Air pressure:	1003 mbar
Verdict:	Pass	Relative humidity:	32 %

8.5.3 Observations, settings and special notes


The test was performed using method described in DTS guidelines section 10.2: Method PKPSD with spectrum analyser settings:

Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Frequency span:	5 MHz
Detector mode:	Peak
Trace mode:	Max Hold

8.5.4 Test data


Table 8.5-1: PSD measurements results

Frequency, MHz	PSD, dBm/100 kHz	PSD limit, dBm/3 kHz	Margin, dB
2402	1.80	8.00	6.20
2442	2.21	8.00	5.79
2480	2.35	8.00	5.65




Date: 16.JAN.2015 14:12:11

Figure 8.5-1: PSD measurement on low channel



Date: 16.JAN.2015 14:12:52

Figure 8.5-2: PSD measurement on mid channel




Date: 16.JAN.2015 14:32:22

Figure 8.5-3: PSD measurement on high channel

Section 9. Block diagrams of test set-ups

9.1 Radiated emissions set-up



9.2 Conducted emissions set-up

