

On-Ramp Wireless, Inc 10920 Via Frontera, Suite 200 San Diego, CA 92127, USA +1 858 592 6008 : phone +1 858 592 6009 : fax info@onrampwireless.com www.onrampwireless.com

Jan 15, 2016

BABT FCB Forsyth House, Churchfield Road, Walton-on-Thames, Surrey, KT12 2TD

Attention: Reviewing Agency or TCB

FCC ID: XTE-ULPAP310

On behalf of On-Ramp Wireless, Inc., I certify that the Dual Latency system's output power is controlled by firmware to transmit a maximum sub-band antenna port power, P_{max} , of 30dbm. The absolute maximum sub-band power transmitted is limited to 36dBm E.I.R.P, such that $P_{max} = 36 + L - G$. G is the antenna gain in dB, not to exceed 9dBi and L the cable loss to the antenna based on the installation, typically less than 3dB. Furthermore, the system is designed to be operated with one or two sub-bands sharing the same antenna and each sub-band is an independent data stream.

Dated this <u>15th</u> day of <u>Jan</u>, 20<u>16</u>.

Jason Wilson

VP Product Management, On-Ramp Wireless, Inc. 10920 Via Frontera, Suite 200, San Diego, CA 92127

Phone: 858-312-8356, Fax: 858-592-6009 jason.wilson@onrampwireless.com